

according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer

Revision date: 22.03.2024 Product code: 23800 Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

UFI: RCW3-7242-Y007-8XDP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

AnalytiChem GmbH Company name:

ACD

Street: Stempelstraße 6 Place: D-47167 Duisburg Telephone: 0203/5194-0

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: number:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

Telefax: 0203/5194-290

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Carc. 1B; H350i Repr. 1B; H360F

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Cobalt(II) chloride hexahydrate Signal word: Danger

Pictograms:









according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

Revision date: 22.03.2024 Product code: 23800 Page 2 of 14

Hazard statements

H290 May be corrosive to metals. H350i May cause cancer by inhalation.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.
P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P391 Collect spillage.

Special labelling of certain mixtures

EUH208 Contains dipotassium hexachloroplatinate, Cobalt(II) chloride hexahydrate. May produce

an allergic reaction.

Restricted to professional users.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (Regulation	on (EC) No 1272/2008)			
7647-01-0	Hydrochloric acid			1 - < 5 %	
	231-595-7	017-002-01-X	01-2119484862-27		
	Skin Corr. 1B, STOT SE 3; H314 H335				
16921-30-5	dipotassium hexachloroplatinate				
	240-979-3	078-007-00-3			
	Acute Tox. 3, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1; H301 H318 H334 H317				
7791-13-1	Cobalt(II) chloride hexahydrate				
	231-589-4	027-004-00-5	01-2119517584-37		
	Carc. 1B, Muta. 2, Repr. 1B, Acute Tox. 4, Resp. Sens. 1, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H350i H341 H360F H302 H334 H317 H400 H410				

Full text of H and EUH statements: see section 16.

Print date: 22.03.2024



Safety Data Sheet

according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

Revision date: 22.03.2024 Product code: 23800 Page 3 of 14

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc.	Limits, M-factors and ATE		
7647-01-0	231-595-7	Hydrochloric acid	1 - < 5 %	
	1	H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 3; H335: >= 10 - 100		
16921-30-5	240-979-3	dipotassium hexachloroplatinate	< 1 %	
	oral: LD50 = 195 mg/kg			
7791-13-1	231-589-4	Cobalt(II) chloride hexahydrate	< 1 %	
	Aquatic Acute	=> 2000 mg/kg; oral: LD50 = 537 mg/kg		

Further Information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: cobalt dichloride

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products



according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

Revision date: 22.03.2024 Product code: 23800 Page 4 of 14

In case of fire may be liberated:

Hydrochloric gas

Metal oxide smoke, toxic

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment; see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).



according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

Revision date: 22.03.2024 Product code: 23800 Page 5 of 14

Provide adequate ventilation.

Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Store in a place accessible by authorized persons only.

Further information on storage conditions

Unsuitable container/equipment material: Metal

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7647-01-0	Hydrogen chloride	5	8		TWA (8 h)	
		10	15		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
7647-01-0	Hydrochloric acid					
Worker DNEL	., long-term	inhalation	local	8 mg/m³		
Worker DNEL, acute		inhalation	local	15 mg/m³		
Consumer DNEL, long-term		inhalation	local	8 mg/m³		
Consumer DN	Consumer DNEL, acute		local	15 mg/m³		
7791-13-1	Cobalt(II) chloride hexahydrate					
Consumer DNEL, long-term		oral	systemic	0,12 mg/kg bw/day		



according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

Revision date: 22.03.2024 Product code: 23800 Page 6 of 14

PNEC values

CAS No	Substance	
Environmenta	al compartment	Value
16921-30-5	dipotassium hexachloroplatinate	
Freshwater		0,00014 mg/l
Freshwater (i	intermittent releases)	0,000205 mg/l
Marine water		0,000017 mg/l
Freshwater s	ediment	0,261 mg/kg
Marine sedim	nent	0,026 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,125 mg/l
Soil		0,005 mg/kg
7791-13-1	Cobalt(II) chloride hexahydrate	
Freshwater		0,0006 mg/l
Marine water		0,00236 mg/l
Freshwater sediment		9,5 mg/kg
Marine sediment		9,5 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,37 mg/l
Soil		10,9 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: Face protection shield goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with occasional contact (splashes): > 480 min



according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

Revision date: 22.03.2024 Product code: 23800 Page 7 of 14

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Protective clothing acid-resistant

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: yellow
Odour: odourless

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

Flammability: not applicable Lower explosion limits: No data available No data available Upper explosion limits: Flash point: Auto-ignition temperature: No data available Decomposition temperature: No data available acidic pH-Value: No data available Viscosity / kinematic: No data available Water solubility:

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Bulk density:

No data available

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties
No data available
Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available



according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

Revision date: 22.03.2024 Product code: 23800 Page 8 of 14

Solvent separation test:

Solvent content:

Solid content:

Solid content:

Sublimation point:

No data available

Viscosity / dynamic:

Flow time:

No data available

No data available

Further Information
Corrosive to metals

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

The product develops hydrogen in an aqueous solution in contact with metals.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Keep away from: Metal.

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

Revision date: 22.03.2024 Product code: 23800 Page 9 of 14

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
16921-30-5	dipotassium hexachloroplatinate					
	oral	LD50 195 mg/kg	Rat	Study report (1995)	OECD Guideline 401	
7791-13-1	Cobalt(II) chloride hexahy	/drate				
	oral	LD50 537 mg/kg	Rat	Revista Española de Fisiologia, 39: 291	OECD Guideline 401	
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2007)	OECD Guideline 402	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

slightly irritant but not relevant for classification.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains dipotassium hexachloroplatinate, Cobalt(II) chloride hexahydrate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer by inhalation. (Cobalt(II) chloride hexahydrate)

May damage fertility. (Cobalt(II) chloride hexahydrate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the mixture itself.

Further information

Irritant

Allergic reactions

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

Revision date: 22.03.2024 Product code: 23800 Page 10 of 14

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
7647-01-0	Hydrochloric acid							
	Acute fish toxicity	LC50	862 mg/l	96 h	Leuciscus idus			
16921-30-5	dipotassium hexachloropl	atinate						
	Acute fish toxicity	LC50 mg/l	76,55	96 h	Oncorhynchus mykiss	Study report (2005)	OECD Guideline 203	
	Acute algae toxicity	ErC50	1,3 mg/l	72 h	Desmodesmus subspicatus	Study report (2001)	OECD Guideline 201	
	Acute crustacea toxicity	EC50 mg/l	0,0608	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202	
	Crustacea toxicity	NOEC mg/l	0,007	21 d	Daphnia magna	J. Fish. Res. Bd. Canada 29: 1691-1700 (A standard guideline was not followed, b	
	Acute bacteria toxicity	EC50	103 mg/l	3 h	activated sludge of a predominantly domestic sewag	Study report (2015)	OECD Guideline 209	
7791-13-1	Cobalt(II) chloride hexahydrate							
	Acute fish toxicity	LC50 mg/l	54,1	96 h	Pimephales promelas	Study report (2009)	other: ASTM guideline	
	Acute algae toxicity	ErC50 mg/l	71,314	96 h	Dunaliella tertiolecta	Study report (2010)	other: American Society for Testing and	
	Acute crustacea toxicity	EC50 mg/l	42,7	48 h	Aeolosoma sp.	Study report (2008)	Newman, J.P., Jr. 1975. The effects of h	
	Fish toxicity	NOEC mg/l	0,21	34 d	Pimephales promelas	Study report (2009)	other: This study was conducted accordin	
	Algae toxicity	NOEC mg/l	0,0018	7 d	Champia parvula	Study report - model refit from original	other: EPA 821-R- 02-014, Method 1009.0	
	Crustacea toxicity	NOEC mg/l	0,1697	14 d	Aeolosoma sp.	Study report (2008)	other: Newman, J.P., Jr. 1975. The effec	
	Acute bacteria toxicity	EC50	120 mg/l	0,5 h	Activated sludge	Study report (2010)	OECD Guideline 209	

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

BCF

CAS No	Chemical name	BCF	Species	Source
7791-13-1	Cobalt(II) chloride hexahydrate	23	Asterias rubens	Marine Pollution Bul

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties



according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

Revision date: 22.03.2024 Product code: 23800 Page 11 of 14

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

Do not empty into drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 3264
-------------------------------	---------

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrochloric acid)

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 8 Classification code: C1 Special Provisions: 274 5 I Limited quantity: Excepted quantity: E1 Transport category: 3 Hazard No: 80 Tunnel restriction code: F

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrochloric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Classification code:C1Special Provisions:274Limited quantity:5 LExcepted quantity:E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrochloric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:223, 274Limited quantity:5 L



according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

Revision date: 22.03.2024 Product code: 23800 Page 12 of 14

Excepted quantity: E1
EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrochloric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:1 LPassenger LQ:Y841Excepted quantity:E1

IATA-packing instructions - Passenger:852IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:856IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: Cobalt(II) chloride hexahydrate

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

Cobalt(II) chloride hexahydrate

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive

2012/18/EU (SEVESO III):

E2 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of

child-bearing age.

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9,12.



according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

Revision date: 22.03.2024 Product code: 23800 Page 13 of 14

Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals

Acute Tox: Acute toxicity Skin Corr: Skin corrosion Eye Dam: Eye damage

Resp. Sens: Respiratory sensitisation

Skin Sens: Skin sensitisation Muta: Germ cell mutagenicity

Carc: Carcinogenicity
Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Carc. 1B; H350i	Calculation method
Repr. 1B; H360F	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

an allergic reaction.

elevant H and EU	H statements (number and full text)
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350i	May cause cancer by inhalation.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains dipotassium hexachloroplatinate, Cobalt(II) chloride hexahydrate. May produce

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



Print date: 22.03.2024



Safety Data Sheet

according to Regulation (EC) No 1907/2006

EBC standard color index (EBC) 10 for determination of the color strength of beer and beer wort

Revision date: 22.03.2024 Product code: 23800 Page 14 of 14

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)