

according to Regulation (EC) No 1907/2006

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

Revision date: 09.02.2023 Product code: 24389 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

e-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

e-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Flam. Liq. 2; H225 Skin Corr. 1B; H314 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

nitric acid

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour. H290 May be corrosive to metals.



according to Regulation (EC) No 1907/2006

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

Revision date: 09.02.2023 Product code: 24389 Page 2 of 13

H314 Causes severe skin burns and eye damage.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC	C) No 1272/2008)	·	
64-17-5	ethanol			95 - < 100 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
7697-37-2	2 nitric acid		5 - < 10 %	
	231-714-2	007-030-00-3	01-2119487297-23	
_	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A; H272 H290 H331 H314 EUH071			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

	_ 				
CAS No	EC No	Chemical name	Quantity		
	Specific Conc. I	Specific Conc. Limits, M-factors and ATE			
64-17-5	200-578-6	200-578-6 ethanol			
	inhalation: LC5 100	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg			
7697-37-2	231-714-2	nitric acid	5 - < 10 %		
	l l	2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 rr. 1B; H314: >= 5 - < 20			

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider



according to Regulation (EC) No 1907/2006

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

Revision date: 09.02.2023 Product code: 24389 Page 3 of 13

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

Irritant

Respiratory complaints

Headache

Dizziness

Dizziness

Inebriation

Anaesthetic state

Unconsciousness

Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO2)

Carbon monoxide

Nitrogen oxides (NOx)

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.



according to Regulation (EC) No 1907/2006

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

Revision date: 09.02.2023 Product code: 24389 Page 4 of 13

Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.



according to Regulation (EC) No 1907/2006

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

Revision date: 09.02.2023 Product code: 24389 Page 5 of 13

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat or drink.

Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store in a cool dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

Protect from sunlight. Protect against: Light Corrosive to metals.

Unsuitable container/equipment material: Metal

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
64-17-5	ethanol					
Worker DNEL, long-term		inhalation	systemic	950 mg/m³		
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day		
Consumer DNEL, long-term		inhalation	systemic	114 mg/m³		
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day		
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day		



according to Regulation (EC) No 1907/2006

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

Revision date: 09.02.2023 Product code: 24389 Page 6 of 13

PNEC values

CAS No	Substance				
Environmental	Environmental compartment Value				
64-17-5	ethanol				
Freshwater		0,96 mg/l			
Freshwater (intermittent releases) 2,7					
Marine water		0,79 mg/l			
Freshwater sediment		3,6 mg/kg			
Marine sediment		2,9 mg/kg			
Secondary poisoning		380 mg/kg			
Micro-organisms in sewage treatment plants (STP) 580 mg/					
Soil 0,63 mg/kg					

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation KCL 890 Vitoject®
Suitable material: FKM (fluoro rubber) 0,7 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation KCL 720 Camapren®

Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 30 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear fire resistant or flame retardant clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Wear suitable protective clothing. Take off immediately all contaminated clothing.



according to Regulation (EC) No 1907/2006

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

Revision date: 09.02.2023 Product code: 24389 Page 7 of 13

Wash hands and face before breaks and after work and take a shower if necessary.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Colour:

Colour:

Odour:

Odour threshold:

Liquid

colourless

like: Alcohol

No data available

Melting point/freezing point: No data available No data available Flammability: Lower explosion limits: No data available No data available Upper explosion limits: Flash point: ~12 °C Auto-ignition temperature: No data available Decomposition temperature: No data available pH-Value: acidic No data available Viscosity / kinematic: No data available Water solubility:

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available
Solvent content:

No data available
Solid content:

No data available
Sublimation point:

No data available
Softening point:

No data available
Pour point:

No data available
No data available
No data available



according to Regulation (EC) No 1907/2006

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

Revision date: 09.02.2023 Product code: 24389 Page 8 of 13

Viscosity / dynamic: No data available Flow time: No data available

Further Information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

Corrosive to metals.

10.2. Chemical stability

Protect against:

Light

Air

10.3. Possibility of hazardous reactions

Oxidising agent, Alkali metals, Alkaline earth metal,

, Nitric acid, aldehydes

Amines, Aluminium, Chlorine (Cl2)

Phosphorus trichloride, Strong acid, Phosgene

Hydrogen peroxide, Nitrogen oxides (NOx), Iron.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Light

Air

10.5. Incompatible materials

Unsuitable container/equipment material: Metal

Plastic articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Chemical name					
	Exposure route	Dose	Species	Source	Method		
64-17-5	ethanol	ethanol					
	oral	LD50 10470 mg/kg	Rat	Study report (1976)	OECD Guideline 401		
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	Study report (1980)	OECD Guideline 403		
7697-37-2	nitric acid						
	inhalation vapour	ATE 2,65 mg/l					



according to Regulation (EC) No 1907/2006

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

Revision date: 09.02.2023 Product code: 24389 Page 9 of 13

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Other information

Observe risk of aspiration if vomiting occurs. Pulmonary oedema Pneumonia

Repeated exposure may cause skin dryness or cracking.

Further information

There are no data available on the mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

Print date: 09.02.2023



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

Revision date: 09.02.2023 Product code: 24389 Page 10 of 13

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
64-17-5	ethanol								
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975		
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11		
	Algae toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989	Study to determine the sensitivity of a		
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th		
7697-37-2	nitric acid								
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26		
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical		
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso		
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209		

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects



according to Regulation (EC) No 1907/2006

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

Revision date: 09.02.2023 Product code: 24389 Page 11 of 13

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (nitric acid, ethanol)

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 3+8 Classification code: FC **Special Provisions:** 274 Limited quantity: 1 I Excepted quantity: E2 Transport category: 2 Hazard No: 338 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (nitric acid, ethanol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+8Classification code:FCSpecial Provisions:274Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Nitric acid, ethanol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+8Special Provisions:274Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2924



according to Regulation (EC) No 1907/2006

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

Revision date: 09.02.2023 Product code: 24389 Page 12 of 13

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Nitric acid, ethanol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+8Special Provisions:A3Limited quantity Passenger:0.5 LPassenger LQ:Y340Excepted quantity:E2

IATA-packing instructions - Passenger:352IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:363IATA-max. quantity - Cargo:5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,4,6,8,9,10,11,12,13.

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H272 May intensify fire; oxidiser. H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H331 Toxic if inhaled.

EUH071 Corrosive to the respiratory tract.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Print date: 09.02.2023



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Salpetersäure 5 % reinst in Ethanol mit MEK vergällt zur metallurgischen Werkstoffprüfung

Revision date: 09.02.2023 Product code: 24389 Page 13 of 13

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)