

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290
Flam. Liq. 2; H225
Acute Tox. 3; H301
Acute Tox. 3; H311
Acute Tox. 3; H331
Skin Corr. 1B; H314
Eye Dam. 1; H318
STOT SE 1; H370

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

methanol

potassium hydroxide

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 2 of 14

Pictograms:



Hazard statements

- H225 Highly flammable liquid and vapour.
- H290 May be corrosive to metals.
- H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.
- H314 Causes severe skin burns and eye damage.
- H370 Causes damage to organs.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-56-1	methanol			85 - < 90 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			
1310-58-3	potassium hydroxide			1 - < 5 %
	215-181-3	019-002-00-8	01-2119487136-33	
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A; H290 H302 H314			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-56-1	200-659-6	methanol	85 - < 90 %
		inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	
1310-58-3	215-181-3	potassium hydroxide	1 - < 5 %
		oral: LD50 = 333 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 3 of 14

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water.

Remove contact lenses, if present and easy to do. Continue rinsing.

Consult an ophthalmologist.

After ingestion

Provide fresh air.

Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

Notes for the doctor : Methanol

4.2. Most important symptoms and effects, both acute and delayed

corrosive, Irritant, Dizziness, Dizziness

Anaesthetic state, Agitation, Spasms

Inebriation, Vomiting, Headache

Impairment of vision, Dyspnoea, Cough

Repeated exposure may cause skin dryness or cracking.

Risk of serious damage to eyes.

Circulatory collapse, Corneal opacity.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor : Methanol

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂)

Foam

Extinguishing powder

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide, Carbon monoxide

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 4 of 14

Beware of reignition.
Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
Wear full chemical protective clothing.
In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers.
Move undamaged containers from immediate hazard area if it can be done safely.
Suppress gases/vapours/mists with water spray jet.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).
Take action to prevent static discharges.
Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion
Do not allow to enter into surface water or drains.
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.
Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Collect in closed and suitable containers for disposal.
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 5 of 14

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid exposure - obtain special instructions before use.
If handled uncovered, arrangements with local exhaust ventilation have to be used.
Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Keep container tightly closed.
Use personal protection equipment. Use extractor hood (laboratory).
Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.
Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.
Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Unsuitable container/equipment material: Aluminium, tin, zinc

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep cool. Protect from sunlight.
storage temperature +15°C - +25°C

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
67-56-1	Methyl alcohol	200	260		TWA (8 h)	
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 6 of 14

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

DNEL/DMEL values

CAS No	Substance	DNEL type	Exposure route	Effect	Value
67-56-1	methanol	Consumer DNEL, acute	inhalation	systemic	50 mg/m ³
		Worker DNEL, long-term	inhalation	systemic	260 mg/m ³
		Worker DNEL, acute	inhalation	systemic	260 mg/m ³
		Worker DNEL, long-term	inhalation	local	260 mg/m ³
		Worker DNEL, acute	inhalation	local	260 mg/m ³
		Worker DNEL, long-term	dermal	systemic	40 mg/kg bw/day
		Worker DNEL, acute	dermal	systemic	40 mg/kg bw/day
		Consumer DNEL, long-term	inhalation	systemic	50 mg/m ³
		Consumer DNEL, long-term	inhalation	local	50 mg/m ³
		Consumer DNEL, acute	inhalation	local	50 mg/m ³
		Consumer DNEL, long-term	dermal	systemic	8 mg/kg bw/day
		Consumer DNEL, acute	dermal	systemic	8 mg/kg bw/day
		Consumer DNEL, long-term	oral	systemic	8 mg/kg bw/day
		Consumer DNEL, acute	oral	systemic	8 mg/kg bw/day
1310-58-3	potassium hydroxide	Worker DNEL, long-term	inhalation	local	1 mg/m ³
		Consumer DNEL, long-term	inhalation	local	1 mg/m ³

PNEC values

CAS No	Substance	Environmental compartment	Value
67-56-1	methanol	Freshwater	20,8 mg/l
		Freshwater (intermittent releases)	1540 mg/l
		Marine water	2,08 mg/l
		Freshwater sediment	77 mg/kg
		Marine sediment	7,7 mg/kg
		Micro-organisms in sewage treatment plants (STP)	100 mg/l
		Soil	100 mg/kg

8.2. Exposure controls

Appropriate engineering controls

- Technical measures and the application of suitable work processes have priority over personal protection equipment.
- If handled uncovered, arrangements with local exhaust ventilation have to be used.
- Do not breathe vapour/aerosol.

Individual protection measures, such as personal protective equipment

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 7 of 14

Eye/face protection

goggles

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

Recommended glove articles KCL 897 Butoject®
Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm
Wearing time with permanent contact: > 480 min

Recommended glove articles KCL 890 Vitoject®
Suitable material: FKM (fluoro rubber) 0,7 mm
Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing
Take off immediately all contaminated clothing and wash it before reuse.
Wear fire resistant or flame retardant clothing.
Wash hands and face before breaks and after work and take a shower if necessary.
Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Methanol	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		~64 °C
Flammability:		not applicable
Lower explosion limits:		~5,5 vol. %
Upper explosion limits:		~44 vol. %

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 8 of 14

Flash point:	~11 °C
Auto-ignition temperature:	~455 °C
Decomposition temperature:	No data available
pH-Value:	alkaline
Viscosity / kinematic:	No data available
Water solubility:	Soluble in: Water
Solubility in other solvents not determined	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,8442 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

not determined

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available:

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

May be corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

Vapours can form explosive mixtures with air.

May be corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 9 of 14

Oxidising agent, Hydrogen peroxide, Acid halides
Reducing agent, Acid, Alkaline earth metal, Alkali metals

10.4. Conditions to avoid

Vapours can form explosive mixtures with air.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles
Glass
metals (including their alloys)

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

Acute toxicity

Toxic if swallowed.
Toxic in contact with skin.
Toxic if inhaled.
If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

ATEmix calculated

ATE (oral) 115,4 mg/kg; ATE (dermal) 354,4 mg/kg; ATE (inhalation vapour) 3,540 mg/l; ATE (inhalation dust/mist) 0,5910 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-56-1	methanol				
	oral	LD50 6000 mg/kg	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG)	Determination of the acute toxicity of t
	dermal	ATE 300 mg/kg			
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			
1310-58-3	potassium hydroxide				
	oral	LD50 333 mg/kg	Rat	Fund. Appl. Toxicol., 8, 97-100 (1987)	OECD Guideline 425

Irritation and corrosivity

Causes severe skin burns and eye damage.
Causes serious eye damage.
Corneal opacity.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 10 of 14

Based on available data, the classification criteria are not met.

STOT-single exposure

Causes damage to organs. (methanol)
eyes
Liver and kidney damage
Irreversible damage to the optic nerve.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

corrosive, Irritant, Dizziness, Dizziness
Anaesthetic state, Agitation, Spasms
Inebriation, Vomiting, Headache
Impairment of vision, Dyspnoea, Cough
Repeated exposure may cause skin dryness or cracking.
Risk of serious damage to eyes.
Circulatory collapse, Corneal opacity.

Further information

Do not empty into drains.
Discharge into the environment must be avoided.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 11 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-56-1	methanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC 446,7 mg/l	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC 208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 12 of 14

Contaminated packaging

This material and its container must be disposed of as hazardous waste.
Handle contaminated packages in the same way as the substance itself.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 3286
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+6.1+8
Classification code:	FTC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	368
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 3286
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+6.1+8
Classification code:	FTC
Special Provisions:	274 802
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 3286
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+6.1/8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 3286
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+6.1 8
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y340

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 13 of 14

Excepted quantity:	E2	
IATA-packing instructions - Passenger:		352
IATA-max. quantity - Passenger:		1 L
IATA-packing instructions - Cargo:		363
IATA-max. quantity - Cargo:		5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. Toxic.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 69, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): H2 ACUTE TOXIC

Additional information: P5c

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9,12.

Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals

Flam. Liq: Flammable liquid

Acute Tox: Acute toxicity

Skin Corr: Skin corrosion

Eye Dam: Eye damage

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium hydroxide solution methanolic 0.5 mol/l - 0.5 N solution Reag. Ph. Eur., chapter 4.2.2

Revision date: 01.03.2024

Product code: 25064

Page 14 of 14

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 3; H301	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H331	Calculation method
Skin Corr. 1B; H314	
Eye Dam. 1; H318	Calculation method
STOT SE 1; H370	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H370	Causes damage to organs.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)