

according to Regulation (EC) No 1907/2006

4-Hydroxy-4-methyl-2-pentanone (Diacetone alcohol) for synthesis

Revision date: 02.08.2023 Product code: 25302 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

4-Hydroxy-4-methyl-2-pentanone (Diacetone alcohol) for synthesis

CAS No: 123-42-2 Index No: 603-016-00-1 EC No: 204-626-7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemical

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

0203/5194-0 Telephone: Telefax: 0203/5194-290

E-mail: info@analytichem.de

Abteilung Produktsicherheit Contact person: Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

www.analvtichem.de Internet:

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

number:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

A registration number is not available for this substance as the substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226 Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour.



according to Regulation (EC) No 1907/2006

4-Hydroxy-4-methyl-2-pentanone (Diacetone alcohol) for synthesis

Revision date: 02.08.2023 Product code: 25302 Page 2 of 11

H319 Causes serious eye irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P233 Keep container tightly closed.

P280

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula: (CH3)2C(OH)
Molecular weight: 116.16 g/mol

Hazardous components

CAS No	Chemical name	Chemical name				
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No 1272/2008)					
123-42-2	4-hydroxy-4-methylpentan-	4-hydroxy-4-methylpentan-2-one				
	204-626-7 603-016-00-1					
	Flam. Liq. 3, Eye Irrit. 2; H226 H319					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	o Chemical name				
	Specific Conc. I	ecific Conc. Limits, M-factors and ATE				
123-42-2	204-626-7	204-626-7 4-hydroxy-4-methylpentan-2-one				
	oral: LD50 = 30	oral: LD50 = 3002 mg/kg Eye Irrit. 2; H319: >= 10 - 100				

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with:

Water and soap

Take off immediately all contaminated clothing and wash it before reuse.



according to Regulation (EC) No 1907/2006

4-Hydroxy-4-methyl-2-pentanone (Diacetone alcohol) for synthesis

Revision date: 02.08.2023 Product code: 25302 Page 3 of 11

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Depression of central nervous system

Headache

Dizziness

Induces narcotic effect.

Unconsciousness

Impairment of vision

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquid.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO2) Carbon monoxide

5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Suppress gases/vapours/mists with water spray jet.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.



according to Regulation (EC) No 1907/2006

4-Hydroxy-4-methyl-2-pentanone (Diacetone alcohol) for synthesis

Revision date: 02.08.2023 Product code: 25302 Page 4 of 11

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

 $Remove\ contaminated,\ saturated\ clothing\ immediately.\ Draw\ up\ and\ observe\ skin\ protection\ programme.$

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



according to Regulation (EC) No 1907/2006

4-Hydroxy-4-methyl-2-pentanone (Diacetone alcohol) for synthesis

Revision date: 02.08.2023 Product code: 25302 Page 5 of 11

Hints on joint storage

Do not store together with:

Oxidising agent

Further information on storage conditions

Vapours may form explosive mixtures with air. storage temperature < +30°C.

7.3. Specific end use(s)

Laboratory use Laboratory chemical

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
123-42-2	4-Hydroxy-4-methyl-2-pentanone	50	240		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
123-42-2	4-hydroxy-4-methylpentan-2-one						
Worker DNEL,	long-term	inhalation	systemic	59,2 mg/m³			
Worker DNEL, acute		inhalation	local	240 mg/m³			
Worker DNEL,	long-term	dermal	systemic	840 mg/kg bw/day			
Consumer DNEL, long-term		inhalation	systemic	10,4 mg/m³			
Consumer DNEL, long-term		dermal	systemic	60 mg/kg bw/day			
Consumer DNEL, long-term		oral	systemic	3 mg/kg bw/day			

PNEC values

CAS No	Substance					
Environment	Environmental compartment Valu					
123-42-2	4-hydroxy-4-methylpentan-2-one					
Freshwater	Freshwater					
Freshwater (1 mg/l					
Marine wate	0,2 mg/l					
Freshwater	9,06 mg/kg					
Marine sedir	0,91 mg/kg					
Micro-organi	10 mg/l					
Soil	0,63 mg/kg					

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.



according to Regulation (EC) No 1907/2006

4-Hydroxy-4-methyl-2-pentanone (Diacetone alcohol) for synthesis

Revision date: 02.08.2023 Product code: 25302 Page 6 of 11

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation KCL 730 Camatril® Velours Suitable material: NBR (Nitrile rubber) 0,4 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation Filtering device with filter or ventilator filtering device of type: ABEK

Environmental exposure controls

Do not empty into drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: light yellow
Odour: characteristic
Odour threshold: No data available

Melting point/freezing point:

No data available
Boiling point or initial boiling point and

166 °C

boiling range:

Flammability: not applicable Lower explosion limits: 1.8 vol. % Upper explosion limits: 6,9 vol. % Flash point: 58 °C Auto-ignition temperature: 643 °C Decomposition temperature: not determined pH-Value: No data available Viscosity / kinematic: No data available Water solubility: No data available

Solubility in other solvents

not determined

Dissolution rate:

No data available
Partition coefficient n-octanol/water:

No data available



according to Regulation (EC) No 1907/2006

4-Hydroxy-4-methyl-2-pentanone (Diacetone alcohol) for synthesis

Revision date: 02.08.2023 Product code: 25302 Page 7 of 11

Dispersion stability:

Vapour pressure:

No data available
1,29 hPa

(at 20 °C)

Vapour pressure:

Density (at 25 °C):

Relative density:

Bulk density:

No data available

No data available

No data available

No data available

Relative vapour density:

not determined

Particle characteristics:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Sustaining combustion:

No data available

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available
Solvent content:

No data available
Solid content:

Sublimation point:

No data available
Softening point:

No data available
Pour point:

No data available

No data available:

Viscosity / dynamic:

Flow time:

No data available

No data available

Further Information No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours can form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent Alkali (lye)

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide



according to Regulation (EC) No 1907/2006

4-Hydroxy-4-methyl-2-pentanone (Diacetone alcohol) for synthesis

Revision date: 02.08.2023 Product code: 25302 Page 8 of 11

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	xposure route Dose Species Source Method							
123-42-2	4-hydroxy-4-methylpentan-2-one							
	oral	LD50 3002 mg/kg	Rat	Study report (1978)	OECD Guideline 401			

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Depression of central nervous system

Headache

Dizziness

Induces narcotic effect.

Unconsciousness

Impairment of vision

Further information

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Print date: 02.08.2023



Safety Data Sheet

according to Regulation (EC) No 1907/2006

4-Hydroxy-4-methyl-2-pentanone (Diacetone alcohol) for synthesis

Revision date: 02.08.2023 Product code: 25302 Page 9 of 11

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
123-42-2	4-hydroxy-4-methylpentan-2-one						
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Oryzias latipes	Study report (1997)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchneriella subcapitata	Study report (1997)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	Study report (1997)	OECD Guideline 202
	Crustacea toxicity	NOEC	100 mg/l	14 d	Daphnia magna	Study report (1997)	OECD Guideline 211
	Acute bacteria toxicity	(EC50 mg/l)	> 1000		activated sludge, domestic	Study report (2012)	OECD Guideline 209

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
123-42-2	4-hydroxy-4-methylpentan-2-one	1,9

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

No data available

Further information

Avoid release to the environment.

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information



according to Regulation (EC) No 1907/2006

4-Hydroxy-4-methyl-2-pentanone (Diacetone alcohol) for synthesis

Revision date: 02.08.2023 Product code: 25302 Page 10 of 11

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1148

14.2. UN proper shipping name: DIACETONE ALCOHOL

14.3. Transport hazard class(es): Ш 14.4. Packing group: Hazard label: 3 Classification code: F1 5 L Limited quantity: Excepted quantity: E1 Transport category: 3 Hazard No: 30 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1148

14.2. UN proper shipping name: DIACETONE ALCOHOL

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Classification code:F1Limited quantity:5 LExcepted quantity:E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1148

14.2. UN proper shipping name: DIACETONE ALCOHOL

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Special Provisions:223Limited quantity:5 LExcepted quantity:E1EmS:F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1148

14.2. UN proper shipping name: DIACETONE ALCOHOL

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Special Provisions:A3Limited quantity Passenger:10 LPassenger LQ:Y344Excepted quantity:E1

IATA-packing instructions - Passenger:355IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:366IATA-max. quantity - Cargo:220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable



according to Regulation (EC) No 1907/2006

4-Hydroxy-4-methyl-2-pentanone (Diacetone alcohol) for synthesis

Revision date: 02.08.2023 Product code: 25302 Page 11 of 11

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to 2012/18/EU

P5c FLAMMABLE LIQUIDS

(SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9,12.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Flam. Liq: Flammable liquid

Eye Irrit: Eye irritation

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H319 Causes serious eye irritation.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.