

**Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt**

Revision date: 30.05.2022

Product code: 26356

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Uses advised against**

Do not use for private purposes (household).

**1.3. Details of the supplier of the safety data sheet**

Company name:	Fa. Bernd Kraft GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@berndkraft.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@berndkraft.de	
Internet:	www.berndkraft.de	
Responsible Department:	Abteilung Produktsicherheit	

**1.4. Emergency telephone number:**

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

**Further Information**

This product is a mixture. REACH Registration Number see section 3.

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225

Acute Tox. 4; H312

Acute Tox. 4; H332

Skin Irrit. 2; H315

Eye Irrit. 2; H319

STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**

**Regulation (EC) No 1272/2008**

**Hazard components for labelling**

xylene (mix)

propan-2-ol; isopropyl alcohol; isopropanol

**Signal word:** Danger

**Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt**

Revision date: 30.05.2022

Product code: 26356

Page 2 of 13

**Pictograms:**



**Hazard statements**

H225	Highly flammable liquid and vapour.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Hazardous components**

CAS No	Chemical name	Quantity
	EC No      Index No      REACH No	
	Classification (Regulation (EC) No 1272/2008)	
	xylene (mix)	65 - < 70 %
	905-588-0      601-022-00-9      01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	30 - < 35 %
	200-661-7      603-117-00-0	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	

Full text of H and EUH statements: see section 16.

**Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt**

Revision date: 30.05.2022

Product code: 26356

Page 3 of 13

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	905-588-0	xylene (mix)	65 - < 70 %
		inhalation: LC50 = 6700 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 12126 mg/kg; oral: LD50 = 3523 mg/kg	

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

No data available

**After inhalation**

Provide fresh air.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.

**After contact with skin**

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.  
Call a physician immediately.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Remove contact lenses, if present and easy to do. Continue rinsing.

**After ingestion**

Rinse mouth immediately and drink plenty of water.  
Observe risk of aspiration if vomiting occurs.  
Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Irritant  
May cause drowsiness or dizziness.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

**Unsuitable extinguishing media**

no restriction

**5.2. Special hazards arising from the substance or mixture**

Combustible liquids  
Hazardous combustion products  
In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Heating causes rise in pressure with risk of bursting.

**Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt**

Revision date: 30.05.2022

Product code: 26356

Page 4 of 13

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.  
In case of fire and/or explosion do not breathe fumes.  
Avoid contact with skin, eyes and clothes.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Use water spray jet to protect personnel and to cool endangered containers.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**General advice**

Keep away from sources of ignition - No smoking.  
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).  
Take action to prevent static discharges.

**For non-emergency personnel**

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures  
Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.  
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.  
Danger of explosion

**6.3. Methods and material for containment and cleaning up**

**For containment**

Cover drains.  
Prevent spread over a wide area (e.g. by containment or oil barriers).  
Collect in closed and suitable containers for disposal.  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

Provide adequate ventilation.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage**

**Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt**

Revision date: 30.05.2022

Product code: 26356

Page 5 of 13

**7.1. Precautions for safe handling**

**Advice on safe handling**

Read label before use. Handle and open container with care.  
When using do not eat, drink, smoke, sniff. Keep container tightly closed.  
Use personal protection equipment. Use extractor hood (laboratory).  
Do not breathe vapour/aerosol. Provide adequate ventilation.

**Advice on protection against fire and explosion**

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.  
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Further information on storage conditions**

Keep cool. Protect from sunlight.

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	
1330-20-7	Xylene, mixed isomers	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

**Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek

**Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt**

Revision date: 30.05.2022

Product code: 26356

Page 6 of 13

**DNEL/DMEL values**

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
	xylene (mix)		
Worker DNEL, long-term	inhalation	systemic	221 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	systemic	442 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	221 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	local	442 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	212 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	65,3 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	systemic	260 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	local	65,3 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	local	260 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	12,5 mg/kg bw/day
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol		
Worker DNEL, long-term	inhalation	systemic	500 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	89 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day

**PNEC values**

CAS No	Substance	
Environmental compartment	Value	
	xylene (mix)	
Freshwater	0,327 mg/l	
Freshwater (intermittent releases)	0,327 mg/l	
Marine water	0,327 mg/l	
Freshwater sediment	12,46 mg/kg	
Marine sediment	12,46 mg/kg	
Micro-organisms in sewage treatment plants (STP)	6,58 mg/l	
Soil	2,31 mg/kg	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater	140,9 mg/l	
Freshwater (intermittent releases)	140,9 mg/l	
Marine water	140,9 mg/l	
Freshwater sediment	552 mg/kg	
Marine sediment	552 mg/kg	
Secondary poisoning	160 mg/kg	
Micro-organisms in sewage treatment plants (STP)	2251 mg/l	
Soil	28 mg/kg	

**8.2. Exposure controls**

**Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt**

Revision date: 30.05.2022

Product code: 26356

Page 7 of 13

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

goggles

Face protection umbrella

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	clear
Odour threshold:	No data available

**Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt**

Revision date: 30.05.2022

Product code: 26356

Page 8 of 13

**Changes in the physical state**

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	>35 °C
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
:	No data available
Flash point:	<21 °C

**Flammability**

Solid/liquid:	not applicable
Gas:	not applicable

**Explosive properties**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Lower explosion limits:	No data available
Upper explosion limits:	No data available
Auto-ignition temperature:	No data available

**Self-ignition temperature**

Solid:	not applicable
Gas:	not applicable

Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / dynamic:	No data available
Viscosity / kinematic:	No data available
Flow time:	No data available
Water solubility:	No data available

**Solubility in other solvents**

No data available

Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,84200 g/cm <sup>3</sup>
Bulk density:	No data available
Relative vapour density:	No data available

**9.2. Other information**

**Information with regard to physical hazard classes**

Sustaining combustion:	Sustaining combustion
Oxidizing properties	
Not oxidising.	

**Other safety characteristics**

Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	No data available
Evaporation rate:	No data available



**Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt**

Revision date: 30.05.2022

Product code: 26356

Page 9 of 13

**Further Information**

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Highly flammable.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Harmful in contact with skin.

Harmful if inhaled.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	xylene (mix)				
	oral	LD50 mg/kg 3523	Rat	Study report (1986)	EU Method B.1
	dermal	LD50 mg/kg 12126	Rabbit	Publication (1962)	Single dermal dose under occlusion follo
	inhalation (4 h) vapour	LC50 mg/l 6700	Rat	Toxicol Appl Pharmacol 33:543-558. (1975)	EU Method B.2
	inhalation dust/mist	ATE 1,5 mg/l			

**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt**

Revision date: 30.05.2022

Product code: 26356

Page 10 of 13

**STOT-single exposure**

May cause respiratory irritation. (xylene (mix))

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards**

**Other information**

There are no data available on the mixture itself.

**Further information**

There are no data available on the mixture itself.

**SECTION 12: Ecological information**

**12.1. Toxicity**

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
	xylene (mix)					
	Acute fish toxicity	LC50 8,4 mg/l	96 h	Oncorhynchus mykiss	Ecotoxicology and Environmental Safety.	OECD Guideline 203
	Acute algae toxicity	ErC50 4,9 mg/l	72 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety.	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l > 3,4	48 h	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	other: US EPA 600/4-91-003
	Fish toxicity	NOEC mg/l > 1,3	56 d	Oncorhynchus mykiss	Appl. Sci. Branch, Eng. Res. Cent. Denve	Fish were exposed in artificial streams
	Crustacea toxicity	NOEC mg/l 1,17	7 d	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	other: US EPA 600/4-91-003
	Acute bacteria toxicity	(EC50 mg/l) > 175	0,5 h	Activated sludge	Research Journal WPCF 60(10) 1850-1856 (	OECD Guideline 209
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l 10000	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

**Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt**

Revision date: 30.05.2022

Product code: 26356

Page 11 of 13

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
	xylene (mix)	3,2
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

**BCF**

CAS No	Chemical name	BCF	Species	Source
	xylene (mix)	> 5,5 - < 12,2	Oncorhynchus mykiss	Appl. Sci. Branch, E

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Do not allow to enter into surface water or drains.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.  
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (propan-2-ol, xylene)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (propan-2-ol, xylene)

**Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt**

Revision date: 30.05.2022

Product code: 26356

Page 12 of 13

**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3  
 Classification code: F1  
 Special Provisions: 274 601 640D  
 Limited quantity: 1 L  
 Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (propan-2-ol, xylene)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3  
 Special Provisions: 274  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (propan-2-ol, xylene)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3  
 Special Provisions: A3  
 Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):  
 Entry 3, Entry 40

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).  
 Water hazard class (D): 2 - obviously hazardous to water  
 Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

**Xylol / 2-Propanol-Gemisch chem. rein volumetrisch 2+1 gemischt**

Revision date: 30.05.2022

Product code: 26356

Page 13 of 13

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 12.

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*