

Safety Data Sheet

according to UK REACH Regulation

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

Revision date: 11.01.2024 Product code: 26411 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6 Place: D-47167 Duisburg

0203/5194-0 Telephone: Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Abteilung Produktsicherheit Responsible Department:

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: number:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Repr. 2: H361d STOT SE 3; H336 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

heptane toluene

Signal word: Danger



Safety Data Sheet

according to UK REACH Regulation

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

Revision date: 11.01.2024 Product code: 26411 Page 2 of 13

Pictograms:









Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H361d Suspected of damaging the unborn child. H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity			
	EC No	Index No	REACH No				
	Classification (GB CLP Regulation)						
142-82-5	heptane			80 - < 85 %			
	205-563-8	601-008-00-2	01-2119457603-38				
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410						
108-88-3	toluene			15 - < 20 %			
	203-625-9	601-021-00-3	01-2119471310-51				
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d H315 H336 H373 H304						

Full text of H and EUH statements: see section 16.



Safety Data Sheet

according to UK REACH Regulation

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

Revision date: 11.01.2024 Product code: 26411 Page 3 of 13

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
142-82-5	205-563-8	heptane	80 - < 85 %	
	inhalation: LC50 = > 29,29 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg			
108-88-3	203-625-9	toluene	15 - < 20 %	
	inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg			

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO2), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.



Safety Data Sheet

according to UK REACH Regulation

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

Revision date: 11.01.2024 Product code: 26411 Page 4 of 13

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.



Safety Data Sheet

according to UK REACH Regulation

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

Revision date: 11.01.2024 Product code: 26411 Page 5 of 13

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

national regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
142-82-5	n-Heptane	500	2085		TWA (8 h)	WEL
108-88-3	Toluene	50	191	ľ	TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL



Safety Data Sheet

according to UK REACH Regulation

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

Revision date: 11.01.2024 Product code: 26411 Page 6 of 13

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
142-82-5	heptane			
Worker DNEL,	long-term	inhalation	systemic	2085 mg/m³
Worker DNEL,	long-term	dermal	systemic	300 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	447 mg/m³
Consumer DN	EL, long-term	dermal	systemic	149 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	149 mg/kg bw/day
108-88-3	toluene			
Worker DNEL,	long-term	inhalation	systemic	192 mg/m³
Worker DNEL,	acute	inhalation	systemic	384 mg/m³
Worker DNEL,	long-term	inhalation	local	192 mg/m³
Worker DNEL,	acute	inhalation	local	384 mg/m³
Worker DNEL,	long-term	dermal	systemic	384 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	56,5 mg/m³
Consumer DN	EL, acute	inhalation	systemic	226 mg/m³
Consumer DN	EL, long-term	inhalation	local	56,5 mg/m³
Consumer DN	EL, acute	inhalation	local	226 mg/m³
Consumer DN	EL, long-term	dermal	systemic	226 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	8,13 mg/kg bw/day

PNEC values

CAS No	Substance			
Environmental compartment Value				
108-88-3	toluene			
Freshwater	Freshwater			
Freshwater (i	0,68 mg/l			
Marine water	0,68 mg/l			
Freshwater s	16,39 mg/kg			
Marine sedim	Marine sediment			
Micro-organis	Micro-organisms in sewage treatment plants (STP)			
Soil		2,89 mg/kg		

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the



Safety Data Sheet

according to UK REACH Regulation

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

Revision date: 11.01.2024 Product code: 26411 Page 7 of 13

specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject®
Suitable material: FKM (fluoro rubber) 0,7 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour threshold: No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

Lower explosion limits:

Auto-ignition temperature:

Decomposition temperature:

Flammability: not applicable

not applicable No data available No data available

Upper explosion limits:

No data available
Flash point:

-4 °C

No data available
No data available

pH-Value:

Viscosity / kinematic:

No data available

No data available

No

Water solubility:



Safety Data Sheet

according to UK REACH Regulation

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

Revision date: 11.01.2024 Product code: 26411 Page 8 of 13

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

No data available Evaporation rate: Solvent separation test: No data available Solvent content: 100% Solid content: No data available Sublimation point: No data available Softening point: No data available Pour point: No data available No data available Viscosity / dynamic: No data available Flow time: No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation



Safety Data Sheet

according to UK REACH Regulation

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

Revision date: 11.01.2024 Product code: 26411 Page 9 of 13

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
142-82-5	heptane								
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401			
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)	OECD Guideline 402			
	inhalation (4 h) vapour	LC50 mg/l	> 29,29	Rat	Study report (1982)	OECD Guideline 403			
108-88-3	toluene								
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1			
	dermal	LD50 mg/kg	> 5000	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o			
	inhalation (4 h) vapour	LC50	28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403			

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (heptane)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the mixture itself.

Further information

There are no data available on the mixture itself.



Safety Data Sheet

according to UK REACH Regulation

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

Revision date: 11.01.2024 Product code: 26411 Page 10 of 13

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
142-82-5	heptane							
	Acute algae toxicity	ErC50 mg/l	4,338	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a	
	Acute crustacea toxicity	EC50	1,5 mg/l	48 h	Daphnia magna	Study report (1987)	other: As described in: The evaluation o	
	Fish toxicity	NOEC mg/l	1,284	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a	
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211	
108-88-3	toluene							
	Acute fish toxicity	LC50	5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th	
	Acute algae toxicity	ErC50 mg/l	> 433	96 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	Method: other	
	Acute crustacea toxicity	EC50 mg/l	11,5	48 h	Daphnia magna	REACh Registration Dossier	Method: other	
	Fish toxicity	NOEC mg/l	1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th	
	Algae toxicity	NOEC mg/l	> 400	7 d	Scenedesmus quadricauda	REACh Registration Dossier	Method: other	
	Crustacea toxicity	NOEC mg/l	0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (other: US EPA 600/4-91-003	

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
142-82-5	heptane	4,5
108-88-3	toluene	2,73

BCF

CAS No	Chemical name	BCF	Species	Source
142-82-5	heptane	552	calculated	Other company data (
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).



Safety Data Sheet

according to UK REACH Regulation

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

Revision date: 11.01.2024 Product code: 26411 Page 11 of 13

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

There are no data available on the mixture itself.

Further information

Do not empty into drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (heptane, toluene)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (heptane, toluene)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (heptane, toluene)



Safety Data Sheet

according to UK REACH Regulation

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

Revision date: 11.01.2024 Product code: 26411 Page 12 of 13

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:274Limited quantity:1 LExcepted quantity:E2EmS:F-E. S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (heptane, toluene)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A3Limited quantity Passenger:1 LPassenger LQ:Y341Excepted quantity:E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: heptane

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 3 - highly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 15.



Safety Data Sheet

according to UK REACH Regulation

n-Heptan / Toluol-Gemisch zur Analyse gravimetrisch 5 + 1 gemischt

Revision date: 11.01.2024 Product code: 26411 Page 13 of 13

Abbreviations and acronyms

Flam. Liq: Flammable liquids Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)