

according to Regulation (EC) No 1907/2006

# Mixed indicator solution methylene blue / neutral red 0.1 % in ethanol denatured with MEK mixed 1 :

Revision date: 06.09.2023 Product code: 26639 Page 1 of 12

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Mixed indicator solution methylene blue / neutral red 0.1 % in ethanol denatured with MEK mixed 1:

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemical

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

# Uses advised against

Do not use for private purposes (household).

#### 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

<u>1.4. Emergency telephone</u> For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

#### **Further Information**

This product is a mixture. REACH Registration Number see section 3.

# SECTION 2: Hazards identification

# 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

# 2.2. Label elements

## Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:





## **Hazard statements**

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No



according to Regulation (EC) No 1907/2006

# Mixed indicator solution methylene blue / neutral red 0.1 % in ethanol denatured with MEK mixed 1:

Revision date: 06.09.2023 Product code: 26639 Page 2 of 12

smoking.

P233 Keep container tightly closed.

P280

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

#### 2.3. Other hazards

No information available.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **Hazardous components**

CAS No	Chemical name	Chemical name		
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64-17-5	ethanol	ethanol		
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name			
	Specific Conc. I	Limits, M-factors and ATE			
64-17-5	200-578-6	ethanol	95 - < 100 %		
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg				

## **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

### **General information**

No data available

# After inhalation

Provide fresh air.

## After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

# After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

## After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

Irritant

Print date: 06.09.2023



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Mixed indicator solution methylene blue / neutral red 0.1 % in ethanol denatured with MEK mixed 1:

Revision date: 06.09.2023 Product code: 26639 Page 3 of 12

Dizziness

The product causes narcotic-like effects.

Inebriation

Vomiting

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

## Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

#### Unsuitable extinguishing media

no restriction

## 5.2. Special hazards arising from the substance or mixture

Combustible liquid.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide

Beware of reignition.

### 5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

Use water spray jet to protect personnel and to cool endangered containers.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Suppress gases/vapours/mists with water spray jet.

Move undamaged containers from immediate hazard area if it can be done safely.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

## General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

#### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

Print date: 06.09.2023



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Mixed indicator solution methylene blue / neutral red 0.1 % in ethanol denatured with MEK mixed 1:

Revision date: 06.09.2023 Product code: 26639 Page 4 of 12

#### 6.3. Methods and material for containment and cleaning up

#### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

#### Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

# Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

#### 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

# Further information on storage conditions

Vapours may form explosive mixtures with air. storage temperature +5°C - +30°C.

#### 7.3. Specific end use(s)

Laboratory use Laboratory chemical

# **SECTION 8: Exposure controls/personal protection**



according to Regulation (EC) No 1907/2006

# Mixed indicator solution methylene blue / neutral red 0.1 % in ethanol denatured with MEK mixed 1:

Revision date: 06.09.2023 Product code: 26639 Page 5 of 12

## 8.1. Control parameters

#### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	

#### **DNEL/DMEL values**

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
64-17-5	ethanol					
Worker DNEL,	long-term	inhalation	systemic	950 mg/m³		
Worker DNEL,	long-term	dermal	systemic	343 mg/kg bw/day		
Consumer DNE	EL, long-term	inhalation	systemic	114 mg/m³		
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day		
Consumer DNE	EL, long-term	oral	systemic	87 mg/kg bw/day		

#### **PNEC** values

CAS No	Substance			
Environmen	Environmental compartment			
64-17-5	ethanol			
Freshwater		0,96 mg/l		
Freshwater (intermittent releases)		2,75 mg/l		
Marine water		0,79 mg/l		
Freshwater sediment		3,6 mg/kg		
Marine sediment		2,9 mg/kg		
Secondary poisoning		380 mg/kg		
Micro-organ	Micro-organisms in sewage treatment plants (STP)			
Soil	Soil			

### 8.2. Exposure controls

# Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

## Individual protection measures, such as personal protective equipment

# Eye/face protection

Suitable eye protection: goggles.

# Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact



according to Regulation (EC) No 1907/2006

# Mixed indicator solution methylene blue / neutral red 0.1 % in ethanol denatured with MEK mixed 1:

Revision date: 06.09.2023 Product code: 26639 Page 6 of 12

Trade name/designation: KCL 720 Camapren®

Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

## Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

#### **Environmental exposure controls**

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: clear
Odour: like: Ethanol
Odour threshold: No data available

Melting point/freezing point:

-114,5 °C

Boiling point or initial boiling point and

78 °C

boiling range:

Flammability: not applicable Lower explosion limits: 3,1 vol. % Upper explosion limits: 27,7 vol. % Flash point: ~17 °C 425 °C Auto-ignition temperature: not determined Decomposition temperature: pH-Value: No data available Viscosity / kinematic: No data available Water solubility: easily soluble

Solubility in other solvents

not determined

Dissolution rate:

Partition coefficient n-octanol/water:

Dispersion stability:

Vapour pressure:

No data available

No data available

No data available

(at 50 °C)

Vapour pressure:No data availableDensity:~0,79 g/cm³Relative density:No data availableBulk density:No data availableRelative vapour density:not determinedParticle characteristics:No data available

## 9.2. Other information



according to Regulation (EC) No 1907/2006

# Mixed indicator solution methylene blue / neutral red 0.1 % in ethanol denatured with MEK mixed 1:

Revision date: 06.09.2023 Product code: 26639 Page 7 of 12

## Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Sustaining combustion:

No data available

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

### Other safety characteristics

Evaporation rate: not determined Solvent separation test: No data available Solvent content: No data available Solid content: No data available Solid content: not determined Sublimation point: No data available Softening point: No data available Pour point: No data available

No data available:

Viscosity / dynamic: 1,2 mPa·s

(at 20 °C)

Flow time: No data available

# Further Information No data available

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Highly flammable.

Vapours can form explosive mixtures with air.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Oxidising agent

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

### 10.5. Incompatible materials

Plastic articles

Rubber articles

## 10.6. Hazardous decomposition products

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide

#### **Further information**

No data available

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

# Mixed indicator solution methylene blue / neutral red 0.1 % in ethanol denatured with MEK mixed 1:

Revision date: 06.09.2023 Product code: 26639 Page 8 of 12

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
64-17-5	ethanol						
	oral	LD50 10 mg/kg	0470	Rat	Study report (1976)	OECD Guideline 401	
	inhalation (4 h) vapour	LC50 12 mg/l	24,7	Rat	Study report (1980)	OECD Guideline 403	

#### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

# Information on likely routes of exposure

There are no data available on the mixture itself.

# Specific effects in experiment on an animal

There are no data available on the mixture itself.

#### Additional information on tests

There are no data available on the mixture itself.

## **Practical experience**

There are no data available on the mixture itself.

### 11.2. Information on other hazards

# **Endocrine disrupting properties**

There are no data available on the mixture itself.

#### Other information

Irritant

Dizziness

The product causes narcotic-like effects.

Inebriation

Vomiting

#### **Further information**

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

### **SECTION 12: Ecological information**



according to Regulation (EC) No 1907/2006

# Mixed indicator solution methylene blue / neutral red 0.1 % in ethanol denatured with MEK mixed 1:

Revision date: 06.09.2023 Product code: 26639 Page 9 of 12

## 12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name	Chemical name					
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
64-17-5	ethanol						
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

## 12.2. Persistence and degradability

There are no data available on the mixture itself.

# 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,77

### **BCF**

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# 12.7. Other adverse effects

Do not empty into drains.

#### **Further information**

Avoid release to the environment.

## **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

## **Disposal recommendations**

Do not allow to enter into surface water or drains.



according to Regulation (EC) No 1907/2006

# Mixed indicator solution methylene blue / neutral red 0.1 % in ethanol denatured with MEK mixed 1 :

Revision date: 06.09.2023 Product code: 26639 Page 10 of 12

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations.

#### Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

## **SECTION 14: Transport information**

I and	trans	nort (	ΔDR	/RID
∟anu	เเฉเเจ	DUIL		

**14.1. UN number or ID number:** UN 1170

14.2. UN proper shipping name: ETHANOL (ETHYL ALCOHOL)

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 3 Classification code: F1 Special Provisions: 144 601 Limited quantity: 1 I Excepted quantity: E2 Transport category: 2 Hazard No: 33 Tunnel restriction code: D/F

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL (ETHYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1Special Provisions:144 601Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL (ETHYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:144Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1170

**14.2. UN proper shipping name:** ETHANOL (ETHYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3

Special Provisions: A3 A58 A180

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2



according to Regulation (EC) No 1907/2006

# Mixed indicator solution methylene blue / neutral red 0.1 % in ethanol denatured with MEK mixed 1:

Revision date: 06.09.2023 Product code: 26639 Page 11 of 12

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to 2012/18/EU

P5c FLAMMABLE LIQUIDS

(SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

## 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

### **SECTION 16: Other information**

## Changes

This data sheet contains changes from the previous version in section(s): 9,12.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% Flam. Liq: Flammable liquid Eye Irrit: Eye irritation

## Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method

# Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.



according to Regulation (EC) No 1907/2006

# Mixed indicator solution methylene blue / neutral red 0.1 % in ethanol denatured with MEK mixed 1:

Revision date: 06.09.2023 Product code: 26639 Page 12 of 12

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)