

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Potassium plumbite solution R Reag. Ph. Eur., chapter 4.1.1

Revision date: 08.12.2023

Product code: 26667

Page 1 of 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Potassium plumbite solution R Reag. Ph. Eur., chapter 4.1.1

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

### Further Information

This product is a mixture. REACH Registration Number see section 3.

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Met. Corr. 1; H290  
Acute Tox. 4; H302  
Skin Corr. 1A; H314  
Eye Dam. 1; H318  
Repr. 1B; H360Df  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

potassium hydroxide  
lead di(acetate)

Signal word: Danger

#### Pictograms:



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Potassium plumbite solution R Reag. Ph. Eur., chapter 4.1.1**

Revision date: 08.12.2023

Product code: 26667

Page 2 of 11

**Hazard statements**

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H360Df	May damage the unborn child. Suspected of damaging fertility.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

**Special labelling of certain mixtures**

EUH201	Contains lead. Should not be used on surfaces liable to be chewed or sucked by children. Restricted to professional users.
--------	--

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Mixtures in aqueous solution

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1310-58-3	potassium hydroxide			30 - < 35 %
	215-181-3	019-002-00-8	01-2119487136-33	
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A; H290 H302 H314			
6080-56-4	lead di(acetate)			1 - < 5 %
	206-104-4	082-005-00-8	01-2119532202-56	
	Repr. 1A, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H360Df H373 H400 H410			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
1310-58-3	215-181-3	potassium hydroxide	30 - < 35 %
	oral: LD50 = 333 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		
6080-56-4	206-104-4	lead di(acetate)	1 - < 5 %
	oral: LD50 = ca. 5610 mg/kg		

**Further Information**

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Potassium plumbite solution R Reag. Ph. Eur., chapter 4.1.1

Revision date: 08.12.2023

Product code: 26667

Page 3 of 11

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

Take off immediately all contaminated clothing.

###### After inhalation

Provide fresh air.

Call a physician immediately.

###### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

###### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

###### After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

##### 4.2. Most important symptoms and effects, both acute and delayed

Vomiting

Spasms

Gastrointestinal complaints

##### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

###### Unsuitable extinguishing media

no restriction

##### 5.2. Special hazards arising from the substance or mixture

Non-combustible solids

Hazardous combustion products

In case of fire may be liberated:

Metal oxide smoke, toxic

##### 5.3. Advice for firefighters

Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

###### Additional information

Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

#### SECTION 6: Accidental release measures

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Potassium plumbite solution R Reag. Ph. Eur., chapter 4.1.1

Revision date: 08.12.2023

Product code: 26667

Page 4 of 11

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Corrosive to metals.

##### **For non-emergency personnel**

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures  
Do not breathe dust/fume/gas/mist/vapours/spray.

##### **For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Cover drains.  
Prevent spread over a wide area (e.g. by containment or oil barriers).  
Collect in closed and suitable containers for disposal.  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

##### **Other information**

Provide adequate ventilation.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### **6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

## **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Read label before use. Handle and open container with care.  
Do not breathe vapour/aerosol. Avoid: aerosol or mist formation  
When using do not eat, drink, smoke, sniff. Keep container tightly closed.  
Use personal protection equipment. Use extractor hood (laboratory).  
Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

##### **Advice on protection against fire and explosion**

Usual measures for fire prevention.

##### **Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs. Make available sufficient washing facilities  
Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

##### **Further information on handling**

Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary.  
Take off immediately all contaminated clothing and wash it before reuse.  
If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Potassium plumbite solution R Reag. Ph. Eur., chapter 4.1.1**

Revision date: 08.12.2023

Product code: 26667

Page 5 of 11

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Store in a well-ventilated place. Keep container tightly closed.  
Store in a place accessible by authorized persons only.

**Further information on storage conditions**

Store in a dry place.  
Unsuitable container/equipment material: Metal

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
1310-58-3	potassium hydroxide			
Worker DNEL, long-term		inhalation	local	1 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	1 mg/m <sup>3</sup>

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.  
If handled uncovered, arrangements with local exhaust ventilation have to be used.  
Do not breathe vapour/aerosol.  
Avoid: aerosol or mist formation

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

goggles  
Wear eye/face protection.

**Hand protection**

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact  
Trade name/designation: KCL 741 Dermatril® L  
Suitable material: NBR (Nitrile rubber) 0,11 mm  
Wearing time with permanent contact: > 480 min

By short-term hand contact  
Trade name/designation: KCL 741 Dermatril® L  
Suitable material: NBR (Nitrile rubber) 0,11 mm  
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Potassium plumbite solution R Reag. Ph. Eur., chapter 4.1.1

Revision date: 08.12.2023

Product code: 26667

Page 6 of 11

of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>,<) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Wear suitable protective clothing.  
Take off immediately all contaminated clothing.  
Wash hands before breaks and after work.

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	No data available	
Odour:	No data available	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		No data available
Viscosity / kinematic:		No data available
Water solubility:		No data available
Solubility in other solvents		No data available
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapour pressure:		No data available
Density:		No data available
Relative density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available
Particle characteristics:		No data available

### 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties	
No data available	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	No data available
Gas:	No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Potassium plumbite solution R Reag. Ph. Eur., chapter 4.1.1

Revision date: 08.12.2023

Product code: 26667

Page 7 of 11

Oxidizing properties  
No data available

#### Other safety characteristics

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	No data available
Flow time:	No data available

#### Further Information

Corrosive to metals.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Corrosive to metals.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Acids

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Corrosive to metals.

### 10.6. Hazardous decomposition products

In case of fire may be liberated:  
SECTION 5: Firefighting measures

#### Further information

No data available

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Harmful if swallowed.

#### ATEmix calculated

ATE (oral) 999,1 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Potassium plumbite solution R Reag. Ph. Eur., chapter 4.1.1**

Revision date: 08.12.2023

Product code: 26667

Page 8 of 11

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
1310-58-3	potassium hydroxide					
	oral	LD50 mg/kg	333	Rat	Fund. Appl. Toxicol., 8, 97-100 (1987)	OECD Guideline 425
6080-56-4	lead di(acetate)					
	oral	LD50 mg/kg	ca. 5610	Rat	Journal of the American College of Toxic	OECD Guideline 401

**Irritation and corrosivity**

Causes severe skin burns and eye damage.  
Causes serious eye damage.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

May damage the unborn child. Suspected of damaging fertility. (lead di(acetate))  
Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

There are no data available on the mixture itself.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

There are no data available on the mixture itself.

**Other information**

There are no data available on the mixture itself.

**Further information**

Vomiting  
Spasms  
Gastrointestinal complaints

**SECTION 12: Ecological information**

**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Potassium plumbite solution R Reag. Ph. Eur., chapter 4.1.1

Revision date: 08.12.2023

Product code: 26667

Page 9 of 11

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method	
6080-56-4	lead di(acetate)						
	Acute crustacea toxicity	EC50 mg/l	< 10	48 h	Daphnia magna	<a href="http://www.inchem.org/pages/ehc.html">http://www.inchem.org/pages/ehc.html</a> (19)	other: not reported

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Discharge into the environment must be avoided.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

**Contaminated packaging**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1719
<b>14.2. UN proper shipping name:</b>	CAUSTIC ALKALI LIQUID, N.O.S. (potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Classification code:	C5
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1719
--------------------------------------	---------

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Potassium plumbite solution R Reag. Ph. Eur., chapter 4.1.1**

Revision date: 08.12.2023

Product code: 26667

Page 10 of 11

<b>14.2. UN proper shipping name:</b>	CAUSTIC ALKALI LIQUID, N.O.S. (potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Classification code:	C5
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 1719
<b>14.2. UN proper shipping name:</b>	CAUSTIC ALKALI LIQUID, N.O.S. (potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 1719
<b>14.2. UN proper shipping name:</b>	CAUSTIC ALKALI LIQUID, N.O.S. (potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y840
Excepted quantity:	E2
IATA-packing instructions - Passenger:	851
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):  
lead di(acetate)

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Potassium plumbite solution R Reag. Ph. Eur., chapter 4.1.1**

Revision date: 08.12.2023

Product code: 26667

Page 11 of 11

Water hazard class (D): 2 - obviously hazardous to water

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 12.

**Abbreviations and acronyms**

- Met. Corr: Substance or mixture corrosive to metals
- Acute Tox: Acute toxicity
- Skin Corr: Skin corrosion
- Eye Dam: Eye damage
- Repr: Reproductive toxicity
- STOT RE: Specific target organ toxicity - repeated exposure
- Aquatic Acute: Acute aquatic hazard
- Aquatic Chronic: Chronic aquatic hazard

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Acute Tox. 4; H302	Calculation method
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Repr. 1B; H360Df	
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

- H290 May be corrosive to metals.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H360Df May damage the unborn child. Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH201 Contains lead. Should not be used on surfaces liable to be chewed or sucked by children.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*