

Safety Data Sheet

according to UK REACH Regulation

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

Revision date: 06.11.2023

Product code: 26840

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

UFI: DCAD-V2DW-200P-5QVT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0
E-mail: info@analytichem.de
Contact person: Abteilung Produktsicherheit
E-mail: produktsicherheit@analytichem.de
Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

Telefax: 0203/5194-290

Telephone: 0203/5194-107/117

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Met. Corr. 1; H290

Skin Corr. 1A; H314

Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

sulphuric acid

Signal word: Danger

Pictograms:



Safety Data Sheet

according to UK REACH Regulation

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

Revision date: 06.11.2023

Product code: 26840

Page 2 of 13

Hazard statements

- H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Precautionary statements

- P260 Do not breathe mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
7664-93-9	sulphuric acid			20 - < 25 %
	231-639-5	016-020-00-8	01-2119458838-20	
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318			
7722-84-1	hydrogen peroxide solution ... %			1 - < 5 %
	231-765-0	008-003-00-9		
	Ox. Liq. 1, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A; H271 H332 H302 H314			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
7664-93-9	231-639-5	sulphuric acid	20 - < 25 %
	oral: LD50 = 2140 mg/kg Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15		
7722-84-1	231-765-0	hydrogen peroxide solution ... %	1 - < 5 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 1026 mg/kg Ox. Liq. 1; H271: >= 70 - 100 Ox. Liq. 2; H272: >= 50 - < 70 Skin Corr. 1A; H314: >= 70 - 100 Skin Corr. 1B; H314: >= 50 - < 70 Skin Irrit. 2; H315: >= 35 - < 50 Eye Dam. 1; H318: >= 8 - < 50 Eye Irrit. 2; H319: >= 5 - < 8 STOT SE 3; H335: >= 35 - 100		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to UK REACH Regulation

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

Revision date: 06.11.2023

Product code: 26840

Page 3 of 13

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

Irritant

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Sulphur oxides

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

Safety Data Sheet

according to UK REACH Regulation

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

Revision date: 06.11.2023

Product code: 26840

Page 4 of 13

For non-emergency personnel

- Provide adequate ventilation.
- Use personal protection equipment.
- Avoid contact with skin, eyes and clothes.
- Remove persons to safety.
- Emergency procedures
- Consult an expert
- Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Read label before use.
- When using do not eat, drink, smoke, sniff.
- Handle and open container with care.
- Use personal protection equipment.
- Provide adequate ventilation.
- Do not breathe vapour/aerosol.
- Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

- Draw up and observe skin protection programme.
- Wash hands and face before breaks and after work and take a shower if necessary.
- Take off immediately all contaminated clothing and wash it before reuse.

Safety Data Sheet

according to UK REACH Regulation

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

Revision date: 06.11.2023

Product code: 26840

Page 5 of 13

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Corrosive to metals.

Unsuitable container/equipment material: Metal

The product develops hydrogen in an aqueous solution in contact with metals.

Hints on joint storage

national regulations

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
7722-84-1	Hydrogen peroxide	1	1.4		TWA (8 h)	WEL
		2	2.8		STEL (15 min)	WEL
7664-93-9	Sulphuric acid (mist)	-	0.05		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
7664-93-9	sulphuric acid			
	Worker DNEL, long-term	inhalation	local	0,05 mg/m ³
	Worker DNEL, acute	inhalation	local	0,1 mg/m ³
7722-84-1	hydrogen peroxide solution ... %			
	Worker DNEL, long-term	inhalation	local	1,4 mg/m ³
	Worker DNEL, acute	inhalation	local	3 mg/m ³
	Consumer DNEL, long-term	inhalation	local	0,21 mg/m ³
	Consumer DNEL, acute	inhalation	local	1,93 mg/m ³

Safety Data Sheet

according to UK REACH Regulation

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

Revision date: 06.11.2023

Product code: 26840

Page 6 of 13

PNEC values

CAS No	Substance	Value
Environmental compartment		
7664-93-9	sulphuric acid	
Freshwater		0,003 mg/l
Marine water		0 mg/l
Freshwater sediment		0,002 mg/kg
Marine sediment		0,002 mg/kg
Micro-organisms in sewage treatment plants (STP)		8,8 mg/l
7722-84-1	hydrogen peroxide solution ... %	
Freshwater		0,013 mg/l
Freshwater (intermittent releases)		0,014 mg/l
Marine water		0,013 mg/l
Freshwater sediment		0,047 mg/kg
Marine sediment		0,047 mg/kg
Micro-organisms in sewage treatment plants (STP)		4,66 mg/l
Soil		0,002 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact

Trade name/designation: KCL 730 Camatril® Velours

Recommended material: NBR (Nitrile rubber) 0,4 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 730 Camatril® Velours

Recommended material: NBR (Nitrile rubber) 0,4 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples

Safety Data Sheet

according to UK REACH Regulation

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

Revision date: 06.11.2023

Product code: 26840

Page 7 of 13

of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.
Wash hands before breaks and after work.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	odourless	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		not applicable not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available
Auto-ignition temperature:		No data available
Decomposition temperature:		not determined
pH-Value:		0,4
Viscosity / kinematic:		No data available
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		1,1444 g/cm ³
Bulk density:		No data available
Relative vapour density:		No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
No data available	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
Not oxidising.	

Other safety characteristics

Evaporation rate:	No data available
-------------------	-------------------

Safety Data Sheet

according to UK REACH Regulation

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

Revision date: 06.11.2023

Product code: 26840

Page 8 of 13

Solvent separation test:	No data available
Solvent content:	0
Solid content:	0
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	No data available
Flow time:	No data available

Further Information

Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Cellulose
Metal

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:
SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to UK REACH Regulation

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

Revision date: 06.11.2023

Product code: 26840

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7664-93-9	sulphuric acid				
	oral	LD50 2140 mg/kg	Rat	Am Ind Hyg Assoc J. 1969 Sep-Oct; 30(5):	The study was performed as part of a ser
7722-84-1	hydrogen peroxide solution ... %				
	oral	LD50 1026 mg/kg	Rat	Study report (1996)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1983)	other: US EPA Toxic Substance Health Eff
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

Safety Data Sheet

according to UK REACH Regulation

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

Revision date: 06.11.2023

Product code: 26840

Page 10 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
7664-93-9	sulphuric acid					
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus	Study report (2009) OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (2009) OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,025	65 d	Jordanella floridae	Water Research Vol. 11, 612 - 626, 1977 Groups of sexually mature flagfish
7722-84-1	hydrogen peroxide solution ... %					
	Acute fish toxicity	LC50 mg/l	16,4	96 h	Pimephales promelas	Study report (1989) other:
	Acute algae toxicity	ErC50 mg/l	1,38	72 h	Skeletonema costatum	Study report (1997) other: Paris Commission guidelines
	Acute crustacea toxicity	EC50	2,4 mg/l	48 h	Daphnia pulex	Study report (1989) other:
	Crustacea toxicity	NOEC mg/l	0,63	21 d	Daphnia magna	Publication (2008) other:
	Acute bacteria toxicity	EC50 ()	466 mg/l	0,5 h	activated sludge of a predominantly domestic sewage	Study report (1999) OECD Guideline 209

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
7722-84-1	hydrogen peroxide solution ... %	-1,57

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Further information

Do not allow to enter into surface water or drains.

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Safety Data Sheet

according to UK REACH Regulation

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

Revision date: 06.11.2023

Product code: 26840

Page 11 of 13

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.
Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B
Segregation group:	1 - acids

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8

Safety Data Sheet

according to UK REACH Regulation

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

Revision date: 06.11.2023

Product code: 26840

Page 12 of 13

Special Provisions:	A3 A803	
Limited quantity Passenger:	0.5 L	
Passenger LQ:	Y840	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		851
IATA-max. quantity - Passenger:		1 L
IATA-packing instructions - Cargo:		855
IATA-max. quantity - Cargo:		30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9.

Abbreviations and acronyms

Ox. Liq: Oxidising liquids

Met. Corr: Corrosive to metals

Acute Tox: Acute toxicity

Skin Corr: Skin corrosion

Eye Dam: Eye damage

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Safety Data Sheet

according to UK REACH Regulation

Wasserstoffperoxidlösung 1% in Schwefelsäure 20 % zur photometrischen Eisenbestimmung

Revision date: 06.11.2023

Product code: 26840

Page 13 of 13

Relevant H and EUH statements (number and full text)

H271	May cause fire or explosion; strong oxidiser.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H332	Harmful if inhaled.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)