

according to Regulation (EC) No 1907/2006

## Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 1 of 14

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

#### **Further Information**

This product is a mixture. REACH Registration Number see section 3.

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

## Regulation (EC) No 1272/2008

### Hazard components for labelling

ethyl acetate cyclohexane

Signal word: Danger



according to Regulation (EC) No 1907/2006

## Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 2 of 14

### Pictograms:









#### **Hazard statements**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

#### 2.3. Other hazards

No data available

## **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

#### **Hazardous components**

CAS No	Chemical name	Chemical name			
	EC No	Index No	Index No REACH No		
	Classification (Regulation (	EC) No 1272/2008)			
141-78-6	41-78-6 ethyl acetate			50 - < 55 %	
	205-500-4	607-022-00-5	01-2119475103-46		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066				
110-82-7	cyclohexane				
	203-806-2	601-017-00-1	01-2119463273-41		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410				

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc. L	Specific Conc. Limits, M-factors and ATE			
141-78-6	205-500-4	ethyl acetate	50 - < 55 %		
	dermal: LD50 = > 20000 mg/kg; oral: LD50 = 4934 mg/kg				
110-82-7	203-806-2	03-806-2 cyclohexane			
	inhalation: LC50 = > 5540 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg				

## **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).



according to Regulation (EC) No 1907/2006

## Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 3 of 14

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

No data available

#### After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

#### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

Remove contact lenses, if present and easy to do. Continue rinsing.

Consult an ophthalmologist.

#### After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Irritant, corrosive

Vapours may cause drowsiness and dizziness.

Dizziness, Unconsciousness, Vomiting, Headache

## 4.3. Indication of any immediate medical attention and special treatment needed

No data available

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO2)

Foam

Extinguishing powder

#### Unsuitable extinguishing media

no restriction

#### 5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

#### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.



according to Regulation (EC) No 1907/2006

## Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 4 of 14

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

#### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

## 6.3. Methods and material for containment and cleaning up

#### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

## For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

## Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

#### **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Provide adequate ventilation. Do not breathe vapour.

## Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 5 of 14

### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

#### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Further information on storage conditions

Keep container tightly closed and dry.

Keep cool. Protect from sunlight.

### 7.3. Specific end use(s)

Laboratory chemicals

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
110-82-7	Cyclohexane	200	700		TWA (8 h)	
141-78-6	Ethyl acetate	200	734		TWA (8 h)	
		400	1468		STEL (15 min)	



according to Regulation (EC) No 1907/2006

# Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 6 of 14

## **DNEL/DMEL values**

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
141-78-6	ethyl acetate					
Worker DNEL	., long-term	inhalation	systemic	734 mg/m³		
Worker DNEL	., acute	inhalation	systemic	1468 mg/m³		
Worker DNEL	., long-term	inhalation	local	734 mg/m³		
Worker DNEL	., acute	inhalation	local	1468 mg/m³		
Worker DNEL	., long-term	dermal	systemic	63 mg/kg bw/day		
Consumer DN	NEL, long-term	inhalation	systemic	367 mg/m³		
Consumer DN	NEL, acute	inhalation	systemic	734 mg/m³		
Consumer DN	NEL, long-term	inhalation	local	367 mg/m³		
Consumer DN	NEL, acute	inhalation	local	734 mg/m³		
Consumer DN	NEL, long-term	dermal	systemic	37 mg/kg bw/day		
Consumer DN	NEL, long-term	oral	systemic	4,5 mg/kg bw/day		
110-82-7	cyclohexane					
Consumer DNEL, long-term		inhalation	systemic	206 mg/m³		
Consumer DN	NEL, acute	inhalation	systemic	412 mg/m³		
Consumer DN	NEL, long-term	inhalation	local	206 mg/m³		
Consumer DN	NEL, acute	inhalation	local	412 mg/m³		
Consumer DN	NEL, long-term	dermal	systemic	1186 mg/kg bw/day		
Consumer DNEL, long-term		oral	systemic	59,4 mg/kg bw/day		
Worker DNEL	., long-term	inhalation	systemic	700 mg/m³		
Worker DNEL, acute		inhalation	systemic	1400 mg/m³		
Worker DNEL	, long-term	inhalation	local	700 mg/m³		
Worker DNEL	, acute	inhalation	local	1400 mg/m³		
Worker DNEL	., long-term	dermal	systemic	2016 mg/kg bw/day		



according to Regulation (EC) No 1907/2006

# Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 7 of 14

#### **PNEC values**

CAS No	Substance			
Environmen	Environmental compartment			
141-78-6	ethyl acetate			
Freshwater	Freshwater			
Freshwater	(intermittent releases)	1,65 mg/l		
Marine wate	r	0,024 mg/l		
Freshwater	sediment	1,15 mg/kg		
Marine sedi	nent	0,115 mg/kg		
Secondary p	poisoning	200 mg/kg		
Micro-organ	650 mg/l			
Soil		0,148 mg/kg		
110-82-7	0-82-7 cyclohexane			
Freshwater		0,207 mg/l		
Freshwater	(intermittent releases)	0,207 mg/l		
Marine wate	Marine water			
Freshwater	16,68 mg/kg			
Marine sedi	16,68 mg/kg			
Micro-organ	Micro-organisms in sewage treatment plants (STP)			
Soil				

#### 8.2. Exposure controls

#### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

## Individual protection measures, such as personal protective equipment

### Eye/face protection

goggles

Face protection umbrella

## Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact: No data available

By short-term hand contact

Trade name/designation: KCL 898 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,7 mm Wearing time with occasional contact (splashes): > 30 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.



according to Regulation (EC) No 1907/2006

## Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 8 of 14

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

#### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: characteristic
Odour threshold: No data available

Melting point/freezing point:

No data available
Boiling point or initial boiling point and

>35 °C

boiling range:

Flammability: No data available No data available Lower explosion limits: Upper explosion limits: No data available <21 °C Flash point: Auto-ignition temperature: No data available Decomposition temperature: No data available No data available pH-Value: Viscosity / kinematic: No data available Water solubility: No data available

Solubility in other solvents

No data available

Dissolution rate: No data available Partition coefficient n-octanol/water: No data available Dispersion stability: No data available Vapour pressure: No data available Vapour pressure: No data available Density: 0,83127 g/cm<sup>3</sup> No data available Relative density: No data available Bulk density: No data available Relative vapour density: Particle characteristics: No data available

#### 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 9 of 14

Solvent separation test: No data available Solvent content: No data available No data available Solid content: Sublimation point: No data available Softening point: No data available Pour point: No data available No data available No data available Viscosity / dynamic: Flow time: No data available

Further Information
No data available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Vapours may form explosive mixtures with air.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Oxidising agent

#### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### 10.5. Incompatible materials

Plastic articles

#### 10.6. Hazardous decomposition products

**SECTION 5: Firefighting measures** 

#### **Further information**

No data available

### **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 10 of 14

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
141-78-6	ethyl acetate	ethyl acetate					
	oral	LD50 mg/kg	4934	Rabbit	Ind. Med. Vol. 41, No.4, 31 - 33 (1972)	OECD Guideline 401	
	dermal	LD50 mg/kg	> 20000	Rabbit	Am Ind Hyg Ass J, 23, 95 (1962)	Similar to one day cuff method of Draize	
110-82-7	cyclohexane						
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401	
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)	OECD Guideline 402	
	inhalation (4 h) vapour	LC50 mg/l	> 5540	Rat	Study report (1981)	OECD Guideline 403	

### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

#### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

May cause drowsiness or dizziness. (ethyl acetate; cyclohexane)

Organs affected: central nervous system

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

#### Information on likely routes of exposure

There are no data available on the mixture itself.

#### Specific effects in experiment on an animal

There are no data available on the mixture itself.

#### Additional information on tests

There are no data available on the mixture itself.

#### **Practical experience**

There are no data available on the mixture itself.

## 11.2. Information on other hazards

## **Endocrine disrupting properties**

There are no data available on the mixture itself.

## Other information

There are no data available on the mixture itself.

## **Further information**

corrosive, Irritant

Vapours may cause drowsiness and dizziness.

Dizziness, Unconsciousness, Vomiting, Headache

## **SECTION 12: Ecological information**



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 11 of 14

#### 12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
141-78-6	ethyl acetate						
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas	Publication (1984)	other: US EPA method E03-05
	Fish toxicity	NOEC mg/l	< 9,65	32 d	Pimephales promelas	http://www.epa.go v/ecotox (1992)	OECD Guideline 210
	Crustacea toxicity	NOEC	2,4 mg/l	21 d	Daphnia magna	Water Research 23: 501-510. (1989)	other: see principles of method below
110-82-7	cyclohexane						
	Acute fish toxicity	LC50 mg/l	4,53	96 h	Pimephales promelas	Vol. 5, Centre for Lake Superior Studies	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	9,317	72 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50	0,9 mg/l	48 h	Daphnia magna	Publication (1987)	OECD Guideline 202

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
141-78-6	ethyl acetate	0,68
110-82-7	cyclohexane	3,44

### **BCF**

CAS No	Chemical name	BCF	Species	Source
141-78-6	ethyl acetate	30	Leuciscus idus melanotus	Chemosphere 14, 1589
110-82-7	cyclohexane	167	Pimephales promelas	J. Fish. Board Can.

### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

## **Further information**

There are no data available on the mixture itself.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods



according to Regulation (EC) No 1907/2006

### Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 12 of 14

#### **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

#### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (cyclohexane, ethyl acetate)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (cyclohexane, ethyl acetate)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (cyclohexane, ethyl acetate)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:274Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (cyclohexane, ethyl acetate)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A3Limited quantity Passenger:1 LPassenger LQ:Y341



according to Regulation (EC) No 1907/2006

## Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 13 of 14

Excepted quantity: E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: cyclohexane

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 57

Information according to 2012/18/EU

(SEVESO III):

P5c

Additional information:

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

E1 Hazardous to the Aquatic Environment

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

## **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 12.

## Abbreviations and acronyms

Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

## Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.
H319 Causes serious eye irritation.



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Ethyl acetate / cyclohexane mixture volumetrically 50: 50 mixture for residue analysis

Revision date: 23.08.2023 Product code: 27191 Page 14 of 14

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)