

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

UFI: 1GRE-125X-H002-66DY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH
ACD
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0
Telefax: 0203/5194-290
E-mail: info@analytichem.de
Contact person: Abteilung Produktsicherheit
Telephone: 0203/5194-107/117
E-mail: produktsicherheit@analytichem.de
Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Warning

Pictograms:



Hazard statements

H290

May be corrosive to metals.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 2 of 14

H315 Causes skin irritation.
H319 Causes serious eye irritation.

Precautionary statements

P280 Wear protective gloves and eye/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352 IF ON SKIN: Wash with plenty of water.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P406 Store in a corrosion-resistant container with a resistant inner liner.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7697-37-2	nitric acid			1 - < 5 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A; H272 H290 H331 H314 EUH071			
7697-37-2	nitric acid			< 0.01 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A; H272 H290 H331 H314 EUH071			
1336-21-6	Ammonia			< 0.001 %
	215-647-6	007-001-01-2	01-2119488876-14	
	Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 2; H314 H400 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
7697-37-2	231-714-2	nitric acid	1 - < 5 %
		inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20	
7697-37-2	231-714-2	nitric acid	< 0.01 %
		inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20	
1336-21-6	215-647-6	Ammonia	< 0.001 %
		inhalation: LC50 = 4230 mg/l (vapours); oral: LD50 = 350 mg/kg STOT SE 3; H335: >= 5 - 100 Aquatic Acute 1; H400: M=10	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 3 of 14

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

Methaemoglobinaemia

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multiement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 4 of 14

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Collect in closed and suitable containers for disposal.
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use.
When using do not eat, drink, smoke, sniff.
Handle and open container with care.
Use personal protection equipment.
Provide adequate ventilation.
Do not breathe vapour/aerosol.
Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 5 of 14

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Corrosive to metals.

Unsuitable container/equipment material: Metal

The product develops hydrogen in an aqueous solution in contact with metals.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
7429-90-5	Aluminium metal (Respirable Fraction)	-	1		TWA (8 h)	
7664-41-7	Ammonia, anhydrous	20	14		TWA (8 h)	
		50	36		STEL (15 min)	
12125-02-9	Ammonium chloride, fume	-	10		TWA (8 h)	
		-	20		STEL (15 min)	
10043-35-3	Borate compounds inorganic: boric acid	-	2		TWA (8 h)	
7440-50-8	Copper, dusts and mists	-	1		TWA (8 h)	
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 6 of 14

DNEL/DMEL values

CAS No	Substance	DNEL type	Exposure route	Effect	Value
12125-02-9	ammonium chloride	Consumer DNEL, long-term	inhalation	systemic	9,9 mg/m ³
		Consumer DNEL, long-term	dermal	systemic	114 mg/kg bw/day
		Consumer DNEL, long-term	oral	systemic	11,4 mg/kg bw/day
		Worker DNEL, long-term	inhalation	systemic	33,5 mg/m ³
		Worker DNEL, long-term	dermal	systemic	190 mg/kg bw/day
1336-21-6	Ammonia	Worker DNEL, long-term	inhalation	systemic	47,6 mg/m ³
		Worker DNEL, acute	inhalation	systemic	47,6 mg/m ³
		Worker DNEL, long-term	inhalation	local	14 mg/m ³
		Worker DNEL, acute	inhalation	local	36 mg/m ³
		Worker DNEL, long-term	dermal	systemic	6,8 mg/kg bw/day
		Worker DNEL, acute	dermal	systemic	6,8 mg/kg bw/day
		Consumer DNEL, long-term	inhalation	systemic	23,8 mg/m ³
		Consumer DNEL, acute	inhalation	systemic	23,8 mg/m ³
		Consumer DNEL, long-term	inhalation	local	2,8 mg/m ³
		Consumer DNEL, acute	inhalation	local	7,2 mg/m ³
		Consumer DNEL, long-term	dermal	systemic	68 mg/kg bw/day
		Consumer DNEL, acute	dermal	systemic	68 mg/kg bw/day
		Consumer DNEL, long-term	oral	systemic	6,8 mg/kg bw/day
		Consumer DNEL, acute	oral	systemic	6,8 mg/kg bw/day
10043-35-3	boric acid	Worker DNEL, long-term	inhalation	systemic	8,3 mg/m ³
		Worker DNEL, long-term	dermal	systemic	392 mg/kg bw/day
		Consumer DNEL, long-term	inhalation	systemic	4,15 mg/m ³
		Consumer DNEL, long-term	dermal	systemic	196 mg/kg bw/day
		Consumer DNEL, long-term	oral	systemic	0,98 mg/kg bw/day
		Consumer DNEL, acute	oral	systemic	0,98 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 7 of 14

PNEC values

CAS No	Substance	Value
Environmental compartment		
12125-02-9	ammonium chloride	
Freshwater		1,2 mg/l
Freshwater (intermittent releases)		1,2 mg/l
Marine water		11,2 mg/l
Micro-organisms in sewage treatment plants (STP)		16,2 mg/l
Soil		0,163 mg/kg
1336-21-6	Ammonia	
Freshwater		0,001 mg/l
Freshwater (intermittent releases)		0,007 mg/l
Marine water		0,001 mg/l
10043-35-3	boric acid	
Freshwater		2,9 mg/l
Freshwater (intermittent releases)		13,7 mg/l
Marine water		2,9 mg/l
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		5,7 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 8 of 14

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>,<) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.
Wash hands before breaks and after work.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation
The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	odourless	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		not applicable not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available
Auto-ignition temperature:		No data available
Decomposition temperature:		not determined
pH-Value:		0
Viscosity / kinematic:		No data available
Water solubility:		completely miscible
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		1,011 g/cm ³
Bulk density:		No data available
Relative vapour density:		not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
No data available	
Sustaining combustion:	No data available
Self-ignition temperature	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 9 of 14

Solid: not applicable
 Gas: not applicable
 Oxidizing properties
 Not oxidising.

Other safety characteristics

Evaporation rate: not determined
 Solvent separation test: No data available
 Solvent content: 0
 Solid content: 0
 Sublimation point: No data available
 Softening point: No data available
 Pour point: No data available
 No data available:
 Viscosity / dynamic: No data available
 Flow time: No data available

Further Information

Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Cellulose
 Metal

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:
 SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 10 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7697-37-2	nitric acid				
	inhalation vapour	ATE 2,65 mg/l			
7697-37-2	nitric acid				
	inhalation vapour	ATE 2,65 mg/l			
1336-21-6	Ammonia				
	oral	LD50 350 mg/kg	Rat	Journal of Industrial Hygiene and Toxicology	OECD Guideline 401
	inhalation (1 h) vapour	LC50 4230 mg/l	Mouse	Bull. Environm. Contam. Toxicol, 1982, 2	Assessment of acute inhalation toxicity

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 11 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
7697-37-2	nitric acid					
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry, other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009) Growth tests estimated the test chemical
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977) Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	Activated sludge	Study report (2008) OECD Guideline 209
7697-37-2	nitric acid					
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry, other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009) Growth tests estimated the test chemical
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977) Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	Activated sludge	Study report (2008) OECD Guideline 209
1336-21-6	Ammonia					
	Acute fish toxicity	LC50 mg/l	0,75 - 3,4	96 h	Pimephales promelas	Trans Amer Fish Soc; 112 (5). 1983. 705- Assessment of acute toxicity in the fath
	Acute crustacea toxicity	EC50	101 mg/l	48 h	Daphnia magna	Environ. Toxicol. Chem. 5: 443-447 (1986) other: ASTM E729-80
	Fish toxicity	NOEC	1,2 mg/l	61 d	Oncorhynchus gorbuscha	Fish. Bull. 78(3): 641-648 (1980) OECD Guideline 210

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1336-21-6	Ammonia	-1,38

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 12 of 14

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C1
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C1
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number or ID number:	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	223, 274
Limited quantity:	5 L
Excepted quantity:	E1

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 13 of 14

EmS: F-A, S-B
Segregation group: 1 - acids

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3264
14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
Hazard label: 8
Special Provisions: A3 A803
Limited quantity Passenger: 1 L
Passenger LQ: Y841
Excepted quantity: E1
IATA-packing instructions - Passenger: 852
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 856
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 30, Entry 75

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung Spurenelemente 3.0 +Chlorid Nr. 3 11 Kationen + 1 Anion in Salpetersäure

Revision date: 10.04.2024

Product code: 27354

Page 14 of 14

Abbreviations and acronyms

Pyr. Sol: Pyrophoric solid
Water-react: Substance and mixture which, in contact with water, emits flammable gas
Ox. Liq: Oxidising liquid
Met. Corr: Substance or mixture corrosive to metals
Flam. Sol: Flammable solid
Acute Tox: Acute toxicity
Skin Corr: Skin corrosion
Skin Irrit: Skin irritation
Eye Irrit: Eye irritation
Repr: Reproductive toxicity
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)