

according to Regulation (EC) No 1907/2006

# Multielement-Standardlösung UWS 1 28 Elemente in Salpetersäure 2%

Revision date: 31.05.2022 Product code: 27599 Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Multielement-Standardlösung UWS 1 28 Elemente in Salpetersäure 2%

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

### Uses advised against

Do not use for private purposes (household).

## 1.3. Details of the supplier of the safety data sheet

Company name: Fa. Bernd Kraft GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

e-mail: info@berndkraft.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

produktsicherheit@berndkraft.de e-mail·

Internet: www.berndkraft.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, number:

Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

#### **Further Information**

This product is a mixture. REACH Registration Number see section 3.

### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Skin Irrit. 2; H315 Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

## Regulation (EC) No 1272/2008

Signal word: Warning

Pictograms:



### **Hazard statements**

H290 May be corrosive to metals. H315 Causes skin irritation. H319 Causes serious eye irritation.



according to Regulation (EC) No 1907/2006

# Multielement-Standardlösung UWS 1 28 Elemente in Salpetersäure 2%

Revision date: 31.05.2022 Product code: 27599 Page 2 of 13

## **Precautionary statements**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P280 Wear protective gloves and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P406 Store in a corrosion-resistant container with a resistant inner liner.

### Special labelling of certain mixtures

EUH208 Contains nickel dinitrate. May produce an allergic reaction.

## 2.3. Other hazards

No information available.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Chemical characterization

Mixtures in aqueous solution

### **Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No	1272/2008)		
7697-37-2	nitric acid			1 - < 5 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, Acute Tox.	3, Skin Corr. 1A; H272 H290 H331 H	H314 EUH071	
13138-45-9	nickel dinitrate		< 0.1 %	
	236-068-5	028-012-00-1		
	Ox. Sol. 2, Carc. 1A, Muta. 2, Repr Resp. Sens. 1, Skin Sens. 1, STOT H360D H332 H302 H315 H318 H3:			
7761-88-8	silver nitrate			< 0.1 %
·	231-853-9	047-001-00-2	01-2119513705-43	
	Ox. Sol. 2, Met. Corr. 1, Skin Corr. H290 H314 H318 H400 H410			

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc.	Limits, M-factors and ATE			
7697-37-2	231-714-2	nitric acid	1 - < 5 %		
		2,65 mg/kg (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= Corr. 1B; H314: >= 5 - < 20			
13138-45-9	236-068-5	nickel dinitrate	< 0.1 %		
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = 361,9 mg/kg Skin Irrit. 2; H315: >= 20 - 100 Skin Sens. 1; H317: >= 0,01 - 100 STOT RE 1; H372: >= 1 - 100 STOT RE 2; H373: >= 0,1 - < 1 M acute; H400: M=1 M chron.; H410: M=1				
7761-88-8	231-853-9	silver nitrate	< 0.1 %		
	dermal: LD50 = M chron.; H410	= > 348 mg/kg; oral: LD50 = > 2000 mg/kg M acute; H400: M=1000 : M=100			



according to Regulation (EC) No 1907/2006

## Multielement-Standardlösung UWS 1 28 Elemente in Salpetersäure 2%

Revision date: 31.05.2022 Product code: 27599 Page 3 of 13

#### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

No data available

#### After inhalation

Provide fresh air.

Call a doctor if you feel unwell.

#### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

## After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

#### After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

Irritant

Methaemoglobinaemia

Allergic reactions

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Non-flammable.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

## **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

## **SECTION 6: Accidental release measures**



according to Regulation (EC) No 1907/2006

## Multielement-Standardlösung UWS 1 28 Elemente in Salpetersäure 2%

Revision date: 31.05.2022 Product code: 27599 Page 4 of 13

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Corrosive to metals.

### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

**Emergency procedures** 

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

#### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

## Advice on safe handling

Read label before use.

When using do not eat, drink, smoke, sniff.

Handle and open container with care.

Use personal protection equipment.

Provide adequate ventilation.

Do not breathe vapour/aerosol.

Avoid contact with skin, eyes and clothes.

# Advice on protection against fire and explosion

Usual measures for fire prevention.

# Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

## Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.



according to Regulation (EC) No 1907/2006

# Multielement-Standardlösung UWS 1 28 Elemente in Salpetersäure 2%

Revision date: 31.05.2022 Product code: 27599 Page 5 of 13

Take off immediately all contaminated clothing and wash it before reuse.

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Corrosive to metals.

Unsuitable container/equipment material: Metal

The product develops hydrogen in an aqueous solution in contact with metals.

## Further information on storage conditions

Keep container tightly closed.

## 7.3. Specific end use(s)

Laboratory chemicals

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

#### **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
13138-45-9	nickel dinitrate	•	•	
Consumer D	NEL, acute	oral	systemic	0,012 mg/kg bw/day
Consumer D	NEL, long-term	oral	systemic	0,02 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	104 mg/m³
Worker DNEL, acute		inhalation	local	1,6 mg/m³
Consumer DNEL, acute		inhalation	systemic	8,8 mg/m³
Consumer D	NEL, acute	inhalation	local	0,1 mg/m³
7761-88-8	silver nitrate			
Consumer D	NEL, long-term	oral	systemic	0,02 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	0,016 mg/m³
Consumer D	NEL, long-term	inhalation	systemic	0,006 mg/m³



according to Regulation (EC) No 1907/2006

# Multielement-Standardlösung UWS 1 28 Elemente in Salpetersäure 2%

Revision date: 31.05.2022 Product code: 27599 Page 6 of 13

#### **PNEC values**

CAS No	Substance			
Environmenta	Environmental compartment			
13138-45-9	nickel dinitrate			
Freshwater		0,0071 mg/l		
Freshwater (i	ntermittent releases)	0 mg/l		
Marine water		0,0086 mg/l		
Freshwater s	ediment	109 mg/kg		
Marine sedim	ent	109 mg/kg		
Secondary poisoning		0,12 mg/kg		
Micro-organisms in sewage treatment plants (STP)		0,33 mg/l		
Soil		29,9 mg/kg		
7761-88-8	silver nitrate			
Freshwater		0,00004 mg/l		
Marine water		0,00086 mg/l		
Freshwater sediment		438,13 mg/kg		
Marine sediment		438,13 mg/kg		
Micro-organisms in sewage treatment plants (STP)		0,025 mg/l		
Soil	Soil			

### 8.2. Exposure controls

## Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

## Individual protection measures, such as personal protective equipment

### Eye/face protection

goggles

Wear eye/face protection.

### **Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with occasional contact (splashes): > 480 min



according to Regulation (EC) No 1907/2006

# Multielement-Standardlösung UWS 1 28 Elemente in Salpetersäure 2%

Revision date: 31.05.2022 Product code: 27599 Page 7 of 13

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

## Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

#### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour:

Odour: odourless

Odour threshold: No data available

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

boiling range:

Sublimation point:

Softening point:

No data available

No data available

Pour point:

No data available

No data available:

Flash point: No data available

**Flammability** 

Solid/liquid: not applicable
Gas: not applicable

**Explosive properties** 

No data available

Lower explosion limits:

Upper explosion limits:

not determined

not determined

No data available

Self-ignition temperature

Solid: not applicable not applicable Gas: Decomposition temperature: not determined pH-Value: acidic Viscosity / dynamic: No data available Viscosity / kinematic: No data available Flow time: No data available Water solubility: completely miscible

Solubility in other solvents

not determined



according to Regulation (EC) No 1907/2006

## Multielement-Standardlösung UWS 1 28 Elemente in Salpetersäure 2%

Revision date: 31.05.2022 Product code: 27599 Page 8 of 13

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Density:

No data available

Bulk density:

No data available

Relative vapour density:

not determined

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion:

No data available

Oxidizing properties Not oxidising.

Other safety characteristics

Solvent separation test:

Solvent content:

Solid content:

Evaporation rate:

No data available

0

not determined

Further Information
Corrosive to metals.

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Corrosive to metals.

## 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

Alkali (lye)

## 10.4. Conditions to avoid

No data available

### 10.5. Incompatible materials

Cellulose

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

# 10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

#### **Further information**

No data available

## **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

#### **Acute toxicity**

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

# Multielement-Standardlösung UWS 1 28 Elemente in Salpetersäure 2%

Revision date: 31.05.2022 Product code: 27599 Page 9 of 13

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
7697-37-2	nitric acid								
	inhalation vapour	ATE 2,6	5 mg/kg						
13138-45-9	nickel dinitrate								
	oral	LD50 mg/kg	361,9	Rat	Regul Toxicol and Pharmacol (doi.org/10.	OECD Guideline 425			
	inhalation vapour	ATE	11 mg/l						
	inhalation dust/mist	ATE	1,5 mg/l						
7761-88-8	silver nitrate								
	oral	LD50 mg/kg	> 2000	Rat	Study report (1993)	OECD Guideline 401			
	dermal	LD50 mg/kg	> 348	Guinea pig	J. Vet. Med. Sci.73: 1417 - 1423. (2011)	OECD Guideline 434			

### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

### Sensitising effects

Contains nickel dinitrate. May produce an allergic reaction.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

## Additional information on tests

There are no data available on the preparation/mixture itself.

#### **Practical experience**

There are no data available on the preparation/mixture itself.

### 11.2. Information on other hazards

### Other information

There are no data available on the preparation/mixture itself.

#### Further information

There are no data available on the preparation/mixture itself.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

# Multielement-Standardlösung UWS 1 28 Elemente in Salpetersäure 2%

Revision date: 31.05.2022 Product code: 27599 Page 10 of 13

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
7697-37-2	nitric acid						
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209
3138-45-9	nickel dinitrate						
	Acute fish toxicity	LC50 mg/l	15,3	96 h	Oncorhynchus mykiss	Aquatic Toxicology 63 (2003) 65-82 (2003	other: not reported
	Acute algae toxicity	ErC50 mg/l	0,237	72 h	Ankistrodesmus falcatus	Publication (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,2663	48 h	Ceriodaphnia dubia	Study report (2004)	other: American society of testing and m
	Fish toxicity	NOEC mg/l	0,057	32 d	Pimephales promelas	Water Resources Research Institute. Kent	other: ASTM 1980, E-729
	Algae toxicity	NOEC	0,6 mg/l	14 d	Anabaena cylindrica	Environ. Pollut. (Series A). 25(4):241-2	other: not reported
	Crustacea toxicity	NOEC mg/l	0,04	42 d	Daphnia magna	Wat. Res. 24(7):845-852 (1990)	Chronic exposure to sublethal concentrat
	Acute bacteria toxicity	(EC50	33 mg/l)	0,5 h	Activated sludge	Journal of Hazardous Materials. B139:332	ISO 8192
7761-88-8	silver nitrate						
	Acute fish toxicity	LC50 mg/l	0,0012	96 h	Pimephales promelas	Environmental Toxicology and Chemistry.	A guideline was not specified. The test
	Acute algae toxicity	ErC50 mg/l	0,0099	96 h	Pseudokirchneriella subcapitata	Environmental Science and Technology. 44	eline: U.S. Environmental Protection Age
	Acute crustacea toxicity	EC50 mg/l	0,00022	48 h	Daphnia magna	Environmental Toxicology and Chemistry.	The protective effect of reactive sulphi
	Fish toxicity	NOEC 0,00125 n	> ng/l	73 d	Oncorhynchus mykiss	Environmental Toxicology and Chemistry 2	other: ASTM 1241-98
	Algae toxicity	NOEC mg/l	0,0012	14 d	Champia parvula	in Bishop WE, Cardwell RD Heidolph BB (E	The toxicity tests lasted 11 days fo th



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Multieleme	ent-Standa	rdlösung	UWS 1 28 Elemente in	Salpetersäure 2	2%	
Revision date: 31.05.2022		Pro	oduct code: 27599		Page 11 d	of 13
Crustacea toxicity	NOEC mg/l	0,00031	20 d Isonychia bicolour	Environmental Toxicology and Chemistry.	20 day sublethal effects on representati	

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### BCF

CAS No	Chemical name	BCF	Species	Source
13138-45-9	nickel dinitrate	23	Spirodela polyrhiza	Ecotoxicology and en
7761-88-8	silver nitrate	70	Cyprinus carpio	Water, Air and Soil

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There are no data available on the mixture itself.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

Discharge into the environment must be avoided.

#### **Further information**

Do not allow to enter into surface water or drains.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

UN 3264 14.1. UN number or ID number:

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid) 14.2. UN proper shipping name:

14.3. Transport hazard class(es): 8 14.4. Packing group: Ш Hazard label: 8 Classification code: C1 **Special Provisions:** 274 Limited quantity: 5 I Excepted quantity: E1 Transport category: 3 Hazard No: 80



according to Regulation (EC) No 1907/2006

# Multielement-Standardlösung UWS 1 28 Elemente in Salpetersäure 2%

Revision date: 31.05.2022 Product code: 27599 Page 12 of 13

Tunnel restriction code:

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Classification code:C1Special Provisions:274Limited quantity:5 LExcepted quantity:E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:223, 274Limited quantity:5 LExcepted quantity:E1

EmS: F-A, S-B Segregation group: 1 - acids

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:1 LPassenger LQ:Y841Excepted quantity:E1

IATA-packing instructions - Passenger:852IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:856IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: strongly corrosive.

## 14.7. Maritime transport in bulk according to IMO instruments

not applicable

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 75

#### **National regulatory information**



according to Regulation (EC) No 1907/2006

# Multielement-Standardlösung UWS 1 28 Elemente in Salpetersäure 2%

Revision date: 31.05.2022 Product code: 27599 Page 13 of 13

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

## Relevant H and EUH statements (number and full text)

	,
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341	Suspected of causing genetic defects.
H350i	May cause cancer by inhalation.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains nickel dinitrate. May produce an allergic reaction.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)