

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 1 of 14

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

**1.4. Emergency telephone** For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

### **Further Information**

This product is a mixture. REACH Registration Number see section 3.

## **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

# Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Flam. Lig. 2; H225

Acute Tox. 3; H301 Acute Tox. 3; H311

Acute Tox. 3: H331

Skin Corr. 1B; H314 Eye Dam. 1; H318

STOT SE 1; H370

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

# Regulation (EC) No 1272/2008

# Hazard components for labelling

methanol

sodium hydroxide

Signal word: Danger



according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 2 of 14

## Pictograms:









### Hazard statements

H225 Highly flammable liquid and vapour.

H290 May be corrosive to metals.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H314 Causes severe skin burns and eye damage.

H370 Causes damage to organs.

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with P303+P361+P353

water or shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if P305+P351+P338

> present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P310 P403+P235 Store in a well-ventilated place. Keep cool.

## 2.3. Other hazards

No data available

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

### Relevant ingredients

CAS No	Chemical name			Quantity	
	EC No	Index No	ndex No REACH No		
	Classification (Regulation (EC) No 1272/2008)				
67-56-1	methanol			95 - < 100 %	
	200-659-6	200-659-6 603-001-00-X 01-2119433307-44			
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370				
1310-73-2	sodium hydroxide			1 - < 5 %	
	215-185-5	011-002-00-6 01-2119457892-27			
	Met. Corr. 1, Skin Corr. 1A; H290 H314				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc. Limits, M-factors and ATE				
67-56-1	200-659-6	659-6 methanol			
	inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10				
1310-73-2	215-185-5	1 - < 5 %			
		H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < ; H319: >= 0,5 - < 2			



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 3 of 14

#### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection!

### After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

#### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

## After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water.

Remove contact lenses, if present and easy to do. Continue rinsing.

Consult an ophthalmologist.

### After ingestion

Provide fresh air.

Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

Notes for the doctor: Methanol

### 4.2. Most important symptoms and effects, both acute and delayed

Irritant, Dizziness, Dizziness

Anaesthetic state, Agitation, Spasms

Inebriation, Vomiting, Headache

Impairment of vision, Dyspnoea, Cough

Repeated exposure may cause skin dryness or cracking., corrosive

Risk of serious damage to eyes.

Circulatory collapse, Corneal opacity.

## 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor : Methanol

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

### Suitable extinguishing media

Carbon dioxide (CO2)

Foam

Extinguishing powder

## Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Combustible liquids

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide, Carbon monoxide

Beware of reignition.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 4 of 14

Heating causes rise in pressure with risk of bursting.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Wear full chemical protective clothing.

In case of fire and/or explosion do not breathe fumes.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

# For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

**Emergency procedures** 

Do not breathe dust/fume/gas/mist/vapours/spray.

### For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

# 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

### 6.3. Methods and material for containment and cleaning up

### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

# For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13



according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 5 of 14

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Avoid exposure - obtain special instructions before use.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

## Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Unsuitable container/equipment material: Aluminium, tin, zinc

# Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

## Further information on storage conditions

Keep cool. Protect from sunlight. storage temperature +15°C - +25°C

### 7.3. Specific end use(s)

Laboratory chemicals

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

# Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-56-1	Methyl alcohol	200	260		TWA (8 h)	
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	

### **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift



according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 6 of 14

### **DNEL/DMEL values**

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
67-56-1	methanol					
Consumer DN	EL, acute	inhalation	systemic	50 mg/m³		
Worker DNEL	long-term	inhalation	systemic	260 mg/m³		
Worker DNEL	acute	inhalation	systemic	260 mg/m³		
Worker DNEL	long-term	inhalation	local	260 mg/m³		
Worker DNEL	acute	inhalation	local	260 mg/m³		
Worker DNEL	long-term	dermal	systemic	40 mg/kg bw/day		
Worker DNEL	acute	dermal	systemic	40 mg/kg bw/day		
Consumer DN	EL, long-term	inhalation	systemic	50 mg/m³		
Consumer DN	EL, long-term	inhalation	local	50 mg/m³		
Consumer DN	EL, acute	inhalation	local	50 mg/m³		
Consumer DN	EL, long-term	dermal	systemic	8 mg/kg bw/day		
Consumer DN	EL, acute	dermal	systemic	8 mg/kg bw/day		
Consumer DN	EL, long-term	oral	systemic	8 mg/kg bw/day		
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day		
1310-73-2	sodium hydroxide					
Worker DNEL	long-term	inhalation	local	1 mg/m³		
Consumer DN	EL, long-term	inhalation	local	1 mg/m³		

## PNEC values

CAS No	Substance		
Environmental compartment Value			
67-56-1	methanol		
Freshwater 20,8 mg/l			
Freshwater (intermittent releases) 1540 mg/l			
Marine water 2,08 mg		2,08 mg/l	
Freshwater sediment		77 mg/kg	
Marine sediment 7,7 mg/k		7,7 mg/kg	
Micro-organisms in sewage treatment plants (STP)		100 mg/l	
Soil	100 mg/kg		

### 8.2. Exposure controls

## Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

# Individual protection measures, such as personal protective equipment

## Eye/face protection

goggles

## **Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is



according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 7 of 14

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

Recommended glove articles KCL 897 Butoject® Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with permanent contact: > 480 min

Recommended glove articles KCL 890 Vitoiect® Suitable material: FKM (fluoro rubber) 0.7 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

## Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

## **Environmental exposure controls**

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: colourless Odour: like: Methanol Odour threshold: No data available

Melting point/freezing point: No data available ~64 °C Boiling point or initial boiling point and

boiling range:

Flammability: not applicable Lower explosion limits: 5,5 vol. % Upper explosion limits: 44 vol. % ~11 °C Flash point: 455 °C Auto-ignition temperature: Decomposition temperature: not determined pH-Value: alkaline Viscosity / kinematic: not determined Water solubility: Soluble in: Water

Solubility in other solvents

not determined

Dissolution rate: No data available



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 8 of 14

Partition coefficient n-octanol/water: not determined Dispersion stability: No data available Vapour pressure: No data available Vapour pressure: No data available Density: 0,8199 g/cm<sup>3</sup> Relative density: No data available Bulk density: No data available Relative vapour density: not determined Particle characteristics: No data available

#### 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Sustaining combustion: Sustaining combustion

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties not determined

Other safety characteristics

Evaporation rate:

Solvent separation test:

not determined
Solvent content:

not determined
Solid content:

not determined
not determined
not determined
Sublimation point:

No data available
Softening point:

No data available
Pour point:

No data available

No data available:

Viscosity / dynamic:

Flow time:

No data available

not determined

### **Further Information**

May be corrosive to metals.

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Highly flammable.

Vapours can form explosive mixtures with air.

May be corrosive to metals.

# 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

# 10.3. Possibility of hazardous reactions

Oxidising agent, Hydrogen peroxide, Acid halides

Reducing agent, Acid, Alkaline earth metal, Alkali metals

## 10.4. Conditions to avoid

Vapours can form explosive mixtures with air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## 10.5. Incompatible materials

Plastic articles

Glass

metals (including their alloys)



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 9 of 14

### 10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

#### **Further information**

No data available

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Toxicocinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

#### **Acute toxicity**

Toxic if swallowed.

Toxic in contact with skin.

Toxic if inhaled.

### **ATEmix calculated**

ATE (oral) 102,5 mg/kg; ATE (dermal) 307,6 mg/kg; ATE (inhalation vapour) 3,080 mg/l; ATE (inhalation dust/mist) 0,5130 mg/l

CAS No	Chemical name	Chemical name							
	Exposure route	Dose		Species	Source	Method			
67-56-1	7-56-1 methanol								
	oral	LD50 mg/kg	6000	Monkey	Amer J Ophtha 40: 76-83 (cited				
	dermal	ATE mg/kg	300						
	inhalation (4 h) vapour	LC50 mg/l	128,2	Rat	Study report (1	980) Study performed according to internal co			
	inhalation dust/mist	ATE	0,5 mg/l						

## Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Corneal opacity.

# Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Causes damage to organs. (methanol)

eyes

Liver and kidney damage

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### Information on likely routes of exposure

There are no data available on the mixture itself.

## Specific effects in experiment on an animal

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 10 of 14

#### Additional information on tests

There are no data available on the mixture itself.

#### **Practical experience**

There are no data available on the mixture itself.

### 11.2. Information on other hazards

## **Endocrine disrupting properties**

There are no data available on the mixture itself.

#### Other information

Irritant, Dizziness, Dizziness Anaesthetic state, Agitation, Spasms Inebriation, Vomiting, Headache

Impairment of vision, Dyspnoea, Cough

Repeated exposure may cause skin dryness or cracking.

Risk of serious damage to eyes.

Circulatory collapse, Corneal opacity.

### **Further information**

Do not empty into drains.

Discharge into the environment must be avoided.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Chemical name								
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method			
67-56-1	methanol									
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975			
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201			
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11			
	Fish toxicity	NOEC mg/l	446,7	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR			
	Crustacea toxicity	NOEC	208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi			
1310-73-2	sodium hydroxide									
	Acute crustacea toxicity	EC50 mg/l	40,4	48 h	Ceriodaphnia sp.	Ecotoxicology and Environmental Safety,4	other: acute 48-h immobilization test ac			

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

## 12.3. Bioaccumulative potential

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 11 of 14

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-56-1	methanol	-0,77

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

# 12.4. Mobility in soil

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

Avoid release to the environment.

#### **Further information**

Do not allow to enter into surface water or drains.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

## **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

### Contaminated packaging

This material and its container must be disposed of as hazardous waste.

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

### **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number or ID number: UN 3286

14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, sodium

hydroxide)

14.3. Transport hazard class(es): 3
14.4. Packing group: II

Hazard label: 3+6.1+8
Classification code: FTC
Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 368
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3286

14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, sodium

hydroxide)



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 12 of 14

14.3. Transport hazard class(es): 3
14.4. Packing group: |

Hazard label: 3+6.1+8
Classification code: FTC
Special Provisions: 274 802
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 3286

14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, sodium

hydroxide)

14.3. Transport hazard class(es): 3
14.4. Packing group: |

Hazard label: 3+6.1+8
Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3286

14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, sodium

5 I

hydroxide)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+6.1+8Limited quantity Passenger:0.5 LPassenger LQ:Y340

Excepted quantity: E2

IATA-packing instructions - Passenger: 352

IATA-max. quantity - Passenger: 1 L

IATA-packing instructions - Cargo: 363

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

IATA-max. quantity - Cargo:

Warning: Combustible liquid. Toxic.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU regulatory information**

Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 69, Entry 75

Information according to Directive H2 ACUTE TOXIC

2012/18/EU (SEVESO III):

Additional information: P5c

**National regulatory information** 



according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 13 of 14

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

## **SECTION 16: Other information**

### Changes

This data sheet contains changes from the previous version in section(s): 9,12.

#### Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals

Flam. Liq: Flammable liquid Acute Tox: Acute toxicity Skin Corr: Skin corrosion Eye Dam: Eye damage

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

# Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure			
Met. Corr. 1; H290	On basis of test data			
Flam. Liq. 2; H225	On basis of test data			
Acute Tox. 3; H301	Calculation method			
Acute Tox. 3; H311	Calculation method			
Acute Tox. 3; H331	Calculation method			
Skin Corr. 1B; H314	Calculation method			
Eye Dam. 1; H318	Calculation method			
STOT SE 1; H370	Calculation method			

# Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H290 May be corrosive to metals.

H301 Toxic if swallowed.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H370 Causes damage to organs.

### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Sodium hydroxide solution 20 g/l in methanol R Reag. Ph. Eur., chapter 2.4.22

Revision date: 16.01.2024 Product code: 27768 Page 14 of 14

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)