

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent Naphtha S Destillation range 180 - 210 °C

Revision date: 03.01.2022

Product code: 28354

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Solvent Naphtha S Destillation range 180 - 210 °C

REACH Registration Number: 01-2119463588-24-XXXX

EC No: 919-284-0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: Fa. Bernd Kraft GmbH

Street: Stempelstraße 6

Place: D-47167 Duisburg

Telephone: 0203/5194-0

Telefax: 0203/5194-290

e-mail: info@berndkraft.de

Contact person: Abteilung Produktsicherheit

Telephone: 0203/5194-107/117

e-mail: produktsicherheit@berndkraft.de

Internet: www.berndkraft.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Carc. 2; H351

STOT SE 3; H336

Asp. Tox. 1; H304

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H304

May be fatal if swallowed and enters airways.

H336

May cause drowsiness or dizziness.

Solvent Naphtha S Distillation range 180 - 210 °C

Revision date: 03.01.2022

Product code: 28354

Page 2 of 12

H351 Suspected of causing cancer.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Hazardous components

| CAS No | Chemical name | | | Quantity |
|---------|---|--------------|----------|-------------|
| | EC No | Index No | REACH No | |
| | Classification (Regulation (EC) No 1272/2008) | | | |
| | Hydrocarbons, C10, aromatics, > 1% naphthalene | | | 90 - < 95 % |
| | Carc. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H351 H336 H304 H411 EUH066 | | | |
| 91-20-3 | naphthalene | | | 10 - < 15 % |
| | 202-049-5 | 601-052-00-2 | | |
| | Flam. Sol. 1, Carc. 2, Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1; H228 H351 H302 H400 H410 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|---------|-----------|--|-------------|
| | | Specific Conc. Limits, M-factors and ATE | |
| | | Hydrocarbons, C10, aromatics, > 1% naphthalene | 90 - < 95 % |
| | | dermal: LD50 = > 2000 mg/kg; oral: LD50 = 10650 mg/kg | |
| 91-20-3 | 202-049-5 | naphthalene | 10 - < 15 % |
| | | inhalation: LC50 = > 77,7 mg/l (vapours); dermal: LD50 = > 16000 mg/kg; oral: LD50 = 710 mg/kg | |

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

After inhalation

Provide fresh air.
If breathing is irregular or stopped, administer artificial respiration.

Solvent Naphtha S Distillation range 180 - 210 °C

Revision date: 03.01.2022

Product code: 28354

Page 3 of 12

Call a physician immediately.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Headache
May cause drowsiness or dizziness.
Dizziness
Gastrointestinal complaints
Irritant
Repeated exposure may cause skin dryness or cracking.
Anaesthetic state
Pneumonia

4.3. Indication of any immediate medical attention and special treatment needed

Aspiration hazard

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible liquids
Hazardous combustion products
In case of fire may be liberated:
Carbon dioxide (CO₂) Carbon monoxide
In case of warming:
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.

Solvent Naphtha S Distillation range 180 - 210 °C

Revision date: 03.01.2022

Product code: 28354

Page 4 of 12

Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.
Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Collect in closed and suitable containers for disposal.
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Keep container tightly closed.
Use personal protection equipment. Use extractor hood (laboratory).
Do not breathe vapour/aerosol. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.
Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary.
If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Solvent Naphtha S Distillation range 180 - 210 °C

Revision date: 03.01.2022

Product code: 28354

Page 5 of 12

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| CAS No | Substance | ppm | mg/m ³ | fib/cm ³ | Category | Origin |
|---------|-------------|-----|-------------------|---------------------|-----------|--------|
| 91-20-3 | Naphthalene | 10 | 50 | | TWA (8 h) | |

DNEL/DMEL values

| CAS No | Substance | Exposure route | Effect | Value |
|---------|---|----------------|----------|-----------------------|
| | Hydrocarbons, C10, aromatics,> 1% naphthalene | | | |
| | Worker DNEL, long-term | dermal | systemic | 12,5 mg/kg bw/day |
| | Consumer DNEL, long-term | inhalation | systemic | 32 mg/m ³ |
| | Consumer DNEL, long-term | dermal | systemic | 7,5 mg/kg bw/day |
| | Consumer DNEL, long-term | oral | systemic | 7,5 mg/kg bw/day |
| | Worker DNEL, long-term | inhalation | systemic | 151 mg/m ³ |
| 91-20-3 | naphthalene | | | |
| | Worker DNEL, long-term | inhalation | systemic | 25 mg/m ³ |
| | Worker DNEL, long-term | inhalation | local | 25 mg/m ³ |
| | Worker DNEL, long-term | dermal | systemic | 3,57 mg/kg bw/day |

PNEC values

| CAS No | Substance | Value |
|---------|--|--------------|
| | Environmental compartment | |
| 91-20-3 | naphthalene | |
| | Freshwater | 0,0024 mg/l |
| | Freshwater (intermittent releases) | 0,02 mg/l |
| | Marine water | 0,0024 mg/l |
| | Freshwater sediment | 0,0672 mg/kg |
| | Marine sediment | 0,0672 mg/kg |
| | Micro-organisms in sewage treatment plants (STP) | 2,9 mg/l |
| | Soil | 0,0533 mg/kg |

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Solvent Naphtha S Distillation range 180 - 210 °C

Revision date: 03.01.2022

Product code: 28354

Page 6 of 12

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation : KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device with filter or ventilator filtering device of type: A

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
 Colour: clear
 Odour: like: aromatic hydrocarbons

Changes in the physical state

Melting point/freezing point: No data available
 Boiling point or initial boiling point and boiling range: 182-206 °C
 Sublimation point: No data available
 Softening point: No data available
 Pour point: No data available
 : No data available
 Flash point: 67 °C

Flammability

Solid/liquid: No data available
 Gas: No data available

Solvent Naphtha S Distillation range 180 - 210 °C

Revision date: 03.01.2022

Product code: 28354

Page 7 of 12

Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Lower explosion limits: 0,9 vol. %

Upper explosion limits: 7 vol. %

Auto-ignition temperature: 448 °C

Self-ignition temperature

Solid: No data available

Gas: No data available

Decomposition temperature: No data available

pH-Value: No data available

Viscosity / dynamic: No data available

Viscosity / kinematic:
(at 20 °C) 1,33 mm²/s

Flow time: No data available

Water solubility: practically insoluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water: No data available

Vapour pressure: No data available

Vapour pressure: No data available

Density: 0,8 g/cm³

Bulk density: No data available

Relative vapour density: No data available

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion: No data available

Oxidizing properties

No data available

Other safety characteristics

Solvent separation test: No data available

Solvent content: 100%

Solid content: No data available

Evaporation rate: No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming:

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

Solvent Naphtha S Distillation range 180 - 210 °C

Revision date: 03.01.2022

Product code: 28354

Page 8 of 12

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | |
|---------|---|--------------------|---------|---|--------------------|
| | Exposure route | Dose | Species | Source | Method |
| | Hydrocarbons, C10, aromatics,> 1% naphthalene | | | | |
| | oral | LD50 10650 mg/kg | Rat | Study report (1991) | OECD Guideline 420 |
| | dermal | LD50 > 2000 mg/kg | Rabbit | Study report (1995) | OECD Guideline 402 |
| 91-20-3 | naphthalene | | | | |
| | oral | LD50 710 mg/kg | Mouse | FUND. APPL. TOXICOL 4: 406-419 (1984) (1) | OECD Guideline 401 |
| | dermal | LD50 > 16000 mg/kg | Rat | Study report (1980) | OECD Guideline 402 |
| | inhalation (4 h) vapour | LC50 > 77,7 mg/l | Rat | Study report (1985) | other: EPA TSCA |

Irritation and corrosivity

Based on available data, the classification criteria are not met.
slightly irritant but not relevant for classification.
Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Hydrocarbons, C10, aromatics,> 1% naphthalene; naphthalene)
Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C10, aromatics,> 1% naphthalene)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available

Solvent Naphtha S Distillation range 180 - 210 °C

Revision date: 03.01.2022

Product code: 28354

Page 9 of 12

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Other information

No data available

Further information

- Headache
- May cause drowsiness or dizziness.
- Dizziness
- Gastrointestinal complaints
- Irritant
- Repeated exposure may cause skin dryness or cracking.
- Anaesthetic state
- Pneumonia

SECTION 12: Ecological information

12.1. Toxicity

| CAS No | Chemical name | | | | | |
|---------|--|------------------------------|-----------|---------------------------------|--|--|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| | Hydrocarbons, C10, aromatics, > 1% naphthalene | | | | | |
| | Acute algae toxicity | ErC50 > 1 - < 3 mg/l | 72 h | Pseudokirchneriella subcapitata | Study report (1993) | OECD Guideline 201 |
| | Fish toxicity | NOEC 0,487 mg/l | 28 d | Oncorhynchus mykiss | CONCAWE, Brussels, Belgium (2010) | The aquatic toxicity was estimated by a |
| | Crustacea toxicity | NOEC 0,851 mg/l | 21 d | Daphnia magna | CONCAWE, Brussels, Belgium (2010) | The aquatic toxicity was estimated by a |
| 91-20-3 | naphthalene | | | | | |
| | Acute fish toxicity | LC50 1,6 mg/l | 96 h | Oncorhynchus mykiss | Arch. Environm. Contam. Toxicol. 11, 487 | OECD Guideline 203 |
| | Acute algae toxicity | ErC50 ca. 0,4 - ca. 0,5 mg/l | 72 h | Skeletonema costatum | Mar Environ Res 11, 183-200 (1984) | Aquatic toxicity of water soluble fracti |
| | Acute crustacea toxicity | EC50 2,16 mg/l | 48 h | Daphnia magna | Transactions of the American Fisheries S | OECD Guideline 202 |
| | Fish toxicity | NOEC 0,37 mg/l | 40 d | Oncorhynchus kisutch | Trans. Am. Fish. Soc. 110:430-436, 1981 | Coho salmon fry were exposed for 40 days |
| | Crustacea toxicity | NOEC 0,59 mg/l | 125 d | Daphnia pulex | Can. J. Fish. Aquat. Sci. 39: 830 - 834 | During chronic studies in closed static |

12.2. Persistence and degradability

Poorly biodegradable.

12.3. Bioaccumulative potential

Solvent Naphtha S Distillation range 180 - 210 °C

Revision date: 03.01.2022

Product code: 28354

Page 10 of 12

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|---------|---------------|---------|
| 91-20-3 | naphthalene | 3,4 |

BCF

| CAS No | Chemical name | BCF | Species | Source |
|---------|---------------|------------|-----------------|---|
| 91-20-3 | naphthalene | 36,5 - 168 | Cyprinus carpio | http://www.safe.nite |

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

No data available

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

| | |
|--|--|
| 14.1. UN number or ID number: | UN 3082 |
| 14.2. UN proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hydrocarbons, C10, aromatics,> 1% naphthalene) |
| 14.3. Transport hazard class(es): | 9 |
| 14.4. Packing group: | III |
| Hazard label: | 9 |
| Classification code: | M6 |
| Special Provisions: | 274 335 375 601 |
| Limited quantity: | 5 L |
| Excepted quantity: | E1 |
| Transport category: | 3 |
| Hazard No: | 90 |
| Tunnel restriction code: | - |

Inland waterways transport (ADN)

| | |
|--|--|
| 14.1. UN number or ID number: | UN 3082 |
| 14.2. UN proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hydrocarbons, C10, aromatics,> 1% naphthalene) |
| 14.3. Transport hazard class(es): | 9 |
| 14.4. Packing group: | III |

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent Naphtha S Distillation range 180 - 210 °C

Revision date: 03.01.2022

Product code: 28354

Page 11 of 12

Hazard label: 9
 Classification code: M6
 Special Provisions: 274 335 375 601
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hydrocarbons, C10, aromatics,> 1% naphthalene)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9
 Special Provisions: 274, 335, 969
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hydrocarbons, C10, aromatics,> 1% naphthalene)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9
 Special Provisions: A97 A158 A197
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y964
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 964
 IATA-max. quantity - Passenger: 450 L
 IATA-packing instructions - Cargo: 964
 IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes
 Danger releasing substance: Hydrocarbons, C10, aromatics,> 1% naphthalene

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
 Entry 3, Entry 40, Entry 75
 Information according to 2012/18/EU (SEVESO III): E2 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
 Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent Naphtha S Distillation range 180 - 210 °C

Revision date: 03.01.2022

Product code: 28354

Page 12 of 12

Changes

This data sheet contains changes from the previous version in section(s): 1.

Relevant H and EUH statements (number and full text)

| | |
|--------|---|
| H228 | Flammable solid. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H336 | May cause drowsiness or dizziness. |
| H351 | Suspected of causing cancer. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.