

Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 :

Revision date: 11.01.2024

10 gemischt... Product code: 29410

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 : 10 gemischt...

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone number:	Exposure, or Accident Call CHEMTI	rous Goods] Incidents Spill, Leak, Fire, REC Day or Night Within USA and Canada: Canada: +1 703-741-5970 (collect calls

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling heptane toluene cyclohexane Signal word: Danger



Safety Data Sheet

according to UK REACH Regulation

Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 :

 10 gemischt...

 Revision date: 11.01.2024
 Product code: 29410
 Page 2 of 15

 Pictograms:
 Image: Colspan="3">Image: Colspan="3">Colspan="3">Pictograms:

 Hazard statements
 Image: Colspan="3">Pictograms:

 Hazard statements
 Image: Colspan="3">Pictograms:

 Hazard statements
 Image: Colspan="3">Pictograms:

 Hazard statements
 Image: Colspan="3">Pictograms:

 H315
 Causes skin irritation.
 Causes skin irritation.

 H361d
 Suspected of damaging the unborn child.
 H336

 May cause drowsiness or dizziness.
 Highly flammable liquid and vapour.

H373 May cause damage to organs through prolonged or repeated exposure.

- H304 May be fatal if swallowed and enters airways.
- H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

oouullonuly olulonion	
P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP R	egulation)			
142-82-5	heptane			65 - < 70 %	
	205-563-8	601-008-00-2	01-2119457603-38		
	Flam. Liq. 2, Skin Irrit. 2, H315 H336 H304 H400 H				
110-82-7	cyclohexane	20 - < 25 %			
	203-806-2	601-017-00-1	01-2119463273-41		
	Flam. Liq. 2, Skin Irrit. 2, H315 H336 H304 H400 H				
108-88-3	toluene			10 - < 15 %	
	203-625-9	601-021-00-3	01-2119471310-51		
	Flam. Liq. 2, Repr. 2, Skir H373 H304				

Full text of H and EUH statements: see section 16.



Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 :

10 gemischt...

Revision date: 11.01.2024

Product code: 29410

Page 3 of 15

Specific Conc	. Limits,	M-factors	and ATE	

CAS No	EC No	Chemical name	Quantity	
	Specific Conc	Limits, M-factors and ATE		
142-82-5	205-563-8	heptane	65 - < 70 %	
	inhalation: LC50 = > 29,29 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg			
110-82-7	203-806-2	cyclohexane	20 - < 25 %	
	inhalation: LC mg/kg	250 = > 5540 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000		
108-88-3	203-625-9	toluene	10 - < 15 %	
	inhalation: LC	50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water. Observe risk of aspiration if vomiting occurs. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids



Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 :

10 gemischt...

Revision date: 11.01.2024

Product code: 29410

Page 4 of 15

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide Vapours are heavier than air, spread along floors and form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Consult an expert Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13



Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 :

10 gemischt...

Revision date: 11.01.2024

Product code: 29410

Page 5 of 15

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

national regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
110-82-7	Cyclohexane	100	350		TWA (8 h)	WEL
		300	1050		STEL (15 min)	WEL
142-82-5	n-Heptane	500	2085		TWA (8 h)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL



Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 :

Revision date: 11.01.2024

10 gemischt...

Product code: 29410

Page 6 of 15

DNEL/DMEL values

CAS No Substance			
DNEL type	Exposure route	Effect	Value
142-82-5 heptane			
Worker DNEL, long-term	inhalation	systemic	2085 mg/m ³
Worker DNEL, long-term	dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	447 mg/m ³
Consumer DNEL, long-term	dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	149 mg/kg bw/day
110-82-7 cyclohexane			
Consumer DNEL, long-term	inhalation	systemic	206 mg/m ³
Consumer DNEL, acute	inhalation	systemic	412 mg/m ³
Consumer DNEL, long-term	inhalation	local	206 mg/m ³
Consumer DNEL, acute	inhalation	local	412 mg/m ³
Consumer DNEL, long-term	dermal	systemic	1186 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	59,4 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	700 mg/m ³
Worker DNEL, acute	inhalation	systemic	1400 mg/m ³
Worker DNEL, long-term	inhalation	local	700 mg/m ³
Worker DNEL, acute	inhalation	local	1400 mg/m ³
Worker DNEL, long-term	dermal	systemic	2016 mg/kg bw/day
108-88-3 toluene			
Worker DNEL, long-term	inhalation	systemic	192 mg/m ³
Worker DNEL, acute	inhalation	systemic	384 mg/m ³
Worker DNEL, long-term	inhalation	local	192 mg/m ³
Worker DNEL, acute	inhalation	local	384 mg/m ³
Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	56,5 mg/m³
Consumer DNEL, acute	inhalation	systemic	226 mg/m ³
Consumer DNEL, long-term	inhalation	local	56,5 mg/m³
Consumer DNEL, acute	inhalation	local	226 mg/m ³
Consumer DNEL, long-term	dermal	systemic	226 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day



Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 :

Revision date: 11.01.2024

10 gemischt... Product code: 29410

Page 7 of 15

PNEC values

CAS No	Substance	
Environmen	tal compartment	Value
110-82-7	cyclohexane	
Freshwater		0,207 mg/l
Freshwater	(intermittent releases)	0,207 mg/l
Marine wate	r	0,207 mg/l
Freshwater	sediment	16,68 mg/kg
Marine sedir	nent	16,68 mg/kg
Micro-organ	3,24 mg/l	
Soil		3,38 mg/kg
108-88-3	toluene	
Freshwater		0,68 mg/l
Freshwater	(intermittent releases)	0,68 mg/l
Marine wate	r	0,68 mg/l
Freshwater	16,39 mg/kg	
Marine sediment		16,39 mg/kg
Micro-organ	13,61 mg/l	
Soil		2,89 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact Trade name/designation KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Trade name/designation KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm Wearing time with occasional contact (splashes): > 480 min



Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 :

10 gemischt...

Revision date: 11.01.2024

Product code: 29410

Page 8 of 15

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Environmental exposure controls

Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	clear	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and		>35 °C
boiling range:		
Flammability:		not applicable
		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		<21 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		No data available
Water solubility:		No
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		<=1100 hPa
(at 50 °C)		
Vapour pressure:		No data available
Density:		0,71900 g/cm ³
Bulk density:		No data available
Relative vapour density:		not determined
9.2. Other information		
Information with regard to physical I	nazard classes	
Explosive properties		
Vapours are heavier than air, spre	ad along floors and form explo	sive mixtures with air.
Self-ignition temperature		
Solid		not applicable



Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 : 10 gemischt					
Revision date: 11.01.2024	Product code: 29410	Page 9 of 15			
Gas: Oxidizing properties Not oxidising.	not applicable				
Other safety characteristics					
Evaporation rate:	not determined				
Solvent separation test:	No data available				
Solvent content:	100%				
Solid content:	0				
Sublimation point:	No data available				
Softening point:	No data available				
Pour point:	No data available				
	No data available				
Viscosity / dynamic:	No data available				
Flow time:	No data available				

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



Safety Data Sheet

according to UK REACH Regulation

Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 : 10 gemischt...

Revision date: 11.01.2024

Product code: 29410

Page 10 of 15

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
142-82-5	heptane								
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401			
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)	OECD Guideline 402			
	inhalation (4 h) vapour	LC50 mg/l	> 29,29	Rat	Study report (1982)	OECD Guideline 403			
110-82-7	cyclohexane								
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401			
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)	OECD Guideline 402			
	inhalation (4 h) vapour	LC50 mg/l	> 5540	Rat	Study report (1981)	OECD Guideline 403			
108-88-3	toluene								
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1			
	dermal	LD50 mg/kg	> 5000	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o			
	inhalation (4 h) vapour	LC50	28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403			

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (heptane; cyclohexane)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the mixture itself.



Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 :

Revision date: 11.01.2024

10 gemischt...

Product code: 29410

Page 11 of 15

Further information

There are no data available on the mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
142-82-5	heptane			-					
	Acute algae toxicity	ErC50 mg/l	4,338	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a		
	Acute crustacea toxicity	EC50	1,5 mg/l	48 h	Daphnia magna	Study report (1987)	other: As described in: The evaluation o		
	Fish toxicity	NOEC mg/l	1,284	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a		
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211		
110-82-7	cyclohexane								
	Acute fish toxicity	LC50 mg/l	4,53	96 h	Pimephales promelas	Vol. 5, Centre for Lake Superior Studies	OECD Guideline 203		
	Acute algae toxicity	ErC50 mg/l	9,317	72 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201		
	Acute crustacea toxicity	EC50	0,9 mg/l	48 h	Daphnia magna	Publication (1987)	OECD Guideline 202		
108-88-3	toluene								
	Acute fish toxicity	LC50	5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th		
	Acute algae toxicity	ErC50 mg/l	> 433	96 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	Method: other		
	Acute crustacea toxicity	EC50 mg/l	11,5	48 h	Daphnia magna	REACh Registration Dossier	Method: other		
	Fish toxicity	NOEC mg/l	1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th		
	Algae toxicity	NOEC mg/l	> 400	7 d	Scenedesmus quadricauda	REACh Registration Dossier	Method: other		
	Crustacea toxicity	NOEC mg/l	0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (other: US EPA 600/4-91-003		

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential



Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 :

10 gemischt...

Revision date: 11.01.2024

Product code: 29410

Page 12 of 15

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
142-82-5	heptane	4,5
110-82-7	cyclohexane	3,44
108-88-3	toluene	2,73

BCF

CAS No	Chemical name	BCF	Species	Source
142-82-5	heptane	552	calculated	Other company data (
110-82-7	cyclohexane	167	Pimephales promelas	J. Fish. Board Can.
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

There are no data available on the mixture itself.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1993		
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (heptane, cyclohexane)		
14.3. Transport hazard class(es):	3		
14.4. Packing group:	II		
Hazard label:	3		
Classification code:	F1		
Special Provisions:	274 601 640D		
Limited quantity:	1 L		
Excepted quantity:	E2		
Transport category:	2		
Hazard No:	33		



	10 gemischt	
Revision date: 11.01.2024	Product code: 29410	Page 13 of 1
Tunnel restriction code:	D/E	
Inland waterways transport (ADN)		
14.1. UN number or ID number:	UN 1993	
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (heptane, cyclohexane)	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	ll	
Hazard label:	3	
Classification code:	F1	
Special Provisions:	274 601 640D	
Limited quantity:	1 L	
Excepted quantity:	E2	
Marine transport (IMDG)		
14.1. UN number or ID number:	UN 1993	
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (heptane, cyclohexane)	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	3 II	
Hazard label:	3	
Special Provisions:	3 274	
Limited quantity:	1L	
Excepted quantity:	E2	
EmS:	E2 F-E, S-E	
	1-L, 0-L	
Air transport (ICAO-TI/IATA-DGR)	1014000	
14.1. UN number or ID number:	UN 1993	
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (heptane, cyclohexane)	
14.3. Transport hazard class(es):	3	
14.4. Packing group:		
Hazard label:	3	
Special Provisions:	A3	
Limited quantity Passenger:	1 L	
Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:	353	
IATA-max. quantity - Passenger:	5 L	
IATA-packing instructions - Cargo:	364	
IATA-max. quantity - Cargo:	60 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	Yes	
Danger releasing substance:	heptane cyclohexane	
14.6. Special precautions for user Warning: Combustible liquid.		
14.7. Maritime transport in bulk according	o IMO instruments	
not applicable		
SECTION 15: Regulatory information		

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 48, Entry 57



Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 :						
10 gemischt						
Revision date: 11.01.2024	Product code: 29410	Page 14 of 15				
Information according to Directive 2012/18/EU (SEVESO III):	E1 Hazardous to the Aquatic Environment					
Additional information:	P5c					
National regulatory information						
Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.						
Water hazard class (D):	3 - highly hazardous to water					
15.2. Chemical safety assessment						
Chemical safety assessments for substances in this mixture were not carried out.						

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 15.

Abbreviations and acronyms

Flam. Liq: Flammable liquids Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Repr: Reproductive toxicity STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50% Relevant H and EUH statements (number and full text) Highly flammable liquid and vapour. H225 H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation.

H315Causes skin irritation.H336May cause drowsiness or dizziness.H361dSuspected of damaging the unborn child.H373May cause damage to organs through prolonged or repeated exposure.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



Aromatisches Prüfmedium n-Heptan / Cyclohexan / Toluol-Gemisch volumetrisch 70 : 20 :

Revision date: 11.01.2024

10 gemischt... Product code: 29410

Page 15 of 15

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)