

## Safety Data Sheet

according to UK REACH Regulation

### Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1 gemischt

Revision date: 25.03.2024

Product code: 30196

Page 1 of 13

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1 gemischt

UFI: 8GMP-F2T4-Y00H-4DHA

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

###### Uses advised against

Do not use for private purposes (household).

##### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

##### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

##### Further Information

inapplicable, this product is a mixture REACH registration number see section 3

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### GB CLP Regulation

Flam. Liq. 2; H225  
Asp. Tox. 1; H304  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
Repr. 2; H361d  
STOT SE 3; H336  
STOT RE 2; H373  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

###### GB CLP Regulation

###### Hazard components for labelling

toluene

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

## Safety Data Sheet

according to UK REACH Regulation

### Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1 gemischt

Revision date: 25.03.2024

Product code: 30196

Page 2 of 13

#### Pictograms:



#### Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P403+P235	Store in a well-ventilated place. Keep cool.

#### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (GB CLP Regulation)	
108-88-3	toluene	50 - < 55 %
	203-625-9	601-021-00-3
	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	45 - < 50 %
	200-661-7	603-117-00-0
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
108-88-3	203-625-9	toluene	50 - < 55 %
	inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg		

#### Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

## Safety Data Sheet

according to UK REACH Regulation

### Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1 gemischt

Revision date: 25.03.2024

Product code: 30196

Page 3 of 13

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

No data available

###### After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

###### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

###### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

###### After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

##### 4.2. Most important symptoms and effects, both acute and delayed

No data available

##### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

###### Unsuitable extinguishing media

no restriction

##### 5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

##### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

###### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

###### General advice

Keep away from sources of ignition - No smoking.

## Safety Data Sheet

according to UK REACH Regulation

### Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1 gemischt

Revision date: 25.03.2024

Product code: 30196

Page 4 of 13

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

#### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

### 6.3. Methods and material for containment and cleaning up

#### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

#### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

#### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

## Safety Data Sheet

according to UK REACH Regulation

### Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1 gemischt

Revision date: 25.03.2024

Product code: 30196

Page 5 of 13

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints on joint storage

national regulations

#### Further information on storage conditions

Keep cool. Protect from sunlight.

#### 7.3. Specific end use(s)

Laboratory chemicals

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
108-88-3	toluene			
	Worker DNEL, long-term	inhalation	systemic	192 mg/m <sup>3</sup>
	Worker DNEL, acute	inhalation	systemic	384 mg/m <sup>3</sup>
	Worker DNEL, long-term	inhalation	local	192 mg/m <sup>3</sup>
	Worker DNEL, acute	inhalation	local	384 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	56,5 mg/m <sup>3</sup>
	Consumer DNEL, acute	inhalation	systemic	226 mg/m <sup>3</sup>
	Consumer DNEL, long-term	inhalation	local	56,5 mg/m <sup>3</sup>
	Consumer DNEL, acute	inhalation	local	226 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	226 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
	Worker DNEL, long-term	inhalation	systemic	500 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	888 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	89 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day

**Safety Data Sheet**

according to UK REACH Regulation

**Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1  
gemischt**

Revision date: 25.03.2024

Product code: 30196

Page 6 of 13

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
108-88-3	toluene	
Freshwater		0,68 mg/l
Freshwater (intermittent releases)		0,68 mg/l
Marine water		0,68 mg/l
Freshwater sediment		16,39 mg/kg
Marine sediment		16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l
Soil		2,89 mg/kg
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Suitable eye protection: goggles.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) with the following specification (test according to EN 374):

By long-term hand contact

Trade name/designation KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480 min

## Safety Data Sheet

according to UK REACH Regulation

### Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1 gemischt

Revision date: 25.03.2024

Product code: 30196

Page 7 of 13

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

#### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		>35 °C
Flammability:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		<21 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		not determined
pH-Value:		No data available
Viscosity / kinematic:		No data available
Water solubility:		No
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure: (at 50 °C)		<=1100 hPa
Vapour pressure:		No data available
Density:		0,82907 g/cm <sup>3</sup>
Bulk density:		No data available
Relative vapour density:		not determined

### 9.2. Other information

#### Information with regard to physical hazard classes

##### Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

##### Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

##### Oxidizing properties

Not oxidising.

#### Other safety characteristics

**Safety Data Sheet**

according to UK REACH Regulation

**Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1  
gemischt**

Revision date: 25.03.2024

Product code: 30196

Page 8 of 13

Evaporation rate:	not determined
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	0
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
Viscosity / dynamic:	No data available
Flow time:	No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Highly flammable.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in GB CLP Regulation**

**Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
108-88-3	toluene					
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 mg/kg	> 5000	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50	28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403



## Safety Data Sheet

according to UK REACH Regulation

### Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1 gemischt

Revision date: 25.03.2024

Product code: 30196

Page 9 of 13

#### **Irritation and corrosivity**

Causes skin irritation.  
Causes serious eye irritation.

#### **Sensitising effects**

Based on available data, the classification criteria are not met.

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of damaging the unborn child. (toluene)  
Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

May cause drowsiness or dizziness. (toluene; propan-2-ol; isopropyl alcohol; isopropanol)

#### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (toluene)

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

#### **Information on likely routes of exposure**

There are no data available on the mixture itself.

#### **Specific effects in experiment on an animal**

There are no data available on the mixture itself.

#### **Additional information on tests**

There are no data available on the mixture itself.

#### **Practical experience**

There are no data available on the mixture itself.

#### **11.2. Information on other hazards**

##### **Endocrine disrupting properties**

There are no data available on the mixture itself.

##### **Other information**

There are no data available on the mixture itself.

#### **Further information**

There are no data available on the mixture itself.

### **SECTION 12: Ecological information**

#### **12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

**Safety Data Sheet**

according to UK REACH Regulation

**Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1  
gemischt**

Revision date: 25.03.2024

Product code: 30196

Page 10 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
108-88-3	toluene					
	Acute fish toxicity	LC50 5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 > 433 mg/l	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	Method: other
	Acute crustacea toxicity	EC50 11,5 mg/l	48 h	Daphnia magna	REACH Registration Dossier	Method: other
	Fish toxicity	NOEC 1,39 mg/l	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Algae toxicity	NOEC > 400 mg/l	7 d	Scenedesmus quadricauda	REACH Registration Dossier	Method: other
	Crustacea toxicity	NOEC 0,74 mg/l	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (	other: US EPA 600/4-91-003
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 10000 mg/l	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

**BCF**

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Do not allow to enter into surface water or drains.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations**

## Safety Data Sheet

according to UK REACH Regulation

**Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1  
gemischt**

Revision date: 25.03.2024

Product code: 30196

Page 11 of 13

**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not empty into drains.

**Contaminated packaging**

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol; isopropyl alcohol; isopropanol)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol; isopropyl alcohol; isopropanol)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol; isopropyl alcohol; isopropanol)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol; isopropyl alcohol; isopropanol)
<b>14.3. Transport hazard class(es):</b>	3

## Safety Data Sheet

according to UK REACH Regulation

### Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1 gemischt

Revision date: 25.03.2024

Product code: 30196

Page 12 of 13

<b>14.4. Packing group:</b>	II	
Hazard label:	3	
Special Provisions:	A3	
Limited quantity Passenger:	1 L	
Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		353
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		364
IATA-max. quantity - Cargo:		60 L

#### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

#### **14.6. Special precautions for user**

Warning: Combustible liquid.

#### **14.7. Maritime transport in bulk according to IMO instruments**

not applicable

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48

##### **National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

3 - highly hazardous to water

#### **15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### **Changes**

This data sheet contains changes from the previous version in section(s): 1,9.

## Safety Data Sheet

according to UK REACH Regulation

### Lösemittelgemisch L2 Toluol / 2-Propanol / Wasser-Gemisch volumetrisch 100 : 99 : 1 gemischt

Revision date: 25.03.2024

Product code: 30196

Page 13 of 13

#### Abbreviations and acronyms

Flam. Liq: Flammable liquids  
 Asp. Tox: Aspiration hazard  
 Skin Irrit: Skin irritation  
 Eye Irrit: Eye irritation  
 Repr: Reproductive toxicity  
 STOT SE: Specific target organ toxicity - single exposure  
 STOT RE: Specific target organ toxicity - repeated exposure  
 Aquatic Chronic: Chronic aquatic hazard  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H361d Suspected of damaging the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H412 Harmful to aquatic life with long lasting effects.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*