

Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt

Revision date: 26.03.2024

Product code: 30199

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt

UFI:

PRMP-Y2VA-W000-3E8H

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone	For Hazardous Materials [or Dangero	ous Goods] Incidents Spill, Leak, Fire,
number:	•	EC Day or Night Within USA and Canada: anada: +1 703-741-5970 (collect calls

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 STOT RE 2; H373 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling toluene

Signal word: Danger

Revision No: 1,05 - Replaces version: 1,04



Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt

Revision date: 26.03.2024

Pictograms:

Product code: 30199

Page 2 of 13



Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P403+P235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Chemical name				
	EC No	EC No Index No REACH No				
	Classification (GB CLP Reg					
108-88-3	toluene					
	203-625-9	203-625-9 601-021-00-3 01-2119471310-51				
	Flam. Liq. 2, Repr. 2, Skin Ir H361d H315 H336 H373 H3					
64-17-5	ethanol					
	200-578-6	603-002-00-5	01-2119457610-43			
	Flam. Liq. 2, Eye Irrit. 2; H225 H319					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

.				
CAS No	EC No	Chemical name	Quantity	
	Specific Conc.	Limits, M-factors and ATE		
108-88-3	203-625-9	toluene	65 - < 70 %	
	inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg			
64-17-5	200-578-6	ethanol	30 - < 35 %	
	inhalation: LC	50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg		
	100			

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).



Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt

Revision date: 26.03.2024

Product code: 30199

Page 3 of 13

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot



Safety Data Sheet

according to UK REACH Regulation

Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt

Revision date: 26.03.2024

Product code: 30199

Page 4 of 13

lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Consult an expert Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Use extractor hood (laboratory). Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.



Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt

Revision date: 26.03.2024

Product code: 30199

Page 5 of 13

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

national regulations

Further information on storage conditions Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
108-88-3	toluene						
Worker DNEI	_, long-term	inhalation	systemic	192 mg/m³			
Worker DNEI	_, acute	inhalation	systemic	384 mg/m³			
Worker DNEI	_, long-term	inhalation	local	192 mg/m³			
Worker DNEI	_, acute	inhalation	local	384 mg/m³			
Worker DNEI	_, long-term	dermal	systemic	384 mg/kg bw/day			
Consumer DI	NEL, long-term	inhalation	systemic	56,5 mg/m³			
Consumer DI	NEL, acute	inhalation	systemic	226 mg/m ³			
Consumer DI	NEL, long-term	inhalation	local	56,5 mg/m³			
Consumer DI	NEL, acute	inhalation	local	226 mg/m ³			
Consumer DI	NEL, long-term	dermal	systemic	226 mg/kg bw/day			
Consumer DI	NEL, long-term	oral	systemic	8,13 mg/kg bw/day			
64-17-5	ethanol						
Worker DNEI	_, long-term	inhalation	systemic	950 mg/m³			
Worker DNEI	_, long-term	dermal	systemic	343 mg/kg bw/day			
Consumer DI	NEL, long-term	inhalation	systemic	114 mg/m ³			
Consumer DI	NEL, long-term	dermal	systemic	206 mg/kg bw/day			
Consumer DI	NEL, long-term	oral	systemic	87 mg/kg bw/day			



Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt

Revision date: 26.03.2024

Product code: 30199

Page 6 of 13

PNEC values

CAS No	Substance	
Environment	al compartment	Value
108-88-3	toluene	
Freshwater		0,68 mg/l
Freshwater (intermittent releases)	0,68 mg/l
Marine water	r	0,68 mg/l
Freshwater s	sediment	16,39 mg/kg
Marine sedin	nent	16,39 mg/kg
Micro-organi	sms in sewage treatment plants (STP)	13,61 mg/l
Soil		2,89 mg/kg
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (intermittent releases)	2,75 mg/l
Marine water	r	0,79 mg/l
Freshwater s	sediment	3,6 mg/kg
Marine sedin	nent	2,9 mg/kg
Secondary p	oisoning	380 mg/kg
Micro-organi	sms in sewage treatment plants (STP)	580 mg/l
Soil		0,63 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact Trade name/designation KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Trade name/designation KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm Wearing time with occasional contact (splashes): > 480 min



Safety Data Sheet

according to UK REACH Regulation

Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt

Revision date: 26.03.2024

Product code: 30199

Page 7 of 13

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Environmental exposure controls

Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and	Ł	>35 °C
boiling range:		
Flammability:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		<21 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		No data available
Water solubility:		No
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		0,84333 g/cm ³
Bulk density:		No data available
Relative vapour density:		not determined
9.2. Other information		
Information with regard to physical	hazard classes	
Explosive properties		
Vapours are heavier than air, spre	ead along floors and form	n explosive mixtures with air.
Self-ignition temperature		
Solid:		not applicable
Gas: Oxidizing properties		not applicable
Not oxidising.		
5		
Other safety characteristics		
Evaporation rate:		not determined
Solvent separation test:		No data available
Solvent content:		No data available



Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt Revision date: 26.03.2024 Product code: 30199 Page 8 of 13 Solid content: 0 Sublimation point: No data available Softening point: No data available Pour point: No data available No data available No data available Viscosity / dynamic: Flow time: No data available **Further Information**

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name	Chemical name							
	Exposure route	Dose		Species	Source	Method			
108-88-3	toluene								
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1			
	dermal	LD50 mg/kg	> 5000	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o			
	inhalation (4 h) vapour	LC50	28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403			
64-17-5	ethanol								
	oral	LD50 mg/kg	10470	Rat	Study report (1976)	OECD Guideline 401			
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980)	OECD Guideline 403			



Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt

Revision date: 26.03.2024

Product code: 30199

Page 9 of 13

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (toluene)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

There are no data available on the mixture itself.

Further information

There are no data available on the mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.



Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt

Revision date: 26.03.2024

Product code: 30199

Page 10 of 13

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
108-88-3	toluene								
	Acute fish toxicity	LC50	5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th		
	Acute algae toxicity	ErC50 mg/l	> 433	96 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	Method: other		
	Acute crustacea toxicity	EC50 mg/l	11,5	48 h	Daphnia magna	REACh Registration Dossier	Method: other		
	Fish toxicity	NOEC mg/l	1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th		
	Algae toxicity	NOEC mg/l	> 400	7 d	Scenedesmus quadricauda	REACh Registration Dossier	Method: other		
	Crustacea toxicity	NOEC mg/l	0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (other: US EPA 600/4-91-003		
64-17-5	ethanol								
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975		
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11		
	Algae toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989	Study to determine the sensitivity of a		
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th		

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
64-17-5	ethanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi



Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt

Revision date: 26.03.2024

Product code: 30199

Page 11 of 13

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not allow to enter into surface water or drains.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, ethanol; ethyl alcohol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, ethanol; ethyl alcohol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Marine transport (IMDG)	
<u>14.1. UN number or ID number:</u>	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, ethanol; ethyl alcohol)
14.3. Transport hazard class(es):	3
	-



Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt

Revision date: 26.03.2024	L3 Ioluol / Ethanol-Gemisch volumetrisch 2:1 gemischt Product code: 30199	Page 12 of
14.4. Packing group:	11	
Hazard label:	3	
Special Provisions:	274	
Limited quantity:	1 L	
Excepted quantity:	E2	
EmS:	F-E, S-E	
Air transport (ICAO-TI/IATA-DGR)		
14.1. UN number or ID number:	UN 1993	
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, ethanol; ethyl alcohol)	
<u>14.3. Transport hazard class(es):</u>	3	
14.4. Packing group:	II	
Hazard label:	3	
Special Provisions:	A3	
Limited quantity Passenger:	1L	
Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:	353	
IATA-max. quantity - Passenger: IATA-packing instructions - Cargo:	5 L 364	
IATA-packing instructions - Cargo:	504 60 L	
	00 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
14.6. Special precautions for user		
Warning: Combustible liquid.		
14.7. Maritime transport in bulk according	to IMO instruments	
not applicable		
SECTION 15: Regulatory information		
5.1. Safety, health and environmental reg	gulations/legislation specific for the substance or mixture	
EU regulatory information		
Restrictions on use (REACH, annex XVI	I):	
Entry 3, Entry 40, Entry 48		
National regulatory information		
	Observa vestvistions to smaller meant for invaniles seconding to the liv	
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'ju	
	work protection guideline' (94/33/EC). Observe employment restriction under the Maternity Protection Directive (92/85/EEC) for expectant of	
	nursing mothers.	л
Water hazard class (D):	3 - highly hazardous to water	
15.2. Chemical safety assessment		
	bstances in this mixture were not carried out.	

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9.



Lösemittelgemisch L3 Toluol / Ethanol-Gemisch volumetrisch 2:1 gemischt

Revision date: 26.03.2024

Product code: 30199

Page 13 of 13

Abbreviations and acronyms

Flam. Liq: Flammable liquids Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Eye Irrit: Eye irritation Repr: Reproductive toxicity STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure Aquatic Chronic: Chronic aquatic hazard ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globallv Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration. 50% LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)