

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kalilauge 10 % reinst in 2-Propanol

Revision date: 11.05.2023

Product code: 30701

Page 1 of 12

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Kalilauge 10 % reinst in 2-Propanol

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

###### Uses advised against

Do not use for private purposes (household).

##### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

##### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

##### Further Information

This product is a mixture. REACH Registration Number see section 3.

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No 1272/2008

Met. Corr. 1; H290  
Flam. Liq. 2; H225  
Skin Corr. 1A; H314  
Eye Dam. 1; H318  
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

###### Regulation (EC) No 1272/2008

###### Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol  
potassium hydroxide

Signal word: Danger

Pictograms:



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kalilauge 10 % reinst in 2-Propanol

Revision date: 11.05.2023

Product code: 30701

Page 2 of 12

#### Hazard statements

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H336	May cause drowsiness or dizziness.

#### Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves and eye/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

#### 2.3. Other hazards

No data available

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
		REACH No
	Classification (Regulation (EC) No 1272/2008)	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	90 - < 95 %
	200-661-7	603-117-00-0
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	
1310-58-3	potassium hydroxide	10 - < 15 %
	215-181-3	019-002-00-8
	01-2119487136-33	
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A; H290 H302 H314	

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1310-58-3	215-181-3	potassium hydroxide	10 - < 15 %
	oral: LD50 = 333 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		

#### Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

No data available

#### After inhalation

Provide fresh air.  
Call a physician immediately.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kalilauge 10 % reinst in 2-Propanol

Revision date: 11.05.2023

Product code: 30701

Page 3 of 12

#### After contact with skin

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Observe risk of aspiration if vomiting occurs.  
Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

corrosive  
Irritant  
Respiratory complaints  
Headache  
Gastrointestinal complaints  
Dizziness  
Dizziness  
Inebriation  
Anaesthetic state  
Unconsciousness  
Repeated exposure may cause skin dryness or cracking.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Combustible liquids  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Hazardous combustion products  
In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>) Carbon monoxide  
Heating causes rise in pressure with risk of bursting.  
Beware of reignition.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.  
In case of fire and/or explosion do not breathe fumes.  
Avoid contact with skin, eyes and clothes.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Use water spray jet to protect personnel and to cool endangered containers.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Keep away from sources of ignition - No smoking.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kalilauge 10 % reinst in 2-Propanol

Revision date: 11.05.2023

Product code: 30701

Page 4 of 12

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

#### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

Avoid: aerosol or mist formation

#### Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat or drink.

Avoid: aerosol or mist formation

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kalilauge 10 % reinst in 2-Propanol**

Revision date: 11.05.2023

Product code: 30701

Page 5 of 12

Do not breathe vapour/aerosol.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Store in a cool dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Further information on storage conditions**

Protect from sunlight.

storage temperature: +15°C - +25°C

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

**Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Worker DNEL, long-term		inhalation	systemic	500 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
1310-58-3	potassium hydroxide			
Worker DNEL, long-term		inhalation	local	1 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	1 mg/m <sup>3</sup>

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kalilauge 10 % reinst in 2-Propanol**

Revision date: 11.05.2023

Product code: 30701

Page 6 of 12

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

goggles

Face protection umbrella

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Recommended glove articles KCL 730 Camatril® Velours

Thickness of the glove material NBR (Nitrile rubber) 0,4 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles KCL 720 Camapren®

Thickness of the glove material CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

Wear fire resistant or flame retardant clothing.

Take off immediately all contaminated clothing and wash it before reuse.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kalilauge 10 % reinst in 2-Propanol

Revision date: 11.05.2023

Product code: 30701

Page 7 of 12

Wear suitable protective clothing. Take off immediately all contaminated clothing.  
Wash hands and face before breaks and after work and take a shower if necessary.

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.  
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.  
Danger of explosion

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Alcohol	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		~82 °C
Flammability:		No data available
Lower explosion limits:		2 vol. %
Upper explosion limits:		13 vol. %
Flash point:		~13 °C
Auto-ignition temperature:		~425 °C
Decomposition temperature:		No data available
pH-Value:		alkaline
Viscosity / kinematic:		No data available
Water solubility:		Soluble in: Water
Solubility in other solvents:		No data available
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density (at 20 °C):		0,8619 g/cm <sup>3</sup>
Bulk density:		No data available
Relative vapour density:		No data available

### 9.2. Other information

#### Information with regard to physical hazard classes

##### Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

##### Sustaining combustion:

Sustaining combustion

##### Self-ignition temperature

###### Solid:

No data available

###### Gas:

No data available

##### Oxidizing properties

No data available

#### Other safety characteristics

##### Evaporation rate:

No data available

##### Solvent separation test:

No data available

##### Solid content:

No data available

##### Sublimation point:

No data available

##### Softening point:

No data available

##### Pour point:

No data available

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kalilauge 10 % reinst in 2-Propanol**

Revision date: 11.05.2023

Product code: 30701

Page 8 of 12

Viscosity / dynamic:

No data available

Flow time:

No data available

No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Vapours may form explosive mixtures with air.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent, Alkali metals, Alkaline earth metal  
, Nitric acid, aldehydes  
Amines, Aluminium, Chlorine (Cl<sub>2</sub>)  
Phosphorus trichloride, Strong acid, Phosgene  
Hydrogen peroxide, Nitrogen oxides (NO<sub>x</sub>), Iron.

**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5. Incompatible materials**

Glass  
Metal  
Plastic articles

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Toxicokinetics, metabolism and distribution**

No data available

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1310-58-3	potassium hydroxide				
	oral	LD50 333 mg/kg	Rat	Fund. Appl. Toxicol., 8, 97-100 (1987)	OECD Guideline 425

**Irritation and corrosivity**

Causes severe skin burns and eye damage.  
Causes serious eye damage.  
Repeated exposure may cause skin dryness or cracking.



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kalilauge 10 % reinst in 2-Propanol**

Revision date: 11.05.2023

Product code: 30701

Page 9 of 12

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

Organs affected: central nervous system

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

Observe risk of aspiration if vomiting occurs.

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

No data available

**11.2. Information on other hazards**

**Other information**

Pulmonary oedema Pneumonia

**Further information**

corrosive

Irritant

Respiratory complaints

Headache

Gastrointestinal complaints

Dizziness

Dizziness

Inebriation

Anaesthetic state

Unconsciousness

Repeated exposure may cause skin dryness or cracking.

**SECTION 12: Ecological information**

**12.1. Toxicity**

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983) OECD Guideline 203

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Kalilauge 10 % reinst in 2-Propanol

Revision date: 11.05.2023

Product code: 30701

Page 10 of 12

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Avoid release to the environment.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol, potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	338
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol, potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Classification code:	FC

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kalilauge 10 % reinst in 2-Propanol**

Revision date: 11.05.2023

Product code: 30701

Page 11 of 12

Special Provisions: 274  
 Limited quantity: 1 L  
 Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 2924  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol, potassium hydroxide)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3+8  
 Special Provisions: 274  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-C

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 2924  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol, potassium hydroxide)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3+8  
 Special Provisions: A3  
 Limited quantity Passenger: 0.5 L  
 Passenger LQ: Y340  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 352  
 IATA-max. quantity - Passenger: 1 L  
 IATA-packing instructions - Cargo: 363  
 IATA-max. quantity - Cargo: 5 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):  
 Entry 3, Entry 40, Entry 75  
 Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).  
 Water hazard class (D): 1 - slightly hazardous to water

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 2,8,9,13.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kalilauge 10 % reinst in 2-Propanol**

Revision date: 11.05.2023

Product code: 30701

Page 12 of 12

**Abbreviations and acronyms**

Met. Corr  
Flam. Liq  
Acute Tox  
Skin Corr  
Eye Dam  
Eye Irrit  
STOT SE

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H336	Calculation method

**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.  
H290 May be corrosive to metals.  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*