

## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Natronlauge 0,005 mol/l - 0,005 N Lösung in Methanol

Revision date: 15.05.2023 Product code: 31256 Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Natronlauge 0,005 mol/l - 0,005 N Lösung in Methanol

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

#### **Further Information**

This product is a mixture. REACH Registration Number see section 3.

### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H331 STOT SE 1; H370

Full text of hazard statements: see SECTION 16.

# 2.2. Label elements

## Regulation (EC) No 1272/2008

## Hazard components for labelling

methanol

Signal word: Danger

Pictograms:







# **Hazard statements**

H225 Highly flammable liquid and vapour.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Natronlauge 0,005 mol/l - 0,005 N Lösung in Methanol

Revision date: 15.05.2023 Product code: 31256 Page 2 of 13

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H370 Causes damage to organs.

**Precautionary statements** 

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.

## 2.3. Other hazards

No data available

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### **Hazardous components**

| CAS No  | Chemical name   | Chemical name                                 |                  |  |
|---------|---|---|------------------|--|
|         | EC No   | EC No Index No REACH No                       |                  |  |
|         | Classification (Regulat   | Classification (Regulation (EC) No 1272/2008) |                  |  |
| 67-56-1 | methanol  | methanol                                      |                  |  |
|         | 200-659-6   | 603-001-00-X                                  | 01-2119433307-44 |  |
|         | Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370 |   |                  |  |

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

| CAS No  | EC No  | Chemical name |              |  |  |  |
|---------|--|---------------|--------------|--|--|--|
|         | Specific Conc. Limits, M-factors and ATE   |               |              |  |  |  |
| 67-56-1 | 200-659-6  | methanol      | 95 - < 100 % |  |  |  |
|         | inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10 |               |              |  |  |  |

#### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## **General information**

First aider: Pay attention to self-protection!

## After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

# After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

## After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Natronlauge 0,005 mol/l - 0,005 N Lösung in Methanol

Revision date: 15.05.2023 Product code: 31256 Page 3 of 13

Remove contact lenses, if present and easy to do. Continue rinsing.

Consult an ophthalmologist.

## After ingestion

Provide fresh air.

Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

Notes for the doctor: Methanol

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant, Dizziness, Dizziness

Anaesthetic state, Agitation, Spasms

Inebriation, Vomiting, Headache

Impairment of vision, Dyspnoea, Cough

Repeated exposure may cause skin dryness or cracking.

Risk of serious damage to eyes.

Circulatory collapse, Corneal opacity.

## 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor: Methanol

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Carbon dioxide (CO2)

Foam

Extinguishing powder

### Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Combustible liquids

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide, Carbon monoxide

Beware of reignition.

Heating causes rise in pressure with risk of bursting.

## 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Wear full chemical protective clothing.

In case of fire and/or explosion do not breathe fumes.

## Additional information

Use water spray jet to protect personnel and to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Natronlauge 0,005 mol/l - 0,005 N Lösung in Methanol

Revision date: 15.05.2023 Product code: 31256 Page 4 of 13

#### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

### 6.3. Methods and material for containment and cleaning up

#### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

## Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

### Advice on safe handling

Avoid exposure - obtain special instructions before use.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

# Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

## Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

## Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Natronlauge 0,005 mol/l - 0,005 N Lösung in Methanol

Revision date: 15.05.2023 Product code: 31256 Page 5 of 13

a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

# 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Unsuitable container/equipment material: Aluminium, tin, zinc

### Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

### Further information on storage conditions

Keep cool. Protect from sunlight. storage temperature +15°C - +25°C

### 7.3. Specific end use(s)

Laboratory chemicals

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

| CAS No  | Substance      | ppm | mg/m³ | fib/cm³ | Category  | Origin |
|---------|----------------|-----|-------|---------|-----------|--------|
| 67-56-1 | Methyl alcohol | 200 | 260   |         | TWA (8 h) |        |

## **Biological limit values**

| CAS No  | Substance | Parameter | Value   | Test material | Sampling time |
|---------|-----------|-----------|---------|---------------|---------------|
| 67-56-1 | Methanol  | Methanol  | 15 mg/L | Urine         | End of shift  |

### **DNEL/DMEL values**

| CAS No                   | Substance          |                |          |                 |
|--------------------------|--------------------|----------------|----------|-----------------|
| DNEL type                |                    | Exposure route | Effect   | Value           |
| 67-56-1                  | methanol           |                |          |                 |
| Consumer DN              | EL, acute          | inhalation     | systemic | 50 mg/m³        |
| Worker DNEL,             | long-term          | inhalation     | systemic | 260 mg/m³       |
| Worker DNEL,             | acute              | inhalation     | systemic | 260 mg/m³       |
| Worker DNEL,             | long-term          | inhalation     | local    | 260 mg/m³       |
| Worker DNEL,             | Worker DNEL, acute |                | local    | 260 mg/m³       |
| Worker DNEL,             | long-term          | dermal         | systemic | 40 mg/kg bw/day |
| Worker DNEL,             | Worker DNEL, acute |                | systemic | 40 mg/kg bw/day |
| Consumer DN              | EL, long-term      | inhalation     | systemic | 50 mg/m³        |
| Consumer DN              | EL, long-term      | inhalation     | local    | 50 mg/m³        |
| Consumer DN              | EL, acute          | inhalation     | local    | 50 mg/m³        |
| Consumer DNEL, long-term |                    | dermal         | systemic | 8 mg/kg bw/day  |
| Consumer DNEL, acute     |                    | dermal         | systemic | 8 mg/kg bw/day  |
| Consumer DNEL, long-term |                    | oral           | systemic | 8 mg/kg bw/day  |
| Consumer DN              | EL, acute          | oral           | systemic | 8 mg/kg bw/day  |



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Natronlauge 0,005 mol/l - 0,005 N Lösung in Methanol

Revision date: 15.05.2023 Product code: 31256 Page 6 of 13

#### **PNEC values**

| CAS No   | Substance                 |           |
|--|---------------------------|-----------|
| Environmental                                    | Environmental compartment |           |
| 67-56-1 methanol                                 |                           |           |
| Freshwater                                       |                           | 20,8 mg/l |
| Freshwater (intermittent releases)               |                           | 1540 mg/l |
| Marine water                                     |                           | 2,08 mg/l |
| Freshwater sediment                              |                           | 77 mg/kg  |
| Marine sediment                                  |                           | 7,7 mg/kg |
| Micro-organisms in sewage treatment plants (STP) |                           | 100 mg/l  |
| Soil   |                           | 100 mg/kg |

# 8.2. Exposure controls

# Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

goggles

## Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Natronlauge 0,005 mol/l - 0,005 N Lösung in Methanol

Revision date: 15.05.2023 Product code: 31256 Page 7 of 13

Draw up and observe skin protection programme.

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: like: Methanol

Melting point/freezing point:

No data available
Boiling point or initial boiling point and

~64 °C

boiling range:

Lower explosion limits:

Flammability: not applicable

not applicable 5,5 vol. % 44 vol. %

Upper explosion limits: 44 vol. % Flash point: ~11 °C Auto-ignition temperature: 455 °C

Decomposition temperature: not determined pH-Value: alkaline Viscosity / kinematic: not determined

Water solubility: Soluble in: Water

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Palk density:

No data available

Relative vapour density:

not determined

### 9.2. Other information

## Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Sustaining combustion: Sustaining combustion

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties not determined

Other safety characteristics

Evaporation rate:

Solvent separation test:

Solid content:

Sublimation point:

No data available
Pour point:

No data available
No data available

No data available:



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Natronlauge 0,005 mol/l - 0,005 N Lösung in Methanol

Revision date: 15.05.2023 Product code: 31256 Page 8 of 13

Viscosity / dynamic:

Flow time:

No data available
not determined

**Further Information** 

May be corrosive to metals.

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Highly flammable.

Vapours can form explosive mixtures with air.

May be corrosive to metals.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

Oxidising agent, Hydrogen peroxide, Acid halides Reducing agent, Acid, Alkaline earth metal, Alkali metals

### 10.4. Conditions to avoid

Vapours can form explosive mixtures with air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

Plastic articles

Glass

metals (including their alloys)

### 10.6. Hazardous decomposition products

**SECTION 5: Firefighting measures** 

#### **Further information**

No data available

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Toxicocinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

### **Acute toxicity**

Toxic if swallowed.

Toxic in contact with skin.

Toxic if inhaled.

### **ATEmix calculated**

ATE (oral) 101,3 mg/kg; ATE (dermal) 303,8 mg/kg; ATE (inhalation vapour) 3,040 mg/l; ATE (inhalation dust/mist) 0,5060 mg/l



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Natronlauge 0,005 mol/l - 0,005 N Lösung in Methanol

Revision date: 15.05.2023 Product code: 31256 Page 9 of 13

| CAS No  | Chemical name           |               |          |         |  |   |  |
|---------|-------------------------|---------------|----------|---------|--|---|--|
|         | Exposure route          | Dose          |          | Species |  | Source                                      | Method                                   |
| 67-56-1 | methanol                |               |          |         |  |   |  |
|         | oral                    | LD50<br>mg/kg | 6000     | Monkey  |  | Amer J Ophthalmol<br>40: 76-83 (cited in DG | Determination of the acute toxicity of t |
|         | dermal                  | ATE<br>mg/kg  | 300      |         |  |   |  |
|         | inhalation (4 h) vapour | LC50<br>mg/l  | 128,2    | Rat     |  | Study report (1980)                         | Study performed according to internal co |
|         | inhalation dust/mist    | ATE           | 0,5 mg/l |         |  |   |  |

### Irritation and corrosivity

Based on available data, the classification criteria are not met. Corneal opacity.

## Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

Causes damage to organs. (methanol) eyes

Liver and kidney damage

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

## Other information

Irritant, Dizziness, Dizziness
Anaesthetic state, Agitation, Spasms
Inebriation, Vomiting, Headache
Impairment of vision, Dyspnoea, Cough
Repeated exposure may cause skin dryne

Repeated exposure may cause skin dryness or cracking.

Risk of serious damage to eyes. Circulatory collapse, Corneal opacity.

#### **Further information**

Do not empty into drains.

Discharge into the environment must be avoided.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

There are no data available on the mixture itself.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Natronlauge 0,005 mol/l - 0,005 N Lösung in Methanol

Revision date: 15.05.2023 Product code: 31256 Page 10 of 13

| CAS No  | Chemical name            |                     |          |           |                                    |  |  |
|---------|--------------------------|---------------------|----------|-----------|------------------------------------|--|--|
|         | Aquatic toxicity         | Dose                |          | [h]   [d] | Species                            | Source   | Method                                   |
| 67-56-1 | methanol                 |                     |          |           |                                    |  |  |
|         | Acute fish toxicity      | LC50<br>mg/l        | 15400    | 96 h      | Lepomis macrochirus                | Bulletin of<br>Environmental<br>Contamination  | other:<br>EPA-660/3-75-00<br>9, 1975     |
|         | Acute algae toxicity     | ErC50<br>22000 mg/l | ca.      | 96 h      | Pseudokirchneriella<br>subcapitata | Ecotoxicology and<br>Environmental<br>Safety 7 | OECD Guideline<br>201                    |
|         | Acute crustacea toxicity | EC50<br>mg/l        | > 10000  | 48 h      | Daphnia magna                      | Water Research<br>23(4): 495-499<br>(1989)     | other: DIN 38412<br>Teil 11              |
|         | Fish toxicity            | NOEC<br>mg/l        | 446,7    | 28 d      | Pimephales promelas                | SAR and QSAR in<br>Environmental<br>Research,  | Calculation<br>performed with<br>ECOSAR  |
|         | Crustacea toxicity       | NOEC                | 208 mg/l | 21 d      | Daphnia magna                      | OECD QSAR<br>Toolbox Report<br>(2013)          | Toxicity of the target chemical is predi |

## 12.2. Persistence and degradability

There are no data available on the mixture itself.

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

### Partition coefficient n-octanol/water

| CAS No  | Chemical name | Log Pow |
|---------|---------------|---------|
| 67-56-1 | methanol      | -0,77   |

### **BCF**

| CAS No  | Chemical name | BCF | Species         | Source               |
|---------|---------------|-----|-----------------|----------------------|
| 67-56-1 | methanol      | 1   | Cyprinus carpio | Comparative Biochemi |

### 12.4. Mobility in soil

There are no data available on the mixture itself.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

No data available

## **Further information**

Do not allow to enter into surface water or drains.

Avoid release to the environment.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

## **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Natronlauge 0,005 mol/l - 0,005 N Lösung in Methanol

Revision date: 15.05.2023 Product code: 31256 Page 11 of 13

### Contaminated packaging

This material and its container must be disposed of as hazardous waste.

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

| 14.1. UN number or ID number:  | UN 1230  |
|--------------------------------|----------|
| 14.2. UN proper shipping name: | METHANOL |

14.3. Transport hazard class(es): 3 14.4. Packing group: Ш Hazard label: 3+6.1 Classification code: FT1 Special Provisions: 279 Limited quantity: 1 L Excepted quantity: F2 Transport category: 2 Hazard No: 336 Tunnel restriction code: D/E

### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1230 **14.2. UN proper shipping name:** METHANOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+6.1Classification code:FT1Special Provisions:279 802Limited quantity:1 LExcepted quantity:E2

## Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1230 **14.2. UN proper shipping name:** METHANOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+6.1Special Provisions:279Limited quantity:1 LExcepted quantity:E2EmS:F-E. S-D

#### Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:UN 123014.2. UN proper shipping name:METHANOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+6.1Special Provisions:A113Limited quantity Passenger:1 LPassenger LQ:Y341Excepted quantity:E2

IATA-packing instructions - Passenger: 352
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 364



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Natronlauge 0,005 mol/l - 0,005 N Lösung in Methanol

Revision date: 15.05.2023 Product code: 31256 Page 12 of 13

IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. Toxic.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

### **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 69, Entry 75

Information according to 2012/18/EU H2 ACUTE TOXIC

(SEVESO III):

Additional information: P5c

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 2,8.

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% Flam. Liq: Flammable liquid Acute Tox: Acute toxicity

STOT SE: Specific target organ toxicity - single exposure

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

| Classification     | Classification procedure |
|--------------------|--------------------------|
| Flam. Liq. 2; H225 | On basis of test data    |
| Acute Tox. 3; H301 | Calculation method       |
| Acute Tox. 3; H311 | Calculation method       |
| Acute Tox. 3; H331 | Calculation method       |
| STOT SE 1; H370    | Calculation method       |

#### Relevant H and EUH statements (number and full text)



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

| Natronlauge | 0.005 mol/l | - 0.005 N I | Lösuna ir | Methanol |
|-------------|-------------|-------------|-----------|----------|
|             | 0,000       | -,          |           |          |

Revision date: 15.05.2023 Product code: 31256 Page 13 of 13

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.

### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)