

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5

%

Revision date: 22.04.2024 Product code: 31445 Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5 %

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Acute Tox. 2; H330 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Carc. 1A; H350 STOT RE 2; H373 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5

Revision date: 22.04.2024 Product code: 31445 Page 2 of 17

Hazard components for labelling

nitric acid

 $beryllium\ compounds\ with\ the\ exception\ of\ aluminium\ beryllium\ silicates,\ and\ with\ those\ specified\ elsewhere\ in$

this Annex

arsenic acid and it salts with the exception of those specified elsewhere in this Annex

cobalt dinitrate

Signal word: Danger

Pictograms:







Hazard statements

H290 May be corrosive to metals.

H330 Fatal if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5 %

Revision date: 22.04.2024 Product code: 31445 Page 3 of 17

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)		
7697-37-2	nitric acid			5 - < 10 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, Ac	ute Tox. 3, Skin Corr. 1A; H272 H2	90 H331 H314 EUH071	
-	beryllium compounds with telsewhere in this Annex	he exception of aluminium berylliu	m silicates, and with those specified	1 - < 5 %
	-	004-002-00-2		
		ute Tox. 3, Skin Irrit. 2, Eye Irrit. 2, 350i H330 H301 H315 H319 H317		
7647-01-0	Hydrochloric acid			< 1 %
	231-595-7	017-002-01-X	01-2119484862-27	
	Skin Corr. 1B, STOT SE 3;	H314 H335		
10043-35-3	boric acid			< 1 %
	233-139-2	005-007-00-2	01-2119486683-25	
	Repr. 1B; H360FD			
-	arsenic acid and it salts wit	n the exception of those specified	elsewhere in this Annex	< 1 %
	-	033-005-00-1		
	Carc. 1A, Acute Tox. 3, Acute H410	ute Tox. 3, Aquatic Acute 1, Aquati	c Chronic 1; H350 H331 H301 H400	
10022-31-8	bariumnitrat	< 1 %		
	233-020-5	056-002-00-7		
	Ox. Sol. 2, Acute Tox. 3, Ac	cute Tox. 4, Eye Irrit. 2; H272 H30	1 H332 H319	
7647-17-8	caesium chloride			< 1 %
	231-600-2		01-2119977124-35	
	Repr. 2; H361			
10141-05-6	cobalt dinitrate			< 0.1 %
	233-402-1	027-009-00-2		
	Carc. 1B, Muta. 2, Repr. 1E H350i H341 H360F H334 F	3, Resp. Sens. 1, Skin Sens. 1, Aq I317 H400 H410	uatic Acute 1, Aquatic Chronic 1;	
10325-94-7	cadmium nitrate; cadmium	< 0.1 %		
	233-710-6	048-014-00-6		
		B, Acute Tox. 4, Acute Tox. 4, Ac H350 H340 H360 H332 H312 H3		

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5 %

Revision date: 22.04.2024 Product code: 31445 Page 4 of 17

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
7697-37-2	231-714-2	nitric acid	5 - < 10 %
	l l	E 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 orr. 1B; H314: >= 5 - < 20	
-	-	beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex	1 - < 5 %
	inhalation: ATI 100 mg/kg	E = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); oral: ATE =	
7647-01-0	231-595-7	Hydrochloric acid	< 1 %
		H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 3; H335: >= 10 - 100	
10043-35-3	233-139-2	boric acid	< 1 %
	inhalation: LC: 3450 mg/kg	50 = > 2,12 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 =	
-	-	arsenic acid and it salts with the exception of those specified elsewhere in this Annex	< 1 %
	inhalation: ATI mg/kg	E = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: ATE = 100	
10022-31-8	233-020-5	bariumnitrat	< 1 %
	inhalation: ATI 50 - < 300 mg/	E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = >	
7647-17-8	231-600-2	caesium chloride	< 1 %
	dermal: LD50	= > 2000 mg/kg; oral: LD50 = 2500 mg/kg	
10141-05-6	233-402-1	cobalt dinitrate	< 0.1 %
		i: >= 0,01 - 100	
	Aquatic Acute		
10325-94-7	233-710-6	c 1; H410: M=10 cadmium nitrate; cadmium dinitrate	< 0.1 %
10020-04-1	inhalation: ATI	E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = al: ATE = 500 mg/kg	V.1 70

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing.

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5

Revision date: 22.04.2024 Product code: 31445 Page 5 of 17

After ingestion

Never give anything by mouth to an unconscious person or a person with cramps.

Rinse mouth immediately and drink plenty of water.

Do not allow a neutralisation agent to be drunk. Do NOT induce vomiting.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage

Causes burns.

Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

5.3. Advice for firefighters

Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5

Revision date: 22.04.2024 Product code: 31445 Page 6 of 17

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Provide adequate ventilation.

Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Make available sufficient washing facilities

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a well-ventilated place. Keep container tightly closed.

Corrosive to metals.

Store in a place accessible by authorized persons only.

Further information on storage conditions

Store in a dry place.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5

Revision date: 22.04.2024 Product code: 31445 Page 7 of 17

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7429-90-5	Aluminium metal (Respirable Fraction)	-	1		TWA (8 h)	
10043-35-3	Borate compounds inorganic: boric acid	-	2		TWA (8 h)	
7647-01-0	Hydrogen chloride	5	8		TWA (8 h)	
		10	15		STEL (15 min)	
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
7647-01-0	Hydrochloric acid			
Worker DNEL,	long-term	inhalation	local	8 mg/m³
Worker DNEL,	acute	inhalation	local	15 mg/m³
Consumer DN	EL, long-term	inhalation	local	8 mg/m³
Consumer DN	EL, acute	inhalation	local	15 mg/m³
10043-35-3	boric acid			
Worker DNEL,	long-term	inhalation	systemic	8,3 mg/m³
Worker DNEL,	long-term	dermal	systemic	392 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	4,15 mg/m³
Consumer DN	EL, long-term	dermal	systemic	196 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	0,98 mg/kg bw/day
Consumer DN	EL, acute	oral	systemic	0,98 mg/kg bw/day
10022-31-8	bariumnitrat			
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³
Worker DNEL,	long-term	dermal	systemic	8,141 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	0,67 mg/m³
Consumer DN	EL, long-term	dermal	systemic	4,07 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,58 mg/kg bw/day
7647-17-8	caesium chloride			
Worker DNEL,	long-term	inhalation	systemic	1,47 mg/m³
Worker DNEL,	long-term	dermal	systemic	4,18 mg/kg bw/day



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5 %

Revision date: 22.04.2024 Product code: 31445 Page 8 of 17

PNEC values

CAS No	Substance			
Environmenta	compartment	Value		
10043-35-3	0043-35-3 boric acid			
Freshwater		2,9 mg/l		
Freshwater (in	termittent releases)	13,7 mg/l		
Marine water		2,9 mg/l		
Micro-organis	ns in sewage treatment plants (STP)	10 mg/l		
Soil		5,7 mg/kg		
10022-31-8	bariumnitrat			
Freshwater		0,115 mg/l		
Freshwater sediment 600 m		600 mg/kg		
Micro-organisms in sewage treatment plants (STP) 62,2 ii		62,2 mg/l		
Soil 2		207,7 mg/kg		
7647-17-8	caesium chloride			
Freshwater		1,25 mg/l		
Freshwater (in	termittent releases)	0,37 mg/l		
Marine water 0,13		0,13 mg/l		
Freshwater sediment 4,9 m		4,9 mg/kg		
Marine sediment 0,49 m		0,49 mg/kg		
Micro-organisi	ns in sewage treatment plants (STP)	100,3 mg/l		
Soil		0,25 mg/kg		

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye protection/face protection.

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

KCL 741 Dermatril® L NBR (Nitrile rubber) 0,11mm

Wearing time with permanent contact: >480min

KCL 741 Dermatril® L

NBR (Nitrile rubber) 0,11mm

Wearing time with occasional contact (splashes): >480min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5

Revision date: 22.04.2024 Product code: 31445 Page 9 of 17

and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing.

Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: clear
Odour: odourless

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

No data available Flammability: No data available Lower explosion limits: No data available Upper explosion limits: Flash point: No data available Auto-ignition temperature: No data available No data available Decomposition temperature: acidic pH-Value: Viscosity / kinematic: No data available No data available Water solubility:

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Vapour pressure:

No data available

Density:

1,03 g/cm³

Bulk density:

No data available

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion: No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5

Revision date: 22.04.2024 Product code: 31445 Page 10 of 17

No data available

Other safety characteristics

Evaporation rate:

Solvent separation test:

Solvent content:

Solid content:

Sublimation point:

Softening point:

No data available

No data available

No data available

No data available

No data available:

Pour point:

Viscosity / dynamic:

Flow time:

No data available

No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

Alkali (lye)

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Fatal if inhaled.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) 3,527 mg/l



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5

Revision date: 22.04.2024 Product code: 31445 Page 11 of 17

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
7697-37-2	nitric acid								
	inhalation vapour	ATE 2,65 r	ng/l						
-	beryllium compounds withis Annex	with the excepti	on of alumir	nium beryllium silio	ates, and with those specified els	sewhere in			
	oral	ATE mg/kg	100						
	inhalation vapour	ATE	0,5 mg/l						
	inhalation dust/mist	ATE	0,05 mg/l						
10043-35-3	boric acid								
	oral	LD50 mg/kg	3450	Rat	Toxicology and Applied Pharmacology 23:	other: No data			
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)	other: FIFRA			
	inhalation (4 h) dust/mist	LC50 mg/l	> 2,12	Rat	Study report (1997)	OECD Guideline 403			
-	arsenic acid and it salts	s with the excep	ption of thos	se specified elsewh	nere in this Annex				
	oral	ATE mg/kg	100						
	inhalation vapour	ATE	3 mg/l						
	inhalation dust/mist	ATE	0,5 mg/l						
10022-31-8	bariumnitrat								
	oral	LD50 300 mg/kg	> 50 - <	Rat	Study report (2013)	OECD Guideline 423			
	inhalation vapour	ATE	11 mg/l						
	inhalation dust/mist	ATE	1,5 mg/l						
7647-17-8	caesium chloride								
	oral	LD50 mg/kg	2500	Mouse	Mutation Research, 244, 295-298 (1990)	other: no data			
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2012)	OECD Guideline 402			
10325-94-7	cadmium nitrate; cadm								
	oral	ATE mg/kg	500						
	dermal	ATE mg/kg	1100						
	inhalation vapour	ATE	11 mg/l						
	inhalation dust/mist	ATE	1,5 mg/l						

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Corrosive to the respiratory tract.

Sensitising effects

May cause an allergic skin reaction. (beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex; cobalt dinitrate)

Carcinogenic/mutagenic/toxic effects for reproduction



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5 %

Revision date: 22.04.2024 Product code: 31445 Page 12 of 17

May cause cancer. (beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex; arsenic acid and it salts with the exception of those specified elsewhere in this Annex; cobalt dinitrate; cadmium nitrate; cadmium dinitrate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex)

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5

Revision date: 22.04.2024 Product code: 31445 Page 13 of 17

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
7697-37-2	nitric acid			,			
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209
7647-01-0	Hydrochloric acid						
	Acute fish toxicity	LC50	862 mg/l	96 h	Leuciscus idus		
10043-35-3	boric acid						
	Acute fish toxicity	LC50 mg/l	79,7	96 h	Pimephales promelas	Study report (2010)	other: ASTM E729-95 Standard Guide for C
	Acute algae toxicity	ErC50	66 mg/l	72 h	Phaeodactylum tricornutum	Study report (2011)	ISO 10253
	Acute crustacea toxicity	EC50	109 mg/l	48 h	Ceriodaphnia dubia	Study report (2010)	other: ASTM E729-95 Standar Guide for C
	Fish toxicity	NOEC mg/l	11,2	32 d	Pimephales promelas	Study report (2010)	other: ASTM E1241-05 Standard Guide for
	Algae toxicity	NOEC mg/l	17,5	3 d	Pseudokirchneriella subcapitata	Study report (2000)	OECD Guideline 201
	Crustacea toxicity	NOEC mg/l	25,9	42 d	other aquatic crustacea: Hyalella azteca	Study report (2010)	other: US EPA 2000 Methods for assessing
	Acute bacteria toxicity	EC50 mg/l ()	> 10000	3 h	activated sludge of a predominantly domestic sewag	Study report (2001)	OECD Guideline 209
10022-31-8	bariumnitrat						
	Acute fish toxicity	LC50 mg/l	> 3,5	96 h	Danio rerio	Study report (2010)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 1,15	72 h	Pseudokirchneriella subcapitata	Study report (2010)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	14,5	48 h	Daphnia magna	Journal of the Fisheries Research Board	Not a guideline study but meets generall
	Fish toxicity	NOEC mg/l	>= 100	33 d	Danio rerio	Study report (2014)	OECD Guideline 210
	Crustacea toxicity	NOEC	2,9 mg/l	21 d	Daphnia magna	Journal of the Fisheries Research Board	The test did not exacty follow an existi
	Acute bacteria toxicity	EC50 mg/l ()	> 1000		activated sludge of a predominantly domestic sewag	Study report (2010)	OECD Guideline 209



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5

Revision date: 22.04.2024 Product code: 31445 Page 14 of 17

7647-17-8	caesium chloride					
	Acute fish toxicity	LC50 mg/l	> 100	96 h Danio rerio	Study report (2011)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	133,99	72 h Pseudokirchnerie subcapitata	Study report (2011)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	37,4	48 h Daphnia magna	Study report (2012)	OECD Guideline 202
	Fish toxicity	NOEC	43 mg/l	35 d Danio rerio	Study report (2012)	OECD Guideline 210
	Crustacea toxicity	NOEC mg/l	15,8	21 d Daphnia magna	Study report (2012)	OECD Guideline 211
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h activated sludge, domestic	Study report (2011)	OECD Guideline 209

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
10043-35-3	boric acid	-1,09
7647-17-8	caesium chloride	0,54

BCF

CAS No	Chemical name	BCF	Species	Source
10043-35-3	boric acid	0,558	Oncorhynchus nerka	Water Research Vol.
10022-31-8	bariumnitrat	68,4	Lepomis macrochirus	Archives of Environm

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Do not allow to enter into surface water or drains.

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Dispose of waste according to applicable legislation.

Do not allow to enter into surface water or drains.

Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 2031 14.2. UN proper shipping name: NITRIC ACID 8

14.3. Transport hazard class(es):



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5

%

Revision date: 22.04.2024 Product code: 31445 Page 15 of 17

14.4. Packing group:IIHazard label:8Classification code:C1Limited quantity:1 LExcepted quantity:E2Transport category:2Hazard No:80Tunnel restriction code:E

Inland waterways transport (ADN)

14.1. UN number or ID number:UN 203114.2. UN proper shipping name:NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Classification code:C1Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number:UN 203114.2. UN proper shipping name:NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:-Limited quantity:1 LExcepted quantity:E2EmS:F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2031
14.2. UN proper shipping name: NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:A212Limited quantity Passenger:ForbiddenPassenger LQ:ForbiddenExcepted quantity:E0

IATA-packing instructions - Passenger: Forbidden
IATA-max. quantity - Passenger: Forbidden
IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

arsenic acid and it salts with the exception of those specified elsewhere in this Annex

Substances of very high concern, SVHC (REACH, article 59): boric acid; cobalt dinitrate; cadmium nitrate; cadmium dinitrate



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5 %

Revision date: 22.04.2024 Product code: 31445 Page 16 of 17

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 23, Entry 28, Entry 30, Entry 75

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information

Abbreviations and acronyms

Pyr. Sol: Pyrophoric solid

Water-react: Substance and mixture which, in contact with water, emits flammable gas

Ox. Liq: Oxidising liquid Ox. Sol: Oxidising solid

Met. Corr: Substance or mixture corrosive to metals

Flam. Sol: Flammable solid Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation

Resp. Sens: Respiratory sensitisation

Skin Sens: Skin sensitisation Muta: Germ cell mutagenicity Carc: Carcinogenicity

Carc: Carcinogenicity
Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Acute Tox. 2; H330	
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Carc. 1A; H350	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Alle Elemente 3" 12 Elemente je 1000 mg/l in Salpetersäure 5 %

Revision date: 22.04.2024 Product code: 31445 Page 17 of 17

Ision date: 22.04.2024	Product code: 31445	Page 17 of 17
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H330	Fatal if inhaled.	
H331	Toxic if inhaled.	
H332	Harmful if inhaled.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335	May cause respiratory irritation.	
H340	May cause genetic defects.	
H341	Suspected of causing genetic defects.	
H350	May cause cancer.	
H350i	May cause cancer by inhalation.	
H360	May damage fertility or the unborn child.	
H360F	May damage fertility.	
H360FD	May damage fertility. May damage the unborn child.	
H361	Suspected of damaging fertility or the unborn child.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH071	Corrosive to the respiratory tract.	
urther Information		

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)