

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Prüfflüssigkeit 3b 64 Vol.% Diesel - 16 Vol.% 1-Methylnaphthalin - 20 Vol.% RME

Revision date: 22.04.2024

Product code: 31491

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Prüfflüssigkeit 3b 64 Vol.% Diesel - 16 Vol.% 1-Methylnaphthalin - 20 Vol.% RME

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Acute Tox. 4; H332

Asp. Tox. 1; H304

Skin Irrit. 2; H315

Carc. 2; H351

STOT RE 2; H373

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Diesel fuel

Signal word: Danger**Pictograms:**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Prüfflüssigkeit 3b 64 Vol.% Diesel - 16 Vol.% 1-Methylnaphthalin - 20 Vol.% RME

Revision date: 22.04.2024

Product code: 31491

Page 2 of 11

Hazard statements

H332	Harmful if inhaled.
H315	Causes skin irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P308+P313	IF exposed or concerned: Get medical advice/attention.

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
68476-34-6	Fuels, diesel, No 2			60 - < 65 %
	270-676-1	649-227-00-2	01-2119484664-27	
	Flam. Liq. 3, Carc. 2, Acute Tox. 4, Skin Irrit. 2, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H226 H351 H332 H315 H373 H304 H411			
90-12-0	1-methylnaphthalene			15 - < 20 %
	201-966-8			
	Acute Tox. 4, Asp. Tox. 1, Aquatic Chronic 2; H302 H304 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
68476-34-6	270-676-1	Fuels, diesel, No 2	60 - < 65 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists)		
90-12-0	201-966-8	1-methylnaphthalene	15 - < 20 %
	oral: ATE = 500 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Prüfflüssigkeit 3b 64 Vol.% Diesel - 16 Vol.% 1-Methylnaphthalin - 20 Vol.% RME

Revision date: 22.04.2024

Product code: 31491

Page 3 of 11

General information

Avoid contact with skin, eyes and clothes.
Take off immediately all contaminated clothing.

After inhalation

Provide fresh air.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
Remove contact lenses, if present and easy to do. Continue rinsing.
Protect uninjured eye.

After ingestion

Call a physician immediately.
Observe risk of aspiration if vomiting occurs.

4.2. Most important symptoms and effects, both acute and delayed

Irritant
Aspiration hazard

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible liquids
Hazardous combustion products
In case of fire may be liberated: Carbon dioxide (CO₂) Carbon monoxide
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Prüfflüssigkeit 3b 64 Vol.% Diesel - 16 Vol.% 1-Methylnaphthalin - 20 Vol.% RME

Revision date: 22.04.2024

Product code: 31491

Page 4 of 11

Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.
Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Collect in closed and suitable containers for disposal.
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff.
Use personal protection equipment. Use extractor hood (laboratory).
Provide adequate ventilation.
Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary.
Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Prüfflüssigkeit 3b 64 Vol.% Diesel - 16 Vol.% 1-Methylnaphthalin - 20 Vol.% RME

Revision date: 22.04.2024

Product code: 31491

Page 5 of 11

Requirements for storage rooms and vessels

- Keep container tightly closed.
- Store in a place accessible by authorized persons only.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

- Keep cool. Protect from sunlight.

7.3. Specific end use(s)

- Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
90-12-0	1-Methylnaphthalene	0.5	-		TWA (8 h)	

8.2. Exposure controls

Appropriate engineering controls

- Technical measures and the application of suitable work processes have priority over personal protection equipment.
- If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

- goggles
- Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

- Trade name/designation KCL 890 Vitoject®
- Recommended material: FKM (fluoro rubber) 0,7 mm
- Wearing time with permanent contact: > 480 min

By short-term hand contact

- Trade name/designation KCL 730 Camatril® Velours
- Recommended material: NBR (Nitrile rubber) 0,4 mm
- Wearing time with occasional contact (splashes): > 30 min

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Prüfflüssigkeit 3b 64 Vol.% Diesel - 16 Vol.% 1-Methylnaphthalin - 20 Vol.% RME

Revision date: 22.04.2024

Product code: 31491

Page 6 of 11

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	clear	
Odour:	like: Diesel fuel	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		>35 °C
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		>65 °C
Auto-ignition temperature:		No data available
pH-Value:		No data available
Viscosity / kinematic:		No data available
Water solubility:		No data available
Solubility in other solvents		No data available
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Density:		0,888 g/cm ³
Bulk density:		No data available
Relative vapour density:		No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Sustaining combustion:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:	No data available
Solvent separation test:	No data available
Solid content:	0
Sublimation point:	No data available
Softening point:	No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Prüfflüssigkeit 3b 64 Vol.% Diesel - 16 Vol.% 1-Methylnaphthalin - 20 Vol.% RME

Revision date: 22.04.2024

Product code: 31491

Page 7 of 11

Pour point: No data available
 No data available:
 Viscosity / dynamic: No data available
 Flow time: No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 17,75 mg/l; ATE (inhalation dust/mist) 2,420 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68476-34-6	Fuels, diesel, No 2				
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
90-12-0	1-methylnaphthalene				
	oral	ATE 500 mg/kg			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Fuels, diesel, No 2)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Prüfflüssigkeit 3b 64 Vol.% Diesel - 16 Vol.% 1-Methylnaphthalin - 20 Vol.% RME

Revision date: 22.04.2024

Product code: 31491

Page 8 of 11

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Fuels, diesel, No 2)

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Discharge into the environment must be avoided.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Prüfflüssigkeit 3b 64 Vol.% Diesel - 16 Vol.% 1-Methylnaphthalin - 20 Vol.% RME

Revision date: 22.04.2024

Product code: 31491

Page 9 of 11

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (Diesel fuel, methylnaphthalene)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9
 Classification code: M6
 Special Provisions: 274 335 375 601
 Limited quantity: 5 L
 Excepted quantity: E1
 Transport category: 3
 Hazard No: 90
 Tunnel restriction code: -

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (Diesel fuel, methylnaphthalene)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9
 Classification code: M6
 Special Provisions: 274 335 375 601
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (Diesel fuel, methylnaphthalene)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9
 Special Provisions: 274, 335, 969
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (Diesel fuel, methylnaphthalene)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9
 Special Provisions: A97 A158 A197
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y964
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 964
 IATA-max. quantity - Passenger: 450 L
 IATA-packing instructions - Cargo: 964
 IATA-max. quantity - Cargo: 450 L

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Prüfflüssigkeit 3b 64 Vol.% Diesel - 16 Vol.% 1-Methylnaphthalin - 20 Vol.% RME

Revision date: 22.04.2024

Product code: 31491

Page 10 of 11

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes
Danger releasing substance: Diesel fuel, methylnaphthalene

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
Entry 3, Entry 40, Entry 75

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Abbreviations and acronyms

Flam. Liq: Flammable liquid
Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Skin Irrit: Skin irritation
Carc: Carcinogenicity
STOT RE: Specific target organ toxicity - repeated exposure
Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H332	Calculation method
Asp. Tox. 1; H304	
Skin Irrit. 2; H315	Calculation method
Carc. 2; H351	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Further Information

Provide appropriate information, instructions and training to users
The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.
The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Prüfflüssigkeit 3b 64 Vol.% Diesel - 16 Vol.% 1-Methylnaphthalin - 20 Vol.% RME

Revision date: 22.04.2024

Product code: 31491

Page 11 of 11

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)