

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 1 of 18

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Acute Tox. 2; H330 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Muta. 1B; H340 Carc. 1A; H350 STOT RE 2; H373 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

nitric acid beryllium nitrate cobalt dinitrate

cadmium nitrate; cadmium dinitrate



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 2 of 18

Signal word: Danger

Pictograms:









Hazard statements

H290 May be corrosive to metals.

H330 Fatal if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 3 of 18

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) I	No 1272/2008)		
7697-37-2	nitric acid			5 - < 10 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, Acute T	ox. 3, Skin Corr. 1A; H272 H2	90 H331 H314 EUH071	
-	beryllium compounds with the e elsewhere in this Annex	xception of aluminium berylliu	m silicates, and with those specified	1 - < 5 %
	-	004-002-00-2		
	Carc. 1B, Acute Tox. 2, Acute T RE 1, Aquatic Chronic 2; H350i		Skin Sens. 1, STOT SE 3, STOT H335 H372 H411	
10043-35-3	boric acid			< 1 %
	233-139-2	005-007-00-2	01-2119486683-25	
	Repr. 1B; H360FD	•	•	
10031-43-3	Copper(II) nitrate trihydrate	< 1 %		
			01-2119969290-34	
	Ox. Sol. 2, Acute Tox. 4, Skin In H315 H319 H400 H410			
-	arsenic acid and it salts with the	< 1 %		
	-	033-005-00-1		
	Carc. 1A, Acute Tox. 3, Acute T H410	ox. 3, Aquatic Acute 1, Aquati	c Chronic 1; H350 H331 H301 H400	
10141-05-6	cobalt dinitrate			< 1 %
	233-402-1	027-009-00-2		
	Carc. 1B, Muta. 2, Repr. 1B, Re H350i H341 H360F H334 H317		uatic Acute 1, Aquatic Chronic 1;	
10325-94-7	cadmium nitrate; cadmium dinitr	ate		< 1 %
	233-710-6	048-014-00-6		
	Carc. 1B, Muta. 1B, Repr. 1B, A Acute 1, Aquatic Chronic 1; H35			
10022-31-8	bariumnitrat			< 1 %
	233-020-5	056-002-00-7		
	Ox. Sol. 2, Acute Tox. 3, Acute	Tox. 4, Eye Irrit. 2; H272 H301	1 H332 H319	

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 4 of 18

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
7697-37-2	231-714-2	nitric acid	5 - < 10 %
		E 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 orr. 1B; H314: >= 5 - < 20	
-	-	beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex	1 - < 5 %
	inhalation: ATE 100 mg/kg	E = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); oral: ATE =	
10043-35-3	233-139-2	boric acid	< 1 %
	inhalation: LC5 3450 mg/kg	50 = > 2,12 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 =	
10031-43-3		Copper(II) nitrate trihydrate	< 1 %
	oral: ATE = 50	0 mg/kg	
-	-	arsenic acid and it salts with the exception of those specified elsewhere in this Annex	< 1 %
	inhalation: ATE	E = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: ATE = 100	
10141-05-6	233-402-1	cobalt dinitrate	< 1 %
	Aquatic Acute	i: >= 0,01 - 100 I; H400: M=10 c 1; H410: M=10	
10325-94-7	233-710-6	cadmium nitrate; cadmium dinitrate	< 1 %
		E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = al: ATE = 500 mg/kg	
10022-31-8	233-020-5	bariumnitrat	< 1 %
	inhalation: ATE 50 - < 300 mg/l	E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = >	

Further Information

No data available

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk.

Call a physician immediately.



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 5 of 18

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

Irritant

Cough

Dyspnoea

Vomitina

Methaemoglobinaemia

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

Metal oxide smoke, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 6 of 18

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a place accessible by authorized persons only.

Corrosive to metals.

Unsuitable container/equipment material: Metal

The product develops hydrogen in an aqueous solution in contact with metals.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 7 of 18

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7429-90-5	Aluminium metal (Respirable Fraction)	-	1		TWA (8 h)	
10043-35-3	Borate compounds inorganic: boric acid	-	2		TWA (8 h)	
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance			
DNEL type	DNEL type		Effect	Value
10043-35-3	boric acid			
Worker DNEL,	long-term	inhalation	systemic	8,3 mg/m³
Worker DNEL,	long-term	dermal	systemic	392 mg/kg bw/day
Consumer DNI	EL, long-term	inhalation	systemic	4,15 mg/m³
Consumer DNI	EL, long-term	dermal	systemic	196 mg/kg bw/day
Consumer DNI	EL, long-term	oral	systemic	0,98 mg/kg bw/day
Consumer DNI	EL, acute	oral	systemic	0,98 mg/kg bw/day
10022-31-8	bariumnitrat			
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³
Worker DNEL,	long-term	dermal	systemic	8,141 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,67 mg/m³
Consumer DNEL, long-term		dermal	systemic	4,07 mg/kg bw/day
Consumer DNI	EL, long-term	oral	systemic	0,58 mg/kg bw/day



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 8 of 18

PNEC values

	-	
CAS No	Substance	
Environmenta	I compartment	Value
10043-35-3	boric acid	
Freshwater		2,9 mg/l
Freshwater (ir	ntermittent releases)	13,7 mg/l
Marine water		2,9 mg/l
Micro-organis	ms in sewage treatment plants (STP)	10 mg/l
Soil		5,7 mg/kg
10031-43-3	Copper(II) nitrate trihydrate	·
Freshwater		0,0078 mg/l
Marine water		0,0052 mg/l
Freshwater sediment		87 mg/kg
Marine sediment		676 mg/kg
Micro-organis	ms in sewage treatment plants (STP)	0,23 mg/l
Soil		65 mg/kg
10022-31-8	bariumnitrat	·
Freshwater		0,115 mg/l
Freshwater sediment 600 m		600 mg/kg
Micro-organisms in sewage treatment plants (STP)		
Soil		207,7 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 9 of 18

Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: clear

Odour: like: Nitric acid

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

Flammability: No data available No data available Lower explosion limits: No data available Upper explosion limits: No data available Flash point: No data available Auto-ignition temperature: Decomposition temperature: No data available acidic pH-Value: Viscosity / kinematic: No data available Water solubility: completely miscible

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Partition coefficient n-octanol/water:

No data available

No data available

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion: No data available

Self-ignition temperature

Solid: No data available



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 10 of 18

Gas: No data available

Oxidizing properties

Oxidizing

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available

Solvent content:

Solid content:

Sublimation point:

Softening point:

No data available

Pour point:

No data available

No data available

No data available

No data available:

Viscosity / dynamic: No data available Flow time: No data available

Further Information
Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

Oxidising agent

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

The product develops hydrogen in an aqueous solution in contact with metals.

Amines, Ammonia, Alcohols, Alkali metals, Hydrogen peroxide

Copper, Combustible solids, Solvent, Alkaline earth metal, mercury (Hg).

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Cellulose

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Fatal if inhaled.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) 3,094 mg/l



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 11 of 18

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
7697-37-2	nitric acid								
	inhalation vapour	ATE 2,65 r	ng/l						
-	beryllium compounds v this Annex	with the excepti	on of alumir	nium beryllium silio	cates, and with those specified el	sewhere in			
	oral	ATE mg/kg	100						
	inhalation vapour	ATE	0,5 mg/l						
	inhalation dust/mist	ATE	0,05 mg/l						
10043-35-3	boric acid								
	oral	LD50 mg/kg	3450	Rat	Toxicology and Applied Pharmacology 23:	other: No data			
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)	other: FIFRA			
	inhalation (4 h) dust/mist	LC50 mg/l	> 2,12	Rat	Study report (1997)	OECD Guideline 403			
10031-43-3	Copper(II) nitrate trihydrate								
	oral	ATE mg/kg	500						
-	arsenic acid and it salts with the exception of those specified elsewhere in this Annex								
	oral	ATE mg/kg	100						
	inhalation vapour	ATE	3 mg/l						
	inhalation dust/mist	ATE	0,5 mg/l						
10325-94-7	cadmium nitrate; cadm	ium dinitrate							
	oral	ATE mg/kg	500						
	dermal	ATE mg/kg	1100						
	inhalation vapour	ATE	11 mg/l						
	inhalation dust/mist	ATE	1,5 mg/l						
10022-31-8	bariumnitrat								
	oral	LD50 300 mg/kg	> 50 - <	Rat	Study report (2013)	OECD Guideline 423			
	inhalation vapour	ATE	11 mg/l						
	inhalation dust/mist	ATE	1,5 mg/l						

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Corrosive to the respiratory tract.

Following ingestion Gastric perforation

Irritating to respiratory system.

Pulmonary oedema

see also Section 4

Sensitising effects

May cause an allergic skin reaction. (beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex; cobalt dinitrate)

Carcinogenic/mutagenic/toxic effects for reproduction



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 12 of 18

May cause genetic defects. (cadmium nitrate; cadmium dinitrate)

May cause cancer. (beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex; arsenic acid and it salts with the exception of those specified elsewhere in this Annex; cobalt dinitrate; cadmium nitrate; cadmium dinitrate)

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex)

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 13 of 18

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
7697-37-2	nitric acid						
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209
0043-35-3	boric acid						
	Acute fish toxicity	LC50 mg/l	79,7	96 h	Pimephales promelas	Study report (2010)	other: ASTM E729-95 Standard Guide for C
	Acute algae toxicity	ErC50	66 mg/l	72 h	Phaeodactylum tricornutum	Study report (2011)	ISO 10253
	Acute crustacea toxicity	EC50	109 mg/l	48 h	Ceriodaphnia dubia	Study report (2010)	other: ASTM E729-95 Standard Guide for C
	Fish toxicity	NOEC mg/l	11,2	32 d	Pimephales promelas	Study report (2010)	other: ASTM E1241-05 Standard Guide for
	Algae toxicity	NOEC mg/l	17,5	3 d	Pseudokirchneriella subcapitata	Study report (2000)	OECD Guideline 201
	Crustacea toxicity	NOEC mg/l	25,9	42 d	other aquatic crustacea: Hyalella azteca	Study report (2010)	other: US EPA 2000 Methods for assessing
	Acute bacteria toxicity	EC50 mg/l ()	> 10000	3 h	activated sludge of a predominantly domestic sewag	Study report (2001)	OECD Guideline 209
10031-43-3	Copper(II) nitrate trihydra	te					
	Acute fish toxicity	LC50 mg/l	0,193	96 h	Pimephales promelas	Study report (1996)	measurements were conducted by standard
	Acute algae toxicity	ErC50 mg/l	0,152	72 h	Pseudokirchneriella subcapitata	Publication (2005)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,007	48 h	Daphnia magna	Study report (1978)	- Test were conducted on Daphnia magna t
	Fish toxicity	NOEC mg/l	0,123	12 d	Atherinops affinis	Mar. Environ. Res. 31: 17-35 (1991)	Three tests are reported, designed to de
	Algae toxicity	NOEC mg/l	0,0102	19 d	other aquatic plant: giant kelp Macrocystis pyrife	Mar. Ecol. Prog. Ser. 68: 147 - 156 (199	Tests were conducted to determine the ef
	Crustacea toxicity	NOEC mg/l	0,033	14 d	Penaeus mergulensis and Penaeus monodon	Bull. Environ. Contain. Toxicol. (1995)	The effects of dissolved copper on the g



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l Revision date: 23.04.2024 Product code: 31546 Page 14 of 18

Acute fish toxicity	LC50 mg/l	> 3,5	96 h	Danio rerio	Study report (2010)	OECD Guideline 203
Acute algae toxicity	ErC50 mg/l	> 1,15		Pseudokirchneriella subcapitata	Study report (2010)	OECD Guideline 201
Acute crustacea toxicity	EC50 mg/l	14,5	48 h 🛭	Daphnia magna	Journal of the Fisheries Research Board	Not a guideline study but meets generall
Fish toxicity	NOEC mg/l	>= 100	33 d 🛭	Danio rerio	Study report (2014)	OECD Guideline 210
Crustacea toxicity	NOEC	2,9 mg/l	21 d 🛭	Daphnia magna	Journal of the Fisheries Research Board	The test did not exacty follow an existi
Acute bacteria toxicity	EC50 mg/l ()	> 1000	р	activated sludge of a predominantly domestic sewag	Study report (2010)	OECD Guideline 209

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
10043-35-3	boric acid	-1,09

BCF

CAS No	Chemical name	BCF	Species	Source
10043-35-3	boric acid	0,558	Oncorhynchus nerka	Water Research Vol.
10031-43-3	Copper(II) nitrate trihydrate	0,02 - 20	Crangon crangon	Symp. Biologica. Hun
10022-31-8	bariumnitrat	68,4	Lepomis macrochirus	Archives of Environm

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Do not allow to enter into surface water or drains.

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 15 of 18

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid, cobalt

dinitrate)

14.3. Transport hazard class(es): 8 14.4. Packing group: Ш Hazard label: 8 Classification code: C1 **Special Provisions:** 274 Limited quantity: 1 L Excepted quantity: E2 Transport category: 2 Hazard No: 80 Tunnel restriction code: F

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid, cobalt

dinitrate)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Classification code:C1Special Provisions:274Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid, cobalt

dinitrate)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:274Limited quantity:1 LExcepted quantity:E2EmS:F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid, cobalt

dinitrate)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:0.5 LPassenger LQ:Y840Excepted quantity:E2

IATA-packing instructions - Passenger:851IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:855IATA-max. quantity - Cargo:30 L



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 16 of 18

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: cobalt dinitrate

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

arsenic acid and it salts with the exception of those specified elsewhere in this Annex

Substances of very high concern, SVHC (REACH, article 59): boric acid; cobalt dinitrate; cadmium nitrate; cadmium dinitrate

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 23, Entry 28, Entry 30, Entry 75

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information

Abbreviations and acronyms

Pyr. Sol: Pyrophoric solid

Water-react: Substance and mixture which, in contact with water, emits flammable gas

Ox. Liq: Oxidising liquid Ox. Sol: Oxidising solid

Met. Corr: Substance or mixture corrosive to metals

Flam. Sol: Flammable solid Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation

Resp. Sens: Respiratory sensitisation

Skin Sens: Skin sensitisation Muta: Germ cell mutagenicity

Carc: Carcinogenicity
Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 17 of 18

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Acute Tox. 2; H330	
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 1B; H340	Calculation method
Carc. 1A; H350	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

Rel

elevant H and EUH state	ements (number and full text)
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H350i	May cause cancer by inhalation.
H360	May damage fertility or the unborn child.
H360F	May damage fertility.
H360FD	May damage fertility. May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "1" 12 Elemente je 1000 mg/l in Salpetersäure 1 mol/l

Revision date: 23.04.2024 Product code: 31546 Page 18 of 18

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)