

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Acute Tox. 4; H332 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Carc. 1B; H350i Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

nitric acid

beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in

this Annex nickel dinitrate cobalt dinitrate

Signal word: Danger



according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 2 of 17

Pictograms:







Hazard statements

H290 May be corrosive to metals.

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H350i May cause cancer by inhalation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

Restricted to professional users.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution



according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 3 of 17

Relevant ingredients

| CAS No | Chemical name | | | | | |
|------------|--|---|---|------------|--|--|
| | EC No | Index No | REACH No | | | |
| | Classification (Regulation | n (EC) No 1272/2008) | <u> </u> | | | |
| 7697-37-2 | nitric acid | | | 5 - < 10 % | | |
| | 231-714-2 | 007-030-00-3 | 01-2119487297-23 | | | |
| | Ox. Liq. 3, Met. Corr. 1, A | Acute Tox. 3, Skin Corr. 1A; H272 I | H290 H331 H314 EUH071 | | | |
| - | beryllium compounds wit elsewhere in this Annex | h the exception of aluminium beryll | ium silicates, and with those specified | < 1 % | | |
| | - | 004-002-00-2 | | | | |
| | | Acute Tox. 3, Skin Irrit. 2, Eye Irrit. 2 H350i H330 H301 H315 H319 H3 | 2, Skin Sens. 1, STOT SE 3, STOT 17 H335 H372 H411 | | | |
| 13138-45-9 | nickel dinitrate | | | < 0.1 % | | |
| | 236-068-5 | 028-012-00-1 | 01-2119492333-38 | | | |
| | Resp. Sens. 1, Skin Sens | a. 2, Repr. 1B, Acute Tox. 4, Acute s. 1, STOT RE 1, Aquatic Acute 1, H318 H334 H317 H372 H400 H4 | Aquatic Chronic 1; H272 H350i H341 | | | |
| 10141-05-6 | cobalt dinitrate | < 0.1 % | | | | |
| | 233-402-1 | 027-009-00-2 | | | | |
| | Carc. 1B, Muta. 2, Repr. H350i H341 H360F H334 | | | | | |
| 10325-94-7 | cadmium nitrate; cadmiu | m dinitrate | | < 0.1 % | | |
| | 233-710-6 | 048-014-00-6 | | | | |
| | • | r. 1B, Acute Tox. 4, Acute Tox. 4, A 1; H350 H340 H360 H332 H312 H | · | | | |
| 7761-88-8 | silver nitrate | | | < 0.1 % | | |
| | 231-853-9 | 047-001-00-2 | 01-2119513705-43 | | | |
| | Ox. Sol. 2, Met. Corr. 1, 3 H290 H314 H318 H400 H | | | | | |

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 4 of 17

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|------------|--|---|------------|
| | Specific Conc. | Limits, M-factors and ATE | |
| 7697-37-2 | 231-714-2 | nitric acid | 5 - < 10 % |
| | | E 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 orr. 1B; H314: >= 5 - < 20 | |
| - | - | beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex | < 1 % |
| | inhalation: AT 100 mg/kg | E = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); oral: ATE = | |
| 13138-45-9 | 236-068-5 | nickel dinitrate | < 0.1 % |
| | 361,9 mg/kg H372: >= 1 - 1 Aquatic Acute | E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = Skin Irrit. 2; H315: >= 20 - 100 | |
| 10141-05-6 | 233-402-1 | cobalt dinitrate | < 0.1 % |
| | Aquatic Acute | 0i: >= 0,01 - 100 1; H400: M=10 ic 1; H410: M=10 | |
| 10325-94-7 | 233-710-6 | cadmium nitrate; cadmium dinitrate | < 0.1 % |
| | | E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = ral: ATE = 500 mg/kg | |
| 7761-88-8 | 231-853-9 | silver nitrate | < 0.1 % |
| | | = > 348 mg/kg; oral: LD50 = > 2000 mg/kg Aquatic Acute 1; H400: M=1000 ic 1; H410: M=100 | |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

Irritant

Cough

Dyspnoea

Vomiting



according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 5 of 17

Methaemoglobinaemia

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.



according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 6 of 17

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eves and clothes.

Do not breathe vapour/aerosol.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Corrosive to metals.

Unsuitable container/equipment material: Metal

The product develops hydrogen in an aqueous solution in contact with metals.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| CAS No | Substance | ppm | mg/m³ | fib/cm³ | Category | Origin |
|------------|--|-----|-------|---------|---------------|--------|
| 7429-90-5 | Aluminium metal (Respirable Fraction) | - | 1 | | TWA (8 h) | |
| 7440-36-0 | Antimony | - | 0.5 | | TWA (8 h) | |
| 10043-35-3 | Borate compounds inorganic: boric acid | - | 2 | | TWA (8 h) | |
| 7440-74-6 | Indium | - | 0.1 | | TWA (8 h) | |
| | | - | 0.3 | | STEL (15 min) | |
| 7697-37-2 | Nitric acid | 1 | 2.6 | | STEL (15 min) | |



according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 7 of 17

DNEL/DMEL values

| CAS No | Substance | | | |
|-------------|------------------|----------------|----------|-----------------------|
| DNEL type | | Exposure route | Effect | Value |
| 10043-35-3 | boric acid | | | |
| Worker DNEL | , long-term | inhalation | systemic | 8,3 mg/m³ |
| Worker DNEL | , long-term | dermal | systemic | 392 mg/kg bw/day |
| Consumer DN | EL, long-term | inhalation | systemic | 4,15 mg/m³ |
| Consumer DN | EL, long-term | dermal | systemic | 196 mg/kg bw/day |
| Consumer DN | EL, long-term | oral | systemic | 0,98 mg/kg bw/day |
| Consumer DN | EL, acute | oral | systemic | 0,98 mg/kg bw/day |
| 13138-45-9 | nickel dinitrate | | | |
| Consumer DN | EL, acute | oral | systemic | 0,012 mg/kg bw/day |
| Consumer DN | EL, long-term | oral | systemic | 0,02 mg/kg bw/day |
| Worker DNEL | , acute | inhalation | systemic | 104 mg/m³ |
| Worker DNEL | , acute | inhalation | local | 1,6 mg/m³ |
| Consumer DN | EL, acute | inhalation | systemic | 8,8 mg/m³ |
| Consumer DN | EL, acute | inhalation | local | 0,1 mg/m³ |
| 7761-88-8 | silver nitrate | | | |
| Consumer DN | EL, long-term | oral | systemic | 0,02 mg/kg bw/day |
| Worker DNEL | , long-term | inhalation | systemic | 0,016 mg/m³ |
| Consumer DN | IEL, long-term | inhalation | systemic | 0,006 mg/m³ |



according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 8 of 17

PNEC values

| CAS No | Substance | |
|---------------------|--------------------------------------|--------------|
| Environment | al compartment | Value |
| 10043-35-3 | boric acid | |
| Freshwater | • | 2,9 mg/l |
| Freshwater (| intermittent releases) | 13,7 mg/l |
| Marine water | r | 2,9 mg/l |
| Micro-organi | sms in sewage treatment plants (STP) | 10 mg/l |
| Soil | | 5,7 mg/kg |
| 13138-45-9 | nickel dinitrate | |
| Freshwater | | 0,0071 mg/l |
| Freshwater (| intermittent releases) | 0 mg/l |
| Marine water | r | 0,0086 mg/l |
| Freshwater sediment | | 109 mg/kg |
| Marine sediment | | 109 mg/kg |
| Secondary p | oisoning | 0,12 mg/kg |
| Micro-organi | sms in sewage treatment plants (STP) | 0,33 mg/l |
| Soil | | 29,9 mg/kg |
| 7761-88-8 | silver nitrate | |
| Freshwater | | 0,00004 mg/l |
| Marine water | | 0,00086 mg/l |
| Freshwater sediment | | 438,13 mg/kg |
| Marine sedin | nent | 438,13 mg/kg |
| Micro-organi | sms in sewage treatment plants (STP) | 0,025 mg/l |
| Soil | | 1,41 mg/kg |

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 741 Dermatril® L



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 9 of 17

Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: clear

Odour: like: Nitric acid

Melting point/freezing point:

No data available
Boiling point or initial boiling point and

No data available

boiling range:

No data available Flammability: No data available Lower explosion limits: No data available Upper explosion limits: Flash point: No data available Auto-ignition temperature: No data available Decomposition temperature: No data available pH-Value: acidic Viscosity / kinematic: No data available Water solubility: completely miscible

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes



according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 10 of 17

Explosive properties

No data available

Sustaining combustion: No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

Oxidizing

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available

Solvent content:

Solid content:

Sublimation point:

Softening point:

No data available

No data available:

Viscosity / dynamic:

Flow time:

No data available

No data available

Further Information
Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals. Oxidising agent

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

The product develops hydrogen in an aqueous solution in contact with metals.

Amines, Ammonia, Alcohols, Alkali metals, Hydrogen peroxide

Copper, Combustible solids, Solvent, Alkaline earth metal, mercury (Hg).

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Cellulose

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.



according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 11 of 17

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

| CAS No | Chemical name | | | | | | | | |
|------------|-------------------------------------|---------------|-----------------|-----------------------|--|--------------------|--|--|--|
| | Exposure route | Dose | | Species | Source | Method | | | |
| 7697-37-2 | nitric acid | | | | | | | | |
| | inhalation vapour | ATE 2,6 | 5 mg/l | | | | | | |
| - | beryllium compounds w this Annex | vith the exce | otion of alumir | nium beryllium silica | tes, and with those specified e | Isewhere in | | | |
| | oral | ATE mg/kg | 100 | | | | | | |
| | inhalation vapour | ATE | 0,5 mg/l | | | | | | |
| | inhalation dust/mist | ATE | 0,05 mg/l | | | | | | |
| 13138-45-9 | nickel dinitrate | | | | | | | | |
| | oral | LD50 mg/kg | 361,9 | Rat | Regul Toxicol and Pharmacol (doi.org/10. | OECD Guideline 425 | | | |
| | inhalation vapour | ATE | 11 mg/l | | | | | | |
| | inhalation dust/mist | ATE | 1,5 mg/l | | | | | | |
| 10325-94-7 | cadmium nitrate; cadmium dinitrate | | | | | | | | |
| | oral | ATE mg/kg | 500 | | | | | | |
| | dermal | ATE mg/kg | 1100 | | | | | | |
| | inhalation vapour | ATE | 11 mg/l | | | | | | |
| | inhalation dust/mist | ATE | 1,5 mg/l | | | | | | |
| 7761-88-8 | silver nitrate | | | | | | | | |
| | oral | LD50 mg/kg | > 2000 | Rat | Study report (1993) | OECD Guideline 401 | | | |
| | dermal | LD50 mg/kg | > 348 | Guinea pig | J. Vet. Med. Sci.73: 1417 - 1423. (2011) | OECD Guideline 434 | | | |

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Corrosive to the respiratory tract.

Following ingestion Gastric perforation

Irritating to respiratory system.

Pulmonary oedema

see also Section 4

Sensitising effects

May cause an allergic skin reaction. (beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex; nickel dinitrate; cobalt dinitrate)

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer by inhalation. (beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex; nickel dinitrate; cobalt dinitrate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 12 of 17

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity



according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 13 of 17

| CAS No | Chemical name | | | | | | |
|------------|--------------------------|-------------------|-----------|-----------|--|---|--|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source | Method |
| 7697-37-2 | nitric acid | 1 | | | , · | | |
| | Acute fish toxicity | LC50 mg/l | 1559 | 96 h | Topeka shiner | Environmental Toxicology and Chemistry, | other: ASTM E729-26 |
| | Fish toxicity | NOEC | 268 mg/l | 30 d | juvenile Topeka shiner and with juvenile Fathead m | Study report (2009) | Growth tests estimated the test chemical |
| | Algae toxicity | NOEC mg/l | > 419 | 10 d | several benthic diatoms; see results | Marine Biology 43:307-315 (1977) | Ten cultures of benthic diatoms were iso |
| | Acute bacteria toxicity | EC50 mg/l () | > 1000 | 3 h | Activated sludge | Study report (2008) | OECD Guideline 209 |
| 13138-45-9 | nickel dinitrate | | | | | | |
| | Acute fish toxicity | LC50 mg/l | 15,3 | 96 h | Oncorhynchus mykiss | Aquatic Toxicology 63 (2003) 65-82 (2003 | other: not reported |
| | Acute algae toxicity | ErC50 mg/l | 0,237 | 72 h | Ankistrodesmus falcatus | Publication (2009) | OECD Guideline 201 |
| | Acute crustacea toxicity | EC50 mg/l | 0,2663 | 48 h | Ceriodaphnia dubia | Study report (2004) | other: American society of testing and m |
| | Fish toxicity | NOEC mg/l | 0,057 | 32 d | Pimephales promelas | Water Resources Research Institute. Kent | other: ASTM 1980, E-729 |
| | Algae toxicity | NOEC | 0,6 mg/l | 14 d | Anabaena cylindrica | Environ. Pollut. (Series A). 25(4):241-2 | other: not reported |
| | Crustacea toxicity | NOEC mg/l | 0,04 | 42 d | Daphnia magna | Wat. Res. 24(7):845-852 (1990) | Chronic exposure to sublethal concentrat |
| | Acute bacteria toxicity | EC50) | 33 mg/l (| 0,5 h | Activated sludge | Journal of Hazardous Materials. B139:332 | ISO 8192 |
| 7761-88-8 | silver nitrate | | | | | | |
| | Acute fish toxicity | LC50 mg/l | 0,0012 | 96 h | Pimephales promelas | Environmental Toxicology and Chemistry. | A guideline was not specified. The test |
| | Acute algae toxicity | ErC50 mg/l | 0,0099 | 96 h | Pseudokirchneriella subcapitata | Environmental Science and Technology. 44 | eline: U.S. Environmental Protection Age |
| | Acute crustacea toxicity | EC50 mg/l | 0,00022 | 48 h | Daphnia magna | Environmental Toxicology and Chemistry. | The protective effect of reactive sulphi |
| | Fish toxicity | NOEC 0,00125 m | > ng/l | 73 d | Oncorhynchus mykiss | Environmental Toxicology and Chemistry 2 | other: ASTM 1241-98 |
| | Algae toxicity | NOEC mg/l | 0,0012 | 14 d | Champia parvula | in Bishop WE, Cardwell RD Heidolph BB (E | The toxicity tests lasted 11 days for th |
| | | | | | | | |



according to Regulation (EC) No 1907/2006

| ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5% | | | | | | |
|---|--------------|---------|-------------------------|---------------------------------|-----------------------------|-------|
| Revision date: 25.04.2024 | | Pro | oduct code: 31635 | | Page 14 | of 17 |
| Crustacea toxicity | NOEC mg/l | 0,00031 | 20 d Isonychia bicolour | Environmental Toxicology and | 20 day sublethal effects on | |

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

BCF

| CAS No | Chemical name | BCF | Species | Source |
|------------|------------------|-----|---------------------|----------------------|
| 13138-45-9 | nickel dinitrate | 23 | Spirodela polyrhiza | Ecotoxicology and en |
| 7761-88-8 | silver nitrate | 70 | Cyprinus carpio | Water, Air and Soil |

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Do not allow to enter into surface water or drains.

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".

SECTION 14: Transport information

Land transport (ADR/RID)

| 14.1. UN number or ID number: | UN 2031 |
|--------------------------------|-------------|
| 14.2. UN proper shipping name: | NITRIC ACID |
| | _ |

14.3. Transport hazard class(es): 8 14.4. Packing group: Ш Hazard label: Classification code: C₁ Limited quantity: 1 I Excepted quantity: E2 Transport category: 2 Hazard No: 80 Tunnel restriction code: Ε

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2031



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 15 of 17

14.2. UN proper shipping name: NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Classification code:C1Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2031
14.2. UN proper shipping name: NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:-Limited quantity:1 LExcepted quantity:E2EmS:F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2031
14.2. UN proper shipping name: NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:A212Limited quantity Passenger:ForbiddenPassenger LQ:ForbiddenExcepted quantity:E0

IATA-packing instructions - Passenger: Forbidden
IATA-max. quantity - Passenger: Forbidden
IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

cobalt dinitrate; cadmium nitrate; cadmium dinitrate

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 23, Entry 27, Entry 28, Entry 30, Entry 75

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information



according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 16 of 17

Abbreviations and acronyms

Pyr. Sol: Pyrophoric solid

Water-react: Substance and mixture which, in contact with water, emits flammable gas

Ox. Liq: Oxidising liquid Ox. Sol: Oxidising solid

Met. Corr: Substance or mixture corrosive to metals

Flam. Sol: Flammable solid Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation

Resp. Sens: Respiratory sensitisation

Skin Sens: Skin sensitisation Muta: Germ cell mutagenicity Carc: Carcinogenicity Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

| Classification | Classification procedure |
|-------------------------|--------------------------|
| Met. Corr. 1; H290 | On basis of test data |
| Acute Tox. 4; H332 | |
| Skin Corr. 1B; H314 | Calculation method |
| Eye Dam. 1; H318 | Calculation method |
| Skin Sens. 1; H317 | Calculation method |
| Carc. 1B; H350i | Calculation method |
| Aquatic Chronic 3; H412 | Calculation method |

Relevant H and EUH statements (number and full text)

| May intensify fire; oxidiser. |
|--|
| May be corrosive to metals. |
| Toxic if swallowed. |
| Harmful if swallowed. |
| Harmful in contact with skin. |
| Causes severe skin burns and eye damage. |
| Causes skin irritation. |
| May cause an allergic skin reaction. |
| Causes serious eye damage. |
| Causes serious eye irritation. |
| Fatal if inhaled. |
| Toxic if inhaled. |
| Harmful if inhaled. |
| May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| May cause respiratory irritation. |
| May cause genetic defects. |
| Suspected of causing genetic defects. |
| May cause cancer. |
| May cause cancer by inhalation. |
| May damage fertility or the unborn child. |
| May damage the unborn child. |
| May damage fertility. |
| |



according to Regulation (EC) No 1907/2006

ICP Multielement-Standardlösung 33 Elemente je 100 mg/l in Salpetersäure 5%

Revision date: 25.04.2024 Product code: 31635 Page 17 of 17

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)