

according to Regulation (EC) No 1907/2006

PAN-Indikator-Lösung 0,15 % (m/v)

Revision date: 08.06.2022

Product code: 31856

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PAN-Indikator-Lösung 0,15 % (m/v)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	Fa. Bernd Kraft GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@berndkraft.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@berndkraft.de	
Internet:	www.berndkraft.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone	For Hazardous Materials [or Danger	ous Goods] Incidents Spill, Leak, Fire,
number:	Exposure, or Accident Call CHEMTF	REC Day or Night Within USA and Canada:
	1-800-424-9300 Outside USA and C	Canada: +1 703-741-5970 (collect calls

Further Information

This product is a mixture. REACH Registration Number see section 3.

accepted)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling poly(oxyethylene) octylphenyl ether

Signal word: Danger

Pictograms:

H225



Hazard statements

Highly flammable liquid and vapour.



according to Regulation (EC) No 1907/2006

PAN-Indikator-Lösung	0,15	%	(m/v)	
----------------------	------	---	-------	--

	PAN-Indikator-Losung 0,15 % (m/v)							
Revision date: 08.06.2022	Product code: 31856	Page 2 of 12						
H315	Causes skin irritation.							
H318	Causes serious eye damage.							
H410	Very toxic to aquatic life with long lasting effects.							
Precautionary statemen	ts							
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.							
P233	Keep container tightly closed.							
P240	Ground and bond container and receiving equipment.							
P241	Use explosion-proof electrical/ventilating/lighting equipment.							
P242	Use non-sparking tools.							
P243	Take action to prevent static discharges.							
P273	Avoid release to the environment.							
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.							
P302+P352	F ON SKIN: Wash with plenty of water.							
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.							
P332+P313	If skin irritation occurs: Get medical advice/attention.							
P362+P364	Take off contaminated clothing and wash it before reuse.							
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.							
P310	Immediately call a POISON CENTER/doctor.							
P391	Collect spillage.							
P403+P235	Store in a well-ventilated place. Keep cool.							
2.3. Other hazards								

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	o Chemical name				Quantity
	EC No	Index No REACH No			
	Classification (Regulation (EC) No 1272/2008)				
64-17-5	5 ethanol				85 - < 90 %
	200-578-6	603-002-00-5	01-211	9457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H31	19	-		
9036-19-5	poly(oxyethylene) octylphenyl ethe	er			10 - < 15 %
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H315 H318 H400 H410				

Full text of H and EUH statements: see section 16.

Specific Co	nc. Limits, M-fa	ictors and ATE					
CAS No	EC No	Chemical name	Quantity				
	Specific Conc	Specific Conc. Limits, M-factors and ATE					
64-17-5	200-578-6	ethanol	85 - < 90 %				
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100						
9036-19-5		poly(oxyethylene) octylphenyl ether	10 - < 15 %				
	oral: ATE = 500 mg/kg M acute; H400: M=10						
	M chron.; H41	0: M=10					



PAN-Indikator-Lösung 0,15 % (m/v)

Revision date: 08.06.2022

Product code: 31856

Page 3 of 12

Further Information

No data available

SECTION 4: First aid measures

4.1. Description of first aid measures

General information No data available

After inhalation

Provide fresh air. Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide Vapours are heavier than air, spread along floors and form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes. Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures



PAN-Indikator-Lösung 0,15 % (m/v)

Revision date: 08.06.2022

Product code: 31856

Page 4 of 12

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Use extractor hood (laboratory). Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.



according to Regulation (EC) No 1907/2006

PAN-Indikator-Lösung 0,15 % (m/v)

Revision date: 08.06.2022

Product code: 31856

Page 5 of 12

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

Keep cool. Protect from sunlight.

Protect against: Light

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
64-17-5	ethanol						
Worker DNEL,	long-term	inhalation	systemic	950 mg/m³			
Worker DNEL,	long-term	dermal	systemic	343 mg/kg bw/day			
Consumer DNE	EL, long-term	inhalation	systemic	114 mg/m ³			
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day			
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day			

PNEC values

CAS No	Substance				
Environmen	tal compartment	Value			
64-17-5	ethanol				
Freshwater 0,96 mg/l					
Freshwater (intermittent releases) 2,75					
Marine wate	r	0,79 mg/l			
Freshwater	3,6 mg/kg				
Marine sediment					
Secondary p	380 mg/kg				
Micro-organ	isms in sewage treatment plants (STP)	580 mg/l			
Soil		0,63 mg/kg			

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection

equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.



PAN-Indikator-Lösung 0,15 % (m/v)

Revision date: 08.06.2022

Product code: 31856

Page 6 of 12

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact Trade name/designation KCL 898 Butoject® Suitable material:: Butyl caoutchouc (butyl rubber) 0,7 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Trade name/designation KCL 720 Camapren® Suitable material:: CR (polychloroprene, chloroprene rubber) 0,65 mm Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse. Wear fire resistant or flame retardant clothing. Wash hands and face before breaks and after work and take a shower if necessary. Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Environmental exposure controls

Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	Liquid clear	
Odour:	like: Ethanol	
Odour threshold:	No data available	
Changes in the physical state		
Melting point/freezing point:		No data available
Boiling point or initial boiling point and		78 °C
boiling range:		
Sublimation point:		No data available



PAN-Inc	dikator-Lösung 0,15 % (m/v)	
Revision date: 08.06.2022	Product code: 31856	Page 7 of 12
Softening point:	No data available	
Pour point:	No data available	
:	No data available	
Flash point:	12 °C	
Flammability		
Solid/liquid:	No data available	
Gas:	No data available	
Explosive properties Vapours are heavier than air, spread along floo	rs and form explosive mixtures with air.	
Lower explosion limits:	No data available	
Upper explosion limits:	No data available	
Auto-ignition temperature:	No data available	
Self-ignition temperature		
Solid: Gas:	No data available No data available	
Decomposition temperature:	No data available	
pH-Value:	No data available	
Viscosity / dynamic:	No data available	
Viscosity / kinematic:	No data available	
Flow time:	No data available	
Water solubility: Solubility in other solvents	No data available	
No data available		
Partition coefficient n-octanol/water:	No data available	
Vapour pressure:	No data available	
Vapour pressure:	No data available	
Density:	0,817 g/cm ³	
Bulk density:	No data available	
Relative vapour density:	No data available	
9.2. Other information		
Information with regard to physical hazard class Oxidizing properties	es	
No data available		
Other safety characteristics		
Solvent separation test:	No data available	
Solvent content:	No data available	
Solid content:	No data available	
Evaporation rate:	No data available	
Further Information		
No data available		
SECTION 10: Stability and reactivity		

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability



an analyti**chem** company

Safety Data Sheet

according to Regulation (EC) No 1907/2006

PAN-Indikator-Lösung 0,15 % (m/v)

Revision date: 08.06.2022

Product code: 31856

Page 8 of 12

Protect against: Light

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect against: Light

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64-17-5	ethanol							
	oral	LD50 mg/kg	10470	Rat	Study report (1976)	OECD Guideline 401		
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980)	OECD Guideline 403		
9036-19-5	poly(oxyethylene) octylphenyl ether							
	oral	ATE mg/kg	500					

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards



according to Regulation (EC) No 1907/2006

PAN-Indikator-Lösung 0,15 % (m/v)

Revision date: 08.06.2022

Product code: 31856

Page 9 of 12

Other information

There are no data available on the mixture itself.

Further information

There are no data available on the mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64-17-5	ethanol						
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,77
BCF		

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.



PAN-Indikator-Lösung 0,15 % (m/v)

Revision date: 08.06.2022

Product code: 31856

Page 10 of 12

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)	
14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (ethanol, poly(oxyethylene) octylphenyl ether)
14.3. Transport hazard class(es):	3
14.4. Packing group:	ll
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (ethanol, poly(oxyethylene) octylphenyl ether)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (ethanol, poly(oxyethylene) octylphenyl ether)
14.3. Transport hazard class(es):	3
14.4. Packing group:	ll
Hazard label:	3
Special Provisions:	274
Limited quantity:	1L
Excepted quantity:	E2
EmS:	F-E, S-E
Air transport (ICAO-TI/IATA-DGR)	
<u>14.1. UN number or ID number:</u>	UN 1993



PAN-Indikator-Lösung 0,15 % (m/v)					
Revision date: 08.06.2022	Product code: 31856	Page 11 of 12			
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (ethanol, poly(oxyethylene) octylphenyl				
	ether)				
<u>14.3. Transport hazard class(es):</u>	3				
14.4. Packing group:	ll				
Hazard label:	3				
Special Provisions:	A3				
Limited quantity Passenger:	1L				
Passenger LQ:	Y341				
Excepted quantity:	E2				
IATA-packing instructions - Passenger:	353				
IATA-max. quantity - Passenger:	5 L				
IATA-packing instructions - Cargo:	364				
IATA-max. quantity - Cargo:	60 L				
14.5. Environmental hazards					
ENVIRONMENTALLY HAZARDOUS:	Yes				
Danger releasing substance:	poly(oxyethylene) octylphenyl ether				

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV): Substances of very high concern, SVHC (REACH, article 59): poly(oxyethylene) octylphenyl ether

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

National regulatory information

Water hazard class (D):

3 - highly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 3.

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

Relevant H and EUH statements (number and full text)

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our



according to Regulation (EC) No 1907/2006

PAN-Indikator-Lösung 0,15 % (m/v)

Revision date: 08.06.2022

Product code: 31856

Page 12 of 12

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)