

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kaliumhydroxid-Lösung 1,8 g/l in 2-Propanol

Revision date: 16.05.2022

Product code: 31951

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kaliumhydroxid-Lösung 1,8 g/l in 2-Propanol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	Fa. Bernd Kraft GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@berndkraft.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@berndkraft.de	
Internet:	www.berndkraft.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290

Flam. Liq. 2; H225

Eye Irrit. 2; H319

STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

propan-2-ol

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H290 May be corrosive to metals.

Kaliumhydroxid-Lösung 1,8 g/l in 2-Propanol

Revision date: 16.05.2022

Product code: 31951

Page 2 of 11

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P390 Absorb spillage to prevent material damage.
P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-63-0	propan-2-ol			95 - < 100 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant
Respiratory complaints
Headache
Dizziness
Dizziness
Inebriation
Anaesthetic state

Kaliumhydroxid-Lösung 1,8 g/l in 2-Propanol

Revision date: 16.05.2022

Product code: 31951

Page 3 of 11

Unconsciousness
Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids
Hazardous combustion products
In case of fire may be liberated: Carbon dioxide (CO₂) Carbon monoxide
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Heating causes rise in pressure with risk of bursting.
Beware of reignition.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).
Take action to prevent static discharges.
Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.
Danger of explosion

6.3. Methods and material for containment and cleaning up

Kaliumhydroxid-Lösung 1,8 g/l in 2-Propanol

Revision date: 16.05.2022

Product code: 31951

Page 4 of 11

For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

- Clean contaminated articles and floor according to the environmental legislation.

Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment. Use extractor hood (laboratory).
- Do not breathe vapour/aerosol. Provide adequate ventilation.

Advice on protection against fire and explosion

- Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

- Keep away from food, drink and animal feedingstuffs.
- Wash hands and face before breaks and after work and take a shower if necessary.
- When using do not eat or drink.
- Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

- Take off immediately all contaminated clothing and wash it before reuse.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep container tightly closed in a cool, well-ventilated place.
- Store in a cool dry place.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Corrosive to metals.

Further information on storage conditions

- Protect from sunlight.
- Protect against: Light
- minimum storage temperature +5°C
- maximum storage temperature +30°C

7.3. Specific end use(s)

- Laboratory chemicals

SECTION 8: Exposure controls/personal protection

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kaliumhydroxid-Lösung 1,8 g/l in 2-Propanol

Revision date: 16.05.2022

Product code: 31951

Page 5 of 11

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek

DNEL/DMEL values

CAS No	Substance	DNEL type	Exposure route	Effect	Value
67-63-0	propan-2-ol	Worker DNEL, long-term	inhalation	systemic	500 mg/m ³
		Worker DNEL, long-term	dermal	systemic	888 mg/kg bw/day
		Consumer DNEL, long-term	inhalation	systemic	89 mg/m ³
		Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day
		Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day

PNEC values

CAS No	Substance	Environmental compartment	Value
67-63-0	propan-2-ol	Freshwater	140,9 mg/l
		Freshwater (intermittent releases)	140,9 mg/l
		Marine water	140,9 mg/l
		Freshwater sediment	552 mg/kg
		Marine sediment	552 mg/kg
		Secondary poisoning	160 mg/kg
		Micro-organisms in sewage treatment plants (STP)	2251 mg/l
		Soil	28 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

- goggles
- Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is

Kaliumhydroxid-Lösung 1,8 g/l in 2-Propanol

Revision date: 16.05.2022

Product code: 31951

Page 6 of 11

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

- Wear fire resistant or flame retardant clothing.
- Take off immediately all contaminated clothing and wash it before reuse.
- Wear suitable protective clothing. Take off immediately all contaminated clothing.
- Wash hands and face before breaks and after work and take a shower if necessary.

Respiratory protection

- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Environmental exposure controls

- Do not allow to enter into surface water or drains.
- Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.
- Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	clear
Odour:	like: Alcohol

Changes in the physical state

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	82 °C
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
:	No data available
Flash point:	12 °C

Flammability

Solid/liquid:	No data available
Gas:	No data available

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Lower explosion limits:	No data available
Upper explosion limits:	No data available
Auto-ignition temperature:	No data available

Self-ignition temperature

Solid:	No data available
Gas:	No data available

Decomposition temperature: No data available

pH-Value: No data available

Viscosity / dynamic: No data available

Viscosity / kinematic: No data available

Flow time: No data available

Water solubility: No data available

Solubility in other solvents

No data available

Kaliumhydroxid-Lösung 1,8 g/l in 2-Propanol

Revision date: 16.05.2022

Product code: 31951

Page 7 of 11

Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,78 g/cm ³
Bulk density:	No data available
Relative vapour density:	No data available

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion: Sustaining combustion

Oxidizing properties
No data available

Other safety characteristics

Solvent separation test:	No data available
Solvent content:	100%
Solid content:	No data available
Evaporation rate:	No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.
Formation of: Peroxides
Corrosive to metals.

10.2. Chemical stability

Protect against:
Light
Air

10.3. Possibility of hazardous reactions

Oxidising agent, Alkali metals, Alkaline earth metal,
, Nitric acid, aldehydes
Amines, Aluminium, Chlorine (Cl₂)
Phosphorus trichloride, Strong acid, Phosgene
Hydrogen peroxide, Nitrogen oxides (NO_x), Iron.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Light
Air

10.5. Incompatible materials

Plastic articles
Metal

10.6. Hazardous decomposition products

Peroxides
SECTION 5: Firefighting measures

Further information

No data available

Kaliumhydroxid-Lösung 1,8 g/l in 2-Propanol

Revision date: 16.05.2022

Product code: 31951

Page 8 of 11

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Other information

Observe risk of aspiration if vomiting occurs. Pulmonary oedema Pneumonia

Repeated exposure may cause skin dryness or cracking.

Further information

No data available

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol					
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983) OECD Guideline 203

12.2. Persistence and degradability

Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol	0,05

Kaliumhydroxid-Lösung 1,8 g/l in 2-Propanol

Revision date: 16.05.2022

Product code: 31951

Page 9 of 11

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol, potassium hydroxide)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	338
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol, potassium hydroxide)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kaliumhydroxid-Lösung 1,8 g/l in 2-Propanol

Revision date: 16.05.2022

Product code: 31951

Page 10 of 11

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol, potassium hydroxide)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol, potassium hydroxide)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Special Provisions:	A3
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y340
Excepted quantity:	E2
IATA-packing instructions - Passenger:	352
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	363
IATA-max. quantity - Cargo:	5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
Entry 3, Entry 40, Entry 75

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1.

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kaliumhydroxid-Lösung 1,8 g/l in 2-Propanol

Revision date: 16.05.2022

Product code: 31951

Page 11 of 11

H290	May be corrosive to metals.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)