

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Carc. 1B; H350i

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

beryllium nitrate

Signal word: Danger

Pictograms:





Hazard statements

H290 May be corrosive to metals.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 2 of 17

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H350i May cause cancer by inhalation.

Precautionary statements

P201 Obtain special instructions before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of Water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P390 Absorb spillage to prevent material damage.

Special labelling of certain mixtures

EUH208 Contains beryllium compounds with the exception of aluminium beryllium silicates, and

with those specified elsewhere in this Annex, nickel dinitrate. May produce an allergic

reaction.

Restricted to professional users.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 3 of 17

Relevant ingredients

CAS No	Chemical name			Quantity		
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No	Classification (Regulation (EC) No 1272/2008)				
7697-37-2	nitric acid			1 - < 5 %		
	231-714-2	007-030-00-3	01-2119487297-23			
	Ox. Liq. 3, Met. Corr. 1, Acute Tox	. 3, Skin Corr. 1A; H272 H290 H331 I				
-	beryllium compounds with the exceeds elsewhere in this Annex	eption of aluminium beryllium silicates	s, and with those specified	< 1 %		
	-	004-002-00-2				
	I I	. 3, Skin Irrit. 2, Eye Irrit. 2, Skin Sens 330 H301 H315 H319 H317 H335 H3				
1336-21-6	Ammonia		< 0.1 %			
	215-647-6	007-001-01-2	01-2119488876-14			
	Skin Corr. 1B, Aquatic Acute 1, Ac	uatic Chronic 2; H314 H400 H411				
13138-45-9	nickel dinitrate		< 0.01 %			
	236-068-5	028-012-00-1	01-2119492333-38			
		r. 1B, Acute Tox. 4, Acute Tox. 4, Ski T RE 1, Aquatic Acute 1, Aquatic Chr 334 H317 H372 H400 H410				
7761-88-8	silver nitrate		< 0.01 %			
	231-853-9	047-001-00-2	01-2119513705-43			
	Ox. Sol. 2, Met. Corr. 1, Skin Corr. H290 H314 H318 H400 H410	1B, Eye Dam. 1, Aquatic Acute 1, Ad	quatic Chronic 1; H272			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
7697-37-2	231-714-2	nitric acid	1 - < 5 %
		E 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 rr. 1B; H314: >= 5 - < 20	
-	-	beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex	< 1 %
	inhalation: ATE 100 mg/kg	E = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); oral: ATE =	
1336-21-6	215-647-6	Ammonia	< 0.1 %
	inhalation: LC5 Aquatic Acute 1	60 = 4230 mg/l (vapours); oral: LD50 = 350 mg/kg STOT SE 3; H335: >= 5 - 100 ; H400: M=10	
13138-45-9	236-068-5	nickel dinitrate	< 0.01 %
	361,9 mg/kg S		
7761-88-8	231-853-9	silver nitrate	< 0.01 %
		= > 348 mg/kg; oral: LD50 = > 2000 mg/kg	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 4 of 17

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 5 of 17

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 6 of 17

Requirements for storage rooms and vessels

Corrosive to metals.

Unsuitable container/equipment material: Metal

The product develops hydrogen in an aqueous solution in contact with metals.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7664-41-7	Ammonia, anhydrous	20	14		TWA (8 h)	
		50	36		STEL (15 min)	
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 7 of 17

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1336-21-6	Ammonia			
Worker DNEL,	long-term	inhalation	systemic	47,6 mg/m³
Worker DNEL,	acute	inhalation	systemic	47,6 mg/m³
Worker DNEL,	long-term	inhalation	local	14 mg/m³
Worker DNEL,	acute	inhalation	local	36 mg/m³
Worker DNEL,	long-term	dermal	systemic	6,8 mg/kg bw/day
Worker DNEL,	acute	dermal	systemic	6,8 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	23,8 mg/m³
Consumer DN	EL, acute	inhalation	systemic	23,8 mg/m³
Consumer DN	EL, long-term	inhalation	local	2,8 mg/m³
Consumer DN	EL, acute	inhalation	local	7,2 mg/m³
Consumer DN	EL, long-term	dermal	systemic	68 mg/kg bw/day
Consumer DN	EL, acute	dermal	systemic	68 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	6,8 mg/kg bw/day
Consumer DN	EL, acute	oral	systemic	6,8 mg/kg bw/day
13138-45-9	nickel dinitrate			
Consumer DN	EL, acute	oral	systemic	0,012 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	0,02 mg/kg bw/day
Worker DNEL,	acute	inhalation	systemic	104 mg/m³
Worker DNEL,	acute	inhalation	local	1,6 mg/m³
Consumer DN	EL, acute	inhalation	systemic	8,8 mg/m³
Consumer DNEL, acute		inhalation	local	0,1 mg/m³
7761-88-8	silver nitrate			
Consumer DNEL, long-term		oral	systemic	0,02 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	0,016 mg/m³
Consumer DN	EL, long-term	inhalation	systemic	0,006 mg/m³



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 8 of 17

PNEC values

CAS No	Substance	
Environment	al compartment	Value
1336-21-6	Ammonia	
Freshwater		0,001 mg/l
Freshwater (intermittent releases)	0,007 mg/l
Marine water	ſ	0,001 mg/l
13138-45-9	nickel dinitrate	
Freshwater		0,0071 mg/l
Freshwater (intermittent releases)	0 mg/l
Marine water	r	0,0086 mg/l
Freshwater sediment		109 mg/kg
Marine sedin	nent	109 mg/kg
Secondary p	oisoning	0,12 mg/kg
Micro-organi	sms in sewage treatment plants (STP)	0,33 mg/l
Soil		29,9 mg/kg
7761-88-8	silver nitrate	
Freshwater		0,00004 mg/l
Marine water		0,00086 mg/l
Freshwater sediment		438,13 mg/kg
Marine sediment		438,13 mg/kg
Micro-organi	sms in sewage treatment plants (STP)	0,025 mg/l
Soil		1,41 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 9 of 17

of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: clear
Odour: odourless

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

Flammability: No data available Lower explosion limits: No data available Upper explosion limits: No data available Flash point: No data available Auto-ignition temperature: No data available Decomposition temperature: No data available pH-Value: acidic Viscosity / kinematic: No data available Water solubility: completely miscible

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Vapour pressure:

No data available

Density:

No data available

Bulk density:

No data available

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion:

No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

Oxidizing



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 10 of 17

No data available

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available

Solvent content:

Solid content:

Sublimation point:

No data available

No data available

No data available

No data available

Pour point: No data available:

Viscosity / dynamic:

Flow time:

No data available

No data available

Further Information
Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 11 of 17

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
7697-37-2	nitric acid								
	inhalation vapour	ATE 2,65	5 mg/l						
-	beryllium compounds withis Annex	th the excep	otion of alumin	ium beryllium silica	ites, and with those specified el	sewhere in			
	oral	ATE mg/kg	100						
	inhalation vapour	ATE	0,5 mg/l						
	inhalation dust/mist	ATE	0,05 mg/l						
1336-21-6	Ammonia								
	oral	LD50 mg/kg	350	Rat	Journal of Industrial Hygiene and Toxico	OECD Guideline 401			
	inhalation (1 h) vapour	LC50	4230 mg/l	Mouse	Bull. Environm. Contam. Toxicol, 1982, 2	Assessment of acute inhalation toxicity			
13138-45-9	nickel dinitrate								
	oral	LD50 mg/kg	361,9	Rat	Regul Toxicol and Pharmacol (doi.org/10.	OECD Guideline 425			
	inhalation vapour	ATE	11 mg/l						
	inhalation dust/mist	ATE	1,5 mg/l						
7761-88-8	silver nitrate								
	oral	LD50 mg/kg	> 2000	Rat	Study report (1993)	OECD Guideline 401			
	dermal	LD50 mg/kg	> 348	Guinea pig	J. Vet. Med. Sci.73: 1417 - 1423. (2011)	OECD Guideline 434			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex, nickel dinitrate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer by inhalation. (beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex; nickel dinitrate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 12 of 17

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 13 of 17

CAS No	Chemical name								
0/10/10	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
7697-37-2	nitric acid			1 31 2	1				
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26		
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical		
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso		
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209		
1336-21-6	Ammonia								
	Acute fish toxicity	LC50 3,4 mg/l	0,75 -	96 h	Pimephales promelas	Trans Amer Fish Soc; 112 (5). 1983. 705-	Assessment of acute toxicity in the fath		
	Acute crustacea toxicity	EC50	101 mg/l	48 h	Daphnia magna	Environ. Toxicol. Chem. 5: 443-447 (1986	other: ASTM E729-80		
	Fish toxicity	NOEC	1,2 mg/l	61 d	Oncorhynchus gorbuscha	Fish. Bull. 78(3): 641-648 (1980)	OECD Guideline 210		
13138-45-9	nickel dinitrate								
	Acute fish toxicity	LC50 mg/l	15,3	96 h	Oncorhynchus mykiss	Aquatic Toxicology 63 (2003) 65-82 (2003	other: not reported		
	Acute algae toxicity	ErC50 mg/l	0,237	72 h	Ankistrodesmus falcatus	Publication (2009)	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	0,2663	48 h	Ceriodaphnia dubia	Study report (2004)	other: American society of testing and m		
	Fish toxicity	NOEC mg/l	0,057	32 d	Pimephales promelas	Water Resources Research Institute. Kent	other: ASTM 1980, E-729		
	Algae toxicity	NOEC	0,6 mg/l	14 d	Anabaena cylindrica	Environ. Pollut. (Series A). 25(4):241-2	other: not reported		
	Crustacea toxicity	NOEC mg/l	0,04	42 d	Daphnia magna	Wat. Res. 24(7):845-852 (1990)	Chronic exposure to sublethal concentrat		
	Acute bacteria toxicity	EC50)	33 mg/l (0,5 h	Activated sludge	Journal of Hazardous Materials. B139:332	ISO 8192		
7761-88-8	silver nitrate								
	Acute fish toxicity	LC50 mg/l	0,0012	96 h	Pimephales promelas	Environmental Toxicology and Chemistry.	A guideline was not specified. The test		
	Acute algae toxicity	ErC50 mg/l	0,0099	96 h	Pseudokirchneriella subcapitata	Environmental Science and Technology. 44	eline: U.S. Environmental Protection Age		



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 14 of 17

Acute crustacea toxicity	EC50 mg/l	0,00022	48 h	Daphnia magna	Environmental Toxicology and Chemistry.	The protective effect of reactive sulphi
Fish toxicity	NOEC 0,00125 mg	> g/l	73 d	Oncorhynchus mykiss	Environmental Toxicology and Chemistry 2	other: ASTM 1241-98
Algae toxicity	NOEC mg/l	0,0012	14 d	Champia parvula	in Bishop WE, Cardwell RD Heidolph BB (E	The toxicity tests lasted 11 days for th
Crustacea toxicity	NOEC mg/l	0,00031	20 d	Isonychia bicolour	Environmental Toxicology and Chemistry.	20 day sublethal effects on representati

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1336-21-6	Ammonia	-1,38

BCF

CAS No	Chemical name	BCF	Species	Source
13138-45-9	nickel dinitrate	23	Spirodela polyrhiza	Ecotoxicology and en
7761-88-8	silver nitrate	70	Cyprinus carpio	Water, Air and Soil

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Do not allow to enter into surface water or drains.

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 15 of 17

8 14.3. Transport hazard class(es): Ш 14.4. Packing group: Hazard label: 8 Classification code: C₁ **Special Provisions:** 274 Limited quantity: 5 L Excepted quantity: E1 Transport category: 3 Hazard No: 80 Tunnel restriction code: F

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Classification code:C1Special Provisions:274Limited quantity:5 LExcepted quantity:E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:223, 274Limited quantity:5 LExcepted quantity:E1EmS:F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:1 LPassenger LQ:Y841Excepted quantity:E1

IATA-packing instructions - Passenger:852IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:856IATA-max. quantity - Cargo:60 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 27, Entry 75

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 16 of 17

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 12.

Abbreviations and acronyms

Ox. Liq: Oxidising liquid Ox. Sol: Oxidising solid

Met. Corr: Substance or mixture corrosive to metals

Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation

Resp. Sens: Respiratory sensitisation

Skin Sens: Skin sensitisation Muta: Germ cell mutagenicity

Carc: Carcinogenicity
Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure		
Met. Corr. 1; H290	On basis of test data		
Skin Irrit. 2; H315	Calculation method		
Eye Irrit. 2; H319	Calculation method		
Carc. 1B; H350i	Calculation method		

Relevant H and EUH statements (number and full text)

H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 30 Elemente in verdünnter Salpetersäure

Revision date: 21.11.2024 Product code: 32390 Page 17 of 17

H350i May cause cancer by inhalation. H360D May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

EUH208 Contains beryllium compounds with the exception of aluminium beryllium silicates, and

with those specified elsewhere in this Annex, nickel dinitrate. May produce an allergic

reaction.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)