

according to Regulation (EC) No 1907/2006

# Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1 : 1 for the determination of t

Revision date: 29.07.2024 Product code: 32633 Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1:1 for the determination of t

UFI: MQCW-W2VK-D00J-5AMJ

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Laboratory chemical

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

### Uses advised against

Do not use for private purposes (household).

## 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone
 number:
 For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,
 Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

## **Further Information**

This product is a mixture. REACH Registration Number see section 3.

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Eye Irrit. 2; H319 STOT SE 3; H336 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

PETROLEUM SPIRIT

Signal word: Danger



according to Regulation (EC) No 1907/2006

# Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1 : 1 for the determination of t

Revision date: 29.07.2024 Product code: 32633 Page 2 of 13

## Pictograms:









### **Hazard statements**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

## Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

No information available.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

## Relevant ingredients

CAS No	Chemical name	Chemical name				
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No	1272/2008)				
64-17-5	ethanol	ethanol				
	200-578-6	603-002-00-5	01-2119457610-43			
	Flam. Liq. 2, Eye Irrit. 2; H225 H319					
64742-49-0	PETROLEUM SPIRIT					
		649-328-00-1 01-2119473851-33				
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066					

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc. L	pecific Conc. Limits, M-factors and ATE			
64-17-5	200-578-6	ethanol	50 - < 55 %		
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg				

## **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).



according to Regulation (EC) No 1907/2006

## Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1 : 1 for the determination of t

Revision date: 29.07.2024 Product code: 32633 Page 3 of 13

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### General information

No data available

### After inhalation

Provide fresh air.

Call a doctor if you feel unwell.

### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

### After ingestion

Call a physician immediately.

Observe risk of aspiration if vomiting occurs.

## 4.2. Most important symptoms and effects, both acute and delayed

Irritant

Dizziness

The product causes narcotic-like effects.

Inebriation

Vomiting

## 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

## Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

## Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Combustible liquid.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

Beware of reignition.

### 5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

Use water spray jet to protect personnel and to cool endangered containers.

## **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Suppress gases/vapours/mists with water spray jet.

Move undamaged containers from immediate hazard area if it can be done safely.

Print date: 29.07.2024



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1 : 1 for the determination of t

Revision date: 29.07.2024 Product code: 32633 Page 4 of 13

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

## For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

### For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

### 6.3. Methods and material for containment and cleaning up

### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

## For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

## Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

## Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other



according to Regulation (EC) No 1907/2006

# Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1 : 1 for the determination of t

Revision date: 29.07.2024 Product code: 32633 Page 5 of 13

ignition sources. No smoking.

## Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

## Further information on storage conditions

Vapours may form explosive mixtures with air.

## 7.3. Specific end use(s)

Laboratory use Laboratory chemical

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	

## **DNEL/DMEL values**

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
64-17-5	ethanol						
Worker DNEL,	long-term	inhalation	systemic	950 mg/m³			
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day			
Consumer DNEL, long-term		inhalation	systemic	114 mg/m³			
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day			
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day			



according to Regulation (EC) No 1907/2006

## Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1 : 1 for the determination of t

Revision date: 29.07.2024 Product code: 32633 Page 6 of 13

#### **PNEC** values

CAS No	Substance	
Environment	al compartment	Value
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (	Freshwater (intermittent releases)	
Marine wate	r	0,79 mg/l
Freshwater	sediment	3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		380 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil	0,63 mg/kg	

### 8.2. Exposure controls

## Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Suitable eye protection: goggles.

## **Hand protection**

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject®
Suitable material: FKM (fluoro rubber) 0,7 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 730 Camatril® Velours

Suitable material: 0,4 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

## Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

## **Environmental exposure controls**

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Print date: 29.07.2024



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1 : 1 for the determination of t

Revision date: 29.07.2024 Product code: 32633 Page 7 of 13

Danger of explosion

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: characteristic

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

>35 °C

boiling range:

not applicable Flammability: Lower explosion limits: No data available Upper explosion limits: No data available <21 °C Flash point: Auto-ignition temperature: No data available Decomposition temperature: No data available Viscosity / kinematic: No data available Water solubility: No data available

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Relative vapour density:

No data available

## 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Sustaining combustion: Sustaining combustion

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties Not oxidising.

## Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available
Solvent content:

No data available
Solid content:

No data available
Sublimation point:

No data available
Softening point:

No data available
Pour point:

No data available
No data available

No data available:

Viscosity / dynamic: No data available

(at 20 °C)

Flow time: No data available

## **Further Information**

No data available



according to Regulation (EC) No 1907/2006

# Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1 : 1 for the determination of t

Revision date: 29.07.2024 Product code: 32633 Page 8 of 13

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Highly flammable.

Vapours can form explosive mixtures with air.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

Oxidising agent

## 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

## 10.5. Incompatible materials

Plastic articles

Rubber articles

## 10.6. Hazardous decomposition products

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

#### **Further information**

No data available

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

## **Acute toxicity**

Based on available data, the classification criteria are not met.

## **ATEmix** calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
64-17-5	ethanol						
	oral	LD50 mg/kg	10470	Rat	Study report (1976)	OECD Guideline 401	
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980)	OECD Guideline 403	

## Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

### Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction



according to Regulation (EC) No 1907/2006

# Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1 : 1 for the determination of t

Revision date: 29.07.2024 Product code: 32633 Page 9 of 13

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

## STOT-single exposure

May cause drowsiness or dizziness. (PETROLEUM SPIRIT)

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

## **Aspiration hazard**

May be fatal if swallowed and enters airways.

## Specific effects in experiment on an animal

There are no data available on the mixture itself.

### Additional information on tests

There are no data available on the mixture itself.

#### **Practical experience**

There are no data available on the mixture itself.

## 11.2. Information on other hazards

## Other information

Irritant

Dizziness

The product causes narcotic-like effects.

Inebriation

Vomiting

## **Further information**

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
64-17-5	ethanol						
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

## 12.2. Persistence and degradability

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

## Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1 : 1 for the determination of t

Revision date: 29.07.2024 Product code: 32633 Page 10 of 13

## 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,77

### **BCF**

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

## 12.4. Mobility in soil

There are no data available on the mixture itself.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

Do not empty into drains.

### **Further information**

Avoid release to the environment.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

### **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

### Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

## **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (ethanol, PETROLEUM SPIRIT)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993



according to Regulation (EC) No 1907/2006

## Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1 : 1 for the determination of t

Revision date: 29.07.2024 Product code: 32633 Page 11 of 13

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (ethanol, PETROLEUM SPIRIT)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993

**14.2. UN** proper shipping name: FLAMMABLE LIQUID, N.O.S. (ethanol, PETROLEUM SPIRIT)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:274Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (ethanol, PETROLEUM SPIRIT)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A3Limited quantity Passenger:1 LPassenger LQ:Y341Excepted quantity:E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: PETROLEUM SPIRIT

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive

E2 Hazardous to the Aquatic Environment

2012/18/EU (SEVESO III):

Additional information: P5c

**National regulatory information** 



according to Regulation (EC) No 1907/2006

## Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1 : 1 for the determination of t

Revision date: 29.07.2024 Product code: 32633 Page 12 of 13

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

## 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## **SECTION 16: Other information**

### Changes

This data sheet contains changes from the previous version in section(s): 1,9,12.

### Abbreviations and acronyms

Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

## Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

## Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

## **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Print date: 29.07.2024



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Ethanol 96 % R / petroleum ether R 3 - mixture volumetrically mixed 1 : 1 for the determination of t

Revision date: 29.07.2024 Product code: 32633 Page 13 of 13

Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)