

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene for analysis, ACS

Revision date: 19.03.2025

Product code: 32696

Page 1 of 14

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Toluene for analysis, ACS

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

### Further Information

This product is a mixture. REACH Registration Number see section 3.

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225  
Acute Tox. 4; H332  
Acute Tox. 4; H312  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
STOT SE 3; H335 H336  
STOT RE 2; H373  
Asp. Tox. 1; H304  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

xylene (mix)  
propan-2-ol; isopropyl alcohol; isopropanol

**Signal word:** Danger

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Toluene for analysis, ACS**

Revision date: 19.03.2025

Product code: 32696

Page 2 of 14

**Pictograms:**



**Hazard statements**

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P403+P235	Store in a well-ventilated place. Keep cool.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Relevant ingredients**

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
	xylene (mix)	65 - < 70 %
	905-588-0	601-022-00-9
		01-2119488216-32
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	30 - < 35 %
	200-661-7	603-117-00-0
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	
64-17-5	ethanol	1 - < 5 %
	200-578-6	603-002-00-5
		01-2119457610-43
	Flam. Liq. 2, Eye Irrit. 2; H225 H319	

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Toluene for analysis, ACS**

Revision date: 19.03.2025

Product code: 32696

Page 3 of 14

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	905-588-0	xylene (mix)	65 - < 70 %
		inhalation: LC50 = 6700 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 12126 mg/kg; oral: LD50 = 3523 mg/kg	
64-17-5	200-578-6	ethanol	1 - < 5 %
		inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100	

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

No data available

**After inhalation**

Provide fresh air.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.

**After contact with skin**

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.  
Call a physician immediately.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Remove contact lenses, if present and easy to do. Continue rinsing.

**After ingestion**

Observe risk of aspiration if vomiting occurs.  
Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Irritant  
Vapours may cause drowsiness and dizziness.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

**Unsuitable extinguishing media**

no restriction

**5.2. Special hazards arising from the substance or mixture**

Combustible liquids  
Hazardous combustion products  
In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Heating causes rise in pressure with risk of bursting.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene for analysis, ACS

Revision date: 19.03.2025

Product code: 32696

Page 4 of 14

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.  
In case of fire and/or explosion do not breathe fumes.  
Avoid contact with skin, eyes and clothes.

#### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Use water spray jet to protect personnel and to cool endangered containers.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Keep away from sources of ignition - No smoking.  
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).  
Take action to prevent static discharges.

##### **For non-emergency personnel**

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures  
Consult an expert  
Do not breathe dust/fume/gas/mist/vapours/spray.

##### **For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.  
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.  
Danger of explosion

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Cover drains.  
Prevent spread over a wide area (e.g. by containment or oil barriers).  
Collect in closed and suitable containers for disposal.  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

##### **Other information**

Provide adequate ventilation.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### **6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Toluene for analysis, ACS**

Revision date: 19.03.2025

Product code: 32696

Page 5 of 14

**Advice on safe handling**

Read label before use. Handle and open container with care.  
When using do not eat, drink, smoke, sniff. Keep container tightly closed.  
Use personal protection equipment. Use extractor hood (laboratory).  
Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

**Advice on protection against fire and explosion**

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.  
Draw up and observe skin protection programme.  
The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.  
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

national regulations

**Further information on storage conditions**

Keep cool. Protect from sunlight.

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	
1330-20-7	Xylene, mixed isomers	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

**Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Toluene for analysis, ACS**

Revision date: 19.03.2025

Product code: 32696

Page 6 of 14

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
	xylene (mix)			
	Worker DNEL, long-term	inhalation	systemic	221 mg/m <sup>3</sup>
	Worker DNEL, acute	inhalation	systemic	442 mg/m <sup>3</sup>
	Worker DNEL, long-term	inhalation	local	221 mg/m <sup>3</sup>
	Worker DNEL, acute	inhalation	local	442 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	212 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	65,3 mg/m <sup>3</sup>
	Consumer DNEL, acute	inhalation	systemic	260 mg/m <sup>3</sup>
	Consumer DNEL, long-term	inhalation	local	65,3 mg/m <sup>3</sup>
	Consumer DNEL, acute	inhalation	local	260 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	125 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	12,5 mg/kg bw/day
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
	Worker DNEL, long-term	inhalation	systemic	500 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	888 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	89 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day
64-17-5	ethanol			
	Worker DNEL, long-term	inhalation	systemic	950 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	114 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Toluene for analysis, ACS**

Revision date: 19.03.2025

Product code: 32696

Page 7 of 14

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
	xylene (mix)	
	Freshwater	0,327 mg/l
	Freshwater (intermittent releases)	0,327 mg/l
	Marine water	0,327 mg/l
	Freshwater sediment	12,46 mg/kg
	Marine sediment	12,46 mg/kg
	Micro-organisms in sewage treatment plants (STP)	6,58 mg/l
	Soil	2,31 mg/kg
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
	Freshwater	140,9 mg/l
	Freshwater (intermittent releases)	140,9 mg/l
	Marine water	140,9 mg/l
	Freshwater sediment	552 mg/kg
	Marine sediment	552 mg/kg
	Secondary poisoning	160 mg/kg
	Micro-organisms in sewage treatment plants (STP)	2251 mg/l
	Soil	28 mg/kg
64-17-5	ethanol	
	Freshwater	0,96 mg/l
	Freshwater (intermittent releases)	2,75 mg/l
	Marine water	0,79 mg/l
	Freshwater sediment	3,6 mg/kg
	Marine sediment	2,9 mg/kg
	Secondary poisoning	380 mg/kg
	Micro-organisms in sewage treatment plants (STP)	580 mg/l
	Soil	0,63 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

goggles

Face protection umbrella

**Hand protection**

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Toluene for analysis, ACS**

Revision date: 19.03.2025

Product code: 32696

Page 8 of 14

By short-term hand contact  
Trade name/designation: KCL 890 Vitoject®  
Suitable material: FKM (fluoro rubber) 0,7 mm  
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

**Skin protection**

Take off immediately all contaminated clothing and wash it before reuse.  
Wear fire resistant or flame retardant clothing.  
Wash hands and face before breaks and after work and take a shower if necessary.

**Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation  
The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

**Environmental exposure controls**

Do not allow to enter into surface water or drains.  
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.  
Danger of explosion

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	clear	
Odour:	like: Hydrocarbons, aromatic	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		>35 °C
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		<21 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		No data available
Viscosity / kinematic:		No data available
Water solubility:		No data available
Solubility in other solvents		No data available
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available

**9.2. Other information**

**Information with regard to physical hazard classes**



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene for analysis, ACS

Revision date: 19.03.2025

Product code: 32696

Page 9 of 14

#### Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

Sustained combustibility

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

#### Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

#### Further Information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Vapours may form explosive mixtures with air.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Oxidising agent

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

Plastic articles

Rubber articles

### 10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

#### Further information

No data available

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Harmful if inhaled.

Harmful in contact with skin.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) 1630 mg/kg; ATE (inhalation vapour) 16,30 mg/l; ATE (inhalation dust/mist) 2,222 mg/l

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Toluene for analysis, ACS**

Revision date: 19.03.2025

Product code: 32696

Page 10 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	xylene (mix)				
	oral	LD50 3523 mg/kg	Rat	Study report (1986)	EU Method B.1
	dermal	LD50 12126 mg/kg	Rabbit	Publication (1962)	Single dermal dose under occlusion follo
	inhalation (4 h) vapour	LC50 6700 mg/l	Rat	Toxicol Appl Pharmacol 33:543-558. (1975)	EU Method B.2
	inhalation dust/mist	ATE 1,5 mg/l			
64-17-5	ethanol				
	oral	LD50 10470 mg/kg	Rat	Study report (1976)	OECD Guideline 401
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	Study report (1980)	OECD Guideline 403

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation.  
Serious eye damage/eye irritation: Causes serious eye irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.  
Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (xylene (mix))  
May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (xylene (mix))

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards**

**Other information**

There are no data available on the mixture itself.

**Further information**

Irritant

**SECTION 12: Ecological information**

**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Toluene for analysis, ACS**

Revision date: 19.03.2025

Product code: 32696

Page 11 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
	xylene (mix)					
	Acute fish toxicity	LC50 8,4 mg/l	96 h	Oncorhynchus mykiss	Ecotoxicology and Environmental Safety.	OECD Guideline 203
	Acute algae toxicity	ErC50 4,9 mg/l	72 h	Raphidocelis subcapitata	Ecotoxicology and Environmental Safety.	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l > 3,4	48 h	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	other: US EPA 600/4-91-003
	Fish toxicity	NOEC mg/l > 1,3	56 d	Oncorhynchus mykiss	Appl. Sci. Branch, Eng. Res. Cent. Denve	Fish were exposed in artificial streams
	Crustacea toxicity	NOEC mg/l 1,17	7 d	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	other: US EPA 600/4-91-003
	Acute bacteria toxicity	EC50 mg/l ( ) > 175	0,5 h	Activated sludge	Research Journal WPCF 60(10) 1850-1856 (	OECD Guideline 209
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l 10000	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203
64-17-5	ethanol					
	Acute fish toxicity	LC50 mg/l 15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l > 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC mg/l 5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989)	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC 2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
	xylene (mix)	3,2
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05
64-17-5	ethanol	-0,77

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Toluene for analysis, ACS**

Revision date: 19.03.2025

Product code: 32696

Page 12 of 14

**BCF**

CAS No	Chemical name	BCF	Species	Source
	xylene (mix)	> 5,5 - < 12,2	Oncorhynchus mykiss	Appl. Sci. Branch, E
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Do not allow to enter into surface water or drains.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not empty into drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.  
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol, xylene)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol, xylene)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Toluene for analysis, ACS**

Revision date: 19.03.2025

Product code: 32696

Page 13 of 14

Special Provisions: 274 601 640D  
 Limited quantity: 1 L  
 Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (propan-2-ol, xylene)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3  
 Special Provisions: 274  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (propan-2-ol, xylene)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3  
 Special Provisions: A3  
 Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):  
 Entry 3, Entry 40, Entry 75

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.  
 Water hazard class (D): 2 - obviously hazardous to water

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 2,12,15.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Toluene for analysis, ACS**

Revision date: 19.03.2025

Product code: 32696

Page 14 of 14

**Abbreviations and acronyms**

- Flam. Liq: Flammable liquid
- Acute Tox: Acute toxicity
- Asp. Tox: Aspiration hazard
- Skin Irrit: Skin irritation
- Eye Irrit: Eye irritation
- STOT SE: Specific target organ toxicity - single exposure
- STOT RE: Specific target organ toxicity - repeated exposure
- Aquatic Chronic: Chronic aquatic hazard

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H332	Calculation method
Acute Tox. 4; H312	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H312+H332 Harmful in contact with skin or if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs (auditory organs, liver, kidneys, central nervous system) through prolonged or repeated exposure if inhaled.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*