

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Sulfuric acid 0.25 M in ethanol 95% (v/v)

Revision date: 14.03.2025

Product code: 32861

Page 1 of 12

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Sulfuric acid 0.25 M in ethanol 95% (v/v)

UFI: S90X-A283-700D-05G8

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Laboratory chemical

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

###### Uses advised against

Do not use for private purposes (household).

##### 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH  
ACD  
Street: Stempelstraße 6  
Place: D-47167 Duisburg  
Telephone: 0203/5194-0  
Telefax: 0203/5194-290  
E-mail: info@analytichem.de  
Contact person: Abteilung Produktsicherheit  
Telephone: 0203/5194-107/117  
E-mail: produktsicherheit@analytichem.de  
Internet: www.analytichem.de  
Responsible Department: Abteilung Produktsicherheit

##### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

##### Further Information

This product is a mixture. REACH Registration Number see section 3.

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225

Met. Corr. 1; H290

Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

###### Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



###### Hazard statements

H225 Highly flammable liquid and vapour.  
H290 May be corrosive to metals.  
H319 Causes serious eye irritation.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid 0.25 M in ethanol 95% (v/v)**

Revision date: 14.03.2025

Product code: 32861

Page 2 of 12

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233 Keep container tightly closed.  
 P390 Absorb spillage to prevent material damage.  
 P403+P235 Store in a well-ventilated place. Keep cool.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Relevant ingredients**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
64-17-5	ethanol	90 - < 95 %
	200-578-6	603-002-00-5
	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319	
7664-93-9	sulphuric acid	1 - < 5 %
	231-639-5	016-020-00-8
	01-2119458838-20	
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318	

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64-17-5	200-578-6	ethanol	90 - < 95 %
		inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
7664-93-9	231-639-5	sulphuric acid	1 - < 5 %
		oral: LD50 = 2140 mg/kg Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15	

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

No data available

**After inhalation**

Provide fresh air.

**After contact with skin**

Wash immediately with: Water  
 Take off immediately all contaminated clothing and wash it before reuse.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Sulfuric acid 0.25 M in ethanol 95% (v/v)

Revision date: 14.03.2025

Product code: 32861

Page 3 of 12

#### After ingestion

Rinse mouth immediately and drink plenty of water.  
Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant  
Dizziness  
The product causes narcotic-like effects.  
Inebriation  
Vomiting

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

#### Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Combustible liquid.  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Hazardous combustion products  
In case of fire may be liberated:  
Carbon dioxide (CO<sub>2</sub>) Carbon monoxide  
Sulphur oxides  
Beware of reignition.

### 5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases.  
Avoid contact with skin, eyes and clothes.  
In case of fire: Wear self-contained breathing apparatus.  
Use water spray jet to protect personnel and to cool endangered containers.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Suppress gases/vapours/mists with water spray jet.  
Move undamaged containers from immediate hazard area if it can be done safely.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Keep away from sources of ignition - No smoking.  
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).  
Take action to prevent static discharges.  
Corrosive to metals.

#### For non-emergency personnel

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Sulfuric acid 0.25 M in ethanol 95% (v/v)

Revision date: 14.03.2025

Product code: 32861

Page 4 of 12

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

#### Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

#### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Unsuitable container/equipment material: Metal

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid 0.25 M in ethanol 95% (v/v)**

Revision date: 14.03.2025

Product code: 32861

Page 5 of 12

**Hints on joint storage**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.  
national regulations

**Further information on storage conditions**

Vapours may form explosive mixtures with air.  
storage temperature +5°C - +30°C.

**7.3. Specific end use(s)**

Laboratory use Laboratory chemical

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	
7664-93-9	Sulphuric acid	-	0.05		TWA (8 h)	

**DNEL/DMEL values**

CAS No	Substance	DNEL type	Exposure route	Effect	Value
64-17-5	ethanol	Worker DNEL, long-term	inhalation	systemic	950 mg/m <sup>3</sup>
		Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
		Consumer DNEL, long-term	inhalation	systemic	114 mg/m <sup>3</sup>
		Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
		Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day
7664-93-9	sulphuric acid	Worker DNEL, long-term	inhalation	local	0,05 mg/m <sup>3</sup>

**PNEC values**

CAS No	Substance	Environmental compartment	Value
64-17-5	ethanol	Freshwater	0,96 mg/l
		Freshwater (intermittent releases)	2,75 mg/l
		Marine water	0,79 mg/l
		Freshwater sediment	3,6 mg/kg
		Marine sediment	2,9 mg/kg
		Secondary poisoning	380 mg/kg
		Micro-organisms in sewage treatment plants (STP)	580 mg/l
		Soil	0,63 mg/kg
7664-93-9	sulphuric acid	Micro-organisms in sewage treatment plants (STP)	8,8 mg/l

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid 0.25 M in ethanol 95% (v/v)**

Revision date: 14.03.2025

Product code: 32861

Page 6 of 12

equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Suitable eye protection: goggles.

**Hand protection**

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 720 Camapren®

Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

Flame-retardant protective clothing. Wear anti-static footwear and clothing

**Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

**Environmental exposure controls**

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		>35 °C
Flammability:		not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		<21 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		acidic
Viscosity / kinematic:		No data available
Water solubility:		No data available

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid 0.25 M in ethanol 95% (v/v)**

Revision date: 14.03.2025

Product code: 32861

Page 7 of 12

Solubility in other solvents

not determined

Dissolution rate:

No data available

Partition coefficient n-octanol/water:

No data available

Dispersion stability:

No data available

Vapour pressure:

No data available

Vapour pressure:

No data available

Density:

~0,8 g/cm<sup>3</sup>

Relative density:

No data available

Bulk density:

No data available

Relative vapour density:

not determined

Particle characteristics:

No data available

**9.2. Other information**

**Information with regard to physical hazard classes**

Explosive properties

Vapours can form explosive mixtures with air.

Sustained combustibility:

Sustained combustibility

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

**Other safety characteristics**

Evaporation rate:

not determined

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available:

Viscosity / dynamic:

No data available

Flow time:

No data available

**Further Information**

Corrosive to metals.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Highly flammable.

Vapours can form explosive mixtures with air.

Corrosive to metals.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

Plastic articles

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid 0.25 M in ethanol 95% (v/v)**

Revision date: 14.03.2025

Product code: 32861

Page 8 of 12

Rubber articles  
Metal

**10.6. Hazardous decomposition products**

Hazardous combustion products  
In case of fire may be liberated:  
Carbon dioxide (CO<sub>2</sub>) Carbon monoxide  
Sulphur oxides

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol				
	oral	LD50 mg/kg	10470	Rat	Study report (1976) OECD Guideline 401
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980) OECD Guideline 403
7664-93-9	sulphuric acid				
	oral	LD50 mg/kg	2140	Rat	Am Ind Hyg Assoc J. 1969 Sep-Oct; 30(5): The study was performed as part of a ser

**Irritation and corrosivity**

Serious eye damage/eye irritation: Causes serious eye irritation.  
Skin corrosion/irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.  
Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

There are no data available on the mixture itself.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid 0.25 M in ethanol 95% (v/v)**

Revision date: 14.03.2025

Product code: 32861

Page 9 of 12

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

There are no data available on the mixture itself.

**Other information**

Irritant

Dizziness

The product causes narcotic-like effects.

Inebriation

Vomiting

**Further information**

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

**SECTION 12: Ecological information**

**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64-17-5	ethanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC 5400 mg/l	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989)	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC 2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th
7664-93-9	sulphuric acid					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	Study report (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (2009)	OECD Guideline 202
	Fish toxicity	NOEC 0,025 mg/l	65 d	Jordanella floridae	Water Research Vol. 11, 612 - 626, 1977	Groups of sexually mature flagfish

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid 0.25 M in ethanol 95% (v/v)**

Revision date: 14.03.2025

Product code: 32861

Page 10 of 12

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,77

**BCF**

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Do not empty into drains.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not allow to enter into surface water or drains.

**Contaminated packaging**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.  
Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, sulphuric acid)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	338
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, sulphuric acid)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid 0.25 M in ethanol 95% (v/v)**

Revision date: 14.03.2025

Product code: 32861

Page 11 of 12

Classification code: FC  
Special Provisions: 274  
Limited quantity: 1 L  
Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 2924  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, sulphuric acid)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3+8  
Special Provisions: 274  
Limited quantity: 1 L  
Excepted quantity: E2  
EmS: F-E, S-C

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 2924  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, sulphuric acid)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3+8  
Special Provisions: A3  
Limited quantity Passenger: 0.5 L  
Passenger LQ: Y340  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 352  
IATA-max. quantity - Passenger: 1 L  
IATA-packing instructions - Cargo: 363  
IATA-max. quantity - Cargo: 5 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Marketing and use of explosives precursors (Regulation (EU) 2019/ 1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid 0.25 M in ethanol 95% (v/v)**

Revision date: 14.03.2025

Product code: 32861

Page 12 of 12

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 9.

**Abbreviations and acronyms**

Met. Corr: Substance or mixture corrosive to metals

Flam. Liq: Flammable liquid

Skin Corr: Skin corrosion

Eye Dam: Eye damage

Eye Irrit: Eye irritation

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Met. Corr. 1; H290	On basis of test data
Eye Irrit. 2; H319	Calculation method

**Relevant H and EUH statements (number and full text)**

- H225 Highly flammable liquid and vapour.
- H290 May be corrosive to metals.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*