

according to Regulation (EC) No 1907/2006

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

Revision date: 21.07.2023 Product code: 32866 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

acetic acid cyclohexane

Signal word: Danger



according to Regulation (EC) No 1907/2006

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

Revision date: 21.07.2023 Product code: 32866 Page 2 of 13

Pictograms:











Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P310 **2.3. Other hazards**

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification (Regulation	n (EC) No 1272/2008)			
64-19-7	acetic acid				
	200-580-7	607-002-00-6	01-2119475328-30		
	Flam. Liq. 3, Skin Corr. 1	A; H226 H314			
110-82-7	cyclohexane				
	203-806-2	601-017-00-1	01-2119463273-41		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
64-19-7	200-580-7	acetic acid	55 - < 60 %
		0 = 11,4 mg/l (vapours); oral: LD50 = 3310 mg/kg	
110-82-7	203-806-2	cyclohexane	40 - < 45 %
	inhalation: LC5 mg/kg	0 = > 5540 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).



according to Regulation (EC) No 1907/2006

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

Revision date: 21.07.2023 Product code: 32866 Page 3 of 13

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

Remove contact lenses, if present and easy to do. Continue rinsing.

Consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

corrosive, Irritant

Vapours may cause drowsiness and dizziness.

Dizziness, Unconsciousness, Vomiting, Headache

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2)

Foam

Extinguishing powder

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.



according to Regulation (EC) No 1907/2006

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

Revision date: 21.07.2023 Product code: 32866 Page 4 of 13

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Provide adequate ventilation. Do not breathe vapour.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



according to Regulation (EC) No 1907/2006

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

Revision date: 21.07.2023 Product code: 32866 Page 5 of 13

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

Keep container tightly closed and dry.

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	
		20	50		STEL (15 min)	
110-82-7	Cyclohexane	200	700		TWA (8 h)	



according to Regulation (EC) No 1907/2006

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

Revision date: 21.07.2023 Product code: 32866 Page 6 of 13

DNEL/DMEL values

CAS No	Substance				
DNEL type	DNEL type		Effect	Value	
64-19-7	acetic acid				
Worker DNEL,	long-term	inhalation	local	25 mg/m³	
Worker DNEL,	acute	inhalation	local	25 mg/m³	
Consumer DNE	EL, long-term	inhalation	local	25 mg/m³	
Consumer DNE	EL, acute	inhalation	local	25 mg/m³	
110-82-7	cyclohexane				
Consumer DNE	EL, long-term	inhalation	systemic	206 mg/m³	
Consumer DNE	EL, acute	inhalation	systemic	412 mg/m³	
Consumer DNE	EL, long-term	inhalation	local	206 mg/m³	
Consumer DNE	EL, acute	inhalation	local	412 mg/m³	
Consumer DNE	Consumer DNEL, long-term		systemic	1186 mg/kg bw/day	
Consumer DNE	EL, long-term	oral	systemic	59,4 mg/kg bw/day	
Worker DNEL,	Worker DNEL, long-term		systemic	700 mg/m³	
Worker DNEL,	Worker DNEL, acute		systemic	1400 mg/m³	
Worker DNEL, long-term		inhalation	local	700 mg/m³	
Worker DNEL, acute		inhalation	local	1400 mg/m³	
Worker DNEL,	long-term	dermal	systemic	2016 mg/kg bw/day	

PNEC values

CAS No	Substance			
Environmental	Environmental compartment			
64-19-7	acetic acid			
Freshwater		3,058 mg/l		
Freshwater (in	ermittent releases)	30,58 mg/l		
Marine water		0,306 mg/l		
Freshwater sed	liment	11,36 mg/kg		
Marine sedime	nt	1,136 mg/kg		
Micro-organisms in sewage treatment plants (STP) 85 mg/l				
Soil 0,47 m				
110-82-7	cyclohexane			
Freshwater 0,207				
Freshwater (intermittent releases) 0,207				
Marine water				
Freshwater sediment 16,68 r				
Marine sediment 16,68 mg/				
Micro-organisms in sewage treatment plants (STP) 3,24 mg/l				
Soil		3,38 mg/kg		

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

Revision date: 21.07.2023 Product code: 32866 Page 7 of 13

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact: No data available

By short-term hand contact

Trade name/designation: KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: characteristic

Melting point/freezing point:

No data available
Boiling point or initial boiling point and

>35 °C

boiling range:

Flammability:

Lower explosion limits:

Upper explosion limits:

No data available

Upper explosion limits:

No data available

Flash point:

<21 °C

Auto-ignition temperature:

No data available

Decomposition temperature:

No data available

pH-Value:

No data available

Print date: 21.07.2023



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

Revision date: 21.07.2023 Product code: 32866 Page 8 of 13

Viscosity / kinematic:

Water solubility:

No data available

No data available

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

No data available Evaporation rate: No data available Solvent separation test: Solvent content: No data available Solid content: No data available Sublimation point: No data available Softening point: No data available No data available Pour point: No data available Viscosity / dynamic: No data available Flow time: No data available

Further InformationNo data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

Print date: 21.07.2023



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

Revision date: 21.07.2023 Product code: 32866 Page 9 of 13

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64-19-7	acetic acid							
	oral	LD50 mg/kg	3310	Rat	J Ind Hyg Toxicol, Vol 23, PP 78-82 (194	The sodium salt of acetic acid was admin		
	inhalation (4 h) vapour	LC50	11,4 mg/l	Rat	Study report (1980)	OECD Guideline 403		
110-82-7	cyclohexane							
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401		
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)	OECD Guideline 402		
	inhalation (4 h) vapour	LC50 mg/l	> 5540	Rat	Study report (1981)	OECD Guideline 403		

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (cyclohexane)

Organs affected: central nervous system

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

No data available



according to Regulation (EC) No 1907/2006

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

Revision date: 21.07.2023 Product code: 32866 Page 10 of 13

Other information

No data available

Further information

corrosive, Irritant

Vapours may cause drowsiness and dizziness. Dizziness, Unconsciousness, Vomiting, Headache

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
64-19-7	acetic acid							
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss	Study report (2005)	other: SOP E257	
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Skeletonema costatum	Study report (2005)	ISO 10253	
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	Study report (1990)	OECD Guideline 202	
110-82-7	cyclohexane							
	Acute fish toxicity	LC50 mg/l	4,53	96 h	Pimephales promelas	Vol. 5, Centre for Lake Superior Studies	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	9,317	72 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201	
	Acute crustacea toxicity	EC50	0,9 mg/l	48 h	Daphnia magna	Publication (1987)	OECD Guideline 202	

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-19-7	acetic acid	-0,17
110-82-7	cyclohexane	3,44

BCF

CAS No	Chemical name	BCF	Species	Source
64-19-7	acetic acid	3,16	fish	Environ. Toxicol. Ch
110-82-7	cyclohexane	167	Pimephales promelas	J. Fish. Board Can.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Print date: 21.07.2023



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

Revision date: 21.07.2023 Product code: 32866 Page 11 of 13

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

Further information

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (cyclohexane, acetic acid)

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 3+8 Classification code: FC **Special Provisions:** 274 Limited quantity: 1 I Excepted quantity: F2 Transport category: 2 Hazard No: 338 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (cyclohexane, acetic acid)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+8Classification code:FCSpecial Provisions:274Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (cyclohexane, acetic acid)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+8Special Provisions:274Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-C

Air transport (ICAO-TI/IATA-DGR)



according to Regulation (EC) No 1907/2006

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

Revision date: 21.07.2023 Product code: 32866 Page 12 of 13

14.1. UN number or ID number: UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (cyclohexane, acetic acid)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+8Special Provisions:A3Limited quantity Passenger:0.5 LPassenger LQ:Y340Excepted quantity:E2

IATA-packing instructions - Passenger:352IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:363IATA-max. quantity - Cargo:5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: cyclohexane

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 57

Information according to 2012/18/EU

E1 Hazardous to the Aquatic Environment

P₅c

(SEVESO III):

Additional information:

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions

under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 11,12.

Abbreviations and acronyms

Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard



according to Regulation (EC) No 1907/2006

Cyclohexan R/Essigsäure 99 % R-Gemisch volumetrisch 1:1 gemischt

Revision date: 21.07.2023 Product code: 32866 Page 13 of 13

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effect

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)