

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ätzlösung nach Grösbeck je 40g Kaliumpermanganat und NaOH in Wasser/l

Revision date: 10.02.2025 Product code: 32897 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Ätzlösung nach Grösbeck je 40g Kaliumpermanganat und NaOH in Wasser/l

UFI: UC3X-J23D-8006-TFFK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Skin Corr. 1B; H314 Eye Dam. 1; H318 Repr. 2; H361d Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

sodium hydroxide

potassium permanganate

Signal word: Danger



according to Regulation (EC) No 1907/2006

Ätzlösung nach Grösbeck je 40g Kaliumpermanganat und NaOH in Wasser/I

Revision date: 10.02.2025 Product code: 32897 Page 2 of 12

Pictograms:







Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.
H361d Suspected of damaging the unborn child.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing and eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name						
	EC No	Index No	REACH No				
	Classification (Regulation (EC) No 1272/2008)						
7722-64-7	potassium permanganate						
	231-760-3	025-002-00-9	01-2119480139-34				
	Ox. Sol. 2, Repr. 2, Acut Aquatic Chronic 1; H272	, STOT RE 2, Aquatic Acute 1, 00 H410					
1310-73-2	sodium hydroxide			1 - < 5 %			
	215-185-5	011-002-00-6	01-2119457892-27				
	Met. Corr. 1, Skin Corr. 1A; H290 H314						

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Conc.	Limits, M-factors and ATE				
7722-64-7	231-760-3	potassium permanganate	1 - < 5 %			
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10				
1310-73-2	215-185-5	sodium hydroxide	1 - < 5 %			
	· · · · · · · · · · · · · · · · · · ·	H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < H319: >= 0,5 - < 2				

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ätzlösung nach Grösbeck je 40g Kaliumpermanganat und NaOH in Wasser/I

Revision date: 10.02.2025 Product code: 32897 Page 3 of 12

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

4.2. Most important symptoms and effects, both acute and delayed

Skin corrosion/irritation

Dyspnoea

Cough

Circulatory collapse

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Avoid contact with skin, eyes and clothes.

Additional information

Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.



according to Regulation (EC) No 1907/2006

Ätzlösung nach Grösbeck je 40g Kaliumpermanganat und NaOH in Wasser/I

Revision date: 10.02.2025 Product code: 32897 Page 4 of 12

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not breathe vapour/aerosol.

Read label before use.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Draw up and observe skin protection programme. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Provide adequate ventilation as well as local exhaustion at critical locations.

Unsuitable container/equipment material:

Metal

Aluminium

Tin



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ätzlösung nach Grösbeck je 40g Kaliumpermanganat und NaOH in Wasser/I

Revision date: 10.02.2025 Product code: 32897 Page 5 of 12

Zinc

Hints on joint storage

national regulations

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
7722-64-7	potassium permanganate					
Worker DNEL	L, long-term	inhalation	systemic	0,218 mg/m³		
Consumer DNEL, long-term		inhalation	systemic	0,039 mg/m³		
Consumer DNEL, long-term		oral	systemic	0,011 mg/kg bw/day		
1310-73-2	sodium hydroxide					
Worker DNEL, long-term		inhalation	local	1 mg/m³		
Consumer DNEL, long-term		inhalation	local	1 mg/m³		

PNEC values

CAS No	Substance			
Environmental compartment Value				
7722-64-7	potassium permanganate			
Freshwater 0,00006 mg		0,00006 mg/l		
Freshwater (intermittent releases) 0,0006 m		0,0006 mg/l		
Micro-organisms in sewage treatment plants (STP) 1,64 mg/l				

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ätzlösung nach Grösbeck je 40g Kaliumpermanganat und NaOH in Wasser/I

Revision date: 10.02.2025 Product code: 32897 Page 6 of 12

supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: odourless
Odour threshold: No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range: Flammability:

Lower explosion limits:No data availableUpper explosion limits:No data availableFlash point:XAuto-ignition temperature:No data availableDecomposition temperature:No data availablepH-Value:alkaline

Viscosity / kinematic:

Water solubility:

No data available
very soluble

Solubility in other solvents not determined

No data available



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ätzlösung nach Grösbeck je 40g Kaliumpermanganat und NaOH in Wasser/l

Revision date: 10.02.2025 Product code: 32897 Page 7 of 12

Dissolution rate: No data available Partition coefficient n-octanol/water: not determined Dispersion stability: No data available No data available Vapour pressure: Vapour pressure: No data available Density (at 20 °C): No data available Relative density: No data available Bulk density: No data available Relative vapour density: not determined No data available Particle characteristics:

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion:

No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate: not determined Solvent separation test: No data available Solvent content: 0% 0% Solid content: Sublimation point: No data available Softening point: No data available Pour point: No data available Viscosity / dynamic: No data available Flow time: No data available

Further Information

Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Metal, Light metal (Formation of: Hydrogen)

Phenols

Combustible substance

Alkaline earth metal (Metal powder)

Acids. Nitriles

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Aluminium, Brass, Glass Tin, Zinc, Aluminium plastic

10.6. Hazardous decomposition products

No known hazardous decomposition products.



according to Regulation (EC) No 1907/2006

Ätzlösung nach Grösbeck je 40g Kaliumpermanganat und NaOH in Wasser/I

Revision date: 10.02.2025 Product code: 32897 Page 8 of 12

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
7722-64-7	potassium permanganate						
	oral	LD50 mg/kg	> 2000	Rat	Study report (2006)	EU Method B.1 tris	
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2006)	EU Method B.3	

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Risk of serious damage to eyes.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (potassium permanganate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the preparation/mixture itself.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ätzlösung nach Grösbeck je 40g Kaliumpermanganat und NaOH in Wasser/I

Revision date: 10.02.2025 Product code: 32897 Page 9 of 12

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

There are no data available on the preparation/mixture itself.

Further information

Skin corrosion/irritation

Dyspnoea

Cough

Circulatory collapse

Risk of serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
7722-64-7	potassium permanganate						
	Acute bacteria toxicity	EC50	164 mg/l		activated sludge of a predominantly domestic sewag	Study report (2006)	EU Method C.11
1310-73-2	sodium hydroxide						
	Acute crustacea toxicity	EC50 mg/l	40,4	48 h	Ceriodaphnia sp.	3,	other: acute 48-h immobilization test ac

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

not applicable

12.4. Mobility in soil

There are no data available on the preparation/mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

Further information

Do not allow to enter into surface water or drains.

Harmful effect due to pH shift.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Do not empty into drains.

Handle contaminated packages in the same way as the substance itself.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ätzlösung nach Grösbeck je 40g Kaliumpermanganat und NaOH in Wasser/I

Revision date: 10.02.2025 Product code: 32897 Page 10 of 12

Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3266

14.2. UN proper shipping name: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (sodium hydroxide)

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 8 Classification code: C5 **Special Provisions:** 274 Limited quantity: 1 I Excepted quantity: E2 Transport category: 2 Hazard No: 80 Tunnel restriction code: F

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3266

14.2. UN proper shipping name: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (sodium hydroxide)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Classification code:C5Special Provisions:274Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 3266

14.2. UN proper shipping name: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (sodium hydroxide)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:274Limited quantity:1 LExcepted quantity:E2EmS:F-A, S-BSegregation group:alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3266

14.2. UN proper shipping name: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (sodium hydroxide)

IRL - en

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:0.5 LPassenger LQ:Y840Excepted quantity:E2

IATA-packing instructions - Passenger:851IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:855IATA-max. quantity - Cargo:30 L



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ätzlösung nach Grösbeck je 40g Kaliumpermanganat und NaOH in Wasser/I

Revision date: 10.02.2025 Product code: 32897 Page 11 of 12

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: potassium permanganate

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive

2012/18/EU (SEVESO III):

E1 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,8,9,11,12.

Abbreviations and acronyms

Ox. Sol: Oxidising solid

Met. Corr: Substance or mixture corrosive to metals

Acute Tox: Acute toxicity Skin Corr: Skin corrosion Eye Dam: Eye damage Repr: Reproductive toxicity

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%



according to Regulation (EC) No 1907/2006

Ätzlösung nach Grösbeck je 40g Kaliumpermanganat und NaOH in Wasser/l

Revision date: 10.02.2025 Product code: 32897 Page 12 of 12

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Repr. 2; H361d	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

Relevant H and EUH statements (number and full text)

H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H302	Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs (brain) through prolonged or repeated exposure if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)