

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kalilauge 45% reinst

Revision date: 13.03.2024

Product code: 33009

Page 1 of 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Kalilauge 45% reinst

UFI: 5YDX-72DU-J00M-WPQT

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH  
ACD  
Street: Stempelstraße 6  
Place: D-47167 Duisburg  
Telephone: 0203/5194-0  
Telefax: 0203/5194-290  
E-mail: info@analytichem.de  
Contact person: Abteilung Produktsicherheit  
Telephone: 0203/5194-107/117  
E-mail: produktsicherheit@analytichem.de  
Internet: www.analytichem.de  
Responsible Department: Abteilung Produktsicherheit

### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

### Further Information

This product is a mixture. REACH Registration Number see section 3.

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Met. Corr. 1; H290

Acute Tox. 4; H302

Skin Corr. 1A; H314

Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

potassium hydroxide

Signal word: Danger

#### Pictograms:



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kalilauge 45% reinst**

Revision date: 13.03.2024

Product code: 33009

Page 2 of 11

**Hazard statements**

H290 May be corrosive to metals.  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.

**Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Mixtures in aqueous solution

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1310-58-3	potassium hydroxide			45 - < 50 %
	215-181-3	019-002-00-8	01-2119487136-33	
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A; H290 H302 H314			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1310-58-3	215-181-3	potassium hydroxide	45 - < 50 %
		oral: LD50 = 333 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2	

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

First aider: Pay attention to self-protection!

**After inhalation**

Provide fresh air.  
Call a physician immediately.

**After contact with skin**

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.  
Call a physician immediately.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kalilauge 45% reinst

Revision date: 13.03.2024

Product code: 33009

Page 3 of 11

#### **After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
Protect uninjured eye.

#### **After ingestion**

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Skin corrosion/irritation  
Dyspnoea  
Cough  
Circulatory collapse  
Vomiting  
Abdominal pain  
Corneal opacity.  
Has degreasing effect on the skin.  
Risk of serious damage to eyes.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

No data available

## SECTION 5: Firefighting measures

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

##### **Unsuitable extinguishing media**

no restriction

#### **5.2. Special hazards arising from the substance or mixture**

Non-flammable.

#### **5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing.  
Avoid contact with skin, eyes and clothes.

#### **Additional information**

Suppress gases/vapours/mists with water spray jet.  
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Corrosive to metals.

##### **For non-emergency personnel**

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures  
Do not breathe dust/fume/gas/mist/vapours/spray.

##### **For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kalilauge 45% reinst

Revision date: 13.03.2024

Product code: 33009

Page 4 of 11

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

##### **Other information**

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol.

##### **Advice on protection against fire and explosion**

Usual measures for fire prevention.

##### **Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

##### **Further information on handling**

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Corrosive to metals.

Provide adequate ventilation as well as local exhaustion at critical locations.

Unsuitable container/equipment material: Metal, Aluminium, Tin, Zinc

##### **Further information on storage conditions**

Store in a dry place.

Keep container tightly closed.

storage temperature +5°C - +30°C

#### **7.3. Specific end use(s)**

Laboratory chemicals

## **SECTION 8: Exposure controls/personal protection**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kalilauge 45% reinst**

Revision date: 13.03.2024

Product code: 33009

Page 5 of 11

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
1310-58-3	potassium hydroxide			
Worker DNEL, long-term		inhalation	local	1 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	1 mg/m <sup>3</sup>

**8.2. Exposure controls**

**Appropriate engineering controls**

- Do not breathe vapour/aerosol.
- If handled uncovered, arrangements with local exhaust ventilation have to be used.
- Technical measures and the application of suitable work processes have priority over personal protection equipment.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Suitable eye protection: goggles.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

- Trade name/designation: KCL 741 Dermatril® L
- Recommended material: NBR (Nitrile rubber) 0,11 mm
- Wearing time with permanent contact: > 480 min

By short-term hand contact

- Trade name/designation: KCL 741 Dermatril® L
- Recommended material: NBR (Nitrile rubber) 0,11 mm
- Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

Wear suitable protective clothing.

**Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kalilauge 45% reinst**

Revision date: 13.03.2024

Product code: 33009

Page 6 of 11

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour:	odourless	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		X
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		>13,5
Viscosity / kinematic:		No data available
Water solubility:		Soluble in: Water
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		1,468 g/cm <sup>3</sup>
Bulk density:		No data available
Relative vapour density:		not determined

**9.2. Other information**

**Information with regard to physical hazard classes**

Explosive properties		
No data available		
Sustaining combustion:		No data available
Self-ignition temperature		
Solid:		not applicable
Gas:		not applicable
Oxidizing properties		
Not oxidising.		

**Other safety characteristics**

Evaporation rate:		not determined
Solvent separation test:		No data available
Solvent content:		No data available
Solid content:		not determined
Sublimation point:		No data available
Softening point:		No data available
Pour point:		No data available
No data available:		
Viscosity / dynamic:		No data available
Flow time:		No data available

**Further Information**

Corrosive to metals.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kalilauge 45% reinst**

Revision date: 13.03.2024

Product code: 33009

Page 7 of 11

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Corrosive to metals.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Acid, White/yellow phosphor, Hydrogen halide

Alkaline earth metal, Light metal, Metal

The product develops hydrogen in an aqueous solution in contact with metals.

**10.4. Conditions to avoid**

No data available

**10.5. Incompatible materials**

Metal

Glass

Keep away from: Metal.

The product develops hydrogen in an aqueous solution in contact with metals.

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Harmful if swallowed.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Pulmonary oedema

**ATEmix calculated**

ATE (oral) 666,0 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1310-58-3	potassium hydroxide				
	oral	LD50 333 mg/kg	Rat	Fund. Appl. Toxicol., 8, 97-100 (1987)	OECD Guideline 425

**Irritation and corrosivity**

Causes severe skin burns and eye damage.

Causes serious eye damage.

Has degreasing effect on the skin.

Corneal opacity.

Risk of serious damage to eyes.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kalilauge 45% reinst

Revision date: 13.03.2024

Product code: 33009

Page 8 of 11

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

No data available

#### **Specific effects in experiment on an animal**

No data available

#### **Additional information on tests**

No data available

#### **Practical experience**

No data available

### **11.2. Information on other hazards**

#### **Other information**

No data available

#### **Further information**

Skin corrosion/irritation

Dyspnoea

Cough

Circulatory collapse

Vomiting

Abdominal pain

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

Based on available data, the classification criteria are not met.

### **12.2. Persistence and degradability**

The methods for determining the biological degradability are not applicable to inorganic substances.

### **12.3. Bioaccumulative potential**

No information available.

### **12.4. Mobility in soil**

No information available.

### **12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### **12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### **12.7. Other adverse effects**

No information available.

#### **Further information**

Do not allow to enter into surface water or drains.

Discharge into the environment must be avoided.

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

#### **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Dispose of waste according to applicable legislation.

Do not allow to enter into surface water or drains.



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kalilauge 45% reinst**

Revision date: 13.03.2024

Product code: 33009

Page 9 of 11

**Contaminated packaging**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1814
<b>14.2. UN proper shipping name:</b>	POTASSIUM HYDROXIDE SOLUTION
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Classification code:	C5
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1814
<b>14.2. UN proper shipping name:</b>	POTASSIUM HYDROXIDE SOLUTION
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Classification code:	C5
Limited quantity:	1 L
Excepted quantity:	E2

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 1814
<b>14.2. UN proper shipping name:</b>	POTASSIUM HYDROXIDE SOLUTION
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 1814
<b>14.2. UN proper shipping name:</b>	POTASSIUM HYDROXIDE SOLUTION
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y840
Excepted quantity:	E2
IATA-packing instructions - Passenger:	851
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:	No
----------------------------	----

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kalilauge 45% reinst**

Revision date: 13.03.2024

Product code: 33009

Page 10 of 11

**14.6. Special precautions for user**

Warning: strongly corrosive.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive 2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 1,9,12.

**Abbreviations and acronyms**

Met. Corr: Substance or mixture corrosive to metals

Acute Tox: Acute toxicity

Skin Corr: Skin corrosion

Eye Dam: Eye damage

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Acute Tox. 4; H302	Calculation method
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method

**Relevant H and EUH statements (number and full text)**

H290 May be corrosive to metals.  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H318 Causes serious eye damage.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### **Kalilauge 45% reinst**

Revision date: 13.03.2024

Product code: 33009

Page 11 of 11

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*