

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone	For Hazardous Materials [or Danger	ous Goods] Incidents Spill, Leak, Fire,
number:	Exposure, or Accident Call CHEMTF	REC Day or Night Within USA and Canada:
	1-800-424-9300 Outside USA and C	Canada: +1 703-741-5970 (collect calls
	accepted)	

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Acute Tox. 4; H332 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Carc. 1A; H350 STOT RE 2; H373 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

nitric acid arsenic acid and it salts with the exception of those specified elsewhere in this Annex nickel dinitrate cobalt dinitrate

Signal word: Danger



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Pictograms:

Product code: 33357

Page 2 of 17



Hazard statements

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

······	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH071	Corrosive to the respiratory tract.
	Restricted to professional users.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution



Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 3 of 17

Relevant ingredients

CAS No	Chemical name			
	EC No	Index No	REACH No	
	Classification (Regulatio	n (EC) No 1272/2008)	·	
7697-37-2	nitric acid			10 - < 15 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, EUH071	Acute Tox. 3, Skin Corr. 1A, Eye Dar	n. 1; H272 H290 H331 H314 H318	
10043-35-3	boric acid			< 1 %
	233-139-2	005-007-00-2	01-2119486683-25	
	Repr. 1B; H360FD		·	
10031-43-3	Copper(II) nitrate trihydr	ate		< 1 %
			01-2119969290-34	
	Ox. Sol. 2, Acute Tox. 4 H315 H319 H400 H410	Skin Irrit. 2, Eye Irrit. 2, Aquatic Acu	te 1, Aquatic Chronic 1; H272 H302	
-	arsenic acid and it salts	with the exception of those specified	elsewhere in this Annex	< 1 %
	-	033-005-00-1		
	Carc. 1A, Acute Tox. 3, H410	Acute Tox. 3, Aquatic Acute 1, Aquat	ic Chronic 1; H350 H331 H301 H400	
13138-45-9	nickel dinitrate			< 1 %
	236-068-5	028-012-00-1	01-2119492333-38	
	Resp. Sens. 1, Skin Ser	ta. 2, Repr. 1B, Acute Tox. 4, Acute s. 1, STOT RE 1, Aquatic Acute 1, A 5 H318 H334 H317 H372 H400 H410	quatic Chronic 1; H272 H350i H341	
10141-05-6	cobalt dinitrate			< 0.1 %
	233-402-1	027-009-00-2		
	Carc. 1B, Muta. 2, Repr. H350i H341 H360F H33	1B, Resp. Sens. 1, Skin Sens. 1, Ao 4 H317 H400 H410	uatic Acute 1, Aquatic Chronic 1;	
10325-94-7	cadmium nitrate; cadmiu	im dinitrate		< 0.1 %
	233-710-6	048-014-00-6		
	Carc. 1B, Muta. 1B, Repr. 1B, Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H350 H340 H360 H332 H312 H302 H372 H400 H410			

Full text of H and EUH statements: see section 16.



Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 4 of 17

Specific Cor	nc. Limits, M-fac	ctors and ATE	
CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
7697-37-2	231-714-2	nitric acid	10 - < 15 %
		E 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 orr. 1B; H314: >= 5 - < 20	
10043-35-3	233-139-2	boric acid	< 1 %
	inhalation: LC 3450 mg/kg	50 = > 2,12 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 =	
10031-43-3		Copper(II) nitrate trihydrate	< 1 %
	oral: ATE = 50	0 mg/kg	
-	-	arsenic acid and it salts with the exception of those specified elsewhere in this Annex	< 1 %
	inhalation: ATI mg/kg	E = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: ATE = 100	
13138-45-9	236-068-5	nickel dinitrate	< 1 %
	361,9 mg/kg 5 H372: >= 1 - 10 Aquatic Acute	E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = Skin Irrit. 2; H315: >= 20 - 100 Skin Sens. 1; H317: >= 0,01 - 100 STOT RE 1; 00 STOT RE 2; H373: >= 0,1 - < 1 1; H400: M=1 c 1; H410: M=1	
10141-05-6	233-402-1	cobalt dinitrate	< 0.1 %
	Aquatic Acute	Di: >= 0,01 - 100 1; H400: M=10 c 1; H410: M=10	
10325-94-7	233-710-6	cadmium nitrate; cadmium dinitrate	< 0.1 %
		E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = ral: ATE = 500 mg/kg_Carc. 1B; H350: >= 0,01 - 100	

Further Information

No data available

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk. Call a physician immediately.



Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 5 of 17

4.2. Most important symptoms and effects, both acute and delayed

Causes burns. Irritant Cough Dyspnoea Vomiting Methaemoglobinaemia Risk of serious damage to eyes. Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids Hazardous combustion products In case of fire may be liberated: Nitrogen oxides (NOx) Metal oxide smoke, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes. Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Consult an expert Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up



Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 6 of 17

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Use personal protection equipment. Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Do not breathe vapour/aerosol. Use extractor hood (laboratory).

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Corrosive to metals. Unsuitable container/equipment material: Metal The product develops hydrogen in an aqueous solution in contact with metals.

Hints on joint storage

national regulations

Further information on storage conditions

Keep container tightly closed.

Store in a place accessible by authorized persons only.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 7 of 17

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
10043-35-3	Borate compounds inorganic: boric acid	-	2		TWA (8 h)	
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
10043-35-3	boric acid			
Worker DNE	L, long-term	inhalation	systemic	8,3 mg/m³
Worker DNE	L, long-term	dermal	systemic	392 mg/kg bw/day
Consumer D	NEL, long-term	inhalation	systemic	4,15 mg/m³
Consumer D	NEL, long-term	dermal	systemic	196 mg/kg bw/day
Consumer D	NEL, long-term	oral	systemic	0,98 mg/kg bw/day
Consumer D	NEL, acute	oral	systemic	0,98 mg/kg bw/day
13138-45-9	nickel dinitrate			
Consumer D	NEL, acute	oral	systemic	0,012 mg/kg bw/day
Consumer D	NEL, long-term	oral	systemic	0,02 mg/kg bw/day
Worker DNE	L, acute	inhalation	systemic	104 mg/m ³
Worker DNE	L, acute	inhalation	local	1,6 mg/m³
Consumer D	NEL, acute	inhalation	systemic	8,8 mg/m³
Consumer D	NEL, acute	inhalation	local	0,1 mg/m³



Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 8 of 17

PNEC values

CAS No	Substance	
Environmenta	al compartment	Value
10043-35-3	boric acid	
Freshwater		2,9 mg/l
Freshwater (i	ntermittent releases)	13,7 mg/l
Marine water		2,9 mg/l
Micro-organis	sms in sewage treatment plants (STP)	10 mg/l
Soil		5,7 mg/kg
10031-43-3	Copper(II) nitrate trihydrate	
Freshwater		0,0078 mg/l
Marine water		0,0052 mg/l
Freshwater se	ediment	87 mg/kg
Marine sedim	nent	676 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	0,23 mg/l
Soil		65 mg/kg
13138-45-9	nickel dinitrate	
Freshwater		0,0071 mg/l
Freshwater (i	ntermittent releases)	0 mg/l
Marine water		0,0086 mg/l
Freshwater sediment		109 mg/kg
Marine sediment		109 mg/kg
Secondary poisoning		0,12 mg/kg
Micro-organisms in sewage treatment plants (STP) 0,33 r		
Soil		29,9 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles Wear eye/face protection.

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11mm Wearing time with occasional contact (splashes): > 480 min



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 9 of 17

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	clear	
Odour:	like: Nitric acid	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and		No data available
boiling range:		
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		acidic
Viscosity / kinematic:		No data available
Water solubility:		completely miscible
Solubility in other solvents		
No data available		
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available
9.2. Other information		
Information with regard to physical ha	azard classes	
Explosive properties		
No data available		
Sustaining combustion:		No data available
Self-ignition temperature		
Solid:		No data available
Gas:		No data available



Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024	Product code: 33357	Page 10 of 17
Oxidizing properties		
Oxidizing		
Other safety characteristics		
Evaporation rate:	No data available	
Solvent separation test:	No data available	
Solvent content:	0	
Solid content:	0	
Sublimation point:	No data available	
Softening point:	No data available	
Pour point:	No data available	
No data available:		
Viscosity / dynamic:	No data available	
Flow time:	No data available	
Further Information		

Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals. Oxidising agent

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

The product develops hydrogen in an aqueous solution in contact with metals. Amines, Ammonia, Alcohols, Alkali metals, Hydrogen peroxide Copper, Combustible solids, Solvent, Alkaline earth metal, mercury (Hg).

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Cellulose

Metal The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Harmful if inhaled.



Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 11 of 17

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
7697-37-2	nitric acid			•		•
	inhalation vapour	ATE 2,65	i mg/l			
10043-35-3	boric acid					
	oral	LD50 mg/kg	3450	Rat	Toxicology and Applied Pharmacology 23:	other: No data
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)	other: FIFRA
	inhalation (4 h) dust/mist	LC50 mg/l	> 2,12	Rat	Study report (1997)	OECD Guideline 403
10031-43-3	Copper(II) nitrate trihyo	Irate				
	oral	ATE mg/kg	500			
-	arsenic acid and it salts with the exception of those specified elsewhere in this Annex					
	oral	ATE mg/kg	100			
	inhalation vapour	ATE	3 mg/l			
	inhalation dust/mist	ATE	0,5 mg/l			
13138-45-9	nickel dinitrate					
	oral	LD50 mg/kg	361,9	Rat	Regul Toxicol and Pharmacol (doi.org/10.	OECD Guideline 425
	inhalation vapour	ATE	11 mg/l			
	inhalation dust/mist	ATE	1,5 mg/l			
10325-94-7	cadmium nitrate; cadm	ium dinitrate				
	oral	ATE mg/kg	500			
	dermal	ATE mg/kg	1100			
	inhalation vapour	ATE	11 mg/l			
	inhalation dust/mist	ATE	1,5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Corrosive to the respiratory tract.

Following ingestion Gastric perforation

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Irritating to respiratory system.

Pulmonary oedema

see also Section 4

Sensitising effects

May cause an allergic skin reaction. (nickel dinitrate; cobalt dinitrate)

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer. (arsenic acid and it salts with the exception of those specified elsewhere in this Annex; nickel dinitrate; cobalt dinitrate; cadmium nitrate; cadmium dinitrate) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 12 of 17

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (nickel dinitrate)

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.



Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 13 of 17

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
7697-37-2	nitric acid						
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 mg/l()	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209
10043-35-3	boric acid						
	Acute fish toxicity	LC50 mg/l	79,7	96 h	Pimephales promelas	Study report (2010)	other: ASTM E729-95 Standard Guide for C
	Acute algae toxicity	ErC50	66 mg/l	72 h	Phaeodactylum tricornutum	Study report (2011)	ISO 10253
	Acute crustacea toxicity	EC50	109 mg/l	48 h	Ceriodaphnia dubia	Study report (2010)	other: ASTM E729-95 Standard Guide for C
	Fish toxicity	NOEC mg/l	11,2	32 d	Pimephales promelas	Study report (2010)	other: ASTM E1241-05 Standard Guide for
	Algae toxicity	NOEC mg/l	17,5	3 d	Pseudokirchneriella subcapitata	Study report (2000)	OECD Guideline 201
	Crustacea toxicity	NOEC mg/l	25,9	42 d	other aquatic crustacea: Hyalella azteca	Study report (2010)	other: US EPA 2000 Methods for assessing
	Acute bacteria toxicity	EC50 mg/l()	> 10000	3 h	activated sludge of a predominantly domestic sewag	Study report (2001)	OECD Guideline 209
10031-43-3	Copper(II) nitrate trihydra	te					
	Acute fish toxicity	LC50 mg/l	0,193	96 h	Pimephales promelas	Study report (1996)	measurements were conducted by standard
	Acute algae toxicity	ErC50 mg/l	0,152	72 h	Pseudokirchneriella subcapitata	Publication (2005)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,007	48 h	Daphnia magna	Study report (1978)	- Test were conducted on Daphnia magna t
	Fish toxicity	NOEC mg/l	0,123	12 d	Atherinops affinis	Mar. Environ. Res. 31: 17-35 (1991)	Three tests are reported, designed to de
	Algae toxicity	NOEC mg/l	0,0102	19 d	other aquatic plant: giant kelp Macrocystis pyrife	Mar. Ecol. Prog. Ser. 68: 147 - 156 (199	Tests were conducted to determine the ef
	Crustacea toxicity	NOEC mg/l	0,033	14 d	Penaeus mergulensis and Penaeus monodon	Bull. Environ. Contain. Toxicol. (1995)	The effects of dissolved copper on the g
13138-45-9	nickel dinitrate						



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 14 of 17

Acute fish toxic	city LC50 mg/l	15,3	96 h	Oncorhynchus mykiss	Aquatic Toxicology 63 (2003) 65-82 (2003	other: not reported
Acute algae to	xicity ErC50 mg/l	0,237		Ankistrodesmus falcatus	Publication (2009)	OECD Guideline 201
Acute crustace	ea toxicity EC50 mg/l	0,2663	48 h	Ceriodaphnia dubia	Study report (2004)	other: American society of testing and m
Fish toxicity	NOEC mg/l	0,057	32 d	Pimephales promelas	Water Resources Research Institute. Kent	other: ASTM 1980, E-729
Algae toxicity	NOEC	0,6 mg/l	14 d	Anabaena cylindrica	Environ. Pollut. (Series A). 25(4):241-2	other: not reported
Crustacea toxi	city NOEC mg/l	0,04	42 d	Daphnia magna	Wat. Res. 24(7):845-852 (1990)	Chronic exposure to sublethal concentrat
Acute bacteria	toxicity EC50)	33 mg/l (0,5 h	Activated sludge	Journal of Hazardous Materials. B139:332	ISO 8192

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
10043-35-3	boric acid	-1,09

BCF

CAS No	Chemical name	BCF	Species	Source
10043-35-3	boric acid	0,558	Oncorhynchus nerka	Water Research Vol.
10031-43-3	Copper(II) nitrate trihydrate	0,02 - 20	Crangon crangon	Symp. Biologica. Hun
13138-45-9	nickel dinitrate	23	Spirodela polyrhiza	Ecotoxicology and en

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods



Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 15 of 17

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

Land transport (ADR/RID)		
14.1. UN number or ID number:	UN 2031	
14.2. UN proper shipping name:	NITRIC ACID	
14.3. Transport hazard class(es):	8	
14.4. Packing group:	II	
Hazard label:	8	
Classification code:	C1	
Limited quantity:	1 L	
Excepted quantity:	E2	
Transport category:	2	
Hazard No:	80	
Tunnel restriction code:	E	
Inland waterways transport (ADN)		
14.1. UN number or ID number:	UN 2031	
14.2. UN proper shipping name:	NITRIC ACID	
14.3. Transport hazard class(es):	8	
14.4. Packing group:	11	
Hazard label:	8	
Classification code:	C1	
Limited quantity:	1 L	
Excepted quantity:	E2	
Marine transport (IMDG)		
<u>14.1. UN number or ID number:</u>	UN 2031	
14.2. UN proper shipping name:	NITRIC ACID	
	8	
14.3. Transport hazard class(es):	8	
14.4. Packing group:		
Hazard label:	8	
Special Provisions:	-	
Limited quantity:	1 L	
Excepted quantity:	E2	
EmS:	F-A, S-B	
Air transport (ICAO-TI/IATA-DGR)		
14.1. UN number or ID number:	UN 2031	
14.2. UN proper shipping name:	NITRIC ACID	
14.3. Transport hazard class(es):	8	
14.4. Packing group:	II	
Hazard label:	8	
Special Provisions:	A212	
Limited quantity Passenger:	Forbidden	
Passenger LQ:	Forbidden	
Excepted quantity:	E0	
IATA-packing instructions - Passenger:		Forbidden



Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l			
Revision date: 23.05.2024	Product code: 33357	Page 16 of 17	
IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	Forbidden 855 30 L		
14.5. Environmental hazards			
ENVIRONMENTALLY HAZARDOUS:	No		
SECTION 15: Regulatory information			
15.1. Safety, health and environmental regu	lations/legislation specific for the substance or mixture		
EU regulatory information			
Authorisations (REACH, annex XIV):			
arsenic acid and it salts with the excep	tion of those specified elsewhere in this Annex		
Substances of very high concern, SVHC (REACH, article 59): boric acid; cobalt dinitrate; cadmium nitrate; cadmium dinitrate Restrictions on use (REACH, annex XVII): Entry 3, Entry 23, Entry 27, Entry 28, Entry 30, Entry 75 Marketing and use of explosives precursors (Regulation (EU) 2019/1148): Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.			
National regulatory information			
Employment restrictions: Water hazard class (D):	Observe restrictions to employment for juveniles according to the 'juve work protection guideline' (94/33/EC). Observe employment restriction under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age. 3 - highly hazardous to water		

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,5,7,9,11,12,13,14,15.

Abbreviations and acronyms

Ox. Liq: Oxidising liquid Ox. Sol: Oxidising solid Met. Corr: Substance or mixture corrosive to metals Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation Resp. Sens: Respiratory sensitisation Skin Sens: Skin sensitisation Muta: Germ cell mutagenicity Carc: Carcinogenicity Repr: Reproductive toxicity STOT RE: Specific target organ toxicity - repeated exposure Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision date: 23.05.2024

Product code: 33357

Page 17 of 17

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure	
Met. Corr. 1; H290	On basis of test data	
Acute Tox. 4; H332	Calculation method	
Skin Corr. 1B; H314	Calculation method	
Eye Dam. 1; H318	Calculation method	
Skin Sens. 1; H317	Calculation method	
Carc. 1A; H350	Calculation method	
STOT RE 2; H373	Calculation method	
Aquatic Chronic 3; H412	Calculation method	

Relevant H and EUH statements (number and full text)

e	evant H and EUH stat	ements (number and full text)
	H272	May intensify fire; oxidiser.
	H290	May be corrosive to metals.
	H301	Toxic if swallowed.
	H302	Harmful if swallowed.
	H312	Harmful in contact with skin.
	H314	Causes severe skin burns and eye damage.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H318	Causes serious eye damage.
	H319	Causes serious eye irritation.
	H331	Toxic if inhaled.
	H332	Harmful if inhaled.
	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	H340	May cause genetic defects.
	H341	Suspected of causing genetic defects.
	H350	May cause cancer.
	H350i	May cause cancer by inhalation.
	H360	May damage fertility or the unborn child.
	H360D	May damage the unborn child.
	H360F	May damage fertility.
	H360FD	May damage fertility. May damage the unborn child.
	H372	Causes damage to organs through prolonged or repeated exposure.
	H373	May cause damage to organs through prolonged or repeated exposure.
	H400	Very toxic to aquatic life.
	H410	Very toxic to aquatic life with long lasting effects.
	H412	Harmful to aquatic life with long lasting effects.
	EUH071	Corrosive to the respiratory tract.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)