

according to Regulation (EC) No 1907/2006

Ammonia solution 3 % NH3 for analysis suitable for determination of silicon dioxide

Revision date: 25.11.2024 Product code: 33609 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Ammonia solution 3 % NH3 for analysis suitable for determination of silicon dioxide

UFI: 9G20-W3J1-A00J-SHCH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Ammonia

Signal word: Danger

Pictograms:







according to Regulation (EC) No 1907/2006

Ammonia solution 3 % NH3 for analysis suitable for determination of silicon dioxide

Revision date: 25.11.2024 Product code: 33609 Page 2 of 11

Hazard statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves and eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

| CAS No | Chemical name | Chemical name | | | |
|-----------|---|-------------------------|------------------|--|--|
| | EC No | EC No Index No REACH No | | | |
| | Classification (Regulation (EC) No 1272/2008) | | | | |
| 1336-21-6 | Ammonia | Ammonia | | | |
| | 215-647-6 | 007-001-01-2 | 01-2119488876-14 | | |
| | Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 2; H314 H400 H411 | | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity | |
|-----------|--|---------------------------|-----------|--|
| | Specific Conc. I | Limits, M-factors and ATE | | |
| 1336-21-6 | 215-647-6 | Ammonia | 1 - < 5 % | |
| | inhalation: LC50 = 4230 mg/l (vapours); oral: LD50 = 350 mg/kg STOT SE 3; H335: >= 5 - 100 Aquatic Acute 1; H400: M=10 | | | |

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

In case of skin irritation, consult a physician.



according to Regulation (EC) No 1907/2006

Ammonia solution 3 % NH3 for analysis suitable for determination of silicon dioxide

Revision date: 25.11.2024 Product code: 33609 Page 3 of 11

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting.

Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

Cough

Dyspnoea

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

Print date: 25.11.2024



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ammonia solution 3 % NH3 for analysis suitable for determination of silicon dioxide

Revision date: 25.11.2024 Product code: 33609 Page 4 of 11

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use.

Handle and open container with care.

When using do not eat, drink, smoke, sniff.

Use personal protection equipment.

Provide adequate ventilation.

Do not breathe vapour/aerosol.

Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

No data available

Further information on storage conditions

Keep away from heat.

Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals



according to Regulation (EC) No 1907/2006

Ammonia solution 3 % NH3 for analysis suitable for determination of silicon dioxide

Revision date: 25.11.2024 Product code: 33609 Page 5 of 11

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| CAS No | Substance | ppm | mg/m³ | fib/cm³ | Category | Origin |
|-----------|--------------------|-----|-------|---------|---------------|--------|
| 7664-41-7 | Ammonia, anhydrous | 20 | 14 | | TWA (8 h) | |
| | | 50 | 36 | | STEL (15 min) | |

DNEL/DMEL values

| CAS No | Substance | | | |
|--------------------------|---------------|----------------|----------|------------------|
| DNEL type | | Exposure route | Effect | Value |
| 1336-21-6 | Ammonia | | | |
| Worker DNEL, | long-term | inhalation | systemic | 47,6 mg/m³ |
| Worker DNEL, | acute | inhalation | systemic | 47,6 mg/m³ |
| Worker DNEL, | long-term | inhalation | local | 14 mg/m³ |
| Worker DNEL, | acute | inhalation | local | 36 mg/m³ |
| Worker DNEL, long-term | | dermal | systemic | 6,8 mg/kg bw/day |
| Worker DNEL, acute | | dermal | systemic | 6,8 mg/kg bw/day |
| Consumer DNEL, long-term | | inhalation | systemic | 23,8 mg/m³ |
| Consumer DNEL, acute | | inhalation | systemic | 23,8 mg/m³ |
| Consumer DNE | EL, long-term | inhalation | local | 2,8 mg/m³ |
| Consumer DNEL, acute | | inhalation | local | 7,2 mg/m³ |
| Consumer DNEL, long-term | | dermal | systemic | 68 mg/kg bw/day |
| Consumer DNEL, acute | | dermal | systemic | 68 mg/kg bw/day |
| Consumer DNEL, long-term | | oral | systemic | 6,8 mg/kg bw/day |
| Consumer DNEL, acute | | oral | systemic | 6,8 mg/kg bw/day |

PNEC values

| CAS No | Substance | | | |
|------------------------------------|-----------|------------|--|--|
| Environmental compartment Value | | Value | | |
| 1336-21-6 | Ammonia | | | |
| Freshwater 0,001 mg/l | | 0,001 mg/l | | |
| Freshwater (intermittent releases) | | 0,007 mg/l | | |
| Marine water | | 0,001 mg/l | | |

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four



according to Regulation (EC) No 1907/2006

Ammonia solution 3 % NH3 for analysis suitable for determination of silicon dioxide

Revision date: 25.11.2024 Product code: 33609 Page 6 of 11

control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®

Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 720 Camapren®

Recommended material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device with filter or ventilator filtering device of type: K

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: stinging

Odour threshold: No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

Flammability:

Lower explosion limits:

Upper explosion limits:

No data available
Upper explosion limits:

No data available
Flash point:

No data available
Auto-ignition temperature:

No data available
Decomposition temperature:

No data available
pH-Value (at 20 °C):

11,1



according to Regulation (EC) No 1907/2006

Ammonia solution 3 % NH3 for analysis suitable for determination of silicon dioxide

Revision date: 25.11.2024 Product code: 33609 Page 7 of 11

Viscosity / kinematic:

Water solubility:

No data available completely miscible

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

No data available

No data available

(at 20 °C)

Vapour pressure:No data availableDensity (at 20 °C):0,9832 g/cm³Bulk density:No data availableRelative vapour density:No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion: No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available

Solvent content:

Solid content:

Sublimation point:

Softening point:

No data available

Pour point:

No data available

No data available

No data available

No data available:

Viscosity / dynamic: No data available Flow time: No data available

Further Information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

Acid

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures



according to Regulation (EC) No 1907/2006

Ammonia solution 3 % NH3 for analysis suitable for determination of silicon dioxide

Revision date: 25.11.2024 Product code: 33609 Page 8 of 11

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

| CAS No | Chemical name | Chemical name | | | | | |
|-----------|-------------------------|---------------|-----------|---------|--|---|--|
| | Exposure route | Dose | | Species | Source | Method | |
| 1336-21-6 | Ammonia | | | | | | |
| | oral | LD50 mg/kg | 350 | Rat | Journal of Industrial Hygiene and Toxico | OECD Guideline 401 | |
| | inhalation (1 h) vapour | LC50 | 4230 mg/l | Mouse | Bull. Environm. Contam. Toxicol, 1982, 2 | Assessment of acute inhalation toxicity | |

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Other information

Irritant

Cough

Dyspnoea

Risk of serious damage to eyes.



according to Regulation (EC) No 1907/2006

Ammonia solution 3 % NH3 for analysis suitable for determination of silicon dioxide

Revision date: 25.11.2024 Product code: 33609 Page 9 of 11

Further information

Dermatitis

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

| CAS No | Chemical name | | | | | | |
|-----------|--------------------------|------------------|----------|-----------|---------------------------|--|--|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source | Method |
| 1336-21-6 | Ammonia | | | | | | |
| | Acute fish toxicity | LC50 3,4 mg/l | 0,75 - | 96 h | Pimephales promelas | Trans Amer Fish Soc; 112 (5). 1983. 705- | Assessment of acute toxicity in the fath |
| | Acute crustacea toxicity | EC50 | 101 mg/l | 48 h | Daphnia magna | Environ. Toxicol. Chem. 5: 443-447 (1986 | other: ASTM E729-80 |
| | Fish toxicity | NOEC | 1,2 mg/l | | Oncorhynchus gorbuscha | Fish. Bull. 78(3): 641-648 (1980) | OECD Guideline 210 |

12.2. Persistence and degradability

Discharge into the environment must be avoided.

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|-----------|---------------|---------|
| 1336-21-6 | Ammonia | -1,38 |

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".



according to Regulation (EC) No 1907/2006

Ammonia solution 3 % NH3 for analysis suitable for determination of silicon dioxide

Revision date: 25.11.2024 Product code: 33609 Page 10 of 11

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to Directive

National regulatory information

E1 Hazardous to the Aquatic Environment

2012/18/EU (SEVESO III):

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,4,7,8,9,11,12,15.



according to Regulation (EC) No 1907/2006

Ammonia solution 3 % NH3 for analysis suitable for determination of silicon dioxide

Revision date: 25.11.2024 Product code: 33609 Page 11 of 11

Abbreviations and acronyms

Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

| Classification | Classification procedure |
|-------------------------|--------------------------|
| Skin Irrit. 2; H315 | Calculation method |
| Eye Dam. 1; H318 | Calculation method |
| Aquatic Acute 1; H400 | Calculation method |
| Aquatic Chronic 3; H412 | Calculation method |

Relevant H and EUH statements (number and full text)

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation. H318 Causes serious eye damage.

H400 Causes serious eye damage.
Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)