

...

according to Regulation (EC) No 1907/2006

Kupfer(II)-chlorid-Ätzlösung in Ethanol + Salzsäure RMIC14 Reagent Etching Solution Lab ID:1.2.7.027					
Revision date: 22.04.2025	Product code: 33627		Page 1 of 14		
SECTION 1: Identification of the s	ubstance/mixture and of the company	y/undertaking			
<u>1.1. Product identifier</u> Kupfer(II)-chlorid-Ätzlösung in E	thanol + Salzsäure RMIC14 Reagent Etchi	ng Solution Lab ID:1.2.7.027			
UFI:	8140-03Y5-U00F-QNUP				
1.2. Relevant identified uses of the su	ubstance or mixture and uses advised aga	ainst			
Use of the substance/mixture Reagents and laboratory chemi Only for laboratory and analysis					
Uses advised against					
Do not use for private purposes	(household).				
1.3. Details of the supplier of the safe Company name:	e <mark>ty data sheet</mark> AnalytiChem GmbH ACD				
Street: Place:	Stempelstraße 6 D-47167 Duisburg				
Telephone:	0203/5194-0	Telefax:0203/5194-290			
E-mail: Contact person: E-mail: Internet: Responsible Department:	info@analytichem.de Abteilung Produktsicherheit produktsicherheit@analytichem.de www.analytichem.de Abteilung Produktsicherheit	Telephone:0203/5194-107/117			
<u>1.4. Emergency telephone</u> number:	For Hazardous Materials [or Dangerous 0 Exposure, or Accident Call CHEMTREC I 1-800-424-9300 Outside USA and Canad accepted)	Day or Night Within USA and Canada	1:		
Further Information					

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226 Met. Corr. 1; H290 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling Hydrochloric acid Kupfer-II-chlorid-2-hydrat

Signal word: Danger



Kupfer(II)-chlorid-Ätzlösung in Ethanol + Salzsäure RMIC14 Reagent Etching Solution Lab

Revision date: 22.04.2025

Pictograms:

ID:1.2.7.027 Product code: 33627

Page 2 of 14



Hazard statements

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

Precautionary statements

•••••••••••••••••••••••••••••••••••••••	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves and eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P403+P235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization Mixtures

Relevant ingredients

CAS No	Chemical name			
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No	1272/2008)		
64-17-5	ethanol			35 - < 40 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
7647-01-0	Hydrochloric acid			20 - < 25 %
	231-595-7	017-002-01-X	01-2119484862-27	
	Met. Corr. 1, Skin Corr. 1B, Eye Da	3 H335		
10125-13-0	Kupfer-II-chlorid-2-hydrat			1 - < 5 %
			01-2119970306-36	
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 2; H312 H302 H315 H318 H400 H411			

Full text of H and EUH statements: see section 16.



Kupfer(II)-chlorid-Ätzlösung in Ethanol + Salzsäure RMIC14 Reagent Etching Solution Lab

ID:1.2.7.027

Revision date: 22.04.2025

Product code: 33627

Page 3 of 14

Specific	Conc.	Limits,	M -factors	and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
64-17-5	200-578-6	ethanol	35 - < 40 %
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100		
7647-01-0	231-595-7	Hydrochloric acid	20 - < 25 %
		⊣314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 3; H335: >= 10 - 100	
10125-13-0		Kupfer-II-chlorid-2-hydrat	1 - < 5 %
	dermal: LD50	= > 2000 mg/kg; oral: LD50 = 584 mg/kg Aguatic Acute 1; H400: M=10	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water. Observe risk of aspiration if vomiting occurs. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant Cough Dyspnoea Dizziness

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

no restriction



Kupfer(II)-chlorid-Ätzlösung in Ethanol + Salzsäure RMIC14 Reagent Etching Solution Lab

ID:1.2.7.027

Revision date: 22.04.2025

Product code: 33627

Page 4 of 14

5.2. Special hazards arising from the substance or mixture

Combustible liquids Hazardous combustion products In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide Hydrochloric gas Metal oxide smoke, toxic Vapours are heavier than air, spread along floors and form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes. Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges. Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Consult an expert Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.



Kupfer(II)-chlorid-Ätzlösung in Ethanol + Salzsäure RMIC14 Reagent Etching Solution Lab

ID:1.2.7.027

Revision date: 22.04.2025

Product code: 33627

Page 5 of 14

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Provide adequate ventilation. Do not breathe vapour/aerosol.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Provide adequate ventilation as well as local exhaustion at critical locations.

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Unsuitable container/equipment material:

Metal.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances. TRGS 410

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Revision No: 1,02 - Replaces version: 1,01



Kupfer(II)-chlorid-Ätzlösung in Ethanol + Salzsäure RMIC14 Reagent Etching Solution Lab

Revision date: 22.04.2025

ID:1.2.7.027 Product code: 33627

Page 6 of 14

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	
7647-01-0	Hydrogen chloride	5	8		TWA (8 h)	
		10	15		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
64-17-5	ethanol					
Worker DNE	L, long-term	inhalation	systemic	950 mg/m³		
Worker DNE	L, long-term	dermal	systemic	343 mg/kg bw/day		
Consumer D	NEL, long-term	inhalation	systemic	114 mg/m³		
Consumer D	NEL, long-term	dermal	systemic	206 mg/kg bw/day		
Consumer D	NEL, long-term	oral	systemic	87 mg/kg bw/day		
7647-01-0	Hydrochloric acid					
Worker DNE	EL, long-term	inhalation	local	8 mg/m³		
Worker DNE	EL, acute	inhalation	local	15 mg/m³		
Consumer DNEL, long-term		inhalation	local	8 mg/m³		
Consumer DNEL, acute		inhalation	local	15 mg/m³		

PNEC values

CAS No	Substance	
Environmenta	al compartment	Value
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (i	intermittent releases)	2,75 mg/l
Marine water		0,79 mg/l
Freshwater s	ediment	3,6 mg/kg
Marine sedim	nent	2,9 mg/kg
Secondary poisoning 380 mg		
Micro-organis	sms in sewage treatment plants (STP)	580 mg/l
Soil		0,63 mg/kg
10125-13-0	Kupfer-II-chlorid-2-hydrat	
Freshwater		0,0078 mg/l
Marine water		0,0052 mg/l
Freshwater s	ediment	87 mg/kg
Marine sedim	676 mg/kg	
Micro-organisms in sewage treatment plants (STP) 0,23 mg/l		
Soil		65 mg/kg

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.



Kupfer(II)-chlorid-Ätzlösung in Ethanol + Salzsäure RMIC14 Reagent Etching Solution Lab

ID:1.2.7.027

Revision date: 22.04.2025

Product code: 33627

Page 7 of 14

Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact Trade name/designation: KCL 897 Butoject® Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Trade name/designation: KCL 720 Camapren® Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm Wearing time with occasional contact (splashes): > 110 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	green-yellow	
Odour:	like: Ethanol	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and		No data available
boiling range:		
Flammability:		not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available



Kupfer(II)-chlorid-Ätzlösung in Ethanol + Salzsäure RMIC14 Reagent Etching Solution Lab ID:1.2.7.027					
Revision date: 22.04.2025	Product code: 33627	Page 8 of 14			
Flash point:	<23 °C				
Auto-ignition temperature:	No data available				
Decomposition temperature:	No data available				
pH-Value:	0				
Viscosity / kinematic:	No data available				
Water solubility:	No data available				
Solubility in other solvents					
No data available					
Partition coefficient n-octanol/water:	No data available				
Vapour pressure:	No data available				
Vapour pressure:	No data available				
Density:	1,0216 g/cm ³				
Bulk density:	No data available				
Relative vapour density:	No data available				
9.2. Other information					
Information with regard to physical hazard classes					
Explosive properties					
Vapours are heavier than air, spread along floors	and form explosive mixtures with air				
Sustained combustibility:	No data available				
Self-ignition temperature					
Solid:	not applicable				
Gas:	not applicable				
Oxidizing properties					
Not oxidising.					
Other safety characteristics					
Evaporation rate:	No data available				
Solvent separation test:	No data available				
Solvent content:	No data available				
Solid content:	No data available				
Sublimation point:	No data available				
Softening point:	No data available				
Pour point:	No data available				
•	No data available				
Viscosity / dynamic:	No data available				
Flow time:	No data available				
Further Information					
No data available					
SECTION 10: Stability and reactivity					
10.1. Reactivity					

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent Alkali (lye)

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.



Kupfer(II)-chlorid-Ätzlösung in Ethanol + Salzsäure RMIC14 Reagent Etching Solution Lab

ID:1.2.7.027

Product code: 33627

Page 9 of 14

10.5. Incompatible materials

Revision date: 22.04.2025

Keep away from: Metal.

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64-17-5	ethanol					
	oral	LD50 mg/kg	10470	Rat	Study report (1976)	OECD Guideline 401
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980)	OECD Guideline 403
10125-13-0	Kupfer-II-chlorid-2-hydra	t				
	oral	LD50 mg/kg	584	Rat	Publication (1991)	The test material was administered to gr
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2003)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Hydrochloric acid)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.



Kupfer(II)-chlorid-Ätzlösung in Ethar	nol + Salzsäure RMIC14 Reagent ID:1.2.7.027	Etching Solution Lab
Revision date: 22.04.2025	Product code: 33627	Page 10 of 14
Additional information on tests There are no data available on the mixture itself.		
Practical experience There are no data available on the mixture itself.		
11.2. Information on other hazards		
Other information There are no data available on the mixture itself.		
Further information There are no data available on the mixture itself.		

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.



Kupfer(II)-chlorid-Ätzlösung in Ethanol + Salzsäure RMIC14 Reagent Etching Solution Lab ID:1.2.7.027

Revision date: 22.04.2025

Product code: 33627

Page 11 of 14

CAS No	Chemical name	ical name					
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64-17-5	ethanol						
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th
7647-01-0	Hydrochloric acid						
	Acute fish toxicity	LC50	862 mg/l	96 h	Leuciscus idus		
10125-13-0	Kupfer-II-chlorid-2-hydrat						
	Acute fish toxicity	LC50 mg/l	0,193	96 h	Pimephales promelas	Study report (1996)	measurements were conducted by standard
	Acute algae toxicity	ErC50 mg/l	0,152	72 h	Pseudokirchneriella subcapitata	Publication (2005)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,007	48 h	Daphnia magna	Study report (1978)	- Test were conducted on Daphnia magna t
	Fish toxicity	NOEC mg/l	0,123	12 d	Atherinops affinis	Mar. Environ. Res. 31: 17-35 (1991)	Three tests are reported, designed to de
	Algae toxicity	NOEC mg/l	0,0102	19 d	other aquatic plant: giant kelp Macrocystis pyrife	Mar. Ecol. Prog. Ser. 68: 147 - 156 (199	Tests were conducted to determine the ef
	Crustacea toxicity	NOEC mg/l	0,033	14 d	Penaeus mergulensis and Penaeus monodon	Bull. Environ. Contain. Toxicol. (1995)	The effects of dissolved copper on the g

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name				Log Pow
64-17-5	ethanol				-0,77
BCF	•				
CAS No	Chemical name	BCF	Species	Source	
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi	
10125-13-0	Kupfer-II-chlorid-2-hydrat	0,02 - 20	Crangon crangon	Symp. Biologica. Hun	



Kupfer(II)-chlorid-Ätzlösung in Ethanol + Salzsäure RMIC14 Reagent Etching Solution Lab

ID:1.2.7.027

Product code: 33627

Page 12 of 14

12.4. Mobility in soil

Revision date: 22.04.2025

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 2920
14.2. UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Hydrochloric acid, ethanol)
14.3. Transport hazard class(es):	8
14.4. Packing group:	ll
Hazard label:	8+3
Classification code:	CF1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	83
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 2920
14.2. UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Hydrochloric acid, ethanol)
14.3. Transport hazard class(es):	8
14.4. Packing group:	ll
Hazard label:	8+3
Classification code:	CF1
Special Provisions:	274
Limited quantity:	1L
Excepted quantity:	E2
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 2920



according to Regulation	(EC) N	0 1907/2006
according to regulation		5 1001/2000

Kunfer(II) eblerid Ötaläeung	Ethonol I Solooöuro DMICA	A Descent Etching Colution	Lah
Kupfer(II)-chlorid-Ätzlösung in Ethanol + Salzsäure RMIC14 Reagent Etching Solution Lab ID:1.2.7.027			
Revision date: 22.04.2025	Product code: 33627		Page 13 of 14
14.2. UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLI	E, N.O.S. (Hydrochloric acid, ethan	ol)
14.3. Transport hazard class(es):	8		
14.4. Packing group:	II		
Hazard label:	8+3		
Special Provisions:	274		
Limited quantity:	1L		
Excepted quantity:	E2		
EmS:	F-E, S-C		
Air transport (ICAO-TI/IATA-DGR)			
14.1. UN number or ID number:	UN 2920		
14.2. UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLI	E, N.O.S. (Hydrochloric acid, ethand	ol)
14.3. Transport hazard class(es):	8		
14.4. Packing group:	II		
Hazard label:	8+3		
Limited quantity Passenger:	0.5 L		
Passenger LQ:	Y840		
Excepted quantity:	E2		
IATA-packing instructions - Passenger:	851		
IATA-max. quantity - Passenger:	1 L		
IATA-packing instructions - Cargo:	855		
IATA-max. quantity - Cargo:	30 L		
14.5. Environmental hazards			
ENVIRONMENTALLY HAZARDOUS:	No		
14.6. Special precautions for user			
Warning: Combustible liquid. strongly c	rrosive.		
14.7. Maritime transport in bulk according to			
not applicable			
SECTION 15: Regulatory information			
15.1. Safety, health and environmental regulation	tions/legislation specific for the su	ubstance or mixture	
EU regulatory information			
Restrictions on use (REACH, annex XVII):			
Entry 3, Entry 40, Entry 75			
Information according to Directive	P5c FLAMMABLE LIQUIDS		
2012/18/EU (SEVESO III):			
National regulatory information			
Employment restrictions:	Observe restrictions to employment	for juveniles according to the 'juver	nile
	work protection guideline' (94/33/EC	C).	
Water hazard class (D):	3 - highly hazardous to water		
Skin resorption/Sensitization:	Causes allergic hypersensitivity rea	ctions.	
15.2. Chemical safety assessment			
Chemical safety assessments for substances in this mixture were not carried out.			
Chemical salety assessments for SUDST		i out.	

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,4,6,7,8,9,10,11,12,13,14,15.



Kupfer(II)-chlorid-Ätzlösung in Ethanol + Salzsäure RMIC14 Reagent Etching Solution Lab

according to Regulation (EC) No 1907/2006

ID:1.2.7.027

Revision date: 22.04.2025

Product code: 33627

Page 14 of 14

Abbreviations and acronyms Met. Corr: Substance or mixture corrosive to metals Flam. Lig: Flammable liquid Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation STOT SE: Specific target organ toxicity - single exposure Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration. 50% LD50: Lethal dose, 50% Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Met. Corr. 1; H290	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

EZZO	Fighly hammable liquid and vapour.
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Highly flommable liquid and vanour

Further Information

L775

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)