

#### Alkohol-Kalibrationslösung 200 g/l Ethanol abs. unvergällt in Wasser + 500 mg Methanol/l Revision date: 03.02.2025 Product code: 33661 Page 1 of 12 SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Alkohol-Kalibrationslösung 200 g/l Ethanol abs. unvergällt in Wasser + 500 mg Methanol/l UFI: VY60-73EP-8009-68NV 1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture Laboratory chemical Industrial uses: Uses of substances as such or in preparations at industrial sites Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Uses advised against Do not use for private purposes (household). 1.3. Details of the supplier of the safety data sheet Company name: AnalytiChem GmbH ACD Street: Stempelstraße 6 Place: D-47167 Duisburg Telephone: 0203/5194-0 Telefax: 0203/5194-290 E-mail: info@analytichem.de Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117 E-mail: produktsicherheit@analytichem.de Internet: www.analytichem.de Abteilung Produktsicherheit Responsible Department: 1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: number: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

# SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

# Regulation (EC) No 1272/2008

Flam. Liq. 3; H226

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

Pictograms:

## Regulation (EC) No 1272/2008

Signal word:





Hazard statements

H226

Flammable liquid and vapour.

#### Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



## Alkohol-Kalibrationslösung 200 g/l Ethanol abs. unvergällt in Wasser + 500 mg Methanol/l

Revision date: 03.02.2025	Product code: 33661	Page 2 of 12
P280	Wear protective gloves and eye protection/face protection.	
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.	
P403+P235	Store in a well-ventilated place. Keep cool.	

#### 2.3. Other hazards

No information available.

### **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

# Chemical characterization

Mixtures in aqueous solution

### **Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No Index No		Index No REACH No	
	Classification (Regulation	n (EC) No 1272/2008)		
64-17-5	ethanol			20 - < 25 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2;	H225 H319		

Full text of H and EUH statements: see section 16.

Specific Conc	:. Limits, M-fac	tors and ATE	
CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	imits, M-factors and ATE	
64-17-5	200-578-6	ethanol	20 - < 25 %
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100		

### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

General information

No data available

#### After inhalation

Provide fresh air.

### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

### After ingestion

Rinse mouth immediately and drink plenty of water. Call a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Irritant

#### Dizziness



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Alkohol-Kalibrationslösung 200 g/l Ethanol abs. unvergällt in Wasser + 500 mg Methanol/l

Revision date: 03.02.2025

Product code: 33661

Page 3 of 12

The product causes narcotic-like effects. Inebriation Vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

### Unsuitable extinguishing media

### no restriction

### 5.2. Special hazards arising from the substance or mixture

#### Combustible liquid.

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

### 5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

Use water spray jet to protect personnel and to cool endangered containers.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Suppress gases/vapours/mists with water spray jet. Move undamaged containers from immediate hazard area if it can be done safely.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

# For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Consult an expert Do not breathe dust/fume/gas/mist/vapours/spray.

### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

### Danger of explosion

### 6.3. Methods and material for containment and cleaning up



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Alkohol-Kalibrationslösung 200 g/l Ethanol abs. unvergällt in Wasser + 500 mg Methanol/l

Revision date: 03.02.2025

Product code: 33661

Page 4 of 12

## For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

### Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Do not breathe vapour/aerosol. Provide adequate ventilation.

### Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

#### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances. national regulations

### Further information on storage conditions

Vapours may form explosive mixtures with air.

### 7.3. Specific end use(s)

Laboratory use Laboratory chemical



# Alkohol-Kalibrationslösung 200 g/l Ethanol abs. unvergällt in Wasser + 500 mg Methanol/l

Revision date: 03.02.2025

Product code: 33661

Page 5 of 12

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### **Occupational exposure limits**

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	

### DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64-17-5	ethanol			
Worker DNEL,	long-term	inhalation	systemic	950 mg/m³
Worker DNEL,	long-term	dermal	systemic	343 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	114 mg/m <sup>3</sup>
Consumer DN	EL, long-term	dermal	systemic	206 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	87 mg/kg bw/day

### **PNEC** values

CAS No	Substance		
Environmen	tal compartment	Value	
64-17-5	ethanol		
Freshwater		0,96 mg/l	
Freshwater (intermittent releases)		2,75 mg/l	
Marine water		0,79 mg/l	
Freshwater	sediment	3,6 mg/kg	
Marine sedi	nent	2,9 mg/kg	
Secondary p	poisoning	380 mg/kg	
Micro-organ	isms in sewage treatment plants (STP)	580 mg/l	
Soil		0,63 mg/kg	

### 8.2. Exposure controls

### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

# Individual protection measures, such as personal protective equipment

### Eye/face protection

Suitable eye protection: goggles.

## Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

#### By long-term hand contact

Trade name/designation: KCL 897 Butoject® Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with permanent contact: > 480 min

#### By short-term hand contact



## Alkohol-Kalibrationslösung 200 g/l Ethanol abs. unvergällt in Wasser + 500 mg Methanol/l

Revision date: 03.02.2025

Product code: 33661

Page 6 of 12

Trade name/designation: KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

### **Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

### **Environmental exposure controls**

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

9.1. Information on pasic physical and the	mical properties	
Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Ethanol	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and		No data available
boiling range:		
Flammability:		not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		~34 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		7
Viscosity / kinematic:		No data available
Water solubility:		easily soluble
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density (at 20 °C):		0,9676 g/cm <sup>3</sup>
Bulk density:		No data available
Relative vapour density:		not determined
9.2. Other information		
Information with regard to physical haz	ard classes	
Explosive properties		
Vapours can form explosive mixtures	with air.	
Sustaining combustion:		No data available
Self-ignition temperature		



#### Alkohol-Kalibrationslösung 200 g/l Ethanol abs. unvergällt in Wasser + 500 mg Methanol/l Revision date: 03.02.2025 Product code: 33661 Page 7 of 12 Solid not applicable Gas: not applicable Oxidizing properties Not oxidising. Other safety characteristics not determined Evaporation rate: Solvent separation test: No data available Solvent content: No data available Solid content: 0 Sublimation point: No data available Softening point: No data available No data available Pour point: No data available: Viscosity / dynamic: No data available Flow time: No data available **Further Information**

No data available

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Vapours can form explosive mixtures with air.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Oxidising agent

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

### 10.5. Incompatible materials

Rubber articles Plastic articles

# 10.6. Hazardous decomposition products

### Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

### Further information

No data available

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

# Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.

### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



## Alkohol-Kalibrationslösung 200 g/l Ethanol abs. unvergällt in Wasser + 500 mg Methanol/l

Revision date: 03.02.2025

Product code: 33661

Page 8 of 12

CAS No	Chemical name					
CASINO	Chemical hame				-	i
	Exposure route	Dose		Species	Source	Method
64-17-5	ethanol					
	oral	LD50 mg/kg	10470	Rat	Study report (1976)	OECD Guideline 401
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980)	OECD Guideline 403

### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Specific effects in experiment on an animal

There are no data available on the mixture itself.

### Additional information on tests

There are no data available on the mixture itself.

### Practical experience

There are no data available on the mixture itself.

## 11.2. Information on other hazards

### Other information

Irritant Dizziness The product causes narcotic-like effects. Inebriation Vomiting

### Further information

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Based on available data, the classification criteria are not met.



## Alkohol-Kalibrationslösung 200 g/l Ethanol abs. unvergällt in Wasser + 500 mg Methanol/l

Revision date: 03.02.2025

Product code: 33661

Page 9 of 12

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
64-17-5	ethanol						
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

# Partition coefficient n-octanol/water

CAS No	Chemical name				Log Pow
64-17-5	ethanol				-0,77
BCF					
CAS No	Chemical name	BCF	Species	Source	

1

Cyprinus carpio

12 4	Mobility	in soil
12.4.		111 3011

64-17-5

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

ethanol

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

Do not empty into drains.

### **Further information**

Avoid release to the environment.

### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

### **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

#### Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific

Comparative Biochemi



# Alkohol-Kalibrationslösung 200 g/l Ethanol abs. unvergällt in Wasser + 500 mg Methanol/l

Revision date: 03.02.2025

. \_

Product code: 33661

Page 10 of 12

to the industry and process.

Handle contaminated packages in the same way as the substance itself.

# **SECTION 14: Transport information** . . . \_ \_ .\_ .\_ .

Land transport (ADR/RID)	
14.1. UN number or ID number:	UN 1170
14.2. UN proper shipping name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Special Provisions:	144 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1170
14.2. UN proper shipping name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
14.3. Transport hazard class(es):	3
14.4. Packing group:	
Hazard label:	3
Classification code:	5 F1
Special Provisions:	144 601
Limited quantity:	5 L
Excepted quantity:	E1
Marine transport (IMDG)	
14.1. UN number or ID number:	
14.2. UN proper shipping name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Special Provisions:	144, 223
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-D
Air transport (ICAO-TI/IATA-DGR)	
<u>14.1. UN number or ID number:</u>	UN 1170
14.2. UN proper shipping name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
<u>14.3. Transport hazard class(es):</u>	3
14.4. Packing group:	III
Hazard label:	3
	5
Special Provisions:	A3 A58 A180
Special Provisions: Limited quantity Passenger:	
-	A3 A58 A180
Limited quantity Passenger:	A3 A58 A180 10 L
Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger:	A3 A58 A180 10 L Y344
Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger: IATA-max. quantity - Passenger:	A3 A58 A180 10 L Y344 E1
Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo:	A3 A58 A180 10 L Y344 E1 355
Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger: IATA-max. quantity - Passenger:	A3 A58 A180 10 L Y344 E1 355 60 L

### 14.5. Environmental hazards



Alkohol-Kalibrationslösung 200 g/l Ethanol abs. unvergällt in Wasser + 500 mg Methanol/l		
Revision date: 03.02.2025	Product code: 33661	Page 11 of 12
ENVIRONMENTALLY HAZARDOUS:	No	
14.6. Special precautions for user		
Warning: Combustible liquid.		
14.7. Maritime transport in bulk according to	IMO instruments	
not applicable		
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regula	ations/legislation specific for the substance or mixture	
EU regulatory information		
Restrictions on use (REACH, annex XVII):		
Entry 3, Entry 40		
Information according to Directive	P5c FLAMMABLE LIQUIDS	
2012/18/EU (SEVESO III):		
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juven work protection guideline' (94/33/EC).	nile
Water hazard class (D):	1 - slightly hazardous to water	
15.2. Chemical safety assessment		
For this substance a chemical safety as	sessment has not been carried out.	
SECTION 16: Other information		

#### Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,12,13,15.

#### Abbreviations and acronyms

Flam. Liq: Flammable liquid Eye Irrit: Eye irritation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data

### Relevant H and EUH statements (number and full text)

Highly flammable liquid and vapour.
Flammable liquid and vapour.
Causes serious eye irritation.

### **Further Information**

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

# Alkohol-Kalibrationslösung 200 g/l Ethanol abs. unvergällt in Wasser + 500 mg Methanol/l

Revision date: 03.02.2025

Product code: 33661

Page 12 of 12

processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)