

according to Regulation (EC) No 1907/2006

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34042 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

UFI: KP81-23DW-X00U-7APF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H336 STOT RE 2; H373 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

toluene

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Print date: 09.02.2024



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34042 Page 2 of 13

Pictograms:







Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Chemical name		
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
108-88-3	toluene			75 - < 80 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			20 - < 25 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No Chemical name		Quantity
	Specific Conc. Limits, M-factors and ATE		
108-88-3	203-625-9	toluene	75 - < 80 %
inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg			

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

Print date: 09.02.2024



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34042 Page 3 of 13

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness.

Dyspnoea

Headache

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures



according to Regulation (EC) No 1907/2006

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34042 Page 4 of 13

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.



according to Regulation (EC) No 1907/2006

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34042 Page 5 of 13

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-88-3	Toluene	Toluene	0.02 mg/L		Prior to last shift of workweek
67-63-0	2-Propanol	Acetone	40 mg/L	I -	End of shift at end of workweek



according to Regulation (EC) No 1907/2006

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34042 Page 6 of 13

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
108-88-3	toluene			
Worker DNEL,	long-term	inhalation	systemic	192 mg/m³
Worker DNEL,	acute	inhalation	systemic	384 mg/m³
Worker DNEL,	long-term	inhalation	local	192 mg/m³
Worker DNEL,	acute	inhalation	local	384 mg/m³
Worker DNEL,	long-term	dermal	systemic	384 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	56,5 mg/m³
Consumer DN	EL, acute	inhalation	systemic	226 mg/m³
Consumer DN	EL, long-term	inhalation	local	56,5 mg/m³
Consumer DN	EL, acute	inhalation	local	226 mg/m³
Consumer DN	EL, long-term	dermal	systemic	226 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	8,13 mg/kg bw/day
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Worker DNEL, long-term		inhalation	systemic	500 mg/m³
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	26 mg/kg bw/day

PNEC values

CAS No	Substance		
Environmental	Environmental compartment		
108-88-3	toluene		
Freshwater		0,68 mg/l	
Freshwater (in	ermittent releases)	0,68 mg/l	
Marine water		0,68 mg/l	
Freshwater sec	diment	16,39 mg/kg	
Marine sedime	nt	16,39 mg/kg	
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l	
Soil		2,89 mg/kg	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol		
Freshwater		140,9 mg/l	
Freshwater (in	Freshwater (intermittent releases)		
Marine water		140,9 mg/l	
Freshwater sediment		552 mg/kg	
Marine sediment		552 mg/kg	
Secondary poisoning 160		160 mg/kg	
Micro-organisms in sewage treatment plants (STP) 2251 mg/l			
Soil		28 mg/kg	

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34042 Page 7 of 13

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation KCL 890 Vitoject®
Suitable material: FKM (fluoro rubber) 0,7 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: colourless

Odour: like: Hydrocarbons, aromatic

Odour threshold: No data available

Melting point/freezing point:

No data available
Boiling point or initial boiling point and

>35 °C

boiling range:

Flammability: No data available



according to Regulation (EC) No 1907/2006

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34042 Page 8 of 13

Lower explosion limits: No data available No data available Upper explosion limits: Flash point: <21 °C Auto-ignition temperature: No data available Decomposition temperature: No data available No data available pH-Value: Viscosity / kinematic: No data available No data available Water solubility:

Solubility in other solvents
No data available

Dissolution rate: No data available Partition coefficient n-octanol/water: No data available Dispersion stability: No data available No data available Vapour pressure: Vapour pressure: No data available Density: ~0,843 g/cm³ Relative density: No data available No data available Bulk density: Relative vapour density: No data available Particle characteristics: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available Solvent separation test: No data available Solid content: No data available No data available Sublimation point: Softening point: No data available No data available Pour point: No data available No data available Viscosity / dynamic: Flow time: No data available

Further Information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent



according to Regulation (EC) No 1907/2006

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34042 Page 9 of 13

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name	Chemical name				
	Exposure route	Dose		Species	Source	Method
108-88-3	toluene					
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 mg/kg	> 5000	Rabbit		Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50	28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (toluene; propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34042 Page 10 of 13

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

Discharge into the environment must be avoided.

Further information

Do not allow to enter into surface water or drains.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
108-88-3	toluene							
	Acute fish toxicity	LC50	5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th	
	Acute algae toxicity	ErC50 mg/l	> 433	96 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	Method: other	
	Acute crustacea toxicity	EC50 mg/l	11,5	48 h	Daphnia magna	REACh Registration Dossier	Method: other	
	Fish toxicity	NOEC mg/l	1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th	
	Algae toxicity	NOEC mg/l	> 400	7 d	Scenedesmus quadricauda	REACh Registration Dossier	Method: other	
	Crustacea toxicity	NOEC mg/l	0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (other: US EPA 600/4-91-003	
67-63-0	propan-2-ol; isopropyl alc	ohol; isopro	panol					
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203	

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

BCF

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment



according to Regulation (EC) No 1907/2006

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34042 Page 11 of 13

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

Further information

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol; isopropyl alcohol;

isopropanol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol; isopropyl alcohol;

isopropanol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640D

Limited quantity: 1 L Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol)

14.3. Transport hazard class(es):



according to Regulation (EC) No 1907/2006

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34042 Page 12 of 13

14.4. Packing group:IIHazard label:3Special Provisions:274Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A3Limited quantity Passenger:1 LPassenger LQ:Y341Excepted quantity:E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48

Information according to Directive

2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,12.

Abbreviations and acronyms

Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Eye Irrit: Eye irritation Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard



according to Regulation (EC) No 1907/2006

Toluol- / 2-Propanol - Gemisch zur Analyse 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34042 Page 13 of 13

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure	
Flam. Liq. 2; H225	On basis of test data	
Asp. Tox. 1; H304	Calculation method	
Skin Irrit. 2; H315	Calculation method	
Eye Irrit. 2; H319	Calculation method	
Repr. 2; H361d	Calculation method	
STOT SE 3; H336	Calculation method	
STOT RE 2; H373	Calculation method	
Aquatic Chronic 3; H412	Calculation method	

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
------	-------------------------------------

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)