Print date: 09.02.2024



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## 1-Propanol- / Toluol - Gemisch reinst 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34049 Page 1 of 13

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

1-Propanol- / Toluol - Gemisch reinst 3: 1 volumetrisch gemischt

UFI: T891-M37Q-3009-UQRW

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

### Uses advised against

Do not use for private purposes (household).

## 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

**1.4. Emergency telephone** For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

### **Further Information**

This product is a mixture. REACH Registration Number see section 3.

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 2; H361d STOT SE 3; H336 STOT RE 2; H373 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

### Regulation (EC) No 1272/2008

### Hazard components for labelling

propan-1-ol toluene

Signal word: Danger



according to Regulation (EC) No 1907/2006

## 1-Propanol- / Toluol - Gemisch reinst 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34049 Page 2 of 13

### Pictograms:









### **Hazard statements**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P403+P235 Store in a well-ventilated place. Keep cool.

#### 2.3. Other hazards

No data available

## **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation	on (EC) No 1272/2008)	•	
71-23-8	propan-1-ol		70 - < 75 %	
	200-746-9	603-003-00-0	01-2119486761-29	
	Flam. Liq. 2, Eye Dam. 1, STOT SE 3; H225 H318 H336			
108-88-3	toluene			25 - < 30 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412			

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

- p		·······················	
CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
71-23-8	200-746-9	propan-1-ol	70 - < 75 %
	dermal: LD50 =	= 4032 mg/kg; oral: LD50 = ca. 8000 mg/kg	
108-88-3	203-625-9	toluene	25 - < 30 %
	inhalation: LC5	i0 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg	

### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006



according to Regulation (EC) No 1907/2006

## 1-Propanol- / Toluol - Gemisch reinst 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34049 Page 3 of 13

(REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### General information

Remove contaminated, saturated clothing immediately.

#### After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

### After ingestion

Rinse mouth immediately and drink plenty of water.

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness.

Dyspnoea

Headache

## 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

### Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.



according to Regulation (EC) No 1907/2006

## 1-Propanol- / Toluol - Gemisch reinst 3 : 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34049 Page 4 of 13

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

### For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

## 6.3. Methods and material for containment and cleaning up

### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

## For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

## Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

# Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



according to Regulation (EC) No 1907/2006

## 1-Propanol- / Toluol - Gemisch reinst 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34049 Page 5 of 13

### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Further information on storage conditions

Keep cool. Protect from sunlight.

## 7.3. Specific end use(s)

Laboratory chemicals

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
71-23-8	n-Propyl alcohol; (n-Propanol)	100	-		TWA (8 h)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

### **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-88-3	Toluene	Toluene	0.02 mg/L		Prior to last shift of workweek



according to Regulation (EC) No 1907/2006

# 1-Propanol- / Toluol - Gemisch reinst 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34049 Page 6 of 13

## **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
71-23-8	propan-1-ol			
Worker DNEL,	long-term	inhalation	systemic	268 mg/m³
Worker DNEL,	acute	inhalation	systemic	1723 mg/m³
Worker DNEL,	long-term	dermal	systemic	136 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	80 mg/m³
Consumer DN	EL, acute	inhalation	systemic	1036 mg/m³
Consumer DN	EL, long-term	dermal	systemic	81 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	61 mg/kg bw/day
108-88-3	toluene			
Worker DNEL,	long-term	inhalation	systemic	192 mg/m³
Worker DNEL,	acute	inhalation	systemic	384 mg/m³
Worker DNEL,	long-term	inhalation	local	192 mg/m³
Worker DNEL,	acute	inhalation	local	384 mg/m³
Worker DNEL,	long-term	dermal	systemic	384 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	56,5 mg/m³
Consumer DN	EL, acute	inhalation	systemic	226 mg/m³
Consumer DN	EL, long-term	inhalation	local	56,5 mg/m³
Consumer DN	EL, acute	inhalation	local	226 mg/m³
Consumer DN	EL, long-term	dermal	systemic	226 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	8,13 mg/kg bw/day

### **PNEC values**

i iteo talao		
CAS No	Substance	
Environmenta	I compartment	Value
71-23-8	propan-1-ol	
Freshwater		6,83 mg/l
Freshwater (ir	ntermittent releases)	10 mg/l
Marine water		0,683 mg/l
Freshwater se	diment	27,5 mg/kg
Marine sedim	ent	2,75 mg/kg
Micro-organisms in sewage treatment plants (STP)		96 mg/l
Soil		1,49 mg/kg
108-88-3	toluene	
Freshwater		0,68 mg/l
Freshwater (ir	ntermittent releases)	0,68 mg/l
Marine water		0,68 mg/l
Freshwater sediment		16,39 mg/kg
Marine sediment		16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l
Soil		2,89 mg/kg



according to Regulation (EC) No 1907/2006

## 1-Propanol- / Toluol - Gemisch reinst 3 : 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34049 Page 7 of 13

### 8.2. Exposure controls

### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

goggles

Face protection umbrella

### Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation KCL 890 Vitoject®
Suitable material: FKM (fluoro rubber) 0,7 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

### Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

## Thermal hazards

No data available

## **Environmental exposure controls**

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: clear

Odour: like: Hydrocarbons, aromatic

Odour threshold: No data available

Melting point/freezing point:

No data available

Boiling point or initial boiling point and

>35 °C

boiling range:



according to Regulation (EC) No 1907/2006

### 1-Propanol- / Toluol - Gemisch reinst 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34049 Page 8 of 13

No data available Flammability: No data available Lower explosion limits: Upper explosion limits: No data available Flash point: <21 °C Auto-ignition temperature: No data available Decomposition temperature: No data available pH-Value: No data available No data available Viscosity / kinematic: No data available Water solubility:

Solubility in other solvents

No data available

Dissolution rate: No data available Partition coefficient n-octanol/water: No data available Dispersion stability: No data available Vapour pressure: No data available Vapour pressure: No data available ~0,843 g/cm3 Density: Relative density: No data available No data available Bulk density: Relative vapour density: No data available Particle characteristics: No data available

### 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

## Other safety characteristics

Evaporation rate: No data available No data available Solvent separation test: Solid content: No data available Sublimation point: No data available Softening point: No data available Pour point: No data available No data available Viscosity / dynamic: No data available Flow time: No data available

## **Further Information**

No data available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Vapours may form explosive mixtures with air.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions



according to Regulation (EC) No 1907/2006

## 1-Propanol- / Toluol - Gemisch reinst 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34049 Page 9 of 13

Oxidising agent

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

### **Further information**

No data available

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix** calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name	Chemical name				
	Exposure route	Dose		Species	Source	Method
71-23-8	propan-1-ol					
	oral	LD50 mg/kg	ca. 8000	Rat	Study report (1975)	OECD Guideline 401
	dermal	LD50 mg/kg	4032	Rabbit	Arch. ind. hyg. occupat. med. 10, 61-68.	OECD Guideline 402
108-88-3	toluene					
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 mg/kg	> 5000	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50	28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403

### Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

### Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

## STOT-single exposure

May cause drowsiness or dizziness. (propan-1-ol; toluene)

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

## Information on likely routes of exposure

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

## 1-Propanol- / Toluol - Gemisch reinst 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34049 Page 10 of 13

### Specific effects in experiment on an animal

There are no data available on the mixture itself.

#### Additional information on tests

There are no data available on the mixture itself.

### Practical experience

There are no data available on the mixture itself.

### 11.2. Information on other hazards

### **Endocrine disrupting properties**

There are no data available on the mixture itself.

#### Other information

Discharge into the environment must be avoided.

#### **Further information**

Do not allow to enter into surface water or drains.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
71-23-8	propan-1-ol							
	Acute fish toxicity	LC50 mg/l	4555	96 h	Pimephales promelas	Vol. 1, pp 3, 5-16, 65-68. Center for La	OECD Guideline 203	
	Acute crustacea toxicity	EC50 mg/l	3644	48 h	Daphnia magna	Water Res 23: 495-499 (1989)	other: DIN 38412 Part 11, Daphnia- Short	
	Crustacea toxicity	NOEC mg/l	> 100	21 d	Daphnia magna	Study report (1997)	OECD Guideline 211	
108-88-3	toluene							
	Acute fish toxicity	LC50	5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th	
	Acute algae toxicity	ErC50 mg/l	> 433	96 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	Method: other	
	Acute crustacea toxicity	EC50 mg/l	11,5	48 h	Daphnia magna	REACh Registration Dossier	Method: other	
	Fish toxicity	NOEC mg/l	1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th	
	Algae toxicity	NOEC mg/l	> 400	7 d	Scenedesmus quadricauda	REACh Registration Dossier	Method: other	
	Crustacea toxicity	NOEC mg/l	0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (	other: US EPA 600/4-91-003	

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

## 1-Propanol- / Toluol - Gemisch reinst 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34049 Page 11 of 13

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
71-23-8	propan-1-ol	1,6
108-88-3	toluene	2,73

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
71-23-8	propan-1-ol	0,88		Unpublished calculat
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).

### 12.4. Mobility in soil

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

### **Further information**

No data available

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (toluene, propan-1-ol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (toluene, propan-1-ol)



according to Regulation (EC) No 1907/2006

## 1-Propanol- / Toluol - Gemisch reinst 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34049 Page 12 of 13

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (toluene, propan-1-ol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:274Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (toluene, propan-1-oll)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A3Limited quantity Passenger:1 LPassenger LQ:Y341Excepted quantity:E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48

Information according to Directive

P5c FLAMMABLE LIQUIDS

2012/18/EU (SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

#### **SECTION 16: Other information**

#### Changes



according to Regulation (EC) No 1907/2006

### 1-Propanol- / Toluol - Gemisch reinst 3: 1 volumetrisch gemischt

Revision date: 08.02.2024 Product code: 34049 Page 13 of 13

This data sheet contains changes from the previous version in section(s): 2,12.

### Abbreviations and acronyms

Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Eye Dam: Eye damage Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
11070	

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)