



according to UK REACH Regulation

Multielement-Standard 10 Elemente "Rhenium" in verdünntem Säuregemisch

Revision date: 27.10.2022 Product code: 34203 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multielement-Standard 10 Elemente "Rhenium" in verdünntem Säuregemisch

UFI: NGQ1-J3HU-800H-Q9GU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: Fa. Bernd Kraft GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

e-mail: info@berndkraft.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

e-mail: produktsicherheit@berndkraft.de

Internet: www.berndkraft.de

Responsible Department: Abteilung Produktsicherheit

<u>1.4. Emergency telephone</u> For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Met. Corr. 1; H290 Skin Corr. 1B; H314 Eye Dam. 1; H318 Carc. 1A; H350 STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrochloric acid nitric acid Arsensäure

Signal word: Danger



according to UK REACH Regulation

Multielement-Standard 10 Elemente "Rhenium" in verdünntem Säuregemisch

Revision date: 27.10.2022 Product code: 34203 Page 2 of 12

Pictograms:







Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

H350 May cause cancer.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

Restricted to professional users.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLF				
7647-01-0	Hydrochloric acid			10 - < 15 %	
	231-595-7	017-002-01-X	01-2119484862-27		
	Skin Corr. 1B, STOT SE 3; H314 H335				
7697-37-2	nitric acid	10 - < 15 %			
	231-714-2	007-030-00-3	01-2119487297-23		
	Ox. Liq. 3, Met. Corr. 1				
-	arsenic acid and it salt	< 1 %			
	-	033-005-00-1			
	Carc. 1A, Acute Tox. 3 H410				

Full text of H and EUH statements: see section 16.



according to UK REACH Regulation

Multielement-Standard 10 Elemente "Rhenium" in verdünntem Säuregemisch

Revision date: 27.10.2022 Product code: 34203 Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. I	Limits, M-factors and ATE		
7647-01-0	231-595-7	Hydrochloric acid	10 - < 15 %	
		H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 3; H335: >= 10 - 100		
7697-37-2	231-714-2	nitric acid	10 - < 15 %	
		inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20		
-	-	arsenic acid and it salts with the exception of those specified elsewhere in this Annex	< 1 %	
	inhalation: ATE mg/kg	E = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: ATE = 100		

Further Information

No data available

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

Irritant

Cough

Dyspnoea

Vomiting

Methaemoglobinaemia

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.





according to UK REACH Regulation

Multielement-Standard 10 Elemente "Rhenium" in verdünntem Säuregemisch

Revision date: 27.10.2022 Product code: 34203 Page 4 of 12

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

Hydrogen chloride (HCI)

Metal oxide smoke, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe vapour/aerosol. Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.


Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13





according to UK REACH Regulation

Multielement-Standard 10 Elemente "Rhenium" in verdünntem Säuregemisch

Revision date: 27.10.2022 Product code: 34203 Page 5 of 12

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol. Use extractor hood (laboratory).

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Corrosive to metals.

Unsuitable container/equipment material: Metal

The product develops hydrogen in an aqueous solution in contact with metals.

Hints on joint storage

national regulations

Further information on storage conditions

Keep container tightly closed.

Store in a place accessible by authorized persons only.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7647-01-0	Hydrogen chloride (gas and aerosol mists)	1	2		TWA (8 h)	WEL
		5	8		STEL (15 min)	WEL
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	WEL



according to UK REACH Regulation

Multielement-Standard 10 Elemente "Rhenium" in verdünntem Säuregemisch

Revision date: 27.10.2022 Product code: 34203 Page 6 of 12

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
7647-01-0	Hydrochloric acid					
Worker DNEL, long-term		inhalation	local	8 mg/m³		
Worker DNEL, acute		inhalation	local	15 mg/m³		
Consumer DNEL, long-term		inhalation	local	8 mg/m³		
Consumer DNEL, acute		inhalation	local	15 mg/m³		

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.

Hand protection

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid



according to UK REACH Regulation

Multielement-Standard 10 Elemente "Rhenium" in verdünntem Säuregemisch

Revision date: 27.10.2022 Product code: 34203 Page 7 of 12

Colour:

Odour: stinging

Odour threshold: No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range: Flammability

Solid/liquid:
 Gas:
 No data available
 No data available
 No data available
 No data available

Upper explosion limits:

Flash point:

Auto-ignition temperature:

Decomposition temperature:

No data available

No data available

No data available

No data available

pH-Value: 0,3
Viscosity / kinematic: No data available

Water solubility: completely miscible

Solubility in other solvents

No data available

Dissolution rate: No data available Partition coefficient n-octanol/water: No data available Dispersion stability: No data available Vapour pressure: No data available No data available Vapour pressure: Density (at 20 °C): 1,1071 g/cm³ Relative density: No data available Bulk density: No data available Relative vapour density: No data available No data available Particle characteristics:

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion:

No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties
Oxidising agent

Other safety characteristics

Evaporation rate:

Solvent separation test:

Solvent content:

No data available
No data available
output
0

Solid content: 0
Sublimation point: No data available
Softening point: No data available
Pour point: No data available
No data available

No data available:

Viscosity / dynamic:

Flow time:

No data available

No data available

Further Information

Corrosive to metals.



according to UK REACH Regulation

Multielement-Standard 10 Elemente "Rhenium" in verdünntem Säuregemisch

Revision date: 27.10.2022 Product code: 34203 Page 8 of 12

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

Oxidising agent

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

The product develops hydrogen in an aqueous solution in contact with metals.

Amines, Ammonia, Alcohols, Alkali metals, Hydrogen peroxide

Copper, Combustible solids, Solvent, Alkaline earth metal, mercury (Hg).

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Cellulose

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity


Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 41025,6 mg/kg; ATE (inhalation vapour) 25,94 mg/l; ATE (inhalation dust/mist) 205,128 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7697-37-2	nitric acid				
	inhalation vapour	ATE 2,65 mg/l			
-	arsenic acid and it salts with the exception of those specified elsewhere in this Annex				
	oral	ATE 100 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0,5 mg/l			

Irritation and corrosivity





according to UK REACH Regulation

Multielement-Standard 10 Elemente "Rhenium" in verdünntem Säuregemisch

Revision date: 27.10.2022 Product code: 34203 Page 9 of 12

Causes severe skin burns and eye damage.

Causes serious eye damage.

Following ingestion Gastric perforation

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Irritating to respiratory system.

Pulmonary oedema

see also Section 4

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer. (arsenic acid and it salts with the exception of those specified elsewhere in this Annex)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Hydrochloric acid)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the preparation/mixture itself.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the preparation/mixture itself.

Other information

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.



according to UK REACH Regulation

Multielement-Standard 10 Elemente "Rhenium" in verdünntem Säuregemisch

Revision date: 27.10.2022 Product code: 34203 Page 10 of 12

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
7647-01-0	Hydrochloric acid							
	Acute fish toxicity	LC50	862 mg/l	96 h	Leuciscus idus			
7697-37-2	nitric acid	nitric acid						
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26	
	Fish toxicity	NOEC	268 mg/l		juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical	
	Algae toxicity	NOEC mg/l	> 419		several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso	
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209	

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3264



according to UK REACH Regulation

Multielement-Standard 10 Elemente "Rhenium" in verdünntem Säuregemisch

Revision date: 27.10.2022 Product code: 34203 Page 11 of 12

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid,

Hydrochloric acid)

14.3. Transport hazard class(es): 8 Ш 14.4. Packing group: Hazard label: 8 Classification code: C1 Special Provisions: 274 Limited quantity: 1 L Excepted quantity: E2 Transport category: 2 Hazard No: 80 Tunnel restriction code: F

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid,

Hydrochloric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Classification code:C1Special Provisions:274Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid,

Hydrochloric acid)

14.3. Transport hazard class(es): 8 14.4. Packing group: П Hazard label: 8 Special Provisions: 274 Limited quantity: 1 L Excepted quantity: E2 EmS: F-A. S-B Segregation group: 1 - acids

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid,

Hydrochloric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:0.5 LPassenger LQ:Y840Excepted quantity:E2

IATA-packing instructions - Passenger: 851
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No



according to UK REACH Regulation

Multielement-Standard 10 Elemente "Rhenium" in verdünntem Säuregemisch

Revision date: 27.10.2022 Product code: 34203 Page 12 of 12

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

arsenic acid and it salts with the exception of those specified elsewhere in this Annex

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Carc. 1A; H350	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
E1111074	Company to the magnification street

EUH071 Corrosive to the respiratory tract.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)