

## Safety Data Sheet

according to UK REACH Regulation

### Schnell-Ätzlösung 5 VLSI 76 % (m/m) H<sub>2</sub>SO<sub>4</sub> + 6,5 % (m/m) HF + 5 % (m/m) HNO<sub>3</sub>

Revision date: 13.02.2024

Product code: 34399

Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Schnell-Ätzlösung 5 VLSI 76 % (m/m) H<sub>2</sub>SO<sub>4</sub> + 6,5 % (m/m) HF + 5 % (m/m) HNO<sub>3</sub>

UFI: QA82-R3TN-900H-C6QG

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

### Further Information

inapplicable, this product is a mixture REACH registration number see section 3

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GB CLP Regulation

Met. Corr. 1; H290  
Acute Tox. 2; H310  
Acute Tox. 3; H301  
Acute Tox. 3; H331  
Skin Corr. 1A; H314  
Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### GB CLP Regulation

#### Hazard components for labelling

sulphuric acid 76 % hydrofluoric acid 6,5 % nitric acid 5 %

Signal word: Danger

## Safety Data Sheet

according to UK REACH Regulation

### Schnell-Ätzlösung 5 VLSI 76 % (m/m) H<sub>2</sub>SO<sub>4</sub> + 6,5 % (m/m) HF + 5 % (m/m) HNO<sub>3</sub>

Revision date: 13.02.2024

Product code: 34399

Page 2 of 13

#### Pictograms:



#### Hazard statements

H290	May be corrosive to metals.
H301+H331	Toxic if swallowed or if inhaled.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.

#### Precautionary statements

P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

#### Special labelling of certain mixtures

EUH071	Corrosive to the respiratory tract.
--------	-------------------------------------

#### Additional advice on labelling

No information available.

#### 2.3. Other hazards

No data available

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Mixtures in aqueous solution

#### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
7664-93-9	sulphuric acid			75 - < 80 %
	231-639-5	016-020-00-8	01-2119458838-20	
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318			
7664-39-3	hydrofluoric acid ... %			5 - < 10 %
	231-634-8	009-003-00-1		
	Acute Tox. 1, Acute Tox. 2, Acute Tox. 2, Skin Corr. 1A; H310 H330 H300 H314			
7697-37-2	nitric acid			5 - < 10 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A; H272 H290 H331 H314 EUH071			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

**Schnell-Ätzlösung 5 VLSI 76 % (m/m) H<sub>2</sub>SO<sub>4</sub> + 6,5 % (m/m) HF + 5 % (m/m) HNO<sub>3</sub>**

Revision date: 13.02.2024

Product code: 34399

Page 3 of 13

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
7664-93-9	231-639-5	sulphuric acid	75 - < 80 %
		oral: LD50 = 2140 mg/kg Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15	
7664-39-3	231-634-8	hydrofluoric acid ... %	5 - < 10 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); inhalation: LC50 = 1610 ppm (gases); dermal: ATE = 5 mg/kg; oral: ATE = 5 mg/kg Skin Corr. 1A; H314: >= 7 - 100 Skin Corr. 1B; H314: >= 1 - < 7 Eye Irrit. 2; H319: >= 0,1 - < 1	
7697-37-2	231-714-2	nitric acid	5 - < 10 %
		inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20	

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

fast help required

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

Call a physician immediately.

**After inhalation**

Provide fresh air. No mouth-to-mouth or mouth-to-nose resuscitation. Use Ambu bag or ventilator. Call a physician immediately.

**After contact with skin**

Rinse with plenty of water for at least 10 minutes. Immediately remove contaminated clothes. Apply calcium gluconate gel (preparation: boil 5 g of calcium gluconate in 85 ml of hot distilled water, add 10 g glycerol. Allow 5 g of Carmellose-sodium to swell in the hot solution. Stable for 6 months, store in a cool place) and massage into the skin until the pain subsides, in between rinse with water and apply fresh gel. Continue gel therapy for another 15 minutes after the pain has subsided. If no calcium gluconate gel is available, apply several dressings thoroughly moistened with 20 % calcium gluconate solution. Medical advice absolutely required!

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

**After ingestion**

Never give anything by mouth to an unconscious person or a person with cramps.

Rinse mouth immediately and drink plenty of water.

Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Gastric perforation, Circulatory collapse, Pulmonary oedema, Vomiting, seizures, Pneumonia, Irritant, Causes burns. Risk of serious damage to eyes.

**4.3. Indication of any immediate medical attention and special treatment needed**

It is recommended to consult a doctor with experience in the treatment of lesions caused by hydrofluoric acid

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

## Safety Data Sheet

according to UK REACH Regulation

### Schnell-Ätzlösung 5 VLSI 76 % (m/m) H<sub>2</sub>SO<sub>4</sub> + 6,5 % (m/m) HF + 5 % (m/m) HNO<sub>3</sub>

Revision date: 13.02.2024

Product code: 34399

Page 4 of 13

#### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

no restriction

#### 5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Hydrogen fluoride

Nitrogen oxides (NO<sub>x</sub>)

Sulphur oxides

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers.

#### Additional information

Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Corrosive to metals. Glass

Do not breathe vapour/aerosol.

#### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Clean contaminated articles and floor according to the environmental legislation.

### 6.3. Methods and material for containment and cleaning up

#### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**Safety Data Sheet**

according to UK REACH Regulation

**Schnell-Ätzlösung 5 VLSI 76 % (m/m) H2SO4 + 6,5 % (m/m) HF + 5 % (m/m) HNO3**

Revision date: 13.02.2024

Product code: 34399

Page 5 of 13

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

Read label before use. Handle and open container with care.  
When using do not eat, drink, smoke, sniff. Keep container tightly closed.  
Use personal protection equipment. Use extractor hood (laboratory).  
Provide adequate ventilation. Do not breathe vapour/aerosol.  
Avoid contact with skin, eyes and clothes.

**Advice on protection against fire and explosion**

Usual measures for fire prevention.

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs. Make available sufficient washing facilities  
Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**Further information on handling**

Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary.  
Take off immediately all contaminated clothing and wash it before reuse.  
If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations.

**Hints on joint storage**

national regulations

**Further information on storage conditions**

Store in a dry place.  
Unsuitable container/equipment material: Metal, Glass

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
7664-39-3	Hydrogen fluoride (as F)	1.8	1.5		TWA (8 h)	WEL
		3	2.5		STEL (15 min)	WEL
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	WEL
7664-93-9	Sulphuric acid (mist)	-	0.05		TWA (8 h)	WEL

**Safety Data Sheet**

according to UK REACH Regulation

**Schnell-Ätzlösung 5 VLSI 76 % (m/m) H2SO4 + 6,5 % (m/m) HF + 5 % (m/m) HNO3**

Revision date: 13.02.2024

Product code: 34399

Page 6 of 13

**DNEL/DMEL values**

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
7664-93-9	sulphuric acid		
Worker DNEL, long-term	inhalation	local	0,05 mg/m <sup>3</sup>

**PNEC values**

CAS No	Substance	
Environmental compartment	Value	
7664-93-9	sulphuric acid	
Micro-organisms in sewage treatment plants (STP)	8,8 mg/l	

**8.2. Exposure controls**

**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Technical measures and the application of suitable work processes have priority over personal protection equipment.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Suitable eye protection: goggles.

Wear eye/face protection.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) with the following specification (test according to EN 374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

Wear suitable protective clothing.

Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

## Safety Data Sheet

according to UK REACH Regulation

### Schnell-Ätzlösung 5 VLSI 76 % (m/m) H<sub>2</sub>SO<sub>4</sub> + 6,5 % (m/m) HF + 5 % (m/m) HNO<sub>3</sub>

Revision date: 13.02.2024

Product code: 34399

Page 7 of 13

#### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

#### Thermal hazards

No data available

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:		
Odour:	stinging	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		X
Auto-ignition temperature:		No data available
Decomposition temperature:		not determined
pH-Value:		<1
Viscosity / kinematic:		not determined
Solubility in other solvents		
not determined		
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		1,722 g/cm <sup>3</sup>
Relative density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available
Particle characteristics:		No data available

### 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties	
No data available	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
Oxidising agent	

#### Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	not determined

## Safety Data Sheet

according to UK REACH Regulation

### Schnell-Ätzlösung 5 VLSI 76 % (m/m) H<sub>2</sub>SO<sub>4</sub> + 6,5 % (m/m) HF + 5 % (m/m) HNO<sub>3</sub>

Revision date: 13.02.2024

Product code: 34399

Page 8 of 13

Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	not determined
Flow time:	not determined

#### Further Information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Alkali (lye)

### 10.4. Conditions to avoid

Radiant heat.

### 10.5. Incompatible materials

Metal

Glass

The product develops hydrogen in an aqueous solution in contact with metals.

### 10.6. Hazardous decomposition products

In case of fire:

SECTION 5: Firefighting measures

#### Further information

No data available

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Fatal in contact with skin.

Toxic if swallowed.

Toxic if inhaled.

#### ATEmix calculated

ATE (oral) 76,90 mg/kg; ATE (dermal) 76,90 mg/kg; ATE (inhalation vapour) 6,720 mg/l; ATE (inhalation dust/mist) 0,7690 mg/l



**Safety Data Sheet**

according to UK REACH Regulation

**Schnell-Ätzlösung 5 VLSI 76 % (m/m) H<sub>2</sub>SO<sub>4</sub> + 6,5 % (m/m) HF + 5 % (m/m) HNO<sub>3</sub>**

Revision date: 13.02.2024

Product code: 34399

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7664-93-9	sulphuric acid				
	oral	LD50 2140 mg/kg	Rat	Am Ind Hyg Assoc J. 1969 Sep-Oct; 30(5):	The study was performed as part of a ser
7664-39-3	hydrofluoric acid ... %				
	oral	ATE 5 mg/kg			
	dermal	ATE 5 mg/kg			
	inhalation vapour	ATE 0,5 mg/l			
	inhalation dust/mist	ATE 0,05 mg/l			
	inhalation (1 h) gas	LC50 1610 ppm	Rat		
7697-37-2	nitric acid				
	inhalation vapour	ATE 2,65 mg/l			

**Irritation and corrosivity**

Causes severe skin burns and eye damage.  
Causes serious eye damage.  
Corrosive to the respiratory tract.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

There are no data available on the mixture itself.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

There are no data available on the mixture itself.

**Other information**

There are no data available on the mixture itself.

**Further information**

Resorption (oral) Resorption (by inhalation) Resorption (dermal)  
Following ingestion gastric perforation  
Damage to: Liver and kidney damage  
Risk of serious damage to eyes. Symptoms may be delayed. Other dangerous properties can not be excluded.

**Safety Data Sheet**

according to UK REACH Regulation

**Schnell-Ätzlösung 5 VLSI 76 % (m/m) H<sub>2</sub>SO<sub>4</sub> + 6,5 % (m/m) HF + 5 % (m/m) HNO<sub>3</sub>**

Revision date: 13.02.2024

Product code: 34399

Page 10 of 13

**SECTION 12: Ecological information**

**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
7664-93-9	sulphuric acid					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	Study report (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (2009)	OECD Guideline 202
	Fish toxicity	NOEC 0,025 mg/l	65 d	Jordanella floridae	Water Research Vol. 11, 612 - 626, 1977	Groups of sexually mature flagfish
7697-37-2	nitric acid					
	Acute fish toxicity	LC50 1559 mg/l	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26
	Fish toxicity	NOEC 268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical
	Algae toxicity	NOEC > 419 mg/l	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 > 1000 mg/l ( )	3 h	Activated sludge	Study report (2008)	OECD Guideline 209

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

There are no data available on the mixture itself.

**Further information**

- Avoid release to the environment.
- Harmful effect due to pH shift.
- Forms corrosive mixtures with water even if diluted.
- Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

- Do not allow to enter into surface water or drains.
- Dispose of waste according to applicable legislation.

## Safety Data Sheet

according to UK REACH Regulation

### Schnell-Ätzlösung 5 VLSI 76 % (m/m) H<sub>2</sub>SO<sub>4</sub> + 6,5 % (m/m) HF + 5 % (m/m) HNO<sub>3</sub>

Revision date: 13.02.2024

Product code: 34399

Page 11 of 13

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.

#### Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number or ID number:</b>	UN 2922
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, TOXIC, N.O.S. (Hydrofluoric acid, nitric acid, sulphuric acid)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8+6.1
Classification code:	CT1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	86
Tunnel restriction code:	E

### Inland waterways transport (ADN)

<b>14.1. UN number or ID number:</b>	UN 2922
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, TOXIC, N.O.S. (Hydrofluoric acid, nitric acid, sulphuric acid)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8+6.1
Classification code:	CT1
Special Provisions:	274 802
Limited quantity:	1 L
Excepted quantity:	E2

### Marine transport (IMDG)

<b>14.1. UN number or ID number:</b>	UN 2922
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, TOXIC, N.O.S. (Hydrofluoric acid, Nitric acid, sulphuric acid)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8+6.1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B

### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number or ID number:</b>	UN 2922
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, TOXIC, N.O.S. (Hydrofluoric acid, Nitric acid, sulphuric acid)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8+6.1
Special Provisions:	A3 A803

**Safety Data Sheet**

according to UK REACH Regulation

**Schnell-Ätzlösung 5 VLSI 76 % (m/m) H<sub>2</sub>SO<sub>4</sub> + 6,5 % (m/m) HF + 5 % (m/m) HNO<sub>3</sub>**

Revision date: 13.02.2024

Product code: 34399

Page 12 of 13

Limited quantity Passenger:	0.5 L	
Passenger LQ:	Y840	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		851
IATA-max. quantity - Passenger:		1 L
IATA-packing instructions - Cargo:		855
IATA-max. quantity - Cargo:		30 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Toxic. strongly corrosive.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): H2 ACUTE TOXIC

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 1,9.

**Safety Data Sheet**

according to UK REACH Regulation

**Schnell-Ätzlösung 5 VLSI 76 % (m/m) H2SO4 + 6,5 % (m/m) HF + 5 % (m/m) HNO3**

Revision date: 13.02.2024

Product code: 34399

Page 13 of 13

**Abbreviations and acronyms**

- Ox. Liq: Oxidising liquids
- Met. Corr: Corrosive to metals
- Acute Tox: Acute toxicity
- Skin Corr: Skin corrosion
- Eye Dam: Eye damage
- ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service
- LC50: Lethal concentration, 50%
- LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Acute Tox. 2; H310	Calculation method
Acute Tox. 3; H301	Calculation method
Acute Tox. 3; H331	Calculation method
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method

**Relevant H and EUH statements (number and full text)**

- H272 May intensify fire; oxidiser.
- H290 May be corrosive to metals.
- H300 Fatal if swallowed.
- H301 Toxic if swallowed.
- H301+H331 Toxic if swallowed or if inhaled.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- EUH071 Corrosive to the respiratory tract.

**Further Information**

Provide appropriate information, instructions and training to users  
 The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.  
 The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*