

Essigsäure 30% tech.

Revision date: 02.05.2023

Product code: 34418

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Essigsäure 30% tech.

UFI:

7X92-C3X6-300W-XPSQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone	For Hazardous Materials [or Danger	ous Goods] Incidents Spill, Leak, Fire,
number:	Exposure, or Accident Call CHEMT	REC Day or Night Within USA and Canada:
	1-800-424-9300 Outside USA and C	Canada: +1 703-741-5970 (collect calls
	accepted)	

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008 Skin Corr. 1B; H314 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling acetic acid

Signal word:

Danger

Pictograms:



Hazard statements

H314

Causes severe skin burns and eye damage.



Essigsäure 30% tech.

Revision date: 02.05.2023

Product code: 34418

Page 2 of 11

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Hazardous components

CAS No	Chemical name	Chemical name					
	EC No	EC No Index No REACH No					
	Classification (Regulation	Classification (Regulation (EC) No 1272/2008)					
64-19-7	acetic acid	acetic acid					
	200-580-7	200-580-7 607-002-00-6 01-2119475328-30					
	Flam. Liq. 3, Skin Corr.	Flam. Liq. 3, Skin Corr. 1A; H226 H314					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	imits, M-factors and ATE	
64-19-7	200-580-7	acetic acid	30 - < 35 %
		0 = 11,4 mg/l (vapours); oral: LD50 = 3310 mg/kg Skin Corr. 1A; H314: >= 90 - : 1B; H314: >= 25 - < 90 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >=	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

After inhalation

Provide fresh air. Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.



according to Regulation (EC) No 1907/2006

Essigsäure 30% tech.

Revision date: 02.05.2023

Product code: 34418

Page 3 of 11

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant corrosive Dyspnoea Gastrointestinal complaints Vomiting Circulatory collapse Corneal opacity. Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

5.2. Special hazards arising from the substance or mixture

Combustible liquids Hazardous combustion products In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide Acetic acid vapour Vapours are heavier than air, spread along floors and form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes. Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe vapour/aerosol.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures



according to Regulation (EC) No 1907/2006

Essigsäure 30% tech.

Revision date: 02.05.2023

Product code: 34418

Page 4 of 11

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Do not breathe vapour/aerosol. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a well-ventilated place. Keep container tightly closed.

Store in a dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

In case of warming: Vapours may form explosive mixtures with air.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

Essigsäure 30% tech.

Revision date: 02.05.2023

Product code: 34418

Page 5 of 11

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	
		20	50		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
64-19-7	acetic acid						
Worker DNEL,	long-term	inhalation	local	25 mg/m³			
Worker DNEL,	acute	inhalation	local	25 mg/m³			
Consumer DNEL, long-term		inhalation	local	25 mg/m³			
Consumer DNE	EL, acute	inhalation	local	25 mg/m³			

PNEC values

CAS No	Substance				
Environmental compartment Value					
64-19-7	acetic acid				
Freshwater	Freshwater				
Freshwater (intermittent releases) 30,58					
Marine wate	0,306 mg/l				
Freshwater	11,36 mg/kg				
Marine sedi	1,136 mg/kg				
Micro-organ	Micro-organisms in sewage treatment plants (STP)				
Soil		0,47 mg/kg			

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact Trade name/designation: KCL 897 Butoject® Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Trade name/designation: KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm Wearing time with occasional contact (splashes): > 60 min



according to Regulation (EC) No 1907/2006

Essigsäure 30% tech.

Revision date: 02.05.2023

Product code: 34418

Page 6 of 11

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse. Wear fire resistant or flame retardant clothing. Wash hands and face before breaks and after work and take a shower if necessary. Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Filtering device (full mask or mouthpiece) with filter: E-(P2)

Environmental exposure controls

Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	stinging	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and		No data available
boiling range:		
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		>100 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		acidic
Viscosity / kinematic:		No data available
Water solubility:		completely miscible
Solubility in other solvents		
No data available		
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Relative density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available
9.2. Other information		
Information with regard to physical haz	ard classes	
Explosive properties		

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Sustaining combustion: Sustaining combustion Self-ignition temperature



	Essigsäure 30% tech.	
Revision date: 02.05.2023	Product code: 34418	Page 7 of 11
Solid:	No data available	
Gas:	No data available	
Oxidizing properties		
No data available		
Other safety characteristics		
Evaporation rate:	No data available	
Solvent separation test:	No data available	
Solvent content:	No data available	
Solid content:	No data available	
Sublimation point:	No data available	
Softening point:	No data available	
Pour point:	No data available	
	No data available	
Viscosity / dynamic:	No data available	
Flow time:	No data available	
Further Information		
May be corrosive to metals.		

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming: Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent peroxides, for example hydrogen peroxide permanganates, e.g. potassium permanganate Oxidising agent, strong Metal iron and steel Zinc Alkali (lye) aldehydes Alcohols Nitric acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Metal (Formation of: Hydrogen)

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.



according to Regulation (EC) No 1907/2006

Essigsäure 30% tech.

Revision date: 02.05.2023

Product code: 34418

Page 8 of 11

Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

ATEmix calculated

ATE (inhalation vapour) 38,00 mg/l

CAS No	Chemical name									
	Exposure route Dose			Species	Source	Method				
64-19-7	acetic acid									
	oral	LD50 mg/kg	3310		, ,,	The sodium salt of acetic acid was admin				
	inhalation (4 h) vapour	LC50	11,4 mg/l	Rat	Study report (1980)	OECD Guideline 403				

Irritation and corrosivity

Causes severe skin burns and eye damage. Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met. Observe risk of aspiration if vomiting occurs.

Information on likely routes of exposure

There are no data available on the preparation/mixture itself.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the preparation/mixture itself.

Other information Irritant corrosive Dyspnoea Gastrointestinal complaints Vomiting Circulatory collapse Corneal opacity.

Risk of serious damage to eyes.

Further information

kidneys



according to Regulation (EC) No 1907/2006

Essigsäure 30% tech.

Revision date: 02.05.2023

Product code: 34418

Page 9 of 11

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name									
	Aquatic toxicity	Dose		[h] [d] Species		Source	Method			
64-19-7	acetic acid									
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss	Study report (2005)	other: SOP E257			
	Acute algae toxicity	ErC50 mg/l	> 1000		Skeletonema costatum	Study report (2005)	ISO 10253			
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	Study report (1990)	OECD Guideline 202			

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-19-7	acetic acid	-0,17

В	С	F

CAS No	Chemical name	BCF	Species	Source
64-19-7	acetic acid	3,16	fish	Environ. Toxicol. Ch

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.



according to Regulation (EC) No 1907/2006

Essigsäure 30% tech.

Revision date: 02.05.2023

Product code: 34418

Page 10 of 11

SECTION 14: Transport information

Land transport (ADR/RID)	
14.1. UN number or ID number:	UN 2790
14.2. UN proper shipping name:	ACETIC ACID SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	111
Hazard label:	8
Classification code:	C3
Special Provisions:	597 647
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 2790
14.2. UN proper shipping name:	ACETIC ACID SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C3
Special Provisions:	597 647
Limited quantity:	5 L
Excepted quantity:	E1
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 2790
14.2. UN proper shipping name:	ACETIC ACID SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	111
Hazard label:	8
Special Provisions:	-
Limited quantity:	5 L
Excepted quantity:	E2
EmS:	F-A, S-B
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	UN 2790
14.2. UN proper shipping name:	ACETIC ACID SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	A803
Limited quantity Passenger:	1 L
Passenger LQ:	Y841
Excepted quantity:	E1
IATA-packing instructions - Passenger:	852
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	856
IATA-max. quantity - Cargo:	60 L
, ,,	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



Essigsäure 30% tech.				
Revision date: 02.05.2023	Product code: 34418	Page 11 of 11		
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 40 Information according to 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)			
National regulatory information				
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).			
Water hazard class (D):	1 - slightly hazardous to water			
SECTION 16: Other information				

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.

- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)