

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HPLC-Eluent Methanol / 2-Propanol / Isooctan

Revision date: 22.05.2023

Product code: 34434

Page 1 of 15

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

HPLC-Eluent Methanol / 2-Propanol / Isooctan

UFI: PAC2-F3YJ-000U-H53R

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

###### Uses advised against

Do not use for private purposes (household).

##### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

##### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

##### Further Information

This product is a mixture. REACH Registration Number see section 3.

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225  
Acute Tox. 3; H301  
Acute Tox. 3; H311  
Acute Tox. 3; H331  
Eye Irrit. 2; H319  
STOT SE 1; H370  
STOT SE 3; H336  
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

###### Regulation (EC) No 1272/2008

###### Hazard components for labelling

methanol  
propan-2-ol; isopropyl alcohol; isopropanol  
2,2,4-trimethylpentane

Signal word: Danger

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HPLC-Eluent Methanol / 2-Propanol / Isooctan**

Revision date: 22.05.2023

Product code: 34434

Page 2 of 15

**Pictograms:**



**Hazard statements**

- H225 Highly flammable liquid and vapour.
- H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H370 Causes damage to organs (central nervous system, eyes).
- H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.
- P403+P235 Store in a well-ventilated place. Keep cool.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-56-1	methanol			75 - < 80 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			15 - < 20 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
540-84-1	2,2,4-trimethylpentane			5 - < 10 %
	208-759-1	601-009-00-8	01-2119457965-22	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-56-1	200-659-6	methanol	75 - < 80 %
		inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	
540-84-1	208-759-1	2,2,4-trimethylpentane	5 - < 10 %
		inhalation: LC50 = > 33,52 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HPLC-Eluent Methanol / 2-Propanol / Isooctan

Revision date: 22.05.2023

Product code: 34434

Page 3 of 15

#### Further Information

No data available

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

First aider: Pay attention to self-protection!

##### After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

##### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

##### After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water.

Remove contact lenses, if present and easy to do. Continue rinsing.

Consult an ophthalmologist.

##### After ingestion

Provide fresh air.

Call a physician immediately.

Notes for the doctor : Methanol

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant, Dizziness

Dizziness, Anaesthetic state

Agitation, Spasms

Inebriation, Vomiting

Headache, Impairment of vision

Repeated exposure may cause skin dryness or cracking.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

##### Unsuitable extinguishing media

no restriction

#### 5.2. Special hazards arising from the substance or mixture

Combustible liquids

Highly flammable.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide, Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Beware of reignition.

Heating causes rise in pressure with risk of bursting.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Wear full chemical protective clothing.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HPLC-Eluent Methanol / 2-Propanol / Isooctan

Revision date: 22.05.2023

Product code: 34434

Page 4 of 15

In case of fire and/or explosion do not breathe fumes.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

##### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

##### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Avoid exposure - obtain special instructions before use.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HPLC-Eluent Methanol / 2-Propanol / Isooctan**

Revision date: 22.05.2023

Product code: 34434

Page 5 of 15

Read label before use. Handle and open container with care.  
When using do not eat, drink, smoke, sniff. Keep container tightly closed.  
Use personal protection equipment.  
Do not breathe gas/fumes/vapour/spray.  
Provide adequate ventilation.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.  
Vapours can form explosive mixtures with air.

**Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.  
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.  
Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

**Further information on storage conditions**

Keep cool. Protect from sunlight.

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
67-56-1	Methyl alcohol	200	260		TWA (8 h)	
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

**Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HPLC-Eluent Methanol / 2-Propanol / Isooctan**

Revision date: 22.05.2023

Product code: 34434

Page 6 of 15

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
67-56-1	methanol			
Consumer DNEL, acute		inhalation	systemic	50 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	systemic	260 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	260 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	260 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	260 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	40 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	50 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	50 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	50 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Worker DNEL, long-term		inhalation	systemic	500 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
540-84-1	2,2,4-trimethylpentane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HPLC-Eluent Methanol / 2-Propanol / Isooctan**

Revision date: 22.05.2023

Product code: 34434

Page 7 of 15

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
67-56-1	methanol	
Freshwater		20,8 mg/l
Freshwater (intermittent releases)		1540 mg/l
Marine water		2,08 mg/l
Freshwater sediment		77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		100 mg/kg
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe gas/fumes/vapour/spray.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

goggles

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact: No data available

By short-term hand contact

Trade name/designation: KCL 720 Camapren®

Recommended material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 45 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HPLC-Eluent Methanol / 2-Propanol / Isooctan

Revision date: 22.05.2023

Product code: 34434

Page 8 of 15

sheet(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing  
Take off immediately all contaminated clothing and wash it before reuse.  
Wear fire resistant or flame retardant clothing.  
Wash hands and face before breaks and after work and take a shower if necessary.  
Draw up and observe skin protection programme.

#### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

#### Thermal hazards

No data available

#### Environmental exposure controls

Do not allow to enter into surface water or drains.  
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.  
Danger of explosion

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Methanol	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		<21 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		No data available
Viscosity / kinematic:		No data available
Water solubility:		No data available
Solubility in other solvents		
No data available		
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		No data available
Relative density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available
Particle characteristics:		No data available

### 9.2. Other information

#### Information with regard to physical hazard classes



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HPLC-Eluent Methanol / 2-Propanol / Isooctan**

Revision date: 22.05.2023

Product code: 34434

Page 9 of 15

**Explosive properties**

Vapours can form explosive mixtures with air.

**Sustaining combustion:**

No data available

**Self-ignition temperature**

Solid:

not applicable

Gas:

not applicable

**Oxidizing properties**

No data available

**Other safety characteristics**

**Evaporation rate:**

No data available

**Solvent separation test:**

No data available

**Solvent content:**

100%

**Solid content:**

No data available

**Sublimation point:**

No data available

**Softening point:**

No data available

**Pour point:**

No data available

**No data available:**

**Viscosity / dynamic:**

No data available

**Flow time:**

No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Highly flammable.

Vapours can form explosive mixtures with air.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.4. Conditions to avoid**

Vapours can form explosive mixtures with air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5. Incompatible materials**

Plastic articles

Zinc

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Toxicokinetics, metabolism and distribution**

Avoid exposure - obtain special instructions before use.

**Acute toxicity**

Toxic if swallowed.

Toxic in contact with skin.

Toxic if inhaled.

**ATEmix calculated**

ATE (oral) 132,5 mg/kg; ATE (dermal) 397,4 mg/kg; ATE (inhalation vapour) 3,970 mg/l; ATE (inhalation dust/mist) 0,6620 mg/l

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HPLC-Eluent Methanol / 2-Propanol / Isooctan**

Revision date: 22.05.2023

Product code: 34434

Page 10 of 15

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-56-1	methanol				
	oral	LD50 mg/kg 6000	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG)	Determination of the acute toxicity of t
	dermal	ATE mg/kg 300			
	inhalation (4 h) vapour	LC50 mg/l 128,2	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			
540-84-1	2,2,4-trimethylpentane				
	oral	LD50 mg/kg > 5000	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 mg/kg > 2000	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 mg/l > 33,52	Rat	Study report (1982)	OECD Guideline 403

**Irritation and corrosivity**

Causes serious eye irritation.  
Skin corrosion/irritation: Based on available data, the classification criteria are not met.  
Has degreasing effect on the skin.  
Irritation to respiratory tract

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Causes damage to organs. (methanol)  
May cause drowsiness or dizziness.  
eyes  
central nervous system

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

There are no data available on the mixture itself.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

There are no data available on the mixture itself.

**Other information**

Irritation to respiratory tract

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HPLC-Eluent Methanol / 2-Propanol / Isooctan**

Revision date: 22.05.2023

Product code: 34434

Page 11 of 15

Repeated exposure may cause skin dryness or cracking.

Causes damage to organs.

Organs affected:

Liver and kidney damage

eyes

heart

**Further information**

Irritant, Dizziness, Dizziness, Anaesthetic state, Agitation, Spasms, Inebriation, Vomiting, Headache,

Impairment of vision

Repeated exposure may cause skin dryness or cracking.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-56-1	methanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC 446,7 mg/l	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC 208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 10000 mg/l	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203
540-84-1	2,2,4-trimethylpentane					
	Acute fish toxicity	LC50 0,11 mg/l	96 h	Oncorhynchus mykiss	SIDS Initial Assessment Report For SIAM	OECD Guideline 203
	Acute algae toxicity	ErC50 2,943 mg/l	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EC50 0,4 mg/l	48 h	Daphnia magna	Publication (1986)	other: As described in: The evaluation o
	Fish toxicity	NOEC 0,82 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## HPLC-Eluent Methanol / 2-Propanol / Isooctan

Revision date: 22.05.2023

Product code: 34434

Page 12 of 15

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-56-1	methanol	-0,77
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05
540-84-1	2,2,4-trimethylpentane	4,08

**BCF**

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi
540-84-1	2,2,4-trimethylpentane	231	calculated	Other company data (

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

There are no data available on the mixture itself.

**Further information**

Do not allow to enter into surface water or drains.  
Avoid release to the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not allow to enter into surface water or drains.

**Contaminated packaging**

This material and its container must be disposed of as hazardous waste.  
Handle contaminated packages in the same way as the substance itself.  
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1992
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, propan-2-ol, 2,2,4-trimethylpentane)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+6.1
Classification code:	FT1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HPLC-Eluent Methanol / 2-Propanol / Isooctan**

Revision date: 22.05.2023

Product code: 34434

Page 13 of 15

Transport category: 2  
Hazard No: 336  
Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1992  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, propan-2-ol, 2,2,4-trimethylpentane)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3+6.1  
Classification code: FT1  
Special Provisions: 274 802  
Limited quantity: 1 L  
Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1992  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, propan-2-ol, 2,2,4-trimethylpentane)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3+6.1  
Special Provisions: 274  
Limited quantity: 1 L  
Excepted quantity: E2  
EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1992  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, propan-2-ol, 2,2,4-trimethylpentane)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3+6.1  
Special Provisions: A3  
Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 352  
IATA-max. quantity - Passenger: 1 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: Yes  
Danger releasing substance: 2,2,4-trimethylpentane

**14.6. Special precautions for user**

Warning: Combustible liquid. Toxic.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HPLC-Eluent Methanol / 2-Propanol / Isooctan

Revision date: 22.05.2023

Product code: 34434

Page 14 of 15

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 69, Entry 75

Information according to 2012/18/EU (SEVESO III): H2 ACUTE TOXIC

Additional information: P5c, E2

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

### SECTION 16: Other information

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Flam. Liq: Flammable liquid

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 3; H301	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H331	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 1; H370	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HPLC-Eluent Methanol / 2-Propanol / Isooctan

Revision date: 22.05.2023

Product code: 34434

Page 15 of 15

H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs (central nervous system, eyes).
H370	Causes damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*