

# Kupfer-di-Ammonium-EDTA-Lösung 0,1 mol/l in Pufferlösung pH 10

Revision date: 19.10.2023

Product code: 34563

Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Kupfer-di-Ammonium-EDTA-Lösung 0,1 mol/l in Pufferlösung pH 10

UFI:

#### PDQ2-S30R-H00P-U692

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

## Uses advised against

Do not use for private purposes (household).

#### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone	For Hazardous Materials [or Danger	rous Goods] Incidents Spill, Leak, Fire,
number:	Exposure, or Accident Call CHEMT	REC Day or Night Within USA and Canada:
	1-800-424-9300 Outside USA and 0	Canada: +1 703-741-5970 (collect calls
	accepted)	

#### **Further Information**

inapplicable, this product is a mixture REACH registration number see section 3

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

#### **GB CLP Regulation**

Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 Aquatic Acute 1; H400 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

**Pictograms:** 

## GB CLP Regulation

## Hazard components for labelling

Ammonia Signal word:

Danger





# Kupfer-di-Ammonium-EDTA-Lösung 0,1 mol/l in Pufferlösung pH 10

Revision date: 19.10.2023

Product code: 34563

Page 2 of 13

#### Hazard statements

H314	Causes severe skin burns and eye damage.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
Precautionary statemer	nts
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves and eye/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

# 2.3. Other hazards

No data available

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

## **Chemical characterization**

Mixtures in aqueous solution

#### Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulatio	n)			
1336-21-6	Ammonia			5 - < 10 %	
	215-647-6	215-647-6 007-001-01-2 01-2119488876-14			
	Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 2; H314 H400 H411				
67989-88-2	Ammonium [(ethylendinitrilo)tetra	5 - < 10 %			
	Skin Irrit. 2, Eye Irrit. 2; H315 H3	19			
12125-02-9	ammonium chloride			5 - < 10 %	
	235-186-4	017-014-00-8	01-2119487950-27		
	Acute Tox. 4, Eye Irrit. 2; H302 H319				

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc. Limits, M-factors and ATE				
1336-21-6	215-647-6	6 Ammonia			
	inhalation: LC50 = 4230 mg/l (vapours); oral: LD50 = 350 mg/kg STOT SE 3; H335: >= 5 - 100 Aquatic Acute 1; H400: M=10				
12125-02-9	235-186-4	35-186-4 ammonium chloride			
	dermal: LD50 =	= > 2000 mg/kg; oral: LD50 = 1410 mg/kg			

#### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures



# Kupfer-di-Ammonium-EDTA-Lösung 0,1 mol/l in Pufferlösung pH 10

Revision date: 19.10.2023

Product code: 34563

Page 3 of 13

## **General information**

Self-protection of the first aider Avoid contact with skin, eyes and clothes. Take off immediately all contaminated clothing.

## After inhalation

Provide fresh air. Call a physician immediately.

## After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

#### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant Corrosion Cough Dyspnoea Gastrointestinal complaints gastric perforation Unconsciousness Vomiting Circulatory collapse Spasms Pulmonary oedema Risk of serious damage to eyes.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

no restriction

#### 5.2. Special hazards arising from the substance or mixture

Hazardous combustion products In case of fire may be liberated: Nitrogen oxides (NOx)

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes. Avoid contact with skin, eyes and clothes.





# Safety Data Sheet

according to UK REACH Regulation

## Kupfer-di-Ammonium-EDTA-Lösung 0,1 mol/l in Pufferlösung pH 10

Revision date: 19.10.2023

Product code: 34563

Page 4 of 13

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### **General advice**

Do not breathe vapour/aerosol.

#### For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Consult an expert Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

## 6.3. Methods and material for containment and cleaning up

#### For containment

Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Collect in closed and suitable containers for disposal. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

## 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Use personal protection equipment. Use extractor hood (laboratory). Provide adequate ventilation. Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothes.

# Advice on protection against fire and explosion

Usual measures for fire prevention.

#### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.



# Safety Data Sheet

according to UK REACH Regulation

# Kupfer-di-Ammonium-EDTA-Lösung 0,1 mol/l in Pufferlösung pH 10

Revision date: 19.10.2023

Product code: 34563

Page 5 of 13

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

#### Further information on handling

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. Take off immediately all contaminated clothing and wash it before reuse.

# 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed. Corrosive to metals.

Unsuitable container/equipment material: Metal, Light metal

## Hints on joint storage

national regulations

## Further information on storage conditions

Keep cool. Protect from sunlight.

## 7.3. Specific end use(s)

Laboratory chemicals

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7664-41-7	Ammonia, anhydrous	25	18		TWA (8 h)	WEL
		35	25		STEL (15 min)	WEL
12125-02-9	Ammonium chloride, fume	-	10		TWA (8 h)	WEL
		-	20		STEL (15 min)	WEL



# Kupfer-di-Ammonium-EDTA-Lösung 0,1 mol/l in Pufferlösung pH 10

Revision date: 19.10.2023

Product code: 34563

Page 6 of 13

## **DNEL/DMEL** values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1336-21-6	Ammonia			
Worker DNEL	, long-term	inhalation	systemic	47,6 mg/m³
Worker DNEL	, acute	inhalation	systemic	47,6 mg/m <sup>3</sup>
Worker DNEL	, long-term	inhalation	local	14 mg/m³
Worker DNEL	, acute	inhalation	local	36 mg/m <sup>3</sup>
Worker DNEL	, long-term	dermal	systemic	6,8 mg/kg bw/day
Worker DNEL	, acute	dermal	systemic	6,8 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	23,8 mg/m <sup>3</sup>
Consumer DN	EL, acute	inhalation	systemic	23,8 mg/m <sup>3</sup>
Consumer DN	EL, long-term	inhalation	local	2,8 mg/m <sup>3</sup>
Consumer DN	EL, acute	inhalation	local	7,2 mg/m³
Consumer DN	EL, long-term	dermal	systemic	68 mg/kg bw/day
Consumer DN	EL, acute	dermal	systemic	68 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	6,8 mg/kg bw/day
Consumer DN	EL, acute	oral	systemic	6,8 mg/kg bw/day
12125-02-9	ammonium chloride			
Consumer DN	EL, long-term	inhalation	systemic	9,9 mg/m³
Consumer DN	EL, long-term	dermal	systemic	114 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	11,4 mg/kg bw/day
Worker DNEL	, long-term	inhalation	systemic	33,5 mg/m³
Worker DNEL	, long-term	dermal	systemic	190 mg/kg bw/day

**PNEC** values

CAS No	Substance				
Environment	Environmental compartment Value				
1336-21-6	Ammonia				
Freshwater		0,001 mg/l			
Freshwater (	intermittent releases)	0,007 mg/l			
Marine water 0,001 m					
12125-02-9	ammonium chloride				
Freshwater		1,2 mg/l			
Freshwater (	intermittent releases)	1,2 mg/l			
Marine wate	ſ	11,2 mg/l			
Micro-organisms in sewage treatment plants (STP)		16,2 mg/l			
Soil		0,163 mg/kg			

## 8.2. Exposure controls

## Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

## Individual protection measures, such as personal protective equipment



## Kupfer-di-Ammonium-EDTA-Lösung 0,1 mol/l in Pufferlösung pH 10

Revision date: 19.10.2023

Product code: 34563

Page 7 of 13

## Eye/face protection

goggles Wear eye/face protection.

## Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact Trade name/designation: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Trade name/designation: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing. Wash hands before breaks and after work.

#### **Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation

# Thermal hazards

No data available

## **Environmental exposure controls**

Do not allow to enter into surface water or drains.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	blue	
Odour:	stinging	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and		No data available
boiling range:		
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available



Kupfer-di-Ammonium-E	DTA-Lösung 0,1 mol/l in Pufferlösung pH 10	0
Revision date: 19.10.2023	Product code: 34563	Page 8 of 13
Auto-ignition temperature:	No data available	
Decomposition temperature:	No data available	
pH-Value:	10,7	
Viscosity / kinematic:	No data available	
Water solubility:	completely miscible	
Solubility in other solvents		
No data available		
Dissolution rate:	No data available	
Partition coefficient n-octanol/water:	No data available	
Dispersion stability:	No data available	
Vapour pressure:	No data available	
Vapour pressure:	No data available	
Density (at 20 °C):	1,0082 g/cm <sup>3</sup>	
Relative density:	No data available	
Bulk density:	No data available	
Relative vapour density:	No data available	
Particle characteristics:	No data available	
9.2. Other information		
Information with regard to physical hazard class	ses	
Explosive properties		
No data available		
Sustaining combustion:	No data available	
Self-ignition temperature		
Solid:	No data available	
Gas:	No data available	
Oxidizing properties		
No data available		
Other safety characteristics		
Evaporation rate:	No data available	
Solvent separation test:	No data available	
Solvent content:	No data available	
Solid content:	No data available	
Sublimation point:	No data available	
Softening point:	No data available No data available	
Pour point: No data available:		
Viscosity / dynamic:	No data available	
Flow time:	No data available	
Further Information		
No data available		

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No data available

# 10.2. Chemical stability

Protect against: Heat

## 10.3. Possibility of hazardous reactions

Oxidising agent, mercury (Hg)., Oxygen, Hydrogen peroxide, Acid, Chlorine, Heavy metals, Nitric acid, Bromine, Hydrogen bromide (HBr), Hydrochloric gas, Nitrogen oxides (NOx), Hydrogen fluoride, Carbon dioxide,



# Kupfer-di-Ammonium-EDTA-Lösung 0,1 mol/l in Pufferlösung pH 10

Revision date: 19.10.2023

Product code: 34563

Page 9 of 13

## 10.4. Conditions to avoid

Heat

#### 10.5. Incompatible materials

Metal, Aluminium, Lead nickel, silver, Zinc Copper

# 10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

## Further information

No data available

## **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in GB CLP Regulation

## Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

#### ATEmix calculated

ATE (oral) 25224 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name	Chemical name							
	Exposure route	Dose		Species	Source	Method			
1336-21-6	Ammonia								
	oral	oral LD50 350 Rat Journal of Industrial OECD Guidel mg/kg Hygiene and Toxico							
	inhalation (1 h) vapour	LC50	4230 mg/l	Mouse	Bull. Environm. Contam. Toxicol, 1982, 2	Assessment of acute inhalation toxicity			
12125-02-9	ammonium chloride	-							
	oral	LD50 mg/kg	1410	Rat	Other company data (1983)	other: not mentioned			
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2010)	EU Method B.3			

## Irritation and corrosivity

Causes severe skin burns and eye damage. Causes serious eye damage.

cause concus eye damag

# Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

# STOT-single exposure

May cause respiratory irritation. (Ammonia)

## STOT-repeated exposure

Based on available data, the classification criteria are not met.



# Kupfer-di-Ammonium-EDTA-Lösung 0,1 mol/l in Pufferlösung pH 10

Revision date: 19.10.2023	Product code: 34563	Page 10 of 13
Aspiration hazard Based on available data, the class	sification criteria are not met.	

## Information on likely routes of exposure

There are no data available on the preparation/mixture itself.

## Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

## Additional information on tests

There are no data available on the preparation/mixture itself.

## **Practical experience**

There are no data available on the preparation/mixture itself.

# 11.2. Information on other hazards

## Endocrine disrupting properties

There are no data available on the preparation/mixture itself.

## Other information

Irritant Corrosion Cough Dyspnoea Gastrointestinal complaints gastric perforation Unconsciousness Vomiting Circulatory collapse Spasms Pulmonary oedema Risk of serious damage to eyes.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

There are no data available on the mixture itself.



# Kupfer-di-Ammonium-EDTA-Lösung 0,1 mol/l in Pufferlösung pH 10

Revision date: 19.10.2023

Product code: 34563

Page 11 of 13

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method		
1336-21-6	Ammonia								
	Acute fish toxicity	LC50 3,4 mg/l	0,75 -	96 h	Pimephales promelas	Trans Amer Fish Soc; 112 (5). 1983. 705-	Assessment of acute toxicity in the fath		
	Acute crustacea toxicity	EC50	101 mg/l	48 h	Daphnia magna	Environ. Toxicol. Chem. 5: 443-447 (1986	other: ASTM E729-80		
	Fish toxicity	NOEC	1,2 mg/l	61 d	Oncorhynchus gorbuscha	Fish. Bull. 78(3): 641-648 (1980)	OECD Guideline 210		
12125-02-9	ammonium chloride								
	Acute fish toxicity	LC50	209 mg/l	96 h	Cyprinus carpio	Indian J. Environ. Health, 17, 140-146,	other: E03-05:APHA, AWWA & WPCF		
	Acute crustacea toxicity	EC50	101 mg/l	48 h	Daphnia magna	Env. Tox. Chem. 5, 443-447 (1986) (1986)	other: ASTM E729-80		
	Fish toxicity	NOEC mg/l	11,8	28 d	Pimephales promelas	Env.Tox. Chem. 5, 437-442 (1986) (1986)	other: - American Society for Testing an		
	Algae toxicity	NOEC mg/l	26,8	10 d	Navicula sp.	Mar. Biol. 43(4), 307-315, (1977) (1977)	no data		
	Crustacea toxicity	NOEC mg/l	14,6	21 d	Daphnia magna	Env. Tox. Chem. 5, 443-447 (1986) (1986)	other: not mentioned		
	Acute bacteria toxicity	(EC50 mg/l)	1618	0,5 h	activated sludge, domestic	Study report (1988)	OECD Guideline 209		

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

## 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1336-21-6	Ammonia	-1,38

## 12.4. Mobility in soil

There are no data available on the mixture itself.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# 12.7. Other adverse effects

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

## Further information

Do not allow to enter into surface water or drains.

Discharge into the environment must be avoided.



# Kupfer-di-Ammonium-EDTA-Lösung 0,1 mol/l in Pufferlösung pH 10

Revision date: 19.10.2023

Product code: 34563

Page 12 of 13

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

## **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not allow to enter into surface water or drains.

#### Contaminated packaging

Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.			
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.			
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.			
14.4. Packing group:	No dangerous good in sense of this transport regulation.			
Inland waterways transport (ADN)				
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.			
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.			
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.			
14.4. Packing group:	No dangerous good in sense of this transport regulation.			
Marine transport (IMDG)				
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.			
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.			
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.			
14.4. Packing group:	No dangerous good in sense of this transport regulation.			
Air transport (ICAO-TI/IATA-DGR)				
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.			
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.			
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.			
14.4. Packing group:	No dangerous good in sense of this transport regulation.			
14.6. Special precautions for user				
No dangerous good in sense of this transport regulation.				

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information	
Restrictions on use (REACH, annex XVII):	
Entry 3	
Information according to 2012/18/EU (SEVESO III):	E1 Hazardous to the Aquatic Environment
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	2 - obviously hazardous to water



# Kupfer-di-Ammonium-EDTA-Lösung 0,1 mol/l in Pufferlösung pH 10

Revision date: 19.10.2023

Product code: 34563

Page 13 of 13

## **SECTION 16: Other information**

## Abbreviations and acronyms

Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation STOT SE: Specific target organ toxicity - single exposure Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

## Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

	· · · · · · · · · · · · · · · · · · ·
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)