

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Salzsäure 0,5 mol/l in Methanol

Revision date: 16.07.2024

Product code: 01263

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Salzsäure 0,5 mol/l in Methanol

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Uses advised against**

Do not use for private purposes (household).

**1.3. Details of the supplier of the safety data sheet**

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

**1.4. Emergency telephone number:**

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

**Further Information**

This product is a mixture. REACH Registration Number see section 3.

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Met. Corr. 1; H290

Flam. Liq. 2; H225

Acute Tox. 3; H301

Acute Tox. 3; H311

Acute Tox. 3; H331

STOT SE 1; H370

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Hazard components for labelling**

methanol

**Signal word:** Danger**Pictograms:**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Salzsäure 0,5 mol/l in Methanol**

Revision date: 16.07.2024

Product code: 01263

Page 2 of 13

**Hazard statements**

H225 Highly flammable liquid and vapour.  
H290 May be corrosive to metals.  
H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.  
H370 Causes damage to organs.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.  
P403+P235 Store in a well-ventilated place. Keep cool.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-56-1	methanol			95 - < 100 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			
7647-01-0	Hydrochloric acid			1 - < 5 %
	231-595-7	017-002-01-X	01-2119484862-27	
	Skin Corr. 1B, STOT SE 3; H314 H335			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-56-1	200-659-6	methanol	95 - < 100 %
	inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10		
7647-01-0	231-595-7	Hydrochloric acid	1 - < 5 %
	Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25 STOT SE 3; H335: >= 10 - 100		

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

First aider: Pay attention to self-protection!  
Remove affected person from the danger area and lay down.

**After inhalation**

Provide fresh air.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Salzsäure 0,5 mol/l in Methanol

Revision date: 16.07.2024

Product code: 01263

Page 3 of 13

If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.

#### After contact with skin

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.  
Call a physician immediately.

#### After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
Consult an ophthalmologist.

#### After ingestion

Provide fresh air.  
Call a physician immediately.  
Notes for the doctor : Methanol

#### **4.2. Most important symptoms and effects, both acute and delayed**

Irritant, Dizziness, Dizziness, Anaesthetic state, Agitation, Spasms, Inebriation, Vomiting, Headache,  
Impairment of vision  
Repeated exposure may cause skin dryness or cracking.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

No data available

## SECTION 5: Firefighting measures

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

#### **Unsuitable extinguishing media**

no restriction

### **5.2. Special hazards arising from the substance or mixture**

Combustible liquids  
Highly flammable.  
Hazardous combustion products  
In case of fire may be liberated:  
Carbon dioxide, Carbon monoxide  
Hydrogen chloride (HCl)  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Beware of reignition.  
Heating causes rise in pressure with risk of bursting.

### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.  
Wear full chemical protective clothing.  
In case of fire and/or explosion do not breathe fumes.

#### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Suppress gases/vapours/mists with water spray jet.  
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **General advice**

Keep away from sources of ignition - No smoking.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Salzsäure 0,5 mol/l in Methanol

Revision date: 16.07.2024

Product code: 01263

Page 4 of 13

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

#### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Salzsäure 0,5 mol/l in Methanol**

Revision date: 16.07.2024

Product code: 01263

Page 5 of 13

drink. The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

**Further information on storage conditions**

Keep cool. Protect from sunlight.

Corrosive to metals.

Unsuitable container/equipment material: Metal

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
7647-01-0	Hydrogen chloride	5	8		TWA (8 h)	
		10	15		STEL (15 min)	
67-56-1	Methyl alcohol	200	260		TWA (8 h)	

**Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Salzsäure 0,5 mol/l in Methanol

Revision date: 16.07.2024

Product code: 01263

Page 6 of 13

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
67-56-1	methanol			
Consumer DNEL, acute		inhalation	systemic	50 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	systemic	260 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	260 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	260 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	260 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	40 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	50 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	50 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	50 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day
7647-01-0	Hydrochloric acid			
Worker DNEL, long-term		inhalation	local	8 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	15 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	8 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	15 mg/m <sup>3</sup>

#### PNEC values

CAS No	Substance	Value
67-56-1	methanol	
Freshwater		20,8 mg/l
Freshwater (intermittent releases)		1540 mg/l
Marine water		2,08 mg/l
Freshwater sediment		77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		100 mg/kg

## 8.2. Exposure controls

### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe gas/fumes/vapour/spray.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

goggles

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Salzsäure 0,5 mol/l in Methanol

Revision date: 16.07.2024

Product code: 01263

Page 7 of 13

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

#### Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing. Material, acid-resistant

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

#### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Methanol	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		~ 11 °C
Auto-ignition temperature:		No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Salzsäure 0,5 mol/l in Methanol

Revision date: 16.07.2024

Product code: 01263

Page 8 of 13

Decomposition temperature:	No data available
pH-Value:	acidic
Viscosity / kinematic:	No data available
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,81632 g/cm <sup>3</sup>
Bulk density:	No data available
Relative vapour density:	No data available

#### **9.2. Other information**

##### **Information with regard to physical hazard classes**

###### Explosive properties

Vapours can form explosive mixtures with air.

###### Sustaining combustion:

Sustaining combustion

###### Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

###### Oxidizing properties

not determined

##### **Other safety characteristics**

###### Evaporation rate:

No data available

###### Solvent separation test:

No data available

###### Solvent content:

No data available

###### Solid content:

No data available

###### Sublimation point:

No data available

###### Softening point:

No data available

###### Pour point:

No data available

###### No data available:

###### Viscosity / dynamic:

No data available

###### Flow time:

No data available

##### **Further Information**

No data available

## SECTION 10: Stability and reactivity

### **10.1. Reactivity**

Highly flammable.

Vapours can form explosive mixtures with air.

Corrosive to metals.

### **10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

### **10.3. Possibility of hazardous reactions**

Oxidising agent

### **10.4. Conditions to avoid**

Vapours can form explosive mixtures with air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### **10.5. Incompatible materials**

Metal

Plastic articles



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Salzsäure 0,5 mol/l in Methanol**

Revision date: 16.07.2024

Product code: 01263

Page 9 of 13

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Toxic if swallowed.  
Toxic in contact with skin.  
Toxic if inhaled.

**ATEmix calculated**

ATE (oral) 102,40 mg/kg; ATE (dermal) 307,10 mg/kg; ATE (inhalation vapour) 3,0700 mg/l; ATE (inhalation dust/mist) 0,5120 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-56-1	methanol				
	oral	LD50 6000 mg/kg	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG)	Determination of the acute toxicity of t
	dermal	ATE 300 mg/kg			
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.  
Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.  
Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Causes damage to organs. (methanol)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Salzsäure 0,5 mol/l in Methanol**

Revision date: 16.07.2024

Product code: 01263

Page 10 of 13

**11.2. Information on other hazards**

**Other information**

Irritation to respiratory tract  
Causes damage to organs.  
Organs affected:  
Liver and kidney damage,  
, Irreversible damage to the optic nerve.

**Further information**

Irritant, Dizziness, Dizziness, Anaesthetic state, Agitation, Spasms, Inebriation, Vomiting, Headache,  
Impairment of vision  
Repeated exposure may cause skin dryness or cracking.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-56-1	methanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC 446,7 mg/l	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC 208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi
7647-01-0	Hydrochloric acid					
	Acute fish toxicity	LC50 862 mg/l	96 h	Leuciscus idus		

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-56-1	methanol	-0,77

**BCF**

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Salzsäure 0,5 mol/l in Methanol**

Revision date: 16.07.2024

Product code: 01263

Page 11 of 13

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Discharge into the environment must be avoided.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not allow to enter into surface water or drains.

**Contaminated packaging**

This material and its container must be disposed of as hazardous waste.  
Handle contaminated packages in the same way as the substance itself.  
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 3286
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, Hydrochloric acid)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+6.1+8
Classification code:	FTC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	368
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 3286
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, Hydrochloric acid)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+6.1+8
Classification code:	FTC
Special Provisions:	274 802
Limited quantity:	1 L
Excepted quantity:	E2

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 3286
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, Hydrochloric acid)
<b>14.3. Transport hazard class(es):</b>	3

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Salzsäure 0,5 mol/l in Methanol

Revision date: 16.07.2024

Product code: 01263

Page 12 of 13

<b>14.4. Packing group:</b>	II
Hazard label:	3+6.1+8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-C

#### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number or ID number:</b>	UN 3286
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, Hydrochloric acid)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+6.1+8
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y340
Excepted quantity:	E2
IATA-packing instructions - Passenger:	352
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	363
IATA-max. quantity - Cargo:	5 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Warning: Combustible liquid. Toxic.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 69

Information according to Directive 2012/18/EU (SEVESO III): H2 ACUTE TOXIC

Additional information: P5c

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 9,12.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Salzsäure 0,5 mol/l in Methanol

Revision date: 16.07.2024

Product code: 01263

Page 13 of 13

#### Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals  
 Flam. Liq: Flammable liquid  
 Acute Tox: Acute toxicity  
 Skin Corr: Skin corrosion  
 STOT SE: Specific target organ toxicity - single exposure  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 3; H301	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H331	Calculation method
STOT SE 1; H370	Calculation method

#### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.  
 H290 May be corrosive to metals.  
 H301 Toxic if swallowed.  
 H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.  
 H311 Toxic in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H331 Toxic if inhaled.  
 H335 May cause respiratory irritation.  
 H370 Causes damage to organs.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*