

Hydrochloric acid 0.1 mol/l - 0.1 N solution dissolved in 7 parts of 1-butanol and 3 parts of ethyl					
Revision date: 24.09.2024	Product code: 01360		Page 1 of 14		
SECTION 1: Identification of the s	ubstance/mixture and of the compa	iny/undertaking			
<u>1.1. Product identifier</u> Hydrochloric acid 0.1 mol/l - 0.1	N solution dissolved in 7 parts of 1-buta	nol and 3 parts of ethyl			
UFI:	8SR3-H0FW-W002-FE0X				
1.2. Relevant identified uses of the su	ubstance or mixture and uses advised a	against			
	nces as such or in preparations at industr in (administration, education, entertainme				
Uses advised against Do not use for private purposes	(household).				
1.3. Details of the supplier of the safe	ety data sheet				
Company name: Street:	AnalytiChem GmbH ACD Stempelstraße 6				
Place:	D-47167 Duisburg				
Telephone:	0203/5194-0	Telefax:0203/5194-290			
E-mail: Contact person: E-mail: Internet: Responsible Department:	info@analytichem.de Abteilung Produktsicherheit produktsicherheit@analytichem.de www.analytichem.de Abteilung Produktsicherheit	Telephone: 0203/5194-107/117			
<u>1.4. Emergency telephone</u> number:	For Hazardous Materials [or Dangerou Exposure, or Accident Call CHEMTRE 1-800-424-9300 Outside USA and Car accepted)	C Day or Night Within USA and Canada	a:		
Further Information This product is a mixture. REAC	CH Registration Number see section 3.				

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Flam. Liq. 3; H226 Acute Tox. 3; H331 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 1B; H360FD STOT SE 3; H335 H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008 Hazard components for labelling butanol 2-ethoxyethanol Signal word: Danger



Hydrochloric acid 0.1 mol/l - 0.1 N solution dissolved in 7 parts of 1-butanol and 3 parts of

ethyl

Revision date: 24.09.2024
Product code: 01360
Page 2 of 14

Pictograms:
Image: Imag

Hazard statements

azaru statements		
H226	Flammable liquid and vapour.	
H290	May be corrosive to metals.	
H302	Harmful if swallowed.	
H315	Causes skin irritation.	
H318	Causes serious eye damage.	
H331	Toxic if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H360FD	May damage fertility. May damage the unborn child.	

Precautionary statements

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308	IF exposed or concerned:
P310	Immediately call a POISON CENTER/doctor.
P403+P235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification (Regulation (EC) No 1272/2008)				
71-36-3	butanol			65 - < 70 %	
	200-751-6	603-004-00-6	01-2119484630-38		
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H302 H315 H318 H335 H336				
110-80-5	2-ethoxyethanol			30 - < 35 %	
	203-804-1	603-012-00-X	01-2119560582-38		
	Flam. Liq. 3, Repr. 1B, Acute Tox. 3, Acute Tox. 4; H226 H360FD H331 H302				

Full text of H and EUH statements: see section 16.



Hydrochloric acid 0.1 mol/I - 0.1 N solution dissolved in 7 parts of 1-butanol and 3 parts of

ethyl

Revision date: 24.09.2024

Product code: 01360

Page 3 of 14

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	imits, M-factors and ATE	
71-36-3	200-751-6	butanol	65 - < 70 %
	dermal: LD50 =	: ca. 3430 mg/kg; oral: LD50 = ca. 2292 mg/kg	
110-80-5	203-804-1	2-ethoxyethanol	30 - < 35 %
	inhalation: LC5 3000 mg/kg	0 = 4000 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: LD50 =	

Further Information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: 2-ethoxyethanol; ethylene glycol monoethyl ether

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Risk of serious damage to eyes. Irritant corrosive Vapours may cause drowsiness and dizziness. Cough Dyspnoea Cardiac arrhythmias Circulatory collapse Vomiting Inebriation Dizziness Anaesthetic state Respiratory complaints

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures



Hydrochloric acid 0.1 mol/l - 0.1 N solution dissolved in 7 parts of 1-butanol and 3 parts of

ethyl

Revision date: 24.09.2024

Product code: 01360

Page 4 of 14

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Foam Extinguishing powder

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide Hydrogen chloride (HCI) In case of warming: Vapours are heavier than air, spread along floors and form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes. Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Consult an expert Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up



Hydrochloric acid 0.1 mol/l - 0.1 N solution dissolved in 7 parts of 1-butanol and 3 parts of

ethyl

360

Page 5 of 14

Revision date: 24.09.2024

Product code: 01360

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Use extractor hood (laboratory). Do not breathe vapour/aerosol. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a place accessible by authorized persons only.

Further information on storage conditions

Protect from sunlight. Unsuitable container/equipment material: Metal Corrosive to metals.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



Hydrochloric acid 0.1 mol/l - 0.1 N solution dissolved in 7 parts of 1-butanol and 3 parts of

Product code: 01360

ethyl

Page 6 of 14

Occupational exposure limits

Revision date: 24.09.2024

CAS No	Substance	ppm	mg/m³	fib/cm ³	Category	Origin
110-80-5	2-Ethoxyethanol	5	18		TWA (8 h)	
71-36-3	Butan-1-ol	20	-		TWA (8 h)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
110-80-5	2-Ethoxyethanol	2-Ethoxyacetic acid	50 mg/L		Measure at end of workweek

DNEL/DMEL values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
71-36-3	butanol						
Worker DNEL,	long-term	inhalation	local	310 mg/m³			
Consumer DNEL, long-term		inhalation	systemic	55,357 mg/m³			
Consumer DN	EL, long-term	inhalation	local	155 mg/m³			
Consumer DN	EL, long-term	dermal	systemic	3,125 mg/kg bw/day			
Consumer DN	EL, long-term	oral	systemic	1,562 mg/kg bw/day			

PNEC values

CAS No	Substance				
Environmen	tal compartment	Value			
71-36-3	butanol				
Freshwater 0,082 mg/l					
Freshwater (intermittent releases) 2,25 mg/l					
Marine wate	0,008 mg/l				
Freshwater sediment 0,32					
Marine sediment 0,03					
Micro-organ	2476 mg/l				
Soil		0,017 mg/kg			

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is



Revision date: 24.09.2024

according to Regulation (EC) No 1907/2006

Hydrochloric acid 0.1 mol/l - 0.1 N solution dissolved in 7 parts of 1-butanol and 3 parts of

Product code: 01360

ethyl

Page 7 of 14

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact Trade name/designation: KCL 897 Butoject® Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Trade name/designation: KCL 730 Camatril® Velours Suitable material: NBR (Nitrile rubber) 0,4 mm Wearing time with occasional contact (splashes): > 240 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear fire resistant or flame retardant clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold:	Liquid colourless characteristic No data available	
Melting point/freezing point: Boiling point or initial boiling point and		No data available ∼ 116 °C
boiling range: Flammability: Lower explosion limits:		No data available No data available
Upper explosion limits: Flash point: Auto-ignition temperature:		No data available ~ 35 °C No data available
Decomposition temperature:		No data available



Hydrochloric acid 0.1 mol/l - 0.1 N solution dissolved in 7 parts of 1-butanol and 3 parts of ethyl					
Revision date: 24.09.2024	Product code: 01360	Page 8 of 14			
pH-Value:	No data available				
Viscosity / kinematic:	No data available				
Water solubility:	No data available				
Solubility in other solvents					
No data available					
Dissolution rate:	No data available				
Partition coefficient n-octanol/water:	No data available				
Dispersion stability:	No data available				
Vapour pressure:	No data available				
Vapour pressure:	No data available				
Density:	No data available				
Relative density:	No data available				
Bulk density:	No data available				
Relative vapour density:	No data available				
Particle characteristics:	No data available				
9.2. Other information					
Information with regard to physical hazard classes	•				
Explosive properties					
In case of warming:					
Vapours are heavier than air, spread along floors	and form explosive mixtures with air.				
Sustaining combustion:	Sustaining combustion				
Self-ignition temperature					
Solid:	No data available				
Gas:	No data available				
Oxidizing properties					
No data available					
Other safety characteristics					
Evaporation rate:	No data available				
Solvent separation test:	No data available				
Solvent content:	No data available				
Solid content:	No data available				
Sublimation point:	No data available				
Softening point:	No data available				
Pour point:	No data available				
	No data available				
Viscosity / dynamic:	No data available				
Flow time:	No data available				
Further Information					
Corrosive to metals.					
SECTION 10: Stability and reactivity					

10.1. Reactivity

In case of warming: Vapours may form explosive mixtures with air. Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent Alkali metals



Hydrochloric acid 0.1 mol/l - 0.1 N solution dissolved in 7 parts of 1-butanol and 3 parts of

ethyl

Revision date: 24.09.2024

Product code: 01360

Page 9 of 14

Alkaline earth metal. Acid chlorides, inorganic Reducing agent Aluminium

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles Rubber articles Metal

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Toxic if inhaled.

Harmful if swallowed.

ATEmix calculated

ATE (oral) 502,5 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 9,150 mg/l; ATE (inhalation dust/mist) 1,524 mg/l

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
71-36-3	butanol						
	oral	LD50 mg/kg	ca. 2292	Rat	Study report (1967)	OECD Guideline 401	
	dermal	LD50 mg/kg	ca. 3430	Rabbit	Study report (1951)	OECD Guideline 402	
110-80-5	2-ethoxyethanol						
	oral	LD50 mg/kg	3000	rat, guinea pig	J Int Hyg Toxicol 23	Method: other: Acute	
	inhalation (4 h) vapour	LC50	4000 mg/l	Rat	A.M.A. Arch. Ind. He	Method: other: Acute	
	inhalation dust/mist	ATE	0,5 mg/l				

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

May damage fertility. May damage the unborn child. (2-ethoxyethanol) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met.



Revision date: 24.09.2024	Product code: 01360	Page 10 of 14
STOT-single exposure May cause respiratory irritation. (butanol) May cause drowsiness or dizziness. (butano)	
STOT-repeated exposure Based on available data, the classification cr	iteria are not met.	
Aspiration hazard Based on available data, the classification cr	iteria are not met.	
Information on likely routes of exposure There are no data available on the mixture its	self.	
Specific effects in experiment on an animal There are no data available on the mixture its	self.	
Additional information on tests There are no data available on the mixture its	self.	
Practical experience There are no data available on the mixture its	self.	
11.2. Information on other hazards		
Endocrine disrupting properties There are no data available on the mixture its	self.	
Other information Vomiting Observe risk of aspiration if vomiting occurs. Liver and kidney damage		
Further information Risk of serious damage to eyes. Irritant corrosive Vapours may cause drowsiness and dizzines Cough Dyspnoea Cardiac arrhythmias Circulatory collapse Vomiting Inebriation Dizziness Anaesthetic state Respiratory complaints	SS.	
SECTION 12: Ecological information		
12.1. Toxicity		



Revision date: 24.09.2024

according to Regulation (EC) No 1907/2006

Hydrochloric acid 0.1 mol/l - 0.1 N solution dissolved in 7 parts of 1-butanol and 3 parts of

Product code: 01360

ethyl

Page 11 of 14

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
71-36-3	butanol						
	Acute fish toxicity	LC50 mg/l	1376	96 h	Pimephales promelas	Study report (1998)	OECD Guideline 203
	Acute algae toxicity	ErC50	225 mg/l	96 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	1328	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202
	Crustacea toxicity	NOEC	4,1 mg/l	21 d	Daphnia magna	Study report (1996)	OECD Guideline 211
110-80-5	5 2-ethoxyethanol						
	Acute fish toxicity	LC50 mg/l	> 10000	96 h	Lepomis macrochirus, and Menidia beryllina	Dawson, G.W. et al.,	Method: other: Acute
	Acute bacteria toxicity	EC50 mg/l()	4,79	0,5 h	Photobacterium phosphoreum	Water Poll. Res. J.	Method: other: Micro

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

110-80-5	2-ethoxyethanol	0,32
71-36-3	butanol	10
CAS No	Chemical name	Log Pow

BCF

CAS No	Chemical name	BCF	Species	Source
71-36-3	butanol	3,16		QSAR (2017)

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.



Hydrochloric acid 0.1 mol/l - 0.1 N solution dissolved in 7 parts of 1-butanol and 3 parts of

ethyl

Revision date: 24.09.2024

Land transport (ADR/RID)

Product code: 01360

Page 12 of 14

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)	
14.1. UN number or ID number:	UN 1992
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (butanol, 2-ethoxyethanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3+6.1
Classification code:	FT1
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	36
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1992
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (butanol, 2-ethoxyethanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3+6.1
Classification code:	FT1
Special Provisions:	274 802
Limited quantity:	5 L
Excepted quantity:	E1
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 1992
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (butanol, 2-ethoxyethanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3+6.1
Special Provisions:	223, 274
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-D
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	UN 1992
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (butanol, 2-ethoxyethanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3+6.1
Special Provisions:	A3
Limited quantity Passenger:	2 L
Passenger LQ:	Y343
Excepted quantity:	E1
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
· · · -	



Hydrochloric acid 0.1 mol/l - 0.1 N solution dissolved in 7 parts of 1-butanol and 3 parts of ethyl		
Revision date: 24.09.2024	Product code: 01360	Page 13 of 14
IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	366 220 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regu	lations/legislation specific for the substance or mixture	
EU regulatory information		
Authorisations (REACH, annex XIV):		
Substances of very high concern, SVH	C (REACH, article 59):	
2-ethoxyethanol		
Restrictions on use (REACH, annex XVII):		
Entry 3, Entry 30, Entry 40		
Information according to Directive 2012/18/EU (SEVESO III):	H2 ACUTE TOXIC	
Additional information:	P5c	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according work protection guideline' (94/33/EC). Observe employmen under the Maternity Protection Directive (92/85/EEC) for ex nursing mothers.	t restrictions
Water hazard class (D):	2 - obviously hazardous to water	

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,12.

Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals
Flam. Liq: Flammable liquid
Acute Tox: Acute toxicity
Skin Irrit: Skin irritation
Eye Dam: Eye damage
Repr: Reproductive toxicity
STOT SE: Specific target organ toxicity - single exposure

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 3; H331	Calculation method
Acute Tox. 4; H302	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Repr. 1B; H360FD	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text) H226

Flammable liquid and vapour.



Hydrochloric acid 0.1 mol/l - 0.1 N solution dissolved in 7 parts of 1-butanol and 3 parts of

according to Regulation (EC) No 1907/2006

ethyl

Page 14 of 14

Revision date: 24.09.2024	Product code: 01360
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360FD	May damage fertility. May damage the unborn child.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)