

Safety Data Sheet

according to UK REACH Regulation

Sulfuric acid reagent approx. 1 mol/l (orange channel) for determination of silicate with ABB 8241

Revision date: 08.03.2023

Product code: 01888

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Sulfuric acid reagent approx. 1 mol/l (orange channel) for determination of silicate with ABB 8241

UFI: N375-R0WH-M00C-QNQ0

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.3. Details of the supplier of the safety data sheet**

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**Met. Corr. 1; H290
Skin Irrit. 2; H315
Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**sulphuric acid
citric acid

Signal word: Danger

Pictograms:**Hazard statements**H290 May be corrosive to metals.
H315 Causes skin irritation.
H318 Causes serious eye damage.**Precautionary statements**P280 Wear protective gloves.
P280
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Safety Data Sheet

according to UK REACH Regulation

Sulfuric acid reagent approx. 1 mol/l (orange channel) for determination of silicate with ABB 8241

Revision date: 08.03.2023

Product code: 01888

Page 2 of 10

P310 Immediately call a POISON CENTER/doctor.
P302+P352 IF ON SKIN: Wash with plenty of water.
P406 Store in a corrosion-resistant container with a resistant inner liner.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
7664-93-9	sulphuric acid			5 - < 10 %
	231-639-5	016-020-00-8	01-2119458838-20	
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318			
77-92-9	citric acid			1 - < 5 %
	201-069-1		01-2119457026-42	
	Eye Irrit. 2, STOT SE 3; H319 H335			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
7664-93-9	231-639-5	sulphuric acid	5 - < 10 %
	oral: LD50 = 2140 mg/kg Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15		
77-92-9	201-069-1	citric acid	1 - < 5 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 5400 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Safety Data Sheet

according to UK REACH Regulation

Sulfuric acid reagent approx. 1 mol/l (orange channel) for determination of silicate with ABB 8241

Revision date: 08.03.2023

Product code: 01888

Page 3 of 10

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

No special environmental measures are necessary. Clean contaminated articles and floor according to the environmental legislation.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Safety Data Sheet

according to UK REACH Regulation

Sulfuric acid reagent approx. 1 mol/l (orange channel) for determination of silicate with ABB 8241

Revision date: 08.03.2023

Product code: 01888

Page 4 of 10

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Unsuitable container/equipment material: Metal.

Hints on joint storage

No special measures are necessary.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
7664-93-9	Sulphuric acid (mist)	-	0.05		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
7664-93-9	sulphuric acid			
Worker DNEL, long-term		inhalation	local	0,05 mg/m ³
Worker DNEL, acute		inhalation	local	0,1 mg/m ³

PNEC values

CAS No	Substance	Value
Environmental compartment		
7664-93-9	sulphuric acid	
Freshwater		0,003 mg/l
Marine water		0 mg/l
Freshwater sediment		0,002 mg/kg
Marine sediment		0,002 mg/kg
Micro-organisms in sewage treatment plants (STP)		8,8 mg/l
77-92-9	citric acid	
Freshwater		0,44 mg/l
Marine water		0,044 mg/l
Freshwater sediment		34,6 mg/kg
Marine sediment		3,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		33,1 mg/kg

8.2. Exposure controls

Safety Data Sheet

according to UK REACH Regulation

Sulfuric acid reagent approx. 1 mol/l (orange channel) for determination of silicate with ABB 8241

Revision date: 08.03.2023

Product code: 01888

Page 5 of 10

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	odourless	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		100 °C
Flammability:		not applicable not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		X
Decomposition temperature:		not determined
pH-Value:		not determined
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		<=1100 hPa
(at 50 °C)		
Density:		1,06500 g/cm ³
Relative vapour density:		not determined

9.2. Other information

Information with regard to physical hazard classes

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined

Safety Data Sheet

according to UK REACH Regulation

Sulfuric acid reagent approx. 1 mol/l (orange channel) for determination of silicate with ABB 8241

Revision date: 08.03.2023

Product code: 01888

Page 6 of 10

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

Keep away from: Metal.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7664-93-9	sulphuric acid				
	oral	LD50 2140 mg/kg	Rat	Am Ind Hyg Assoc J. 1969 Sep-Oct; 30(5):	The study was performed as part of a ser
77-92-9	citric acid				
	oral	LD50 5400 mg/kg	Mouse	Study report (1981)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2006)	OECD Guideline 402

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

Safety Data Sheet

according to UK REACH Regulation

**Sulfuric acid reagent approx. 1 mol/l (orange channel) for determination of silicate with ABB
8241**

Revision date: 08.03.2023

Product code: 01888

Page 7 of 10

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
7664-93-9	sulphuric acid					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	Study report (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (2009)	OECD Guideline 202
	Fish toxicity	NOEC 0,025 mg/l	65 d	Jordanella floridae	Water Research Vol. 11, 612 - 626, 1977	Groups of sexually mature flagfish
77-92-9	citric acid					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Pimephales promelas	Photogr. Sci. Eng. 16(5):370-377 (1972)	
	Acute crustacea toxicity	EC50 > 50 mg/l	48 h	other aquatic crustacea: Dreissena polymorpha	Environ.Toxicol.C hem. 16(9): 1930-1934 (other: ASTM
	Algae toxicity	NOEC 425 mg/l	8 d	Scenedesmus quadricauda	Water Research 14: 231-241 (1980)	other: Bringmann and Kuhn

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
77-92-9	citric acid	-1,55

BCF

CAS No	Chemical name	BCF	Species	Source
77-92-9	citric acid	3,2		In: (2009)

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Safety Data Sheet

according to UK REACH Regulation

**Sulfuric acid reagent approx. 1 mol/l (orange channel) for determination of silicate with ABB
8241**

Revision date: 08.03.2023

Product code: 01888

Page 8 of 10

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 2796
14.2. UN proper shipping name:	Sulphuric acid
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Other applicable information (land transport)

E2

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2796
14.2. UN proper shipping name:	Sulphuric acid
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C1
Limited quantity:	1 L
Excepted quantity:	E2

Other applicable information (inland waterways transport)

E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 2796
14.2. UN proper shipping name:	Sulphuric acid
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 2796
14.2. UN proper shipping name:	Sulphuric acid
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y840
Excepted quantity:	E2

IATA-packing instructions - Passenger: 851

Safety Data Sheet

according to UK REACH Regulation

Sulfuric acid reagent approx. 1 mol/l (orange channel) for determination of silicate with ABB 8241

Revision date: 08.03.2023

Product code: 01888

Page 9 of 10

IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9,11.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be

Safety Data Sheet

according to UK REACH Regulation

**Sulfuric acid reagent approx. 1 mol/l (orange channel) for determination of silicate with ABB
8241**

Revision date: 08.03.2023

Product code: 01888

Page 10 of 10

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)