

Safety Data Sheet

according to Regulation (EC) No 1907/2006

AAS standard uranium 1.000 g U/I U in nitric acid 2-5 %

Revision date: 20.04.2022

Product code: 03765

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

AAS standard uranium 1.000 g U/I U in nitric acid 2-5 %

UFI: 48EA-S0FN-H008-AEG3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

| | | |
|-------------------------|---------------------------------|------------------------------|
| Company name: | Fa. Bernd Kraft GmbH | |
| Street: | Stempelstraße 6 | |
| Place: | D-47167 Duisburg | |
| Telephone: | 0203/5194-0 | Telefax: 0203/5194-290 |
| e-mail: | info@berndkraft.de | |
| Contact person: | Abteilung Produktsicherheit | Telephone: 0203/5194-107/117 |
| e-mail: | produktsicherheit@berndkraft.de | |
| Internet: | www.berndkraft.de | |
| Responsible Department: | Abteilung Produktsicherheit | |

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Warning

Pictograms:



Hazard statements

H290 May be corrosive to metals.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

AAS standard uranium 1.000 g U/I U in nitric acid 2-5 %

Revision date: 20.04.2022

Product code: 03765

Page 2 of 10

Precautionary statements

- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Hazardous components

| CAS No | Chemical name | | | Quantity |
|-----------|---|--------------|------------------|-----------|
| | EC No | Index No | REACH No | |
| | Classification (Regulation (EC) No 1272/2008) | | | |
| 7697-37-2 | nitric acid | | | 1 - < 5 % |
| | 231-714-2 | 007-030-00-3 | 01-2119487297-23 | |
| | Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A; H272 H290 H331 H314 EUH071 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|-----------|--|---------------|-----------|
| | Specific Conc. Limits, M-factors and ATE | | |
| 7697-37-2 | 231-714-2 | nitric acid | 1 - < 5 % |
| | inhalation: ATE 2,65 mg/kg (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20 | | |

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

After contact with skin

Wash immediately with: Water
 Take off immediately all contaminated clothing and wash it before reuse.
 In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
 Remove contact lenses, if present and easy to do. Continue rinsing.
 Protect uninjured eye.

AAS standard uranium 1.000 g U/I U in nitric acid 2-5 %

Revision date: 20.04.2022

Product code: 03765

Page 3 of 10

After ingestion

Rinse mouth immediately and drink plenty of water.
Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids
Hazardous combustion products
In case of fire may be liberated:
Nitrogen oxides (NO_x)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Collect in closed and suitable containers for disposal.
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

AAS standard uranium 1.000 g U/I U in nitric acid 2-5 %

Revision date: 20.04.2022

Product code: 03765

Page 4 of 10

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Use personal protection equipment.
Provide adequate ventilation. Avoid contact with skin, eyes and clothes.
Do not breathe vapour/aerosol.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary.
Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Corrosive to metals.
Unsuitable container/equipment material: Metal
The product develops hydrogen in an aqueous solution in contact with metals.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| CAS No | Substance | ppm | mg/m ³ | fib/cm ³ | Category | Origin |
|-----------|-------------|-----|-------------------|---------------------|---------------|--------|
| 7697-37-2 | Nitric acid | 1 | 2.6 | | STEL (15 min) | |

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.
If handled uncovered, arrangements with local exhaust ventilation have to be used.

AAS standard uranium 1.000 g U/I U in nitric acid 2-5 %

Revision date: 20.04.2022

Product code: 03765

Page 5 of 10

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles
Wear eye/face protection.

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact
Recommended glove articles: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact
Recommended glove articles: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.
Wash hands before breaks and after work.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|------------------|-------------------|
| Physical state: | Liquid |
| Colour: | colourless |
| Odour: | odourless |
| Odour threshold: | No data available |

Changes in the physical state

| | |
|---|-------------------|
| Melting point/freezing point: | No data available |
| Boiling point or initial boiling point and boiling range: | No data available |
| Sublimation point: | No data available |
| Softening point: | No data available |
| Pour point: | No data available |
| No data available: | |
| Flash point: | No data available |

Flammability

| | |
|---------------|-------------------|
| Solid/liquid: | No data available |
| Gas: | No data available |

AAS standard uranium 1.000 g U/I U in nitric acid 2-5 %

Revision date: 20.04.2022

Product code: 03765

Page 6 of 10

Explosive properties

No data available

Lower explosion limits:

No data available

Upper explosion limits:

No data available

Auto-ignition temperature:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Decomposition temperature:

No data available

pH-Value:

<1

Viscosity / dynamic:

No data available

Viscosity / kinematic:

No data available

Flow time:

No data available

Water solubility:

completely miscible

Solubility in other solvents

No data available

Dissolution rate:

No data available

Partition coefficient n-octanol/water:

No data available

Dispersion stability:

No data available

Vapour pressure:

No data available

Vapour pressure:

No data available

Density:

No data available

Bulk density:

No data available

Relative vapour density:

No data available

Particle characteristics:

No data available

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion:

No data available

Oxidizing properties

No data available

Other safety characteristics

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Evaporation rate:

No data available

Further Information

Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

AAS standard uranium 1.000 g U/I U in nitric acid 2-5 %

Revision date: 20.04.2022

Product code: 03765

Page 7 of 10

The product develops hydrogen in an aqueous solution in contact with metals.

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Cellulose

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | |
|-----------|-------------------|----------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 7697-37-2 | nitric acid | | | | |
| | inhalation vapour | ATE 2,65 mg/kg | | | |

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the preparation/mixture itself.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the preparation/mixture itself.

AAS standard uranium 1.000 g U/I U in nitric acid 2-5 %

Revision date: 20.04.2022

Product code: 03765

Page 8 of 10

Other information

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

| CAS No | Chemical name | | | | | |
|-----------|-------------------------|--------------------|-----------|--|---|--|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| 7697-37-2 | nitric acid | | | | | |
| | Acute fish toxicity | LC50 1559 mg/l | 96 h | Topeka shiner | Environmental Toxicology and Chemistry, | other: ASTM E729-26 |
| | Fish toxicity | NOEC 268 mg/l | 30 d | juvenile Topeka shiner and with juvenile Fathead m | Study report (2009) | Growth tests estimated the test chemical |
| | Algae toxicity | NOEC > 419 mg/l | 10 d | several benthic diatoms; see results | Marine Biology 43:307-315 (1977) | Ten cultures of benthic diatoms were iso |
| | Acute bacteria toxicity | (EC50 > 1000 mg/l) | 3 h | Activated sludge | Study report (2008) | OECD Guideline 209 |

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

There are no data available on the preparation/mixture itself.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

AAS standard uranium 1.000 g U/I U in nitric acid 2-5 %

Revision date: 20.04.2022

Product code: 03765

Page 9 of 10

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

| | |
|--|---|
| 14.1. UN number or ID number: | UN 3264 |
| 14.2. UN proper shipping name: | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid) |
| 14.3. Transport hazard class(es): | 8 |
| 14.4. Packing group: | III |
| Hazard label: | 8 |
| Classification code: | C1 |
| Special Provisions: | 274 |
| Limited quantity: | 5 L |
| Excepted quantity: | E1 |
| Transport category: | 3 |
| Hazard No: | 80 |
| Tunnel restriction code: | E |

Inland waterways transport (ADN)

| | |
|--|---|
| 14.1. UN number or ID number: | UN 3264 |
| 14.2. UN proper shipping name: | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid) |
| 14.3. Transport hazard class(es): | 8 |
| 14.4. Packing group: | III |
| Hazard label: | 8 |
| Classification code: | C1 |
| Special Provisions: | 274 |
| Limited quantity: | 5 L |
| Excepted quantity: | E1 |

Marine transport (IMDG)

| | |
|--|---|
| 14.1. UN number or ID number: | UN 3264 |
| 14.2. UN proper shipping name: | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid) |
| 14.3. Transport hazard class(es): | 8 |
| 14.4. Packing group: | III |
| Hazard label: | 8 |
| Special Provisions: | 223, 274 |
| Limited quantity: | 5 L |
| Excepted quantity: | E1 |
| EmS: | F-A, S-B |

Air transport (ICAO-TI/IATA-DGR)

| | |
|--|---|
| 14.1. UN number or ID number: | UN 3264 |
| 14.2. UN proper shipping name: | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid) |
| 14.3. Transport hazard class(es): | 8 |
| 14.4. Packing group: | III |
| Hazard label: | 8 |
| Special Provisions: | A3 A803 |
| Limited quantity Passenger: | 1 L |
| Passenger LQ: | Y841 |
| Excepted quantity: | E1 |
| IATA-packing instructions - Passenger: | 852 |
| IATA-max. quantity - Passenger: | 5 L |
| IATA-packing instructions - Cargo: | 856 |
| IATA-max. quantity - Cargo: | 60 L |

14.5. Environmental hazards

| | |
|----------------------------|----|
| ENVIRONMENTALLY HAZARDOUS: | No |
|----------------------------|----|

AAS standard uranium 1.000 g U/I U in nitric acid 2-5 %

Revision date: 20.04.2022

Product code: 03765

Page 10 of 10

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to 2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9.

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

| Classification | Classification procedure |
|---------------------|--------------------------|
| Met. Corr. 1; H290 | On basis of test data |
| Skin Irrit. 2; H315 | Calculation method |
| Eye Irrit. 2; H319 | Calculation method |

Relevant H and EUH statements (number and full text)

- H272 May intensify fire; oxidiser.
- H290 May be corrosive to metals.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- EUH071 Corrosive to the respiratory tract.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)