

according to Regulation (EC) No 1907/2006

# AAS standard cerium 1.000 g Ce/I Ce in nitric acid 0.5 mol/I traceable to NIST

Revision date: 05.04.2024 Product code: 03808 Page 1 of 10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

AAS standard cerium 1.000 g Ce/l Ce in nitric acid 0.5 mol/l traceable to NIST

UFI: 6XHA-J04Q-P00J-S3HV

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

# 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

#### **Further Information**

This product is a mixture. REACH Registration Number see section 3.

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Skin Irrit. 2; H315 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

### Regulation (EC) No 1272/2008

### Hazard components for labelling

nitric acid

Signal word: Danger

Pictograms:



### **Hazard statements**

H290 May be corrosive to metals.



according to Regulation (EC) No 1907/2006

# AAS standard cerium 1.000 g Ce/l Ce in nitric acid 0.5 mol/l traceable to NIST

Revision date: 05.04.2024 Product code: 03808 Page 2 of 10

H315 Causes skin irritation.
H318 Causes serious eye damage.

**Precautionary statements** 

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

### **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### Chemical characterization

Mixtures in aqueous solution

### Relevant ingredients

CAS No	Chemical name			Quantity	
	EC No Index No REACH No				
	Classification (Regulation (EC) No 1272/2008)				
7697-37-2	nitric acid				
	231-714-2	007-030-00-3	01-2119487297-23		
	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A; H272 H290 H331 H314 EUH071				

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. L	Specific Conc. Limits, M-factors and ATE		
7697-37-2	231-714-2	nitric acid	1 - < 5 %	
	inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20			

### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **General information**

No data available

# After inhalation

Provide fresh air.

Call a doctor if you feel unwell.

### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.



according to Regulation (EC) No 1907/2006

# AAS standard cerium 1.000 g Ce/I Ce in nitric acid 0.5 mol/I traceable to NIST

Revision date: 05.04.2024 Product code: 03808 Page 3 of 10

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

### After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Irritant

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

### Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Avoid contact with skin, eyes and clothes.

### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Use water spray jet to protect personnel and to cool endangered containers.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Corrosive to metals.

#### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

# 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).



according to Regulation (EC) No 1907/2006

### AAS standard cerium 1.000 g Ce/I Ce in nitric acid 0.5 mol/I traceable to NIST

Revision date: 05.04.2024 Product code: 03808 Page 4 of 10

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol.

### Advice on protection against fire and explosion

Usual measures for fire prevention.

#### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

# Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

# 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Corrosive to metals.

Unsuitable container/equipment material: Metal

The product develops hydrogen in an aqueous solution in contact with metals.

# Further information on storage conditions

Keep container tightly closed.

# 7.3. Specific end use(s)

Laboratory chemicals

### **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

# Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

### 8.2. Exposure controls

### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection



according to Regulation (EC) No 1907/2006

# AAS standard cerium 1.000 g Ce/I Ce in nitric acid 0.5 mol/I traceable to NIST

Revision date: 05.04.2024 Product code: 03808 Page 5 of 10

equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Individual protection measures, such as personal protective equipment

#### Eve/face protection

goggles

Wear eye/face protection.

### Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

#### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

# SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: odourless

Odour threshold: No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

Flammability:

Lower explosion limits:

Upper explosion limits:

No data available
Upper explosion limits:

No data available
Flash point:

No data available
Auto-ignition temperature:

No data available
Decomposition temperature:

No data available
pH-Value:

<1</p>
Viscosity / kinematic:

No data available

Water solubility:

completely miscible



according to Regulation (EC) No 1907/2006

# AAS standard cerium 1.000 g Ce/I Ce in nitric acid 0.5 mol/I traceable to NIST

Revision date: 05.04.2024 Product code: 03808 Page 6 of 10

Solubility in other solvents

No data available

Dissolution rate: No data available Partition coefficient n-octanol/water: No data available Dispersion stability: No data available Vapour pressure: No data available Vapour pressure: No data available Density: No data available Relative density: No data available No data available Bulk density: Relative vapour density: No data available Particle characteristics: No data available

### 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion: No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

Oxidizing

### Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available
Solvent content:

No data available
Solid content:

No data available
Sublimation point:

No data available
Softening point:

No data available
Pour point:

No data available

No data available:

Viscosity / dynamic: No data available Flow time: No data available

### **Further Information**

Corrosive to metals.

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Corrosive to metals.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

# 10.3. Possibility of hazardous reactions

Alkali (lye)

The product develops hydrogen in an aqueous solution in contact with metals.

### 10.4. Conditions to avoid

No data available

#### 10.5. Incompatible materials

Cellulose

Metal

The product develops hydrogen in an aqueous solution in contact with metals.



according to Regulation (EC) No 1907/2006

# AAS standard cerium 1.000 g Ce/I Ce in nitric acid 0.5 mol/I traceable to NIST

Revision date: 05.04.2024 Product code: 03808 Page 7 of 10

### 10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

#### **Further information**

No data available

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
7697-37-2	nitric acid					
	inhalation vapour	ATE 2,65 mg/l				

#### Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

# Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### Information on likely routes of exposure

There are no data available on the preparation/mixture itself.

### Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

### Additional information on tests

There are no data available on the preparation/mixture itself.

#### **Practical experience**

There are no data available on the preparation/mixture itself.

# 11.2. Information on other hazards

### **Endocrine disrupting properties**

There are no data available on the preparation/mixture itself.

### Other information

There are no data available on the preparation/mixture itself.

#### **Further information**

There are no data available on the preparation/mixture itself.



according to Regulation (EC) No 1907/2006

# AAS standard cerium 1.000 g Ce/I Ce in nitric acid 0.5 mol/I traceable to NIST

Revision date: 05.04.2024 Product code: 03808 Page 8 of 10

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
7697-37-2	nitric acid						
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l		juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical
	Algae toxicity	NOEC mg/l	> 419	· ·	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 mg/l ( )	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

### 12.4. Mobility in soil

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

Discharge into the environment must be avoided.

### **Further information**

Do not allow to enter into surface water or drains.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

#### **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

#### Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)



according to Regulation (EC) No 1907/2006

# AAS standard cerium 1.000 g Ce/l Ce in nitric acid 0.5 mol/l traceable to NIST

Revision date: 05.04.2024 Product code: 03808 Page 9 of 10

8 14.3. Transport hazard class(es): Ш 14.4. Packing group: Hazard label: 8 Classification code: C<sub>1</sub> **Special Provisions:** 274 Limited quantity: 5 L Excepted quantity: E1 Transport category: 3 Hazard No: 80 Tunnel restriction code: F

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Classification code:C1Special Provisions:274Limited quantity:5 LExcepted quantity:E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:223, 274Limited quantity:5 LExcepted quantity:E1EmS:F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:1 LPassenger LQ:Y841Excepted quantity:E1

IATA-packing instructions - Passenger:852IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:856IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No.

#### **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3



according to Regulation (EC) No 1907/2006

# AAS standard cerium 1.000 g Ce/l Ce in nitric acid 0.5 mol/l traceable to NIST

Revision date: 05.04.2024 Product code: 03808 Page 10 of 10

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 1,12.

#### Abbreviations and acronyms

Ox. Liq: Oxidising liquid

Met. Corr: Substance or mixture corrosive to metals

Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure				
Met. Corr. 1; H290	On basis of test data				
Skin Irrit. 2; H315	Calculation method				
Eye Dam. 1; H318	Calculation method				

### Relevant H and EUH statements (number and full text)

H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

EUH071 Corrosive to the respiratory tract.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)