

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Doctor solution for testing liquid fuels according to ASTM 235

Revision date: 21.07.2023

Product code: 05041

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Doctor solution for testing liquid fuels according to ASTM 235

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290

Skin Corr. 1A; H314

Eye Dam. 1; H318

Carc. 2; H351

Repr. 1A; H360Df

Lact.; H362

STOT RE 2; H373

Aquatic Acute 1; H400

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

sodium hydroxide

lead monoxide

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Doctor solution for testing liquid fuels according to ASTM 235

Revision date: 21.07.2023

Product code: 05041

Page 2 of 13

Pictograms:



Hazard statements

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H351	Suspected of causing cancer.
H360Df	May damage the unborn child. Suspected of damaging fertility.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH201	Contains lead. Should not be used on surfaces liable to be chewed or sucked by children. Restricted to professional users.
--------	--

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization in aqueous solution

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1310-73-2	sodium hydroxide			11,3625 %
	215-185-5	011-002-00-6	01-2119457892-27	
	Met. Corr. 1, Skin Corr. 1A; H290 H314			
1317-36-8	lead monoxide			5 - < 10 %
	215-267-0	082-001-00-6	01-2119531110-62	
	Carc. 2, Repr. 1A, Lact., Acute Tox. 4, Acute Tox. 4, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H351 H360Df H362 H332 H302 H372 H400 H410 EUH201			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Doctor solution for testing liquid fuels according to ASTM 235

Revision date: 21.07.2023

Product code: 05041

Page 3 of 13

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1310-73-2	215-185-5	sodium hydroxide	11,3625 %
		Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2	
1317-36-8	215-267-0	lead monoxide	5 - < 10 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg Aquatic Acute 1; H400: M=10	

Further Information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: Lead oxide

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!
Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air.
Call a physician immediately.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water.
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water.
Adverse human health effects and symptoms:
Gastric perforation.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Skin corrosion/irritation
Dyspnoea
Cough
Circulatory collapse

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-flammable.
Hazardous combustion products

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Doctor solution for testing liquid fuels according to ASTM 235

Revision date: 21.07.2023

Product code: 05041

Page 4 of 13

In case of fire may be liberated:
Metal oxide smoke, toxic

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.
Avoid contact with skin, eyes and clothes.

Additional information

Suppress gases/vapours/mists with water spray jet.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Collect in closed and suitable containers for disposal.
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Use personal protection equipment.
Provide adequate ventilation. Avoid contact with skin, eyes and clothes.
Do not breathe vapour/aerosol.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Doctor solution for testing liquid fuels according to ASTM 235

Revision date: 21.07.2023

Product code: 05041

Page 5 of 13

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Further information on handling

Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary.
Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Corrosive to metals.
Provide adequate ventilation as well as local exhaustion at critical locations.
Unsuitable container/equipment material:
Metal.

Further information on storage conditions

Store in a dry place.
Keep container tightly closed.
Store in a place accessible by authorized persons only.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
1310-73-2	sodium hydroxide			
Worker DNEL, long-term		inhalation	local	1 mg/m ³
Consumer DNEL, long-term		inhalation	local	1 mg/m ³

PNEC values

CAS No	Substance	Value
1317-36-8	lead monoxide	
Freshwater		0,0031 mg/l
Marine water		0,0035 mg/l
Freshwater sediment		174 mg/kg
Marine sediment		164 mg/kg
Secondary poisoning		10,9 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,1 mg/l
Soil		212 mg/kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Doctor solution for testing liquid fuels according to ASTM 235

Revision date: 21.07.2023

Product code: 05041

Page 6 of 13

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>,<) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	odourless	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		not applicable

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Doctor solution for testing liquid fuels according to ASTM 235

Revision date: 21.07.2023

Product code: 05041

Page 7 of 13

Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	X
Auto-ignition temperature:	No data available
Decomposition temperature:	not determined
pH-Value:	alkaline
Viscosity / kinematic:	No data available
Solubility in other solvents	
not determined	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	not determined
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density (at 20 °C):	1,1457 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	not determined
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
No data available	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
Not oxidising.	

Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	not determined
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	No data available
Flow time:	No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali metals

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Doctor solution for testing liquid fuels according to ASTM 235

Revision date: 21.07.2023

Product code: 05041

Page 8 of 13

Ammonia (NH₃)

Metal

Acid

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Aluminium, Brass, Glass, Plastic articles

Keep away from: Metal.

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1317-36-8	lead monoxide				
	oral	LD50 > 2000 mg/kg	Rat	Study report (2003)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2003)	OECD Guideline 402
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (lead monoxide)

May damage the unborn child. Suspected of damaging fertility. (lead monoxide)

May cause harm to breast-fed children. (lead monoxide)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (lead monoxide)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Doctor solution for testing liquid fuels according to ASTM 235

Revision date: 21.07.2023

Product code: 05041

Page 9 of 13

Aspiration hazard

Based on available data, the classification criteria are not met.
There are no data available on the preparation/mixture itself.

Information on likely routes of exposure

There are no data available on the preparation/mixture itself.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the preparation/mixture itself.

Other information

There are no data available on the preparation/mixture itself.

Further information

Adverse human health effects and symptoms: Gastric perforation.

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name		Dose		[h] [d]	Species	Source	Method
1310-73-2	sodium hydroxide							
	Aquatic toxicity							
	Acute crustacea toxicity	EC50 mg/l	40,4	48 h	Ceriodaphnia sp.	Ecotoxicology and Environmental Safety,4	other: acute 48-h immobilization test ac	
1317-36-8	lead monoxide							
	Acute fish toxicity	LC50 mg/l	1,17	96 h	Oncorhynchus mykiss	Publication (1976)	Acute bioassays	
	Acute algae toxicity	ErC50 mg/l	0,123	72 h	Pseudokirchneriella subcapitata	Study report (2008)	OECD Guideline 201	
	Acute crustacea toxicity	EC50 mg/l	0,59683	48 h	Ceriodaphnia dubia	Study report (2007)	other: USEP	
	Fish toxicity	NOEC mg/l	0,048	90 d	Salmo salar	Publication (1983)	long term toxicity testing of lead to fi	
	Crustacea toxicity	NOEC mg/l	0,0769	7 d	Ceriodaphnia dubia	Study report (2007)	other: USEPA	

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

BCF

CAS No	Chemical name	BCF	Species	Source
1317-36-8	lead monoxide	40000	Asellus meridianus	Freshwater Biology 7

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Doctor solution for testing liquid fuels according to ASTM 235

Revision date: 21.07.2023

Product code: 05041

Page 10 of 13

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

There are no data available on the mixture itself.

Further information

Do not allow to enter into surface water or drains.
Discharge into the environment must be avoided.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains.
Send to a physico-chemical treatment facility under observation of official regulations.
Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 3266
14.2. UN proper shipping name:	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (sodium hydroxide)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C5
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 3266
14.2. UN proper shipping name:	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (sodium hydroxide)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C5
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 3266
14.2. UN proper shipping name:	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (sodium hydroxide)
14.3. Transport hazard class(es):	8

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Doctor solution for testing liquid fuels according to ASTM 235

Revision date: 21.07.2023

Product code: 05041

Page 11 of 13

14.4. Packing group: II
Hazard label: 8
Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3266
14.2. UN proper shipping name: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (sodium hydroxide)
14.3. Transport hazard class(es): 8
14.4. Packing group: II
Hazard label: 8
Special Provisions: A3 A803
Limited quantity Passenger: 0.5 L
Passenger LQ: Y840
Excepted quantity: E2
IATA-packing instructions - Passenger: 851
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes
Danger releasing substance: lead monoxide

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
 lead monoxide

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 63, Entry 75

Information according to 2012/18/EU (SEVESO III): E1 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D):

3 - highly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Doctor solution for testing liquid fuels according to ASTM 235

Revision date: 21.07.2023

Product code: 05041

Page 12 of 13

Changes

This data sheet contains changes from the previous version in section(s): 9,12.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
Met. Corr: Substance or mixture corrosive to metals
Acute Tox: Acute toxicity
Skin Corr: Skin corrosion
Eye Dam: Eye damage
Carc: Carcinogenicity
Repr: Reproductive toxicity
Lact: Lactation effects
STOT RE: Specific target organ toxicity - repeated exposure
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Carc. 2; H351	Calculation method
Repr. 1A; H360Df	Calculation method
Lact.; H362	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H290 May be corrosive to metals.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H351 Suspected of causing cancer.
H360Df May damage the unborn child. Suspected of damaging fertility.
H362 May cause harm to breast-fed children.
H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
EUH201 Contains lead. Should not be used on surfaces liable to be chewed or sucked by children.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Doctor solution for testing liquid fuels according to ASTM 235

Revision date: 21.07.2023

Product code: 05041

Page 13 of 13

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)