

## Safety Data Sheet

according to UK REACH Regulation

### Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured

Revision date: 06.03.2024

Product code: 05053

Page 1 of 13

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured

UFI: RUYE-P0FY-000P-A416

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Laboratory chemical

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

###### Uses advised against

Do not use for private purposes (household).

##### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

##### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

##### Further Information

inapplicable, this product is a mixture REACH registration number see section 3

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### GB CLP Regulation

Met. Corr. 1; H290

Flam. Liq. 2; H225

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

###### GB CLP Regulation

###### Hazard components for labelling

potassium hydroxide

Signal word: Danger

###### Pictograms:



## Safety Data Sheet

according to UK REACH Regulation

### Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured

Revision date: 06.03.2024

Product code: 05053

Page 2 of 13

#### Hazard statements

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.

#### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64-17-5	ethanol			85 - < 90 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
1310-58-3	potassium hydroxide			< 1 %
	215-181-3	019-002-00-8	01-2119487136-33	
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A; H290 H302 H314			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64-17-5	200-578-6	ethanol	85 - < 90 %
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100		
1310-58-3	215-181-3	potassium hydroxide	< 1 %
	oral: LD50 = 333 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		

#### Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Self-protection of the first aider

## Safety Data Sheet

according to UK REACH Regulation

### Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured

Revision date: 06.03.2024

Product code: 05053

Page 3 of 13

#### After inhalation

Provide fresh air.

#### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

#### After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

corrosive

Irritant

Cough

Dyspnoea

Dizziness

The product causes narcotic-like effects.

Inebriation

Vomiting

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

#### Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Combustible liquid.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>) Carbon monoxide

Beware of reignition.

### 5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

Use water spray jet to protect personnel and to cool endangered containers.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Suppress gases/vapours/mists with water spray jet.

Move undamaged containers from immediate hazard area if it can be done safely.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Keep away from sources of ignition - No smoking.

## Safety Data Sheet

according to UK REACH Regulation

### Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured

Revision date: 06.03.2024

Product code: 05053

Page 4 of 13

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

#### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

#### Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

## Safety Data Sheet

according to UK REACH Regulation

### Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured

Revision date: 06.03.2024

Product code: 05053

Page 5 of 13

#### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.  
Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

##### Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.  
national regulations

##### Further information on storage conditions

Vapours may form explosive mixtures with air.  
storage temperature +15°C - +25°C

#### 7.3. Specific end use(s)

Laboratory use Laboratory chemical

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	WEL

##### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-17-5	ethanol			
	Worker DNEL, long-term	inhalation	systemic	950 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	114 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day
1310-58-3	potassium hydroxide			
	Worker DNEL, long-term	inhalation	local	1 mg/m <sup>3</sup>
	Consumer DNEL, long-term	inhalation	local	1 mg/m <sup>3</sup>

**Safety Data Sheet**

according to UK REACH Regulation

**Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured**

Revision date: 06.03.2024

Product code: 05053

Page 6 of 13

**PNEC values**

CAS No	Substance	
Environmental compartment		Value
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (intermittent releases)		2,75 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		380 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Suitable eye protection: goggles.

**Hand protection**

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) with the following specification (test according to EN 374):

By long-term hand contact

Recommended glove articles: KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles KCL 720 Camapren®

Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

Flame-retardant protective clothing. Wear anti-static footwear and clothing

**Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation

**Environmental exposure controls**

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

**Safety Data Sheet**

according to UK REACH Regulation

**Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured**

Revision date: 06.03.2024

Product code: 05053

Page 7 of 13

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	clear / yellow
Odour:	like: Ethanol
Odour threshold:	No data available
Melting point/freezing point:	~114 °C
Boiling point or initial boiling point and boiling range:	~78 °C
Flammability:	not applicable
Lower explosion limits:	3,5 vol. %
Upper explosion limits:	15 vol. %
Flash point:	12 °C
Auto-ignition temperature:	425 °C
Decomposition temperature:	not determined
pH-Value:	alkaline
Viscosity / kinematic:	No data available
Water solubility:	Soluble in: Water
Solubility in other solvents	not determined
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	59 hPa
(at 20 °C)	
Vapour pressure:	No data available
Density:	~0,827 g/cm <sup>3</sup>
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	not determined
Particle characteristics:	No data available

**9.2. Other information**

**Information with regard to physical hazard classes**

**Explosive properties**

Vapours can form explosive mixtures with air.

**Sustaining combustion:**

Sustaining combustion

**Self-ignition temperature**

Solid:

not applicable

Gas:

not applicable

**Oxidizing properties**

Not oxidising.

**Other safety characteristics**

Evaporation rate:	not determined
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	not determined
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	

## Safety Data Sheet

according to UK REACH Regulation

### Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured

Revision date: 06.03.2024

Product code: 05053

Page 8 of 13

Viscosity / dynamic:  
(at 20 °C) 1,2 mPa·s

Flow time: No data available

#### Further Information

May be corrosive to metals.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable.  
Vapours can form explosive mixtures with air.  
May be corrosive to metals.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Oxidising agent, Hydrogen peroxide, Nitric acid, Alkali metals, Alkaline earth metal  
Chlorine, Fluorine, silver, permanganates, e.g. potassium permanganate

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

### 10.5. Incompatible materials

Glass  
Plastic articles  
Metal

### 10.6. Hazardous decomposition products

Hazardous combustion products  
In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>) Carbon monoxide

#### Further information

No data available

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.  
If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).  
Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.  
Resorption (by inhalation)

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



**Safety Data Sheet**

according to UK REACH Regulation

**Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured**

Revision date: 06.03.2024

Product code: 05053

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol				
	oral	LD50 mg/kg	10470	Rat	Study report (1976) OECD Guideline 401
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980) OECD Guideline 403
1310-58-3	potassium hydroxide				
	oral	LD50 mg/kg	333	Rat	Fund. Appl. Toxicol., 8, 97-100 (1987) OECD Guideline 425

**Irritation and corrosivity**

- Causes skin irritation.
- Causes serious eye irritation.
- Risk of serious damage to eyes.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

- Based on available data, the classification criteria are not met.
- Observe risk of aspiration if vomiting occurs.

**Information on likely routes of exposure**

There are no data available on the mixture itself.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

There are no data available on the mixture itself.

**Other information**

- corrosive
- Irritant
- Cough
- Dyspnoea
- Dizziness
- The product causes narcotic-like effects.
- Inebriation
- Vomiting
- Risk of serious damage to eyes.
- Corneal opacity.

**Further information**

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin

**Safety Data Sheet**

according to UK REACH Regulation

**Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured**

Revision date: 06.03.2024

Product code: 05053

Page 10 of 13

inflammation).

**SECTION 12: Ecological information**

**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64-17-5	ethanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC 5400 mg/l	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989)	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC 2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,77

**BCF**

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

There are no data available on the mixture itself.

**Further information**

Avoid release to the environment.  
Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations**

**Safety Data Sheet**

according to UK REACH Regulation

**Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured**

Revision date: 06.03.2024

Product code: 05053

Page 11 of 13

**13.1. Waste treatment methods**

**Disposal recommendations**

Do not allow to enter into surface water or drains.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**Contaminated packaging**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.  
Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number or ID number:** UN 2924  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3+8  
Classification code: FC  
Special Provisions: 274  
Limited quantity: 1 L  
Excepted quantity: E2  
Transport category: 2  
Hazard No: 338  
Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 2924  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3+8  
Classification code: FC  
Special Provisions: 274  
Limited quantity: 1 L  
Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 2924  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3+8  
Special Provisions: 274  
Limited quantity: 1 L  
Excepted quantity: E2  
EmS: F-E, S-C

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 2924  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)  
**14.3. Transport hazard class(es):** 3

## Safety Data Sheet

according to UK REACH Regulation

**Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured**

Revision date: 06.03.2024

Product code: 05053

Page 12 of 13

<b>14.4. Packing group:</b>	II	
Hazard label:	3+8	
Special Provisions:	A3	
Limited quantity Passenger:	0.5 L	
Passenger LQ:	Y340	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		352
IATA-max. quantity - Passenger:		1 L
IATA-packing instructions - Cargo:		363
IATA-max. quantity - Cargo:		5 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,9.

**Abbreviations and acronyms**

Met. Corr: Corrosive to metals

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Skin Corr: Skin corrosion

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Safety Data Sheet**

according to UK REACH Regulation

**Potassium hydroxide 0.1 mol/l - 0.1 N solution in ethanol 92 vol. % denatured**

Revision date: 06.03.2024

Product code: 05053

Page 13 of 13

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	
Eye Irrit. 2; H319	

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

**Further Information**

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*